

Oracle® Database

Semantic Technologies Developer's Guide

11g Release 2 (11.2)

E11828-10

November 2010

Provides usage and reference information about Oracle Database support for semantic technologies, including storage, inference, and query capabilities for data and ontologies based on Resource Description Framework (RDF), RDF Schema (RDFS), and Web Ontology Language (OWL).

Oracle Database Semantic Technologies Developer's Guide, 11g Release 2 (11.2)

E11828-10

Copyright © 2005, 2010, Oracle and/or its affiliates. All rights reserved.

Primary Author: Chuck Murray

Contributors: Eugene Inseok Chong, Souri Das, Vladimir Kolovski, Matt Perry, Jags Srinivasan, Seema Sundara, Zhe (Alan) Wu, Aravind Yalamanchi

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Contents

Preface	xv
Audience	xv
Documentation Accessibility	xv
Related Documents	xvi
Conventions	xvi
What's New in Semantic Technologies?	xvii
Release 11.2 Features	xvii
Release 11.1 Features	xx
1 Oracle Database Semantic Technologies Overview	
1.1 Introduction to Oracle Semantic Technologies	1-2
1.2 Semantic Data Modeling	1-3
1.3 Semantic Data in the Database	1-3
1.3.1 Metadata for Models	1-3
1.3.2 Statements	1-5
1.3.2.1 Triple Uniqueness and Data Types for Literals	1-6
1.3.3 Subjects and Objects	1-7
1.3.4 Blank Nodes	1-7
1.3.5 Properties	1-7
1.3.6 Inferencing: Rules and Rulebases	1-7
1.3.7 Entailments (Rules Indexes)	1-10
1.3.8 Virtual Models	1-11
1.3.9 Semantic Data Security Considerations	1-14
1.4 Semantic Metadata Tables and Views	1-14
1.5 Semantic Data Types, Constructors, and Methods	1-15
1.5.1 Constructors for Inserting Triples Without Any Blank Nodes	1-17
1.5.2 Constructors for Inserting Triples With or Without Any Blank Nodes	1-17
1.6 Using the SEM_MATCH Table Function to Query Semantic Data	1-18
1.6.1 Performing Queries with Incomplete or Invalid Entailments	1-21
1.6.2 Graph Patterns: Support for Curly Brace Syntax, and OPTIONAL, FILTER, and UNION Keywords	1-22
1.6.3 Inline Query Optimizer Hints	1-26
1.6.4 Full-Text Search	1-26
1.6.5 Best Practices for Query Performance	1-27

1.6.5.1	FILTER Constructs Involving xsd:dateTime, xsd:date, and xsd:time	1-28
1.6.5.2	Function-Based Indexes for FILTER Constructs Involving xsd Data Types	1-28
1.6.5.3	FILTER Constructs Involving Relational Expressions	1-29
1.6.5.4	Optimizer Statistics	1-29
1.6.5.5	Virtual Models and Semantic Network Indexes	1-29
1.7	Loading and Exporting Semantic Data	1-30
1.7.1	Bulk Loading Semantic Data Using a Staging Table	1-30
1.7.1.1	Recording Event Traces during Bulk Loading	1-31
1.7.2	Batch Loading Semantic Data Using the Java API	1-31
1.7.2.1	When to Choose Batch Loading	1-33
1.7.3	Loading Semantic Data Using INSERT Statements	1-33
1.7.4	Exporting Semantic Data	1-33
1.8	Using Semantic Network Indexes	1-34
1.9	Quick Start for Using Semantic Data	1-35
1.10	Semantic Data Examples (PL/SQL and Java)	1-36
1.10.1	Example: Journal Article Information	1-36
1.10.2	Example: Family Information	1-38
1.11	Software Naming Changes for Semantic Technologies	1-45
1.12	For More Information About Semantic Technologies	1-45

2 OWL Concepts

2.1	Ontologies	2-1
2.1.1	Example: Cancer Ontology	2-1
2.1.2	Supported OWL Subsets	2-2
2.2	Using OWL Inferencing	2-4
2.2.1	Creating a Simple OWL Ontology	2-4
2.2.2	Performing Native OWL inferencing	2-5
2.2.3	Performing OWL and User-Defined Rules inferencing	2-5
2.2.4	Generating OWL inferencing Proofs	2-6
2.2.5	Validating OWL Models and Entailments	2-7
2.2.6	Using SEM_APIS.CREATE_ENTAILMENT for RDFS Inference	2-8
2.2.7	Enhancing Inference Performance	2-8
2.2.8	Optimizing owl:sameAs Inference	2-9
2.2.8.1	Querying owl:sameAs Consolidated Inference Graphs	2-10
2.2.9	Performing Incremental Inference	2-11
2.2.10	Using Parallel Inference	2-12
2.2.11	Performing Selective Inferencing (Advanced Information)	2-12
2.3	Using Semantic Operators to Query Relational Data	2-13
2.3.1	Using the SEM_RELATED Operator	2-13
2.3.2	Using the SEM_DISTANCE Ancillary Operator	2-15
2.3.2.1	Computation of Distance Information	2-16
2.3.3	Creating a Semantic Index of Type MDSYS.SEM_INDEXTYPE	2-16
2.3.4	Using SEM_RELATED and SEM_DISTANCE When the Indexed Column Is Not the First Parameter 2-17	
2.3.5	Using URIPREFIX When Values Are Not Stored as URIs	2-18

3 Simple Knowledge Organization System (SKOS) Support

3.1	Supported and Unsupported SKOS Semantics	3-2
3.1.1	Supported SKOS Semantics	3-2
3.1.2	Unsupported SKOS Semantics	3-3
3.2	Performing Inference on SKOS Models.....	3-3
3.2.1	Validating SKOS Models and Entailments	3-3
3.2.2	Property Chain Handling	3-4

4 Semantic Indexing for Documents

4.1	Information Extractors for Semantically Indexing Documents	4-2
4.2	Extractor Policies.....	4-3
4.3	Semantically Indexing Documents.....	4-4
4.4	SEM_CONTAINS and SEM_CONTAINS_SELECT Syntax	4-5
4.5	Searching for Documents Using SPARQL Query Patterns	4-6
4.6	Bindings from Matched Documents (SEM_CONTAINS_SELECT Ancillary Operator) .	4-7
4.7	Improving the Quality of Document Search Operations	4-8
4.8	Indexing External Documents.....	4-8
4.9	Configuring the Calais Extractor type	4-10
4.10	Working with General Architecture for Text Engineering (GATE)	4-11
4.11	Creating a New Extractor Type	4-12
4.12	Metadata Views for Semantic Indexing.....	4-13
4.12.1	MDSYS.RDFCTX_POLICIES View	4-13
4.12.2	RDFCTX_INDEX_POLICIES View	4-13
4.12.3	RDFCTX_INDEX_EXCEPTIONS View	4-14
4.13	Default Style Sheet for GATE Extractor Output.....	4-14

5 Fine-Grained Access Control for RDF Data

5.1	Virtual Private Database (VPD) for RDF Data.....	5-2
5.1.1	VPD Policy for RDF Data	5-3
5.1.2	RDF Metadata for Enforcing VPD Policies	5-5
5.1.3	Data Access Constraints	5-7
5.1.4	RDFVPD_POLICIES View	5-10
5.1.5	RDFVPD_MODELS View.....	5-10
5.1.6	RDFVPD_POLICY_CONSTRAINTS View	5-11
5.1.7	RDFVPD_PREDICATE_MDATA View	5-11
5.1.8	RDFVPD_RESOURCE_REL View.....	5-12
5.2	Oracle Label Security (OLS) for RDF Data.....	5-12
5.2.1	Triple-Level Security	5-12
5.2.2	Resource-Level Security.....	5-14
5.2.2.1	Securing RDF Subjects	5-15
5.2.2.2	Securing RDF Predicates	5-15
5.2.2.3	Securing RDF Objects.....	5-16
5.2.2.4	Generating Labels for Inferred Triples.....	5-16
5.2.2.5	Using Labels Based on Application Logic	5-18
5.2.2.6	RDFOLS_SECURE_RESOURCE View	5-20

6 Workspace Manager Support for RDF Data

6.1	Enabling Workspace Manager Support for RDF Data	6-1
6.1.1	Removing Workspace Manager Support for RDF Data.....	6-2
6.2	Version-Enabling an RDF Model.....	6-2
6.3	Inferring from Version-Enabled RDF Models	6-3
6.4	Merging and Refreshing Workspaces in Version-Enabled RDF Models.....	6-3

7 Jena Adapter for Oracle Database

7.1	Setting Up the Software Environment	7-1
7.2	Setting Up the SPARQL Service	7-3
7.2.1	Creating the Required Data Source Using WebLogic Server	7-5
7.2.2	Configuring the SPARQL Service	7-6
7.2.2.1	Client Identifiers	7-8
7.2.3	Terminating Long-Running SPARQL Queries.....	7-8
7.2.4	N-Triples Encoding for Non-ASCII Characters	7-8
7.3	Setting Up the Semantic Technologies Environment	7-9
7.4	SEM_MATCH and Jena Adapter Queries Compared.....	7-9
7.5	Optimized Handling of SPARQL Queries	7-10
7.5.1	Compilation of SPARQL queries to a single SEM_MATCH Call.....	7-10
7.5.2	Optimized Handling of Property Paths	7-11
7.5.3	Optimized Handling of Plain BGP and OPTIONAL Queries.....	7-12
7.6	Additions to the SPARQL Syntax to Support Other Features	7-12
7.6.1	SQL Hints.....	7-12
7.6.2	Using Bind Variables in SPARQL Queries.....	7-13
7.6.3	Additional WHERE Clause Predicates	7-15
7.6.4	Additional Query Options	7-15
7.6.4.1	JOIN Option and Federated Queries	7-16
7.6.4.2	S2S Option Benefits and Usage Information	7-18
7.6.5	Midtier Resource Caching	7-18
7.7	Functions Supported in SPARQL Queries through the Jena Adapter	7-18
7.7.1	Functions in the ARQ Function Library	7-19
7.7.2	Native Oracle Database Functions for Projected Variables.....	7-19
7.7.3	User-Defined Functions	7-20
7.8	Support for Server-Side APIs	7-23
7.8.1	Virtual Models Support	7-24
7.8.2	Connection Pooling Support.....	7-25
7.8.3	Semantic Model PL/SQL Interfaces	7-26
7.8.4	Inference Options.....	7-26
7.8.5	PelletInfGraph Class Support Deprecated.....	7-26
7.9	Bulk Loading Using the Jena Adapter	7-27
7.10	Example Queries Using the Jena Adapter.....	7-28
7.10.1	Test.java: Query Family Relationships	7-29
7.10.2	Test6.java: Load OWL Ontology and Perform OWLPrime inference.....	7-30
7.10.3	Test7.java: Bulk Load OWL Ontology and Perform OWLPrime inference	7-32
7.10.4	Test8.java: SPARQL OPTIONAL Query	7-33
7.10.5	Test9.java: SPARQL Query with LIMIT and OFFSET.....	7-35
7.10.6	Test10.java: SPARQL Query with TIMEOUT and DOP	7-36

7.10.7	Test11.java: Query Involving Named Graphs	7-37
7.10.8	Test12.java: SPARQL ASK Query	7-39
7.10.9	Test13.java: SPARQL DESCRIBE Query	7-40
7.10.10	Test14.java: SPARQL CONSTRUCT Query.....	7-41
7.10.11	Test15.java: Query Multiple Models and Specify "Allow Duplicates"	7-42
7.10.12	Test16.java: SPARUL (SPARQL Update) Example.....	7-44
7.10.13	Test17.java: SPARQL Query with ARQ Built-In Functions.....	7-45
7.10.14	Test18.java: SELECT Cast Query	7-46
7.10.15	Test19.java: Instantiate Oracle Database Using OracleConnection.....	7-47
7.10.16	Test20.java: Oracle Database Connection Pooling	7-48

8 Sesame Adapter for Oracle Database

8.1	Sesame Adapter Overview	8-1
8.2	Setup and Configuration for the Sesame Adapter	8-3
8.2.1	Setting Up the Software Environment.....	8-3
8.2.2	Setting Up the SPARQL Service	8-4
8.2.2.1	Creating the Required Data Source Using WebLogic Server.....	8-13
8.2.2.2	Configuring the SPARQL Service	8-14
8.2.2.3	Terminating Long-Running SPARQL Queries	8-14
8.2.3	Setting Up the Semantic Technologies Environment	8-14
8.3	SEM_MATCH and Sesame Adapter Queries Compared	8-15
8.4	Optimized Handling of SPARQL Queries	8-16
8.4.1	Compilation of SPARQL Queries to a Single SEM_MATCH Call	8-16
8.5	Recommendations for Best Performance	8-16
8.5.1	Statement Storage and Implications for Sesame Adapter Queries.....	8-16
8.6	Additions to the SPARQL Syntax to Support Other Features	8-17
8.6.1	SQL Hints.....	8-17
8.6.2	Additional WHERE Clause Predicates	8-17
8.6.3	Additional Query Options	8-18
8.7	Support for Server-Side APIs	8-18
8.7.1	Virtual Models Support	8-19
8.7.2	Connection Pooling Support.....	8-20
8.7.3	Semantic Model PL/SQL Interfaces	8-21
8.7.4	Inference Options.....	8-21
8.8	Oracle-Specific Extensions to Sesame APIs.....	8-21
8.8.1	Statement Uniqueness.....	8-21
8.8.2	Indexes and Interoperability with the Jena Adapter	8-22
8.8.3	Inference	8-23
8.8.4	Performing Analysis Operations	8-23
8.9	Using the Sesame Console with the Sesame Adapter	8-23
8.10	Example Queries Using the Sesame Adapter	8-26
8.10.1	Example1.java: Basic Operations.....	8-27
8.10.2	Example2.java: Add a Data File (in TRIG format)	8-29
8.10.3	Example3.java: Simple Query	8-30
8.10.4	Example4.java: Simple Bulk Load	8-32
8.10.5	Example5.java: Bulk Load RDF/XML and Application Table Index Maintenance	8-34

8.10.6	Example6.java: Bulk Load With StatusListener to Handle Loading with Bad Data	8-36
8.10.7	Example7.java: Load Data from Sesame Store into Oracle Database	8-38
8.10.8	Example8.java: SPARQL ASK Query	8-40
8.10.9	Example9.java: SPARQL CONSTRUCT and DESCRIBE.....	8-41
8.10.10	Example10.java: Inference	8-43
8.10.11	Example11.java: Named Graph Query.....	8-46
8.10.12	Example12.java: Indexes on Application Table [<i>Advanced</i>].....	8-48
8.10.13	Example13.java: Uniqueness Constraint on Application Table [<i>Advanced</i>]	8-49
8.10.14	Example14.java: Query Timeout and Parallel Execution [<i>Advanced</i>].....	8-51
8.10.15	Example15.java: Get COUNT of Matches [<i>Advanced</i>]	8-53
8.10.16	Example16.java: Specify Bind Variable for Constant in Query Pattern [<i>Advanced</i>]	8-54
8.10.17	Example17.java: Specify Bind Variable for Constant in Different Position in Query Pattern [<i>Advanced</i>]	8-56
8.10.18	Example18.java: Build URIs from Internal Numeric IDs [<i>Advanced</i>].....	8-58

9 SEM_APIS Package Subprograms

SEM_APIS.ADD_SEM_INDEX.....	9-2
SEM_APIS.ALTER_ENTAILMENT	9-3
SEM_APIS.ALTER_MODEL	9-4
SEM_APIS.ALTER_SEM_INDEX_ON_ENTAILMENT	9-5
SEM_APIS.ALTER_SEM_INDEX_ON_MODEL	9-7
SEM_APIS.ANALYZE_ENTAILMENT	9-9
SEM_APIS.ANALYZE_MODEL	9-11
SEM_APIS.BULK_LOAD_FROM_STAGING_TABLE	9-13
SEM_APIS.CLEANUP_FAILED.....	9-15
SEM_APIS.COMPOSE_RDF_TERM.....	9-16
SEM_APIS.CREATE_ENTAILMENT	9-19
SEM_APIS.CREATE_RULEBASE	9-27
SEM_APIS.CREATE_SEM_MODEL.....	9-28
SEM_APIS.CREATE_SEM_NETWORK.....	9-29
SEM_APIS.CREATE_VIRTUAL_MODEL	9-30
SEM_APIS.DISABLE_CHANGE_TRACKING	9-32
SEM_APIS.DISABLE_INC_INFERENCE.....	9-33
SEM_APIS.DROP_ENTAILMENT	9-34
SEM_APIS.DROP_RULEBASE	9-35
SEM_APIS.DROP_SEM_INDEX.....	9-36
SEM_APIS.DROP_SEM_MODEL.....	9-37
SEM_APIS.DROP_SEM_NETWORK.....	9-38
SEM_APIS.DROP_USER_INFERENCE_OBJS	9-39
SEM_APIS.DROP_VIRTUAL_MODEL	9-40
SEM_APIS.ENABLE_CHANGE_TRACKING	9-41
SEM_APIS.ENABLE_INC_INFERENCE	9-42
SEM_APIS.GET_CHANGE_TRACKING_INFO	9-43

SEM_APIS.GET_INC_INF_INFO.....	9-44
SEM_APIS.GET_MODEL_ID.....	9-45
SEM_APIS.GET_MODEL_NAME.....	9-46
SEM_APIS.GET_TRIPLE_ID.....	9-47
SEM_APIS.GETV\$DATETIMETZVAL.....	9-49
SEM_APIS.GETV\$DATETZVAL.....	9-50
SEM_APIS.GETV\$NUMERICVAL.....	9-51
SEM_APIS.GETV\$STRINGVAL.....	9-52
SEM_APIS.GETV\$TIMETZVAL.....	9-53
SEM_APIS.IS_TRIPLE.....	9-55
SEM_APIS.LOOKUP_ENTAILMENT.....	9-57
SEM_APIS.MERGE_MODELS.....	9-58
SEM_APIS.REMOVE_DUPLICATES.....	9-60
SEM_APIS.RENAME_ENTAILMENT.....	9-61
SEM_APIS.RENAME_MODEL.....	9-62
SEM_APIS.SWAP_NAMES.....	9-63
SEM_APIS.VALIDATE_ENTAILMENT.....	9-64
SEM_APIS.VALIDATE_MODEL.....	9-66
SEM_APIS.VALUE_NAME_PREFIX.....	9-68
SEM_APIS.VALUE_NAME_SUFFIX.....	9-70

10 SEM_PERF Package Subprograms

SEM_PERF.GATHER_STATS.....	10-2
----------------------------	------

11 SEM_RDFCTX Package Subprograms

SEM_RDFCTX.CREATE_POLICY.....	11-2
SEM_RDFCTX.DROP_POLICY.....	11-4
SEM_RDFCTX.MAINTAIN_TRIPLES.....	11-5
SEM_RDFCTX.SET_DEFAULT_POLICY.....	11-7
SEM_RDFCTX.SET_EXTRACTOR_PARAM.....	11-8

12 SEM_RDFSA Package Subprograms

SEM_RDFSA.ADD_VPD_CONSTRAINT.....	12-2
SEM_RDFSA.APPLY_OLS_POLICY.....	12-4
SEM_RDFSA.APPLY_VPD_POLICY.....	12-7
SEM_RDFSA.CREATE_VPD_POLICY.....	12-8
SEM_RDFSA.DELETE_VPD_CONSTRAINT.....	12-10
SEM_RDFSA.DISABLE_OLS_POLICY.....	12-11
SEM_RDFSA.DROP_VPD_POLICY.....	12-12
SEM_RDFSA.ENABLE_OLS_POLICY.....	12-13
SEM_RDFSA.MAINT_VPD_METADATA.....	12-14

SEM_RDFSA.REMOVE_OLS_POLICY	12-16
SEM_RDFSA.REMOVE_VPD_POLICY	12-17
SEM_RDFSA.RESET_MODEL_LABELS	12-18
SEM_RDFSA.SET_PREDICATE_LABEL	12-19
SEM_RDFSA.SET_RDFS_LABEL	12-21
SEM_RDFSA.SET_RESOURCE_LABEL	12-23
SEM_RDFSA.SET_RULE_LABEL	12-25
A.1 Enabling Semantic Technologies Support	A-1
A.1.1 Enabling Semantic Technologies Support in a New Database Installation	A-1
A.1.2 Upgrading Semantic Technologies Support from Release 11.1	A-2
A.1.2.1 Handling of Empty RDF Literals	A-3
A.1.3 Upgrading Semantic Technologies Support from Release 10.2	A-4
A.1.4 Release 11.2.0.2: Required Actions if Semantic Technologies Installation is Invalid	A-4
A.1.5 Spatial and Partitioning Requirements.....	A-5
A.2 Downgrading Semantic Technologies Support to a Previous Release	A-5
A.2.1 Downgrading to Release 11.1 Semantic Technologies Support.....	A-5
A.2.2 Downgrading to Release 10.2 Semantic Technologies Support.....	A-7
A.3 Removing Semantic Technologies Support	A-8

Index

List of Examples

1-1	Inserting a Rule into a Rulebase	1-9
1-2	Using Rulebases for Inferencing	1-10
1-3	Creating an Entailment	1-11
1-4	Querying a Virtual Model	1-12
1-5	SDO_RDF_TRIPLE_S Methods	1-16
1-6	SDO_RDF_TRIPLE_S Constructor to Insert a Triple	1-17
1-7	SDO_RDF_TRIPLE_S Constructor to Reusing a Blank Node	1-18
1-8	SEM_MATCH Table Function	1-20
1-9	HINT0 Option with SEM_MATCH Table Function	1-21
1-10	SEM_MATCH Table Function	1-21
1-11	Curly Brace Syntax	1-22
1-12	Curly Brace Syntax and OPTIONAL Construct	1-22
1-13	Curly Brace Syntax and Multi-Pattern OPTIONAL Construct	1-23
1-14	Curly Brace Syntax and Nested OPTIONAL Construct	1-23
1-15	Curly Brace Syntax and Parallel OPTIONAL Construct	1-23
1-16	Curly Brace Syntax and FILTER Construct	1-24
1-17	Curly Brace Syntax and FILTER with REGEX and STR Built-In Constructs	1-25
1-18	Curly Brace Syntax and UNION and FILTER Constructs	1-25
1-19	Inline Query Optimizer Hints	1-26
1-20	Creating a Full-Text Index on the MDSYS.RDF_VALUE\$ Table	1-27
1-21	Full-Text Search	1-27
1-22	Using HINT0 to Ensure Use of Function-Based Index	1-28
1-23	Gathering Multicolumn and General Statistics	1-29
1-24	Using a Model for Journal Article Information	1-36
1-25	Using a Model for Family Information	1-38
2-1	Creating a Simple OWL Ontology	2-4
2-2	Performing Native OWL Inferencing	2-5
2-3	Performing OWL and User-Defined Rules Inferencing	2-5
2-4	Displaying Proof Information	2-6
2-5	Validating an Entailment	2-7
2-6	Performing Selective Inferencing	2-12
2-7	SEM_RELATED Operator	2-14
2-8	SEM_DISTANCE Ancillary Operator	2-15
2-9	Using SEM_DISTANCE to Restrict the Number of Rows Returned	2-15
2-10	Creating a Semantic Index	2-17
2-11	Creating a Semantic Index Specifying a Model and Rulebase	2-17
2-12	Query Benefitting from Generation of Statistical Information	2-17
2-13	Specifying a URI Prefix During Semantic Index Creation	2-18
3-1	SKOS Definition of an Electronics Scheme	3-1
3-2	Validating an SKOS Entailment	3-3
3-3	Property Chain Insertions to Implement S55	3-4
4-1	RDFCTX_EXTRACTOR Abstract Type Definition	4-2
5-1	Creating a Custom Label Generator Type	5-19
7-1	Loading Data into the Staging Table (prepareBulk)	7-27
7-2	Loading Data from the Staging Table into the Semantic Network (completeBulk)	7-28
7-3	Using prepareBulk with RDFa	7-28
7-4	Query Family Relationships	7-29
7-5	Load OWL Ontology and Perform OWLPrime inference	7-30
7-6	Bulk Load OWL Ontology and Perform OWLPrime inference	7-32
7-7	SPARQL OPTIONAL Query	7-33
7-8	SPARQL Query with LIMIT and OFFSET	7-35
7-9	SPARQL Query with TIMEOUT and DOP	7-36
7-10	Named Graph Based Query	7-37
7-11	SPARQL ASK Query	7-39

7-12	SPARQL DESCRIBE Query	7-40
7-13	SPARQL CONSTRUCT Query	7-41
7-14	Query Multiple Models and Specify "Allow Duplicates"	7-42
7-15	SPARUL (SPARQL Update) Example	7-44
7-16	SPARQL Query with ARQ Built-In Functions	7-45
7-17	SELECT Cast Query	7-46
7-18	Instantiate Oracle Database Using OracleConnection.....	7-47
7-19	Oracle Database Connection Pooling.....	7-48
8-1	Sample Usage flow for Sesame Adapter	8-2
8-2	Migration Between Jena Adapter and Sesame Adapter Models	8-22
8-3	Using the Sesame Console	8-25
8-4	Basic Operations.....	8-27
8-5	Add a Data File (in TRIG format)	8-29
8-6	Simple Query	8-30
8-7	Simple Bulk Load	8-32
8-8	Bulk Load RDF/XML and Application Table Index Maintenance	8-34
8-9	Bulk Load With StatusListener to Handle Loading with Bad Data	8-36
8-10	Load Data from Sesame Store into Oracle Database	8-38
8-11	SPARQL ASK Query	8-40
8-12	SPARQL CONSTRUCT and DESCRIBE.....	8-41
8-13	Inference	8-43
8-14	Named Graph Query	8-46
8-15	Indexes on Application Table [Advanced].....	8-48
8-16	Uniqueness Constraint on Application Table [Advanced].....	8-49
8-17	Query Timeout and Parallel Execution [Advanced].....	8-51
8-18	Get COUNT of Matches [Advanced]	8-53
8-19	Specify Bind Variable for Constant in Query Pattern [Advanced].....	8-54
8-20	Specify Bind Variable for Constant in Different Position in Query Pattern [Advanced].....	8-56
8-21	Build URIs from Internal Numeric IDs [Advanced].....	8-58

List of Figures

1-1	Oracle Semantic Capabilities.....	1-2
1-2	Inferencing	1-8
1-3	Family Tree for RDF Example.....	1-38
2-1	Cancer Ontology Example.....	2-2
6-1	Physical Versioning of Entailment (Rules Index).....	6-3

List of Tables

1-1	MDSYS.SEM_MODEL\$ View Columns	1-4
1-2	MDSYS.SEMM_model-name View Columns	1-4
1-3	MDSYS.RDF_VALUE\$ Table Columns	1-5
1-4	MDSYS.SEMR_rulebase-name View Columns	1-9
1-5	MDSYS.SEM_RULEBASE_INFO View Columns	1-9
1-6	MDSYS.SEM_RULES_INDEX_INFO View Columns	1-10
1-7	MDSYS.SEM_RULES_INDEX_DATASETS View Columns	1-11
1-8	MDSYS.SEM_MODEL\$ View Column Explanations for Virtual Models	1-13
1-9	MDSYS.SEM_VMODEL_INFO View Columns	1-13
1-10	MDSYS.SEM_VMODEL_DATASETS View Columns	1-14
1-11	Semantic Metadata Tables and Views	1-15
1-12	Built-in Functions Available for FILTER Clause	1-24
1-13	Semantic Technology Software Objects: Old and New Names	1-45
2-1	PATIENTS Table Example Data	2-2
2-2	RDFS/OWL Vocabulary Constructs Included in Each Supported Rulebase	2-3
2-3	MDSYS.SEMCL_entailment_name View Columns	2-10
4-1	MDSYS.RDFCTX_POLICIES View Columns	4-13
4-2	MDSYS.RDFCTX_INDEX_POLICIES View Columns	4-13
4-3	MDSYS.RDFCTX_INDEX_EXCEPTIONS View Columns	4-14
5-1	MDSYS.RDFVPD_POLICIES View Columns	5-10
5-2	MDSYS.RDFVPD_MODELS View Columns	5-10
5-3	MDSYS.RDFVPD_POLICY_CONSTRAINTS View Columns	5-11
5-4	MDSYS.RDFVPD_PREDICATE_MDATA View Columns	5-11
5-5	MDSYS.RDFVPD_RESOURCE_REL View Columns	5-12
5-6	MDSYS.RDFOLS_SECURE_RESOURCE View Columns	5-20
7-1	Functions and Return Values for my_strlen Example	7-20
7-2	PL/SQL Subprograms and Corresponding Jena Adapter Java Class and Methods ...	7-26
8-1	PL/SQL Subprograms and Corresponding Sesame Adapter Java Class and Methods	8-21
9-1	Inferencing Keywords for inf_components_in Parameter	9-21
9-2	SEM_RDFSA Package Constants for label_gen Parameter	9-24
12-1	SEM_RDFSA Package Constants for rdlsa_options Parameter	12-5

Preface

Oracle Database Semantic Technologies Developer's Guide provides usage and reference information about Oracle Database Enterprise Edition support for semantic technologies, including storage, inference, and query capabilities for data and ontologies based on Resource Description Framework (RDF), RDF Schema (RDFS), and Web Ontology Language (OWL). The Semantic Technologies feature is licensed with the Oracle Spatial option to Oracle Database Enterprise Edition, and it requires the Oracle Partitioning option to Oracle Database Enterprise Edition.

Note: You must perform certain actions and meet prerequisites before you can use any types, synonyms, or PL/SQL packages related to Oracle semantic technologies support. These actions and prerequisites are explained in [Section A.1](#).

Audience

This guide is intended for those who need to use semantic technology to store, manage, and query semantic data in the database.

You should be familiar with at least the main concepts and techniques for the Resource Description Framework (RDF) and the Web Ontology Language (OWL).

Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible to all users, including users that are disabled. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at <http://www.oracle.com/accessibility/>.

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/support/contact.html> or visit <http://www.oracle.com/accessibility/support.html> if you are hearing impaired.

Related Documents

For an excellent explanation of RDF concepts, see the World Wide Web Consortium (W3C) *RDF Primer* at <http://www.w3.org/TR/rdf-primer/>.

For information about OWL, see the *OWL Web Ontology Language Reference* at <http://www.w3.org/TR/owl-ref/>.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

What's New in Semantic Technologies?

This section describes new and changed semantic technologies features for Oracle Database Release 11.

Release 11.2 Features

The following are new and changed features for Oracle Database 11g Release 2 (11.2).

This release also includes the features that were supplied in the interim patch 7600122 for Release 11.1.0.7.0, which are listed in ["Features Added for Release 11.1.0.7 \(November, 2008\)"](#).

Release 11.2.0.2: Required Actions if Semantic Technologies Installation is Invalid: Further action may be required if your Semantic Technologies installation is invalid after upgrading to Release 11.2.0.2.0. For information, see [Section A.1.4](#).

Jena Adapter for Oracle Database (Updated November, 2010)

The Jena Adapter for Oracle Database provides a Java-based interface to Oracle Semantic Technologies by implementing the well-known Jena Graph and Model APIs. For information about downloading and using the Jena Adapter, see [Chapter 7](#).

Note: An update of the Jena Adapter was made available in November, 2010. For information about the new features in that update, see the "readme" file included in the download .zip file.

Enhanced Optimizer Hint Support in SEM_MATCH (11.2.0.2)

Effective with Release 11.2.0.2, you can embed inline HINT0 query optimizer hints using SPARQL comments in SEM_MATCH, which allows optimizer hints to be associated with non-root BGPs in a SPARQL query. In addition, new hints have been introduced to influence joins between BGPs. For information, see [Section 1.6.3, "Inline Query Optimizer Hints"](#).

Full-Text Indexing and Searching for RDF Terms (11.2.0.2)

Effective with Release 11.2.0.2, you can create an Oracle Text index on the MDSYS.RDF_VALUE\$ table and use the `orardf:textContains` SPARQL FILTER function to execute efficient full-text searches in semantic queries. For information, see [Section 1.6.4, "Full-Text Search"](#).

OLS Triple-Level Security (Added in Patch 9819833 in June 2010)

Oracle Label Security (OLS) for RDF data provides the triple-level security option, in addition to the resource-level security previously available. Triple-level provides superior performance and ease of use, and is described in [Section 5.2.1](#).

Features Added in Patch to Release 11.2 (Released March 2010)

The following features are included in a Release 11.2 Semantic Technologies patch that was made available on the Oracle Technology Network (OTN) in March 2010. You must apply that patch in order to be able to use these features.

- The recommended best practices in [Section 1.6.5.1, "FILTER Constructs Involving xsd:dateTime, xsd:date, and xsd:time"](#) and [Section 1.6.5.2, "Function-Based Indexes for FILTER Constructs Involving xsd Data Types"](#)
- The functions with names in the form `SEM_APIS.GETV$...` in [Chapter 9, "SEM_APIS Package Subprograms"](#)

In addition, [Section A.1.2, "Upgrading Semantic Technologies Support from Release 11.1"](#) has been expanded to include [Section A.1.2.1, "Handling of Empty RDF Literals"](#).

Sesame Adapter for Oracle Database

The Sesame Adapter for Oracle Database integrates the popular Sesame Java APIs with Oracle Semantic Technologies support. For information about downloading and using the Sesame Adapter, see [Chapter 8](#).

Note: Support for the Sesame Adapter was provided in a patch that was made available in January, 2010, on the Oracle Technology Network (OTN), and is updated in a patch made available in March or April, 2010.

Semantic Indexing for Documents

You can use semantic indexing to enable queries on information extracted from unstructured documents. Documents indexed semantically can be searched using the `SEM_CONTAINS` operator within a standard SQL query. For information about using semantic indexing, see [Chapter 4](#).

The `SEM_RDFCTX` PL/SQL package contains subprograms to manage extractor policies and semantic indexes created for documents. This package is documented in [Chapter 11](#).

Virtual Private Database (VPD) and Oracle Label Security (OLS) Support

You can enforce a fine-grained access control mechanism for RDF data by using either the Virtual Private Database (VPD) or Oracle Label Security (OLS) feature of Oracle Database, as explained in [Chapter 5](#).

Workspace Manager Support for RDF Data

You can use Oracle Workspace Manager to version-enable RDF data in the semantic data store, as explained in [Chapter 6](#).

New Procedures to Enable, Downgrade, and Remove Semantic Technologies Support

The procedures for enabling, downgrading, and removing semantic technologies support in the database have been redesigned. These procedures are explained in [Appendix A](#).

Note that you still must perform certain actions and meet prerequisites before you can use any types, synonyms, or PL/SQL packages related to Oracle semantic technologies support. These actions and prerequisites are explained in [Section A.1](#).

Optimized owl:sameAs Inference

You can optimize the performance of owl:sameAs inference, as explained in [Section 2.2.8](#).

Optimizing Entailment Performance Through Compact Structures

You can specify RAW8=T in the options parameter to the [SEM_APIS.CREATE_ENTAILMENT](#) procedure, to cause RAW8 datatypes to be used instead of NUMBER in many intermediate tables created during the inference process. This option can improve entailment performance by up to 30% in some cases.

Incremental Inference

You can use incremental inference update entailments (rules indexes) efficiently after triple additions, as explained in [Section 2.2.9](#).

Parallel Inference

You can use parallel inference to improve inference performance by taking advantage of the capabilities of a multi-core or multi-CPU architectures, as explained in [Section 2.2.10](#).

Filter and Union Support in Curly Brace Syntax for SEM_MATCH

You can now specify FILTER or UNION, or both, in addition to OPTIONAL as keywords in the curly brace syntax supported for the SEM_MATCH table function. These keywords are explained in [Section 1.6.2](#).

Simple Knowledge Organization System (SKOS) Support

You can perform inferencing based on a core subset of the Simple Knowledge Organization System (SKOS) data model, as explained in [Chapter 3](#).

Inference Beyond OWLPrime

You can specify additional inference components to cover OWL constructs, such as owl:intersectionOf and owl:unionOf, as explained in [Table 9-1, "Inferencing Keywords for inf_components_in Parameter"](#) in the Usage Notes for the [SEM_APIS.CREATE_ENTAILMENT](#) procedure in [Chapter 9](#).

Systematized Nomenclature of Medicine - Clinical Terms (SNOMED CT) Support

The current release includes a built-in rulebase that supports the expressiveness of Systematized Nomenclature of Medicine - Clinical Terms (SNOMED CT) terminology. To include this support, specify the SNOMED keyword in the inf_components_in parameter in the call to the [SEM_APIS.CREATE_ENTAILMENT](#) procedure .

New SEM_APIS Package Subprograms

The following subprograms have been added to the SEM_APIS PL/SQL package, which is documented in [Chapter 9](#).

- [SEM_APIS.MERGE_MODELS](#)
- [SEM_APIS.REMOVE_DUPLICATES](#)
- [SEM_APIS.RENAME_MODEL](#)
- [SEM_APIS.SWAP_NAMES](#)

Parameters for SEM_PERF.GATHER_STATISTICS

The [SEM_PERF.GATHER_STATS](#) procedure now accepts two parameters, both optional: `just_on_values_table` and `parallel`. This procedure is documented in [Chapter 10](#).

SEM_APIS.*_RULES_INDEX Subprograms Deprecated

In the SEM_APIS PL/SQL package, the subprograms containing "_RULES_INDEX" in their names are deprecated and removed from this manual. Instead, you should use subprograms containing "_ENTAILMENT" in their names:

- Instead of [SEM_APIS.ALTER_SEM_INDEX_ON_RULES_INDEX](#), use [SEM_APIS.ALTER_SEM_INDEX_ON_ENTAILMENT](#).
- Instead of [SEM_APIS.ANALYZE_RULES_INDEX](#), use [SEM_APIS.ANALYZE_ENTAILMENT](#).
- Instead of [SEM_APIS.CREATE_RULES_INDEX](#), use [SEM_APIS.CREATE_ENTAILMENT](#).
- Instead of [SEM_APIS.DROP_RULES_INDEX](#), use [SEM_APIS.DROP_ENTAILMENT](#).
- Instead of [SEM_APIS.LOOKUP_RULES_INDEX](#), use [SEM_APIS.LOOKUP_ENTAILMENT](#).

The old "*_RULES_INDEX" formats will continue to work, but you are encouraged to switch to using the "*_ENTAILMENT" subprograms.

Note that several metadata views still include "RULES_INDEX" in their names.

The terms *entailment* and *rules index* are synonyms in this manual, although *entailment* is used predominantly

Release 11.1 Features

The following are new and changed features for Oracle Database 11g Release 1 (11.1).

Features Added for Release 11.1.0.7 (November, 2008)

This section describes features that are included in interim patch 7600122 for Release 11.1.0.7.0, which was made available on Oracle *MetaLink* in November, 2008.

- Support for virtual models (see [Section 1.3.8](#))
- Curly brace syntax for SEM_MATCH graph pattern, including support for the OPTIONAL construct (see [Section 1.6.2](#))
- Using HINT0 ("hint-zero") in a SEM_MATCH query (see [Section 1.6](#))
- New columns returned from SEM_MATCH: `id`, `_prefix`, `_suffix` (see [Section 1.6](#))

- Ability to create and manage semantic network indexes on models and rules indexes (see [Section 1.8](#))
- [SEM_APIS.BULK_LOAD_FROM_STAGING_TABLE](#) procedure: New options in the flags parameter `join_hint` for tasks IZC, MBV, and MBT; `parallel=n`)
- Simplification of staging table definition (fewer columns) and privilege requirements (see [Section 1.7.1](#))
- Simpler event tracing during bulk load (see the information about the new `RDF$SET_TAB` table in [Section 1.7.1.1](#))

Storage Model Enhancements and Migration

The storage model has been enhanced to support OWL inferencing: some internal data structures and indexes have been changed, added, and removed. These changes also result in enhanced performance.

Because of the extent of these changes, if you have semantic data that you used with the previous release, you must upgrade that data to migrate it to the new format before you can use any new features for this release. For more information, see [Appendix A, "Enabling, Downgrading, or Removing Semantic Technologies Support"](#).

Support for OWL Inferencing

Support has been added to support storing, validating, and querying Web Ontology Language (OWL)-based ontologies. Support is provided for a subset of the OWL DL language.

To query ontology data, you can use table functions and operators that examine semantic relationships, such as `SEM_MATCH`, `SEM_RELATED`, and `SEM_DISTANCE`.

New Bulk Loading Interface for Improved Performance

You can improve performance for bulk loading of semantic data in bulk using a staging table and calling the [SEM_APIS.BULK_LOAD_FROM_STAGING_TABLE](#) procedure. For more information, see [Section 1.7.1](#).

Ontology-Assisted Querying of Relational Data

You can go beyond syntactic matching to perform semantic relatedness-based querying of relational data, by associating an ontology with the data and using the new `SEM_RELATED` operator (and optionally its `SEM_DISTANCE` ancillary operator). The new `SEM_INDEXTYPE` index type improves performance for semantic queries.

Required Procedure for Using Semantic Technology Support

Before you can use any types, synonyms, or PL/SQL packages related to Oracle semantic technologies support, you must enable support for semantic technologies. For more information, see [Appendix A, "Enabling, Downgrading, or Removing Semantic Technologies Support"](#).

Oracle Database Semantic Technologies Overview

This chapter describes the support in Oracle Database Enterprise Edition for semantic technologies, specifically Resource Description Framework (RDF) and a subset of the Web Ontology Language (OWL). It assumes that you are familiar with the major concepts associated with RDF and OWL, such as {subject, predicate, object} triples, URIs, blank nodes, plain and typed literals, and ontologies. This chapter does not explain these concepts in detail, but focuses instead on how the concepts are implemented in Oracle.

- For an excellent explanation of RDF concepts, see the World Wide Web Consortium (W3C) *RDF Primer* at <http://www.w3.org/TR/rdf-primer/>.
- For information about OWL, see the *OWL Web Ontology Language Reference* at <http://www.w3.org/TR/owl-ref/>.

The PL/SQL subprograms for working with semantic data are in the SEM_APIS package, which is documented in [Chapter 9](#).

The RDF and OWL support are features of Oracle Spatial, which must be installed for these features to be used. However, the use of RDF and OWL is not restricted to spatial data.

This chapter contains the following major sections:

- [Section 1.1, "Introduction to Oracle Semantic Technologies"](#)
- [Section 1.2, "Semantic Data Modeling"](#)
- [Section 1.3, "Semantic Data in the Database"](#)
- [Section 1.4, "Semantic Metadata Tables and Views"](#)
- [Section 1.5, "Semantic Data Types, Constructors, and Methods"](#)
- [Section 1.6, "Using the SEM_MATCH Table Function to Query Semantic Data"](#)
- [Section 1.7, "Loading and Exporting Semantic Data"](#)
- [Section 1.8, "Using Semantic Network Indexes"](#)
- [Section 1.9, "Quick Start for Using Semantic Data"](#)
- [Section 1.10, "Semantic Data Examples \(PL/SQL and Java\)"](#)
- [Section 1.11, "Software Naming Changes for Semantic Technologies"](#)

For information about OWL concepts and the Oracle Database support for OWL capabilities, see [Chapter 2](#).


Required Actions to Enable Semantic Technologies Support: Before performing any operations described in this guide, you must enable semantic technologies support in the database and meet other prerequisites, as explained in [Section A.1, "Enabling Semantic Technologies Support"](#).

Release 11.2.0.2: Required Actions if Semantic Technologies Installation is Invalid: Further action may be required if your Semantic Technologies installation is invalid after upgrading to Release 11.2.0.2.0. For information, see [Section A.1.4](#).

1.1 Introduction to Oracle Semantic Technologies

Oracle Database enables you to store semantic data and ontologies, to query semantic data and to perform ontology-assisted query of enterprise relational data, and to use supplied or user-defined inferencing to expand the power of querying on semantic data. [Figure 1-1](#) shows how these capabilities interact.

Figure 1-1 Oracle Semantic Capabilities



As shown in [Figure 1-1](#), the database contains semantic data and ontologies (RDF/OWL models), as well as traditional relational data. To load semantic data, bulk loading is the most efficient approach, although you can load data incrementally using transactional INSERT statements.

Note: If you want to use existing semantic data from a release before Oracle Database 11.1, the data must be upgraded as described in [Section A.1](#).

You can query semantic data and ontologies, and you can also perform ontology-assisted queries of semantic and traditional relational data to find semantic relationships. To perform ontology-assisted queries, use the SEM_RELATED operator, which is described in [Section 2.3](#).

You can expand the power of queries on semantic data by using inferencing, which uses rules in rulebases. Inferencing enables you to make logical deductions based on the data and the rules. For information about using rules and rulebases for inferencing, see [Section 1.3.6](#).

1.2 Semantic Data Modeling

In addition to its formal semantics, semantic data has a simple data structure that is effectively modeled using a directed graph. The metadata statements are represented as triples: nodes are used to represent two parts of the triple, and the third part is represented by a directed link that describes the relationship between the nodes. The triples are stored in a semantic data network. In addition, information is maintained about specific semantic data models created by database users. A user-created **model** has a model name, and refers to triples stored in a specified table column.

Statements are expressed in triples: {subject or resource, predicate or property, object or value}. In this manual, {subject, property, object} is used to describe a triple, and the terms *statement* and *triple* may sometimes be used interchangeably. Each triple is a complete and unique fact about a specific domain, and can be represented by a link in a directed graph.

1.3 Semantic Data in the Database

There is one universe for all semantic data stored in the database. All triples are parsed and stored in the system as entries in tables under the MDSYS schema. A triple {subject, property, object} is treated as one database object. As a result, a single document containing multiple triples results in multiple database objects.

All the subjects and objects of triples are mapped to nodes in a semantic data network, and properties are mapped to network links that have their start node and end node as subject and object, respectively. The possible node types are blank nodes, URIs, plain literals, and typed literals.

The following requirements apply to the specifications of URIs and the storage of semantic data in the database:

- A subject must be a URI or a blank node.
- A property must be a URI.
- An object can be any type, such as a URI, a blank node, or a literal. (However, null values and null strings are not supported.)

1.3.1 Metadata for Models

The MDSYS.SEM_MODEL\$ view contains information about all models defined in the database. When you create a model using the [SEM_APIS.CREATE_SEM_MODEL](#) procedure, you specify a name for the model, as well as a table and column to hold references to the semantic data, and the system automatically generates a model ID.

Oracle maintains the MDSYS.SEM_MODEL\$ view automatically when you create and drop models. Users should never modify this view directly. For example, do not use SQL INSERT, UPDATE, or DELETE statements with this view.

The MDSYS.SEM_MODEL\$ view contains the columns shown in [Table 1-1](#).

Table 1–1 MDSYS.SEM_MODEL\$ View Columns

Column Name	Data Type	Description
OWNER	VARCHAR2(30)	Schema of the owner of the model.
MODEL_ID	NUMBER	Unique model ID number, automatically generated.
MODEL_NAME	VARCHAR2(25)	Name of the model.
TABLE_NAME	VARCHAR2(30)	Name of the table to hold references to semantic data for the model.
COLUMN_NAME	VARCHAR2(30)	Name of the column of type SDO_RDF_TRIPLE_S in the table to hold references to semantic data for the model.
MODEL_TABLESPACE_NAME	VARCHAR2(30)	Name of the tablespace to be used for storing the triples for this model.

When you create a model, a view for the triples associated with the model is also created under the MDSYS schema. This view has a name in the format `SEMM_model-name`, and it is visible only to the owner of the model and to users with suitable privileges. Each `MDSYS.SEMM_model-name` view contains a row for each triple (stored as a link in a network), and it has the columns shown in [Table 1–2](#).

Table 1–2 MDSYS.SEMM_model-name View Columns

Column Name	Data Type	Description
P_VALUE_ID	NUMBER	The VALUE_ID for the text value of the predicate of the triple. Part of the primary key.
START_NODE_ID	NUMBER	The VALUE_ID for the text value of the subject of the triple. Also part of the primary key.
CANON_END_NODE_ID	NUMBER	The VALUE_ID for the text value of the canonical form of the object of the triple. Also part of the primary key.
END_NODE_ID	NUMBER	The VALUE_ID for the text value of the object of the triple
MODEL_ID	NUMBER	The ID for the RDF graph to which the triple belongs. It logically partitions the table by RDF graphs.
COST	NUMBER	(Reserved for future use)
CTXT1	NUMBER	(Reserved for future use)
CTXT2	VARCHAR2(4000)	(Reserved for future use)
DISTANCE	NUMBER	(Reserved for future use)
EXPLAIN	VARCHAR2(4000)	(Reserved for future use)
PATH	VARCHAR2(4000)	(Reserved for future use)
LINK_ID	VARCHAR2(71)	Unique triple identifier value. (It is currently a computed column, and its definition may change in a future release.)

Note: In [Table 1–2](#), for columns P_VALUE_ID, START_NODE_ID, END_NODE_ID, and CANON_END_NODE_ID, the actual ID values are computed from the corresponding lexical values. However, a lexical value may not always map to the same ID value.

1.3.2 Statements

The MDSYS.RDF_VALUE\$ table contains information about the subjects, properties, and objects used to represent RDF statements. It uniquely stores the text values (URIs or literals) for these three pieces of information, using a separate row for each part of each triple.

Oracle maintains the MDSYS.RDF_VALUE\$ table automatically. Users should never modify this view directly. For example, do not use SQL INSERT, UPDATE, or DELETE statements with this view.

The RDF_VALUE\$ table contains the columns shown in [Table 1–3](#).

Table 1–3 MDSYS.RDF_VALUE\$ Table Columns

Column Name	Data Type	Description
VALUE_ID	NUMBER	Unique value ID number, automatically generated.
VALUE_TYPE	VARCHAR2(10)	The type of text information stored in the VALUE_NAME column. Possible values: UR for URI, BN for blank node, PL for plain literal, PL@ for plain literal with a language tag, PLL for plain long literal, PLL@ for plain long literal with a language tag, TL for typed literal, or TLL for typed long literal. A long literal is a literal with more than 4000 bytes.
VNAME_PREFIX	VARCHAR2(4000)	If the length of the lexical value is 4000 bytes or less, this column stores a prefix of a portion of the lexical value. The SEM_APIS.VALUE_NAME_PREFIX function can be used for prefix computation. For example, the prefix for the portion of the lexical value <code><http://www.w3.org/1999/02/22-rdf-syntax-ns#type></code> without the angle brackets is <code>http://www.w3.org/1999/02/22-rdf-syntax-ns#</code> .
VNAME_SUFFIX	VARCHAR2(512)	If the length of the lexical value is 4000 bytes or less, this column stores a suffix of a portion of the lexical value. The SEM_APIS.VALUE_NAME_SUFFIX function can be used for suffix computation. For the lexical value mentioned in the description of the VNAME_PREFIX column, the suffix is <code>type</code> .
LITERAL_TYPE	VARCHAR2(4000)	For typed literals, the type information; otherwise, null. For example, for a row representing a creation date of 1999-08-16, the VALUE_TYPE column can contain TL, and the LITERAL_TYPE column can contain <code>http://www.w3.org/2001/XMLSchema#date</code> .
LANGUAGE_TYPE	VARCHAR2(80)	Language tag (for example, fr for French) for a literal with a language tag (that is, if VALUE_TYPE is PL@ or PLL@). Otherwise, this column has a null value.
CANON_ID	NUMBER	The ID for the canonical lexical value for the current lexical value. (The use of this column may change in a future release.)

Table 1–3 (Cont.) MDSYS.RDF_VALUE\$ Table Columns

Column Name	Data Type	Description
COLLISION_EXT	VARCHAR2(64)	Used for collision handling for the lexical value. (The use of this column may change in a future release.)
CANON_COLLISION_EXT	VARCHAR2(64)	Used for collision handling for the canonical lexical value. (The use of this column may change in a future release.)
LONG_VALUE	CLOB	The character string if the length of the lexical value is greater than 4000 bytes. Otherwise, this column has a null value.
VALUE_NAME	VARCHAR2(4000)	This is a computed column. If length of the lexical value is 4000 bytes or less, the value of this column is the concatenation of the values of VNAME_PREFIX column and the VNAME_SUFFIX column.

1.3.2.1 Triple Uniqueness and Data Types for Literals

Duplicate triples are not stored in the database. To check if a triple is a duplicate of an existing triple, the subject, property, and object of the incoming triple are checked against triple values in the specified model. If the incoming subject, property, and object are all URIs, an exact match of their values determines a duplicate. However, if the object of incoming triple is a literal, an exact match of the subject and property, and a value (canonical) match of the object, determine a duplicate. For example, the following two triples are duplicates:

```
<eg:a> <eg:b> "123"^^http://www.w3.org/2001/XMLSchema#int
<eg:a> <eg:b> "123"^^http://www.w3.org/2001/XMLSchema#unsignedByte
```

The second triple is treated as a duplicate of the first, because "123"^^http://www.w3.org/2001/XMLSchema#int has an equivalent value (is canonically equivalent) to "123"^^http://www.w3.org/2001/XMLSchema#unsignedByte. Two entities are canonically equivalent if they can be reduced to the same value.

To use a non-RDF example, $A * (B - C)$, $A * B - C * A$, $(B - C) * A$, and $-A * C + A * B$ all convert into the same canonical form.

Value-based matching of lexical forms is supported for the following data types:

- **STRING:** plain literal, xsd:string and some of its XML Schema subtypes
- **NUMERIC:** xsd:decimal and its XML Schema subtypes, xsd:float, and xsd:double. (Support is not provided for float/double INF, -INF, and NaN values.)
- **DATETIME:** xsd:datetime, with support for time zone. (Without time zone there are still multiple representations for a single value, for example, "2004-02-18T15:12:54" and "2004-02-18T15:12:54.0000".)
- **DATE:** xsd:date, with or without time zone
- **OTHER:** Everything else. (No attempt is made to match different representations).

Canonicalization is performed when the time zone is present for literals of type xsd:time and xsd:dateTime.

The following namespace definition is used:

```
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
```

The first occurrence of a literal in the RDF_VALUE\$ table is taken as the canonical form and given the VALUE_TYPE value of CPL, CPL@, CTL, CPLL, CPLL@, or CTLL as

appropriate; that is, a C for canonical is prefixed to the actual value type. If a literal with the same canonical form (but a different lexical representation) as a previously inserted literal is inserted into the RDF_VALUE\$ table, the VALUE_TYPE value assigned to the new insert is PL, PL@, TL, PLL, PLL@, or TLL as appropriate.

Canonically equivalent text values having different lexical representations are thus stored in the RDF_VALUE\$ table; however, canonically equivalent triples are not stored in the database.

1.3.3 Subjects and Objects

RDF subjects and objects are mapped to nodes in a semantic data network. Subject nodes are the start nodes of links, and object nodes are the end nodes of links. Non-literal nodes (that is, URIs and blank nodes) can be used as both subject and object nodes. Literals can be used only as object nodes.

1.3.4 Blank Nodes

Blank nodes can be used as subject and object nodes in the semantic network. Blank node identifiers are different from URIs in that they are scoped within a semantic model. Thus, although multiple occurrences of the same blank node identifier within a single semantic model necessarily refer to the same resource, occurrences of the same blank node identifier in two different semantic models do not refer to the same resource.

In an Oracle semantic network, this behavior is modeled by requiring that blank nodes are always reused (that is, are used to represent the same resource if the same blank node identifier is used) within a semantic model, and never reused between two different models. Thus, when inserting triples involving blank nodes into a model, you must use the SDO_RDF_TRIPLE_S constructor that supports reuse of blank nodes.

1.3.5 Properties


Properties are mapped to links that have their start node and end node as subjects and objects, respectively. Therefore, a link represents a complete triple.

When a triple is inserted into a model, the subject, property, and object text values are checked to see if they already exist in the database. If they already exist (due to previous statements in other models), no new entries are made; if they do not exist, three new rows are inserted into the RDF_VALUE\$ table (described in [Section 1.3.2](#)).

1.3.6 Inferencing: Rules and Rulebases

Inferencing is the ability to make logical deductions based on rules. Inferencing enables you to construct queries that perform semantic matching based on meaningful relationships among pieces of data, as opposed to just syntactic matching based on string or other values. Inferencing involves the use of rules, either supplied by Oracle or user-defined, placed in rulebases.

[Figure 1–2](#) shows triple sets being inferred from model data and the application of rules in one or more rulebases. In this illustration, the database can have any number of semantic models, rulebases, and inferred triple sets, and an inferred triple set can be derived using rules in one or more rulebases.

Figure 1–2 Inferencing

A **rule** is an object that can be applied to draw inferences from semantic data. A rule is identified by a name and consists of:

- An IF side pattern for the antecedents
- An optional filter condition that further restricts the subgraphs matched by the IF side pattern
- A THEN side pattern for the consequents

For example, the rule that *a chairperson of a conference is also a reviewer of the conference* could be represented as follows:

```

('chairpersonRule', -- rule name
 '(?r :ChairPersonOf ?c)', -- IF side pattern
 NULL, -- filter condition
 '(?r :ReviewerOf ?c)', -- THEN side pattern
 SEM_ALIASES (SEM_ALIAS('', 'http://some.org/test/'))
)

```

In this case, the rule does not have a filter condition, so that component of the representation is NULL. For best performance, use a single-triple pattern on the THEN side of the rule. If a rule has multiple triple patterns on the THEN side, you can easily break it into multiple rules, each with a single-triple pattern, on the THEN side.

A **rulebase** is an object that contains rules. The following Oracle-supplied rulebases are provided:

- RDFS
- RDF (a subset of RDFS)
- OWLSIF (empty)
- RDFS++ (empty)
- OWLPrime (empty)
- SKOSCORE (empty)

The RDFS and RDF rulebases are created when you call the `SEM_API.CREATE_SEM_NETWORK` procedure to add RDF support to the database. The RDFS rulebase implements the RDFS entailment rules, as described in the World Wide Web Consortium (W3C) *RDF Semantics* document at <http://www.w3.org/TR/rdf-mt/>. The RDF rulebase represents the RDF entailment rules, which are a subset of the RDFS entailment rules. You can see the contents of these rulebases by examining the `MDSYS.SEMR_RDFS` and `MDSYS.SEMR_RDF` views.

You can also create user-defined rulebases using the [SEM_APIS.CREATE_RULEBASE](#) procedure. User-defined rulebases enable you to provide additional specialized inferencing capabilities.

For each rulebase, a system table is created to hold rules in the rulebase, along with a system view with a name in the format `MDSYS.SEMR_rulebase-name` (for example, `MDSYS.SEMR_FAMILY_RB` for a rulebase named `FAMILY_RB`). You must use this view to insert, delete, and modify rules in the rulebase. Each `MDSYS.SEMR_rulebase-name` view has the columns shown in [Table 1-4](#).

Table 1-4 *MDSYS.SEMR_rulebase-name View Columns*

Column Name	Data Type	Description
RULE_NAME	VARCHAR2(30)	Name of the rule
ANTECEDENTS	VARCHAR2(4000)	IF side pattern for the antecedents
FILTER	VARCHAR2(4000)	Filter condition that further restricts the subgraphs matched by the IF side pattern. Null indicates no filter condition is to be applied.
CONSEQUENTS	VARCHAR2(4000)	THEN side pattern for the consequents
ALIASES	SEM_ALIASES	One or more namespaces to be used. (The SEM_ALIASES data type is described in Section 1.6 .)

Information about all rulebases is maintained in the `MDSYS.SEM_RULEBASE_INFO` view, which has the columns shown in [Table 1-5](#) and one row for each rulebase.

Table 1-5 *MDSYS.SEM_RULEBASE_INFO View Columns*

Column Name	Data Type	Description
OWNER	VARCHAR2(30)	Owner of the rulebase
RULEBASE_NAME	VARCHAR2(25)	Name of the rulebase
RULEBASE_VIEW_NAME	VARCHAR2(30)	Name of the view that you must use for any SQL statements that insert, delete, or modify rules in the rulebase
STATUS	VARCHAR2(30)	Contains <code>VALID</code> if the rulebase is valid, <code>INPROGRESS</code> if the rulebase is being created, or <code>FAILED</code> if a system failure occurred during the creation of the rulebase.

[Example 1-1](#) creates a rulebase named `family_rb`, and then inserts a rule named `grandparent_rule` into the `family_rb` rulebase. This rule says that if a person is the parent of a child who is the parent of a child, that person is a grandparent of (that is, has the `grandParentOf` relationship with respect to) his or her child's child. It also specifies a namespace to be used. (This example is an excerpt from [Example 1-25](#) in [Section 1.10.2](#).)

Example 1-1 *Inserting a Rule into a Rulebase*

```
EXECUTE SEM_APIS.CREATE_RULEBASE('family_rb');

INSERT INTO mdsys.semr_family_rb VALUES(
  'grandparent_rule',
  '(?x :parentOf ?y) (?y :parentOf ?z)',
  NULL,
  '(?x :grandParentOf ?z)',
  SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/')));
```

Note that the kind of grandparent rule shown in [Example 1–1](#) can be implemented using the OWL 2 property chain construct. For information about property chain handling, see [Section 3.2.2](#).

You can specify one or more rulebases when calling the SEM_MATCH table function (described in [Section 1.6](#)), to control the behavior of queries against semantic data. [Example 1–2](#) refers to the family_rb rulebase and to the grandParentOf relationship created in [Example 1–1](#), to find all grandfathers (grandparents who are male) and their grandchildren. (This example is an excerpt from [Example 1–25](#) in [Section 1.10.2](#).)

Example 1–2 Using Rulebases for Inferencing

```
-- Select all grandfathers and their grandchildren from the family model.
-- Use inferencing from both the RDFS and family_rb rulebases.
SELECT x, y
  FROM TABLE(SEM_MATCH(
    '(?x :grandParentOf ?y) (?x rdf:type :Male)',
    SEM_Models('family'),
    SEM_Rulebases('RDFS', 'family_rb'),
    SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/'),
    null));
```

For information about support for native OWL inferencing, see [Section 2.2](#).

1.3.7 Entailments (Rules Indexes)

An **entailment** (rules index) is an object containing precomputed triples that can be inferred from applying a specified set of rulebases to a specified set of models. If a SEM_MATCH query refers to any rulebases, an entailment must exist for each rulebase-model combination in the query.

To create an entailment, use the [SEM_APIS.CREATE_ENTAILMENT](#) procedure. To drop (delete) an entailment, use the [SEM_APIS.DROP_ENTAILMENT](#) procedure.

When you create an entailment, a view for the triples associated with the entailment is also created under the MDSYS schema. This view has a name in the format SEMI_ entailment-name, and it is visible only to the owner of the entailment and to users with suitable privileges. Each MDSYS.SEMI_ entailment-name view contains a row for each triple (stored as a link in a network), and it has the same columns as the SEMM_ model-name view, which is described in [Table 1–2](#) in [Section 1.3.1](#).

Information about all entailments is maintained in the MDSYS.SEM_RULES_INDEX_INFO view, which has the columns shown in [Table 1–6](#) and one row for each entailment.

Table 1–6 MDSYS.SEM_RULES_INDEX_INFO View Columns

Column Name	Data Type	Description
OWNER	VARCHAR2(30)	Owner of the entailment
INDEX_NAME	VARCHAR2(25)	Name of the entailment
INDEX_VIEW_NAME	VARCHAR2(30)	Name of the view that you must use for any SQL statements that insert, delete, or modify rules in the entailment

Table 1–6 (Cont.) MDSYS.SEM_RULES_INDEX_INFO View Columns

Column Name	Data Type	Description
STATUS	VARCHAR2(30)	Contains <code>VALID</code> if the entailment is valid, <code>INVALID</code> if the entailment is not valid, <code>INCOMPLETE</code> if the entailment is incomplete (similar to <code>INVALID</code> but requiring less time to re-create), <code>INPROGRESS</code> if the entailment is being created, or <code>FAILED</code> if a system failure occurred during the creation of the entailment.
MODEL_COUNT	NUMBER	Number of models included in the entailment
RULEBASE_COUNT	NUMBER	Number of rulebases included in the entailment

Information about all database objects, such as models and rulebases, related to entailments is maintained in the `MDSYS.SEM_RULES_INDEX_DATASETS` view. This view has the columns shown in [Table 1–7](#) and one row for each unique combination of values of all the columns.

Table 1–7 MDSYS.SEM_RULES_INDEX_DATASETS View Columns

Column Name	Data Type	Description
INDEX_NAME	VARCHAR2(25)	Name of the entailment
DATA_TYPE	VARCHAR2(8)	Type of data included in the entailment. Examples: <code>MODEL</code> and <code>RULEBASE</code>
DATA_NAME	VARCHAR2(25)	Name of the object of the type in the <code>DATA_TYPE</code> column

[Example 1–3](#) creates an entailment named `family_rb_rix_family`, using the `family` model and the `RDFS` and `family_rb` rulebases. (This example is an excerpt from [Example 1–25](#) in [Section 1.10.2](#).)

Example 1–3 Creating an Entailment

```
BEGIN
  SEM_APIS.CREATE_ENTAILMENT(
    'rdfs_rix_family',
    SEM_Models('family'),
    SEM_Rulebases('RDFS', 'family_rb'));
END;
/
```

1.3.8 Virtual Models

A virtual model is a logical graph that can be used in a `SEM_MATCH` query. A virtual model is the result of a `UNION` or `UNION ALL` operation on one or more models and optionally the corresponding entailment.

Using a virtual model can provide several benefits:

- It can simplify management of access privileges for semantic data. For example, assume that you have created three semantic models and one entailment based on the three models and the `OWLPrime` rulebase. Without a virtual model, you must individually grant and revoke access privileges for each model and the entailment. However, if you create a virtual model that contains the three models and the entailment, you will only need to grant and revoke access privileges for the single virtual model.

- It can facilitate rapid updates to semantic models. For example, assume that virtual model VM1 contains model M1 and entailment R1 (that is, VM1 = M1 UNION ALL R1), and assume that semantic model M1_UPD is a copy of M1 that has been updated with additional triples and that R1_UPD is an entailment created for M1_UPD. Now, to have user queries over VM1 go to the updated model and entailment, you can redefine virtual model VM1 (that is, VM1 = M1_UPD UNION ALL R1_UPD).
- It can simplify query specification because querying a virtual model is equivalent to querying multiple models in a SEM_MATCH query. For example, assume that models m1, m2, and m3 already exist, and that an entailment has been created for m1, m2, and m3 using the OWLPrime rulebase. You could create a virtual model vm1 as follows:

```
EXECUTE sem_apis.create_virtual_model('vm1', sem_models('m1', 'm2', 'm3'),
                                     sem_rulebases('OWLPRIME'));
```

To query the virtual model, use the virtual model name as if it were a model in a SEM_MATCH query. For example, the following query on the virtual model:

```
SELECT * FROM TABLE (sem_match('{...}', sem_models('vm1'), null, ...));
```

is equivalent to the following query on all the individual models:

```
SELECT * FROM TABLE (sem_match('{...}', sem_models('m1', 'm2', 'm3'),
                                     sem_rulebases('OWLPRIME'), ...));
```

A SEM_MATCH query over a virtual model will query either the SEMV or SEMU view (SEMU by default and SEMV if the ALLOW_DUP=T option is specified) rather than querying the UNION or UNION ALL of each model and entailment. For information about these views and options, see the reference section for the [SEM_APIS.CREATE_VIRTUAL_MODEL](#) procedure.

Note that you cannot use Oracle Workspace Manager version-enabling on a model that participates in a virtual model. (Workspace Manager support for RDF data is described in [Chapter 6](#).)

Virtual models use views (described later in this section) and add some metadata entries, but do not significantly increase system storage requirements.

To create a virtual model, use the [SEM_APIS.CREATE_VIRTUAL_MODEL](#) procedure. To drop (delete) a virtual model, use the [SEM_APIS.DROP_VIRTUAL_MODEL](#) procedure. A virtual model is dropped automatically if any of its component models, rulebases, or entailment are dropped.

To query a virtual model, specify the virtual model name in the models parameter of the SEM_MATCH table function, as shown in [Example 1-4](#).

Example 1-4 Querying a Virtual Model

```
SELECT COUNT(protein)
FROM TABLE (SEM_MATCH (
  '(?protein rdf:type :Protein)
  (?protein :citation ?citation)
  (?citation :author "Bairoch A.")',
  SEM_MODELS('UNIPROT_VM'),
  NULL,
  SEM_ALIASES(SEM_ALIAS('', 'http://purl.uniprot.org/core/')),
  NULL,
  NULL,
  'ALLOW_DUP=T'));
```

For information about the SEM_MATCH table function, see [Section 1.6](#), which includes information using certain attributes when querying a virtual model.

When you create a virtual model, an entry is created for it in the MDSYS.SEM_MODEL\$ view, which is described in [Table 1-1](#) in [Section 1.3.1](#). However, the values in several of the columns are different for virtual models as opposed to semantic models, as explained in [Table 1-8](#).

Table 1-8 MDSYS.SEM_MODEL\$ View Column Explanations for Virtual Models

Column Name	Data Type	Description
OWNER	VARCHAR2(30)	Schema of the owner of the virtual model
MODEL_ID	NUMBER	Unique model ID number, automatically generated. Will be a negative number, to indicate that this is a virtual model.
MODEL_NAME	VARCHAR2(25)	Name of the virtual model
TABLE_NAME	VARCHAR2(30)	Null for a virtual model
COLUMN_NAME	VARCHAR2(30)	Null for a virtual model
MODEL_TABLESPACE_NAME	VARCHAR2(30)	Null for a virtual model

Information about all virtual models is maintained in the MDSYS.SEM_VMODEL_INFO view, which has the columns shown in [Table 1-9](#) and one row for each virtual model.

Table 1-9 MDSYS.SEM_VMODEL_INFO View Columns

Column Name	Data Type	Description
OWNER	VARCHAR2(30)	Owner of the virtual model
VIRTUAL_MODEL_NAME	VARCHAR2(25)	Name of the virtual model
UNIQUE_VIEW_NAME	VARCHAR2(30)	Name of the view that contains unique triples in the virtual model, or null if the view was not created
DUPLICATE_VIEW_NAME	VARCHAR2(30)	Name of the view that contains duplicate triples (if any) in the virtual model
STATUS	VARCHAR2(30)	Contains VALID if the associated entailment is valid, INVALID if the entailment is not valid, INCOMPLETE if the entailment is incomplete (similar to INVALID but requiring less time to re-create), INPROGRESS if the entailment is being created, FAILED if a system failure occurred during the creation of the entailment, or NORIDX if no entailment is associated with the virtual model.
MODEL_COUNT	NUMBER	Number of models in the virtual model
RULEBASE_COUNT	NUMBER	Number of rulebases used for the virtual model
RULES_INDEX_COUNT	NUMBER	Number of entailments in the virtual model

Information about all objects (models, rulebases, and entailment) related to virtual models is maintained in the MDSYS.SEM_VMODEL_DATASETS view. This view has

the columns shown in [Table 1–10](#) and one row for each unique combination of values of all the columns.

Table 1–10 *MDSYS.SEM_VMODEL_DATASETS View Columns*

Column Name	Data Type	Description
VIRTUAL_MODEL_NAME	VARCHAR2(25)	Name of the virtual model
DATA_TYPE	VARCHAR2(8)	Type of object included in the virtual model. Examples: MODEL for a semantic model, RULEBASE for a rulebase, or RULEIDX for an entailment
DATA_NAME	VARCHAR2(25)	Name of the object of the type in the DATA_TYPE column

1.3.9 Semantic Data Security Considerations

The following database security considerations apply to the use of semantic data:

- When a model or entailment is created, the owner gets the SELECT privilege with the GRANT option on the associated view. Users that have the SELECT privilege on these views can perform SEM_MATCH queries against the associated model or entailment.
- When a rulebase is created, the owner gets the SELECT, INSERT, UPDATE, and DELETE privileges on the rulebase, with the GRANT option. Users that have the SELECT privilege on a rulebase can create an entailment that includes the rulebase. The INSERT, UPDATE, and DELETE privileges control which users can modify the rulebase and how they can modify it.
- To perform data manipulation language (DML) operations on a model, a user must have DML privileges for the corresponding base table.
- The creator of the base table corresponding to a model can grant privileges to other users.
- To perform data manipulation language (DML) operations on a rulebase, a user must have the appropriate privileges on the corresponding database view.
- The creator of a model can grant SELECT privileges on the corresponding database view to other users.
- A user can query only those models for which that user has SELECT privileges to the corresponding database views.
- Only the creator of a model or a rulebase can drop it.

1.4 Semantic Metadata Tables and Views

Oracle Database maintains several tables and views in the MDSYS schema to hold metadata related to semantic data. (Some of these tables and views are created by the [SEM_APIS.CREATE_SEM_NETWORK](#) procedure, as explained in [Section 1.9](#), and some are created only as needed.) [Table 1–11](#) lists the tables and views in alphabetical order. (In addition, several tables and views are created for Oracle internal use, and these are accessible only by users with DBA privileges.)

Table 1–11 Semantic Metadata Tables and Views

Name	Contains Information About	Described In
RDF_VALUES\$	Subjects, properties, and objects used to represent statements	Section 1.3.2
RDFOLS_SECURE_RESOURCE	Resources secured with Oracle Label Security (OLS) policies and the sensitivity labels associated with these resources	Section 5.2.2.6
RDFVPD_MODELS	RDF models and their associated VPD policies	Section 5.1.5
RDFVPD_POLICIES	All VPD policies defined in the schema or the policies to which the user has FULL access	Section 5.1.4
RDFVPD_POLICY_CONSTRAINTS	Constraints defined in the VPD policy that are accessible to the current user	Section 5.1.6
RDFVPD_PREDICATE_METADATA	Predicate metadata associated with a VPD policy	Section 5.1.7
RDFVPD_RESOURCE_REL	Subclass, subproperty, and equivalence property relationships that are defined between resources in a VPD policy	Section 5.1.8
SEM_MODEL\$	All models defined in the database	Section 1.3.1
SEMM_ <i>model-name</i>	Triples in the specified model	Section 1.3.1
SEM_RULEBASE_INFO	Rulebases	Section 1.3.6
SEM_RULES_INDEX_DATASETS	Database objects used in entailments	Section 1.3.7
SEM_RULES_INDEX_INFO	Entailments (rules indexes)	Section 1.3.7
SEM_VMODEL_INFO	Virtual models	Section 1.3.8
SEM_VMODEL_DATASETS	Database objects used in virtual models	Section 1.3.8
SEMCL_ <i>entailment-name</i>	owl:sameAs clique members and canonical representatives	Section 2.2.8
SEMI_ <i>entailment-name</i>	Triples in the specified entailment	Section 1.3.7
SEMR_ <i>rulebase-name</i>	Rules in the specified rulebase	Section 1.3.6
SEMU_ <i>virtual-model-name</i>	Unique triples in the virtual model	Section 1.3.8
SEMV_ <i>virtual-model-name</i>	Triples in the virtual model	Section 1.3.8

1.5 Semantic Data Types, Constructors, and Methods

The SDO_RDF_TRIPLE object type represents semantic data in triple format, and the SDO_RDF_TRIPLE_S object type (the _S for storage) stores persistent semantic data in the database. The SDO_RDF_TRIPLE_S type has references to the data, because the actual semantic data is stored only in the central RDF schema. This type has methods to retrieve the entire triple or part of the triple.

Note: Blank nodes are always reused within an RDF model and cannot be reused across models

The SDO_RDF_TRIPLE type is used to display triples, whereas the SDO_RDF_TRIPLE_S type is used to store the triples in database tables.

The SDO_RDF_TRIPLE object type has the following attributes:

```
SDO_RDF_TRIPLE (
  subject VARCHAR2(4000),
  property VARCHAR2(4000),
  object VARCHAR2(10000))
```

The SDO_RDF_TRIPLE_S object type has the following attributes:

```
SDO_RDF_TRIPLE_S (
  RDF_C_ID NUMBER, -- Canonical object value ID
  SEM_M_ID NUMBER, -- Model ID
  RDF_S_ID NUMBER, -- Subject value ID
  RDF_P_ID NUMBER, -- Property value ID
  RDF_O_ID NUMBER) -- Object value ID
```

The SDO_RDF_TRIPLE_S type has the following methods that retrieve a triple or a part (subject, property, or object) of a triple:

```
GET_TRIPLE() RETURNS SDO_RDF_TRIPLE
GET_SUBJECT() RETURNS VARCHAR2
GET_PROPERTY() RETURNS VARCHAR2
GET_OBJECT() RETURNS CLOB
```

[Example 1–5](#) shows the SDO_RDF_TRIPLE_S methods.

Example 1–5 SDO_RDF_TRIPLE_S Methods

```
SELECT a.triple.GET_TRIPLE() AS triple
  FROM articles_rdf_data a WHERE a.id = 1;

TRIPLE(SUBJECT, PROPERTY, OBJECT)
-----
SDO_RDF_TRIPLE('<http://nature.example.com/Article1>', '<http://purl.org/dc/elements/1.1/title>', '<All about XYZ>')

SELECT a.triple.GET_SUBJECT() AS subject
  FROM articles_rdf_data a WHERE a.id = 1;

SUBJECT
-----
<http://nature.example.com/Article1>

SELECT a.triple.GET_PROPERTY() AS property
  FROM articles_rdf_data a WHERE a.id = 1;

PROPERTY
-----
<http://purl.org/dc/elements/1.1/title>

SELECT a.triple.GET_OBJECT() AS object
  FROM articles_rdf_data a WHERE a.id = 1;

OBJECT
-----
<All about XYZ>
```

1.5.1 Constructors for Inserting Triples Without Any Blank Nodes

The following constructor formats are available for inserting triples into a model table. The only difference is that in the second format the data type for the object is CLOB, to accommodate very long literals.

```
SDO_RDF_TRIPLE_S (
  model_name VARCHAR2, -- Model name
  subject    VARCHAR2, -- Subject
  property   VARCHAR2, -- Property
  object     VARCHAR2) -- Object
RETURN      SELF;
```

```
SDO_RDF_TRIPLE_S (
  model_name VARCHAR2, -- Model name
  subject    VARCHAR2, -- Subject
  property   VARCHAR2, -- Property
  object     CLOB) -- Object
RETURN      SELF;
```

```
GET_OBJ_VALUE() RETURN VARCHAR2;
```

[Example 1–6](#) uses the first constructor format to insert a triple.

Example 1–6 SDO_RDF_TRIPLE_S Constructor to Insert a Triple

```
INSERT INTO articles_rdf_data VALUES (2,
  SDO_RDF_TRIPLE_S ('articles', '<http://nature.example.com/Article1>',
    '<http://purl.org/dc/elements/1.1/creator>',
    'Jane Smith'));
```

1.5.2 Constructors for Inserting Triples With or Without Any Blank Nodes

The following constructor formats are available for inserting triples referring to blank nodes into a model table. The only difference is that in the second format the data type for the fourth attribute is CLOB, to accommodate very long literals.

```
SDO_RDF_TRIPLE_S (
  model_name VARCHAR2, -- Model name
  sub_or_bn  VARCHAR2, -- Subject or blank node
  property   VARCHAR2, -- Property
  obj_or_bn  VARCHAR2, -- Object or blank node
  bn_m_id    NUMBER) -- ID of the model from which to reuse the blank node
RETURN      SELF;
```

```
SDO_RDF_TRIPLE_S (
  model_name VARCHAR2, -- Model name
  sub_or_bn  VARCHAR2, -- Subject or blank node
  property   VARCHAR2, -- Property
  object     CLOB, -- Object
  bn_m_id    NUMBER) -- ID of the model from which to reuse the blank node
RETURN      SELF;
```

If the value of `bn_m_id` is positive, it must be the same as the model ID of the target model.

[Example 1–7](#) uses the first constructor format to insert a triple that reuses a blank node for the subject.

Example 1–7 SDO_RDF_TRIPLE_S Constructor to Reusing a Blank Node

```
INSERT INTO nsu_data VALUES (SDO_RDF_TRIPLE_S(
  'nsu',
  ' _:BNSEQN1001A',
  '<http://www.w3.org/1999/02/22-rdf-syntax-ns#type>',
  '<http://www.w3.org/1999/02/22-rdf-syntax-ns#Seq>',
  4));
```

1.6 Using the SEM_MATCH Table Function to Query Semantic Data

To query semantic data, use the SEM_MATCH table function. This function has the following attributes:

```
SEM_MATCH(
  query          VARCHAR2,
  models         SEM_MODELS,
  rulebases     SEM_RULEBASES,
  aliases       SEM_ALIASES,
  filter        VARCHAR2,
  index_status  VARCHAR2,
  options       VARCHAR2
) RETURN ANYDATASET;
```

The `query` attribute is required. The other attributes are optional (that is, each can be a null value).

The `query` attribute is a string literal (or concatenation of string literals) with one or more triple patterns, usually containing variables. (The `query` attribute cannot be a bind variable or an expression involving a bind variable.) A triple pattern is a triple of atoms enclosed in parentheses. Each atom can be a variable (for example, `?x`), a qualified name (for example, `rdf:type`) that is expanded based on the default namespaces and the value of the `aliases` attribute, or a full URI (for example, `<http://www.example.org/family/Male>`). In addition, the third atom can be a numeric literal (for example, `3.14`), a plain literal (for example, `"Herman"`), a language-tagged plain literal (for example, `"Herman"@en`), or a typed literal (for example, `"123"^^xsd:int`).

For example, the following `query` attribute specifies three triple patterns to find grandfathers (that is, grandparents who are also male) and the height of each of their grandchildren:

```
'(?x :grandParentOf ?y) (?x rdf:type :Male) (?y :height ?h)'
```

The `models` attribute identifies the model or models to use. Its data type is SEM_MODELS, which has the following definition: TABLE OF VARCHAR2 (25). If you are querying a virtual model, specify only the name of the virtual model and no other models. (Virtual models are explained in [Section 1.3.8](#).)

The `rulebases` attribute identifies one or more rulebases whose rules are to be applied to the query. Its data type is SDO_RDF_RULEBASES, which has the following definition: TABLE OF VARCHAR2 (25). If you are querying a virtual model, this attribute must be null.

The `aliases` attribute identifies one or more namespaces, in addition to the default namespaces, to be used for expansion of qualified names in the query pattern. Its data type is SEM_ALIASES, which has the following definition: TABLE OF SEM_ALIAS, where each SEM_ALIAS element identifies a namespace ID and namespace value. The SEM_ALIAS data type has the following definition: (namespace_id VARCHAR2 (30), namespace_val VARCHAR2 (4000))

The following default namespaces (namespace_id and namespace_val attributes) are used by the SEM_MATCH table function:

```
('rdf', 'http://www.w3.org/1999/02/22-rdf-syntax-ns#')
('rdfs', 'http://www.w3.org/2000/01/rdf-schema#')
('xsd', 'http://www.w3.org/2001/XMLSchema#')
```

You can override any of these defaults by specifying the namespace_id value and a different namespace_val value in the aliases attribute.

The filter attribute identifies any additional selection criteria. If this attribute is not null, it should be a string in the form of a WHERE clause without the WHERE keyword. For example: '(h >= 6)' to limit the result to cases where the height of the grandfather's grandchild is 6 or greater (using the example of triple patterns earlier in this section).

The index_status attribute lets you query semantic data even when the relevant entailment does not have a valid status. (If you are querying a virtual model, this attribute refers to the entailment associated with the virtual model.) If this attribute is null, the query returns an error if the entailment does not have a valid status. If this attribute is not null, it must be the string INCOMPLETE or INVALID. For an explanation of query behavior with different index_status values, see [Section 1.6.1](#).

The options attribute identifies options that can affect the results of queries. Options are expressed as keyword-value pairs. The following options are supported:

- ALL_BGP_HASH and ALL_BGP_NL are global query optimizer hints that specify that all inter-BGP joins (for example, the join between the root BGP and an OPTIONAL BGP) should use the specified join type.

[Example 1–13](#) shows the ALL_BGP_HASH option used in a SEM_MATCH query.

- ALL_ORDERED is a global query optimizer hint that specifies that the triple patterns in each BGP in the query should be evaluated in order. If ALL_ORDERED is used with a HINT0 hint specified in the options attribute, the HINT0 hint overrides the ALL_ORDERED hint for the root BGP.

[Example 1–13](#) shows the ALL_ORDERED option used in a SEM_MATCH query.

- ALLOW_DUP=T generates an underlying SQL statement that performs a "union all" instead of a union of the semantic models and inferred data (if applicable). This option may introduce more rows (duplicate triples) in the result set, and you may need to adjust the application logic accordingly. If you do not specify this option, duplicate triples are automatically removed across all the models and inferred data to maintain the set semantics of merged RDF graphs; however, removing duplicate triples increases query processing time. In general, specifying 'ALLOW_DUP=T' improves performance significantly when multiple semantic models are involved in a SEM_MATCH query.

If you are querying a virtual model, specifying ALLOW_DUP=T causes the SEMV_vm_name view to be queried; otherwise, the SEMU_vm_name view is queried.

- HINT0={<hint-string>} (pronounced and written "hint" and the number zero) specifies one or more keywords with hints to influence the execution plan and results of queries. Conceptually, a graph pattern with n triple patterns and referring to m distinct variables results in an $(n+m)$ -way join: n -way self-join of the target RDF model or models and optionally the corresponding entailment, and then m joins with RDF_VALUE\$ for looking up the values for the m variables. A hint specification affects the join order and join type used for the query execution.

The hint specification, <hint-string>, uses keywords, some of which have parameters consisting of a sequence or set of aliases, or references, for individual

triple patterns and variables used in the query. Aliases for triple patterns are of the form t_i where i refers to the 0-based ordinal numbers of triple patterns in the query. For example, the alias for the first triple pattern in a query is t_0 , the alias for the second one is t_1 , and so on. Aliases for the variables used in a query are simply the names of those variables. Thus, $?x$ will be used in the hint specification as the alias for a variable $?x$ used in the graph pattern.

Hints used for influencing query execution plans include LEADING(<sequence of aliases>), USE_NL(<set of aliases>), USE_HASH(<set of aliases>), and INDEX(<alias> <index_name>). Hints used for influencing the results of queries include GET_CANON_VALUE(<set of aliases for variables>), which ensures that the values returned for the referenced variables will be their canonical lexical forms. These hints have the same format and basic meaning as hints in SQL statements, which are explained in *Oracle Database SQL Language Reference*.

[Example 1-9](#) shows the HINT0 option used in a SEM_MATCH query.

- INF_ONLY=T queries only the entailed graph for the specified models and rulebases.

The SEM_MATCH table function returns an object of type ANYDATASET, with elements that depend on the input variables. In the following explanations, var represents the name of a variable used in the query. For each variable var , the result elements have the following attributes: var , var \$RDFVID, var \$_PREFIX, var \$_SUFFIX, var \$RDFVTYP, var \$RDFCLOB, var \$RDFTYP, and var \$RDFLANG.

In such cases, var has the lexical value bound to the variable, var \$RDFVID has the VALUE_ID of the value bound to the variable, var \$_PREFIX and var \$_SUFFIX are the prefix and suffix of the value bound to the variable, var \$RDFVTYP indicates the type of value bound to the variable (URI, LIT [literal], or BLN [blank node]), var \$RDFCLOB has the lexical value bound to the variable if the value is a long literal, var \$RDFTYP indicates the type of literal bound if a literal is bound, and var \$RDFLANG has the language tag of the bound literal if a literal with language tag is bound. var \$RDFCLOB is of type CLOB, while all other attributes are of type VARCHAR2.

For a literal value or a blank node, its prefix is the value itself and its suffix is null. For a URI value, its prefix is the left portion of the value up to and including the rightmost occurrence of any of the three characters / (slash), # (pound), or : (colon), and its suffix is the remaining portion of the value to the right. For example, the prefix and suffix for the URI value `http://www.example.org/family/grandParentOf` are `http://www.example.org/family/` and `grandParentOf`, respectively.

[Example 1-8](#) selects all grandfathers (grandparents who are male) and their grandchildren from the family model, using inferencing from both the RDFS and family_rb rulebases. (This example is an excerpt from [Example 1-25](#) in [Section 1.10.2](#).)

Example 1-8 SEM_MATCH Table Function

```
SELECT x, y
FROM TABLE(SEM_MATCH(
  '(?x :grandParentOf ?y) (?x rdf:type :Male)',
  SEM_Models('family'),
  SEM_Rulebases('RDFS', 'family_rb'),
  SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/'),
  null));
```

[Example 1-9](#) is functionally the same as [Example 1-8](#), but it adds the HINT0 option.

Example 1–9 HINT0 Option with SEM_MATCH Table Function

```
SELECT x, y
FROM TABLE(SEM_MATCH(
  '(?x :grandParentOf ?y) (?x rdf:type :Male)',
  SEM_Models('family'),
  SEM_Rulebases('RDFS','family_rb'),
  SEM_Aliases(SEM_ALIAS('', 'http://www.example.org/family/')),
  null,
  null,
  'HINT0={LEADING(t0 t1) USE_NL(?x ?y) GET_CANON_VALUE(?x ?y)}'));
```

[Example 1–10](#) uses the Pathway/Genome BioPax ontology to get all chemical compound types that belong to both Proteins and Complexes:

Example 1–10 SEM_MATCH Table Function

```
SELECT t.r
FROM TABLE (SEM_MATCH (
  '(?r rdfs:subClassOf :Proteins)
  (?r rdfs:subClassOf :Complexes)',
  SEM_Models ('BioPax'),
  SEM_Rulebases ('rdfs'),
  SEM_Aliases (SEM_ALIAS('',
'http://www.biopax.org/release1/biopax-release1.owl')),
  NULL)) t;
```

As shown in [Example 1–10](#), the search pattern for the SEM_MATCH table function is specified using SPARQL-like syntax where the variable starts with the question-mark character (?). In this example, the variable ?r must match to the same term, and thus it must be a subclass of both Proteins and Complexes.

To use the SEM_RELATED operator to query an OWL ontology, see [Section 2.3](#).

When you are querying multiple models or querying one or more models and the corresponding entailment, consider using virtual models (explained in [Section 1.3.8](#)) because of the potential performance benefits.

1.6.1 Performing Queries with Incomplete or Invalid Entailments

You can query semantic data even when the relevant entailment does not have a valid status if you specify the string value INCOMPLETE or INVALID for the index_status attribute of the SEM_MATCH table function. (The entailment status is stored in the STATUS column of the MDSYS.SEM_RULES_INDEX_INFO view, which is described in [Section 1.3.7](#). The SEM_MATCH table function is described in [Section 1.6](#).)

The index_status attribute value affects the query behavior as follows:

- If the entailment has a valid status, the query behavior is not affected by the value of the index_status attribute.
- If you provide no value or specify a null value for index_status, the query returns an error if the entailment does not have a valid status.
- If you specify the string INCOMPLETE for the index_status attribute, the query is performed if the status of the entailment is incomplete or valid.
- If you specify the string INVALID for the index_status attribute, the query is performed regardless of the actual status of the entailment (invalid, incomplete, or valid).

However, the following considerations apply if the status of the entailment is incomplete or invalid:

- If the status is incomplete, the content of an entailment may be approximate, because some triples that are inferable (due to the recent insertions into the underlying models) may not actually be present in the entailment, and therefore results returned by the query may be inaccurate.
- If the status is invalid, the content of the entailment may be approximate, because some triples that are no longer inferable (due to recent modifications to the underlying models or rulebases, or both) may still be present in the entailment, and this may affect the accuracy of the result returned by the query. In addition to possible presence of triples that are no longer inferable, some inferable rows may not actually be present in the entailment.

1.6.2 Graph Patterns: Support for Curly Brace Syntax, and OPTIONAL, FILTER, and UNION Keywords

The SEM_MATCH table function accepts the syntax for the graph pattern in which a sequence of triple patterns is enclosed within curly braces. The period is usually required as a separator unless followed by the OPTIONAL, FILTER, or UNION keyword. With this syntax, you can do any combination of the following:

- Use the OPTIONAL construct to retrieve results even in the case of a partial match
- Use the FILTER construct to specify a filter expression in the graph pattern to restrict the solutions to a query
- Use the UNION construct to match one of multiple alternative graph patterns

[Example 1–11](#) is functionally the same as [Example 1–8](#), but it uses the syntax with curly braces and a period to express a graph pattern in the SEM_MATCH table function.

Example 1–11 Curly Brace Syntax

```
SELECT x, y
FROM TABLE(SEM_MATCH(
  '{?x :grandParentOf ?y . ?x rdf:type :Male}',
  SEM_Models('family'),
  SEM_Rulebases('RDFS', 'family_rb'),
  SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/')),
  null));
```

[Example 1–12](#) uses the OPTIONAL construct to modify [Example 1–11](#), so that it also returns, for each grandfather, the names of the games that he plays or null if he does not play any games.

Example 1–12 Curly Brace Syntax and OPTIONAL Construct

```
SELECT x, y, game
FROM TABLE(SEM_MATCH(
  '{?x :grandParentOf ?y . ?x rdf:type :Male .
   OPTIONAL{?x :plays ?game}
  }',
  SEM_Models('family'),
  SEM_Rulebases('RDFS', 'family_rb'),
  SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/')),
  null,
  null,
```

```
'HINT0={LEADING(t0 t1) USE_NL(?x ?y)}});
```

When multiple triple patterns are present in an OPTIONAL graph pattern, values for optional variables are returned only if a match is found for each triple pattern in the OPTIONAL graph pattern. [Example 1–13](#) modifies [Example 1–12](#) so that it returns, for each grandfather, the names of the games both he and his grandchildren play, or null if he and his grandchildren have no such games in common. It also uses global query optimizer hints to specify that triple patterns should be evaluated in order within each BGP and that a hash join should be used to join the root BGP with the OPTIONAL BGP.

Example 1–13 Curly Brace Syntax and Multi-Pattern OPTIONAL Construct

```
SELECT x, y, game
FROM TABLE(SEM_MATCH(
  '{?x :grandParentOf ?y . ?x rdf:type :Male .
  OPTIONAL{?x :plays ?game . ?y :plays ?game}
  }',
  SEM_Models('family'),
  SEM_Rulebases('RDFS','family_rb'),
  SEM_ALIASES(SEM_ALIAS('','http://www.example.org/family/')),
  null,
  'ALL_ORDERED ALL_BGP_HASH'));
```

A single query can contain multiple OPTIONAL graph patterns, which can be nested or parallel. [Example 1–14](#) modifies [Example 1–13](#) with a nested OPTIONAL graph pattern. This example returns, for each grandfather, (1) the games he plays or null if he plays no games and (2) if he plays games, the ages of his grandchildren that play the same game, or null if he has no games in common with his grandchildren. Note that in [Example 1–14](#) a value is returned for ?game even if the nested OPTIONAL graph pattern ?y :plays ?game . ?y :age ?age is not matched.

Example 1–14 Curly Brace Syntax and Nested OPTIONAL Construct

```
SELECT x, y, game, age
FROM TABLE(SEM_MATCH(
  '{?x :grandParentOf ?y . ?x rdf:type :Male .
  OPTIONAL{?x :plays ?game
  OPTIONAL {?y :plays ?game . ?y :age ?age} }
  }',
  SEM_Models('family'),
  SEM_Rulebases('RDFS','family_rb'),
  SEM_ALIASES(SEM_ALIAS('','http://www.example.org/family/')),
  null));
```

[Example 1–15](#) modifies [Example 1–13](#) with a parallel OPTIONAL graph pattern. This example returns, for each grandfather, (1) the games he plays or null if he plays no games and (2) his e-mail address or null if he has no e-mail address. Note that, unlike nested OPTIONAL graph patterns, parallel OPTIONAL graph patterns are treated independently. That is, if an e-mail address is found, it will be returned regardless of whether or not a game was found; and if a game was found, it will be returned regardless of whether an e-mail address was found.

Example 1–15 Curly Brace Syntax and Parallel OPTIONAL Construct

```
SELECT x, y, game, email
FROM TABLE(SEM_MATCH(
  '{?x :grandParentOf ?y . ?x rdf:type :Male .
  OPTIONAL{?x :plays ?game}
```

```

    OPTIONAL{?x :email ?email}
  }',
  SEM_Models('family'),
  SEM_Rulebases('RDFS', 'family_rb'),
  SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/'),
  null));

```

Example 1–16 uses the FILTER construct to modify **Example 1–11**, so that it returns grandchildren information for only those grandfathers who are residents of either NY or CA.

Example 1–16 Curly Brace Syntax and FILTER Construct

```

SELECT x, y
FROM TABLE(SEM_MATCH(
  '{?x :grandParentOf ?y . ?x rdf:type :Male . ?x :residentOf ?z
   FILTER (?z = "NY" || ?z = "CA")}}',
  SEM_Models('family'),
  SEM_Rulebases('RDFS', 'family_rb'),
  SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/'),
  null));

```

In addition to arithmetic operators (+, -, *, /), boolean operators and logical connectives (||, &&, !), and comparison operators (<, >, <=, >=, =, !=), several built-in functions are available for use in FILTER clauses. **Table 1–12** lists built-in functions that you can use in the FILTER clause. In the Description column of **Table 1–12**, *x*, *y*, and *z* are arguments of the appropriate types.

Table 1–12 Built-in Functions Available for FILTER Clause

Function	Description
BOUND(variable)	BOUND(x) returns true if x is bound (that is, non-null) in the result, false otherwise.
DATATYPE(literal)	DATATYPE(x) returns a URI representing the datatype of x.
isBLANK(RDF term)	isBLANK(x) returns true if x is a blank node, false otherwise.
isIRI(RDF term)	isIRI(x) returns true if x is an IRI, false otherwise.
isLITERAL(RDF term)	isLiteral(x) returns true if x is a literal, false otherwise.
isURI(RDF term)	isURI(x) returns true if x is a URI, false otherwise.
LANG(literal)	LANG(x) returns a plain literal serializing the language tag of x.
langMATCHES(literal, literal)	langMATCHES(x, y) returns true if language tag x matches language range y, false otherwise.
REGEX(string, pattern)	REGEX(x,y) returns true if x matches the regular expression y, false otherwise. For more information about the regular expressions supported, see the Oracle Regular Expression Support appendix in <i>Oracle Database SQL Language Reference</i> .
REGEX(string, pattern, flags)	REGEX(x,y,z) returns true if x matches the regular expression y using the options given in z, false otherwise. Available options: 's' – dot all mode ('.' matches any character including the newline character); 'm' – multiline mode ('^' matches the beginning of any line and '\$' matches the end of any line); 'i' – case insensitive mode; 'x' – remove whitespace characters from the regular expression before matching.
sameTERM(RDF term, RDF term)	sameTERM(x, y) returns true if x and y are the same RDF term, false otherwise.

Table 1–12 (Cont.) Built-in Functions Available for FILTER Clause

Function	Description
STR(RDF term)	STR(x) returns a plain literal of the string representation of x (that is, what would be stored in the VALUE_NAME column of MDSYS.RDF_VALUE\$ enclosed within double quotes).

See also the descriptions of the built-in functions defined in the SPARQL query language specification (<http://www.w3.org/TR/rdf-sparql-query/>), to better understand the built-in functions available in SEM_MATCH.

[Example 1–17](#) uses the REGEX built-in function to select all grandfathers that have an Oracle e-mail address. Note that backslash (\) characters in the regular expression pattern must be escaped in the query string; for example, \\. produces the following: pattern \.

Example 1–17 Curly Brace Syntax and FILTER with REGEX and STR Built-In Constructs

```
SELECT x, y, z
FROM TABLE(SEM_MATCH(
  '{?x :grandParentOf ?y . ?x rdf:type :Male . ?x :email ?z
   FILTER (REGEX(STR(?z), "@oracle\\.com$"))}',
  SEM_Models('family'),
  SEM_Rulebases('RDFS', 'family_rb'),
  SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/'),
  null));
```

[Example 1–18](#) uses the UNION construct to modify [Example 1–16](#), so that grandfathers are returned only if they are residents of NY or CA or own property in NY or CA, or if both conditions are true (they reside in and own property in NY or CA).

Example 1–18 Curly Brace Syntax and UNION and FILTER Constructs

```
SELECT x, y
FROM TABLE(SEM_MATCH(
  '{?x :grandParentOf ?y . ?x rdf:type :Male
   {{?x :residentOf ?z} UNION {?x :ownsPropertyIn ?z}}
   FILTER (?z = "NY" || ?z = "CA")}',
  SEM_Models('family'),
  SEM_Rulebases('RDFS', 'family_rb'),
  SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/'),
  null));
```

If you use the syntax with curly braces to express a graph pattern:

- The query always returns canonical lexical forms for the matching values for the variables.
- Any hints specified using HINT0={<hint-string>} (explained in [Section 1.6](#)), should be constructed only on the basis of the portion of the graph pattern outside the OPTIONAL construct. For example, the only valid aliases for use in a hint specification for the query in [Example 1–12](#) are t0, t1, ?x, and ?y.
- Hints are not supported for queries involving UNION.
- The FILTER construct is not supported for variables bound to long literals.

1.6.3 Inline Query Optimizer Hints

In SEM_MATCH, the SPARQL comment construct has been overloaded to allow inline HINT0 query optimizer hints. In SPARQL, the hash (#) character indicates that the remainder of the line is a comment. To associate an inline hint with a particular BGP, place a HINT0 hint string inside a SPARQL comment and insert the comment between the opening curly bracket ({} and the first triple pattern in the BGP. Inline hints enable you to influence the execution plan for each BGP in a query. [Example 1–19](#) shows a query with inline query optimizer hints.

Example 1–19 Inline Query Optimizer Hints

```
SELECT x, y, hp, cp
FROM TABLE(SEM_MATCH(
  '{ # HINT0={ LEADING(t0) USE_NL(?x ?y ?bd) }
    ?x :grandParentOf ?y . ?x rdf:type :Male . ?x :birthDate ?bd
    OPTIONAL { # HINT0={ LEADING(t0 t1) BGP_JOIN(USE_HASH) }
      ?x :homepage ?hp . ?x :cellPhoneNum ?cp }
    }',
  SEM_Models('family'),
  SEM_Rulebases('RDFS', 'family_rb'),
  SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/'),
  null));
```

The BGP_JOIN hint influences inter-BGP joins and has the following syntax: BGP_JOIN(<join_type>), where <join_type> is USE_HASH or USE_NL. [Example 1–19](#) uses the BGP_JOIN(USE_HASH) hint to specify that a hash join should be used when joining the OPTIONAL BGP with its parent BGP.

Inline optimizer hints override any hints passed to SEM_MATCH through the options argument. For example, a global ALL_ORDERED hint applies to each BGP that does not specify an inline optimizer hint, but those BGPs with an inline hint use the inline hint instead of the ALL_ORDERED hint.

1.6.4 Full-Text Search

The Oracle-specific orardf:textContains SPARQL FILTER function uses full-text indexes on the MDSYS.RDF_VALUE\$ table. This function has the following syntax (where orardf is a built-in prefix that expands to <http://xmlns.oracle.com/rdf/>):

```
orardf:textContains(variable, pattern)
```

The first argument to orardf:textContains must be a local variable (that is, a variable present in the BGP that contains the orardf:textContains filter), and the second argument must be a constant plain literal.

For example, orardf:textContains(x, y) returns true if x matches the expression y, where y is a valid expression for the Oracle Text SQL operator CONTAINS. For more information about such expressions, see *Oracle Text Reference*.

[Example 1–20](#) is PL/SQL code that creates a full-text index on the MDSYS.RDF_VALUE\$ table and stores the index in the tbs_3 tablespace. To index all lexical components of an RDF term, you should include the following columns of the MDSYS.RDF_VALUE\$ table in the index: vname_prefix, vname_suffix, literal_type, language_type, long_value. Do not include the value_name column because this is a virtual column. For more information about creating full-text indexes, see the indexing elements chapter in *Oracle Text Reference*. (When performing large bulk loads into a

semantic network with a text index, the overall load time may be faster if you drop the text index, perform the bulk load, and then re-create the text index.)

Example 1–20 Creating a Full-Text Index on the MDSYS.RDF_VALUE\$ Table

```
begin
  ctx_ddl.create_preference('RDF_VALUE_MULTI', 'MULTI_COLUMN_DATASTORE');
  -- index all components of RDF term
  ctx_ddl.set_attribute('RDF_VALUE_MULTI', 'columns',
    'vname_prefix, vname_suffix, literal_type,
    language_type, long_value');

  -- create a storage preference using the tbs_3 tablespace
  ctx_ddl.create_preference('RDF_VALUE_STORAGE', 'BASIC_STORAGE');

  ctx_ddl.set_attribute('RDF_VALUE_STORAGE', 'I_TABLE_CLAUSE',
    'TABLESPACE tbs_3');
  ctx_ddl.set_attribute('RDF_VALUE_STORAGE', 'K_TABLE_CLAUSE',
    'TABLESPACE tbs_3');
  ctx_ddl.set_attribute('RDF_VALUE_STORAGE', 'R_TABLE_CLAUSE',
    'TABLESPACE tbs_3 LOB(DATA) STORE AS (CACHE)');
  ctx_ddl.set_attribute('RDF_VALUE_STORAGE', 'N_TABLE_CLAUSE',
    'TABLESPACE tbs_3');
  ctx_ddl.set_attribute('RDF_VALUE_STORAGE', 'I_INDEX_CLAUSE',
    'TABLESPACE tbs_3 COMPRESS 2');
  ctx_ddl.set_attribute('RDF_VALUE_STORAGE', 'P_TABLE_CLAUSE',
    'TABLESPACE tbs_3');
  ctx_ddl.set_attribute('RDF_VALUE_STORAGE', 'S_TABLE_CLAUSE',
    'TABLESPACE tbs_3 NOCOMPRESS');

  execute immediate '
create index mdsys.rdf_v$text_idx
on MDSYS.RDF_VALUE$(vname_prefix)
indextype is ctxsys.context
parameters('
  datastore SYS.RDF_VALUE_MULTI
  storage SYS.RDF_VALUE_STORAGE
  sync (on commit) ');
end;
/
```

After creating a text index, you can use the `orardf:textContains` FILTER function in SEM_MATCH queries. [Example 1–21](#) uses `orardf:textContains` to find all grandfathers whose names start with the letter *A* or *B*.

Example 1–21 Full-Text Search

```
SELECT x, y, hp, cp
FROM TABLE(SEM_MATCH(
  '{ ?x :grandParentOf ?y . ?x rdf:type :Male . ?x :name ?n
  FILTER (orardf:textContains(?n, " A% | B% ")) }',
  SEM_Models('family'),
  SEM_Rulebases('RDFS', 'family_rb'),
  SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/'),
    null));
```

1.6.5 Best Practices for Query Performance

This section describes some recommended practices for using the SEM_MATCH table function to query semantic data. It includes the following subsections:

- [Section 1.6.5.1, "FILTER Constructs Involving xsd:dateTime, xsd:date, and xsd:time"](#)
- [Section 1.6.5.2, "Function-Based Indexes for FILTER Constructs Involving xsd Data Types"](#)
- [Section 1.6.5.3, "FILTER Constructs Involving Relational Expressions"](#)
- [Section 1.6.5.4, "Optimizer Statistics"](#)
- [Section 1.6.5.5, "Virtual Models and Semantic Network Indexes"](#)

1.6.5.1 FILTER Constructs Involving xsd:dateTime, xsd:date, and xsd:time

By default, SEM_MATCH complies with the XML Schema standard for comparison of xsd:date, xsd:time, and xsd:dateTime values. According to this standard, when comparing two calendar values c1 and c2 where c1 has an explicitly specified time zone and c2 does not have a specified time zone, c2 is converted into the interval [c2-14:00, c2+14:00]. If c2-14:00 <= c1 <= c2+14:00, then the comparison is undefined and will always evaluate to false. If c1 is outside this interval, then the comparison is defined.

However, the extra logic required to evaluate such comparisons (value with a time zone and value without a time zone) can significantly slow down queries with FILTER constructs that involve calendar values. For improved query performance, you can disable this extra logic by specifying FAST_DATE_FILTER=T in the options parameter of the SEM_MATCH table function. When FAST_DATE_FILTER=T is specified, all calendar values without time zones are assumed to be in Greenwich Mean Time (GMT).

Note that using FAST_DATE_FILTER=T does *not* affect query *correctness* when either (1) all calendar values in the data set have a time zone or (2) all calendar values in the data set do not have a time zone.

1.6.5.2 Function-Based Indexes for FILTER Constructs Involving xsd Data Types

The evaluation of SEM_MATCH queries involving the FILTER construct often requires executing one or more SQL functions against the RDF_VALUE\$ table. For example, the filter (?x < "1929-11-16Z"^^xsd:date) invokes the [SEM_APIS.GETV\\$DATETZVAL](#) function.

Function-based indexes can be used to improve the performance of queries that contain a filter condition involving a typed literal. For example, the following index may speed up evaluation of the filter (?x < "1929-11-16Z"^^xsd:date):

```
CREATE INDEX v_date_idx ON
  MDSYS.RDF_VALUE$ (SEM_APIS.getV$DateTZVal(value_type, vname_prefix,
    vname_suffix, literal_type, language_type));
```

You can use the HINT0 hint to ensure that the created index is used during query evaluation, as shown in Example 1-19, which finds all grandfathers who were born before November 16, 1929.

Example 1–22 Using HINT0 to Ensure Use of Function-Based Index

```
SELECT x, y
FROM TABLE(SEM_MATCH(
  '{?x :grandParentOf ?y . ?x rdf:type :Male . ?x :birthDate ?bd
  FILTER (?bd < "1929-11-16Z"^^xsd:date) }',
  SEM_Models('family'),
  SEM_Rulebases('RDFS', 'family_rb'),
```

```
SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/'),
null, null,
'HINTO={ LEADING(?bd) INDEX(?bd v_date_idx) } FAST_DATE_FILTER=T' );
```

For optimal query performance, you may want to create function-based indexes on the following functions, which are described in [Chapter 9](#):

- [SEM_APIS.GETV\\$NUMERICVAL](#)
- [SEM_APIS.GETV\\$STRINGVAL](#)
- [SEM_APIS.GETV\\$DATETIMETZVAL](#)
- [SEM_APIS.GETV\\$DATETZVAL](#)
- [SEM_APIS.GETV\\$TIMETZVAL](#)

Note, however, that the existence of these function-based indexes on the MDSYS.RDF_VALUE\$ table can significantly slow down bulk load operations. In many cases it may be faster to drop the indexes, perform the bulk load, and then re-create the indexes, as opposed to doing the bulk load with the indexes in place.

1.6.5.3 FILTER Constructs Involving Relational Expressions

The following recommendations apply to FILTER constructs involving relational expressions:

- The `sameTerm` built-in function is more efficient than using `=` or `!=` when comparing two variables in a FILTER clause, so (for example) use `sameTerm(?a, ?b)` instead of `(?a = ?b)` and use `(!sameTerm(?a, ?b))` instead of `(?a != ?b)` whenever possible.
- When comparing values in FILTER expressions, you may get better performance by reducing the use of negation. For example, it is more efficient to evaluate `(?x <= "10"^^xsd:int)` than it is to evaluate the expression `(!(?x > "10"^^xsd:int))`.

1.6.5.4 Optimizer Statistics

Having sufficient statistics for the query optimizer is critical for good query performance. In general, you should gather column group statistics for the PC and PS columns when using the recommended PSCM and PCSM semantic network indexes. For more information, see the section about multicolumn statistics in the chapter about managing optimizer statistics in *Oracle Database Performance Tuning Guide*.

[Example 1–23](#) gathers multi-column statistics for model `m1` and general statistics for the values table in the RDF network.

Example 1–23 Gathering Multicolumn and General Statistics

```
EXECUTE sem_apis.analyze_model('m1',
METHOD_OPT =>'FOR COLUMNS (P_VALUE_ID, CANON_END_NODE_ID) SIZE AUTO');
EXECUTE sem_apis.analyze_model('m1',
METHOD_OPT =>'FOR COLUMNS (P_VALUE_ID, START_NODE_ID) SIZE AUTO');
EXECUTE sem_perf.gather_stats(just_on_values_table=>true);
```

1.6.5.5 Virtual Models and Semantic Network Indexes

The following recommendations apply to the use of multiple semantic models, semantic models plus entailments, and virtual models:

- If you execute SEM_MATCH queries against multiple semantic models or against semantic models plus entailments, you can probably improve query performance

if you create a virtual model (see [Section 1.3.8](#)) that contains all the models and entailments you are querying and then query this single virtual model.

- If your workload contains many queries against virtual models, you can probably improve query performance if you create a semantic network index (see [Section 1.8](#)) with the `index_code` 'PSCM' and drop the default index with `index_code` 'PSCF'.

1.7 Loading and Exporting Semantic Data

To load semantic data into a model, use one or more of the following options:

- Bulk load using a SQL*Loader direct-path load to get data from an N-Triple format into a staging table and then use a PL/SQL procedure to load or append data into the semantic data store, as explained in [Section 1.7.1](#).

This is the fastest option for loading large amounts of data; however, it cannot handle triples containing object values with more than 4000 bytes.

- Batch load using a Java client interface to load or append data from an N-Triple format file into the semantic data store (see [Section 1.7.2](#)).

This option is slower than bulk loading, but it handles triples containing object values with more than 4000 bytes.

- Load into tables using SQL INSERT statements that call the `SDO_RDF_TRIPLE_S` constructor, as explained in [Section 1.7.3](#).

To export semantic data, use the Java API, as described in [Section 1.7.4](#).

1.7.1 Bulk Loading Semantic Data Using a Staging Table

You can load semantic data (and optionally associated non-semantic data) in bulk using a staging table. The data must first be parsed to check for syntax correctness and then loaded into the staging table. Then, you can call the `SEM_APIS.BULK_LOAD_FROM_STAGING_TABLE` procedure (described in [Chapter 9](#)).

The following example shows the format for the staging table, including all required columns and the required names for these columns:

```
CREATE TABLE stage_table (
    RDF$STC_sub varchar2(4000) not null,
    RDF$STC_pred varchar2(4000) not null,
    RDF$STC_obj varchar2(4000) not null
);
```

If you also want to load non-semantic data, specify additional columns for the non-semantic data in the CREATE TABLE statement. The non-semantic column names must be different from the names of the required columns. The following example creates the staging table with two additional columns (SOURCE and ID) for non-semantic attributes.

```
CREATE TABLE stage_table_with_extra_cols (
    source VARCHAR2(4000),
    id NUMBER,
    RDF$STC_sub varchar2(4000) not null,
    RDF$STC_pred varchar2(4000) not null,
    RDF$STC_obj varchar2(4000) not null
);
```

Note: For either form of the CREATE TABLE statement, you may want to add the COMPRESS clause to use table compression, which will reduce the disk space requirements and may improve bulk-load performance.

Both the invoker and the MDSYS user must have the following privileges: SELECT privilege on the staging table, and INSERT privilege on the application table.

You can use the SQL*Loader utility to parse and load semantic data into a staging table. If you installed the demo files from the Oracle Database Examples media (see *Oracle Database Examples Installation Guide*), a sample control file is available at `$ORACLE_HOME/md/demo/network/rdf_demos/bulkload.ctl`. You can modify and use this file.

Objects longer than 4000 bytes cannot be loaded. If you use the sample SQL*Loader control file, triples (rows) containing such long values will be automatically rejected and stored in a SQL*Loader "bad" file.

However, triples containing object values longer than 4000 bytes can be loaded using the following approach:

1. Use the [SEM_APIS.BULK_LOAD_FROM_STAGING_TABLE](#) procedure to load all rows that can be stored in the staging table.
2. Load the remaining rows (that is, the rejected rows when using SQL*Loader with the sample control file) from an N-Triple format file, as described in [Section 1.7.2](#).

1.7.1.1 Recording Event Traces during Bulk Loading

If a table named RDF\$ET_TAB exists in the invoker's schema and if the MDSYS user has been granted the INSERT and UPDATE privileges on this table, event traces for some of the tasks performed during executions of the [SEM_APIS.BULK_LOAD_FROM_STAGING_TABLE](#) procedure will be added to the table. You may find the content of this table useful if you ever need to report any problems in bulk load. The RDF\$ET_TAB table must be created as follows:

```
CREATE TABLE RDF$ET_TAB (
  proc_sid VARCHAR2(30),
  proc_sig VARCHAR2(200),
  event_name varchar2(200),
  start_time timestamp,
  end_time timestamp,
  start_comment varchar2(1000) DEFAULT NULL,
  end_comment varchar2(1000) DEFAULT NULL
);
GRANT INSERT, UPDATE on RDF$ET_TAB to MDSYS;
```

1.7.2 Batch Loading Semantic Data Using the Java API

You can perform a batch load operation using the Java class `oracle.spatial.rdf.client.BatchLoader`, which is packaged in `<ORACLE_HOME>/md/jlib/sdordf.jar`. Before performing a batch load operation, ensure that the following are true:

- The semantic data is in N-Triple format. (Several tools are available for converting RDF/XML to N-Triple format; see the Oracle Technology Network or perform a Web search for information about RDF/XML to N-Triple conversion.)

- Oracle Database Release 11, with Oracle Spatial, is installed, and partitioning is enabled.
- A semantic technologies network, an application table, and its corresponding semantic model have been created in the database.
- The CLASSPATH definition includes `ojdbc5.jar`.
- You are using JDK version 1.5 or later. (You can use the Java version packaged under `<ORACLE_HOME>/jdk/bin`.)

To run the `oracle.spatial.rdf.client.BatchLoader` class, use a command (on a single command line) in the following general form (replacing the sample example database connection information with your own connection information).

- Linux systems:

```
java -Ddb.user=scott -Ddb.password=password -Ddb.host=127.0.0.1 -Ddb.port=1522
-Ddb.sid=orcl -classpath ${ORACLE_HOME}/md/jlib/sdordf.jar:${ORACLE_
HOME}/jdbc/lib/ojdbc5.jar oracle.spatial.rdf.client.BatchLoader <N-TripleFile>
<tablename> <tablespaceName> <modelName>
```

- Windows systems:

```
java -Ddb.user=scott -Ddb.password=password -Ddb.host=127.0.0.1 -Ddb.port=1522
-Ddb.sid=orcl -classpath %ORACLE_HOME%\md\jlib\sdordf.jar;%ORACLE_
HOME%\jdbc\lib\ojdbc5.jar oracle.spatial.rdf.client.BatchLoader <N-TripleFile>
<tablename> <tablespaceName> <modelName>
```

The values for `-Ddb.user` and `-Ddb.password` must correspond either to the owner of the model `<modelName>` or to a DBA user.

By default, `BatchLoader` assumes there are at least two columns, a column named `ID` of type `NUMBER` and a column named `TRIPLE` of type `SDO_RDF_TRIPLE_S`, in the user's application table. However, you can override the default names by using the JVM properties `-DidColumn=<idColumnName>` and `-DtripleColumn=<tripleColumnName>`. Note that the `ID` column is not required; and to prevent `BatchLoader` from generating a sequence-like identifier in the `ID` column for each triple inserted, specify the JVM property `-DjustTriple=true`.

If the application table is not empty and if you want the batch loading to be done in append mode, specify an additional JVM property: `-Dappend=true`. Moreover, in append mode you might want to choose a different starting value for `ID` column in user's application table, and to accomplish this you can add the JVM property `-DstartID=<startingIntegerValue>` to the command line. By default, the `ID` column starts at 1 and is increased sequentially as new triples are inserted into the application table.

To skip the first n triples in `<N-TripleFile>`, add the JVM property `-Dskip=<numberOfTriplesSkipped>` to the command line.

To load an N-Triple file with a character set different from the default, specify the JVM property `-Dcharset=<charsetName>`. For example, `-Dcharset="UTF-8"` will recognize UTF-8 encoding. However, for UTF-8 characters to be stored properly in the N-Triple file, the Oracle database must be configured to use a corresponding universal character set, such as `AL32UTF8`.

The `BatchLoader` class supports loading an N-Triple file in compressed format. If the `<N-TripleFile>` has a file extension of `.zip` or `.jar`, the file will be uncompressed and loaded at the same time.

1.7.2.1 When to Choose Batch Loading

Batch loading is faster than loading semantic data using INSERT statements (described in [Section 1.7.3](#)). However, bulk loading (described in [Section 1.7.1](#)) is much faster than batch loading for large amounts of data. Batch loading is typically a good option when the following conditions are true:

- The data to be loaded is less than a few million triples.
- The data contains a significant amount long literals (longer than 4000 bytes).

1.7.3 Loading Semantic Data Using INSERT Statements

To load semantic data using INSERT statements, the data should be encoded using < > (angle brackets) for URIs, _: (underscore colon) for blank nodes, and " " (quotation marks) for literals. Spaces are not allowed in URIs or blank nodes. Use the SDO_RDF_TRIPLE_S constructor to insert the data, as described in [Section 1.5.1](#). You must have INSERT privilege on the application table.

Note: If URIs are not encoded with < > and literals with " ", statements will still be processed. However, the statements will take longer to load, since they will have to be further processed to determine their VALUE_TYPE values.

The following example includes statements with URIs, a blank node (the model_id for nsu is 4), a literal, a literal with a language tag, and a typed literal:

```
INSERT INTO nsu_data VALUES (SDO_RDF_TRIPLE_S('nsu', '<http://nature.example.com/nsu/rss.rdf>',
  '<http://purl.org/rss/1.0/title>', '"Nature's Science Update"'));
INSERT INTO nsu_data VALUES (SDO_RDF_TRIPLE_S('nsu', ' _:BNSEQN1001A',
  '<http://www.w3.org/1999/02/22-rdf-syntax-ns#type>',
  '<http://www.w3.org/1999/02/22-rdf-syntax-ns#Seq>', 4));
INSERT INTO nsu_data VALUES (SDO_RDF_TRIPLE_S('nsu',
  '<http://nature.example.com/cgi- taf/dynapage. taf?file=/nature/journal/v428/n6978/index.html>',
  '<http://purl.org/dc/elements/1.1/language>', '"English"@en-GB'));
INSERT INTO nature VALUES (SDO_RDF_TRIPLE_S('nsu', '<http://dx.doi.org/10.1038/428004b>',
  '<http://purl.org/dc/elements/1.1/date>', '"2004-03-04"^^xsd:date'));
```

To convert semantic XML data to INSERT statements, you can edit the sample `rss2insert.xsl` XSLT file to convert all the features in the semantic data XML file. The blank node constructor is used to insert statements with blank nodes. After editing the XSLT, download the Xalan XSLT processor (<http://xml.apache.org/xalan>) and follow the installation instructions. To convert a semantic data XML file to INSERT statements using your edited version of the `rss2insert.xsl` file, use a command in the following format:

```
java org.apache.xalan.xslt.Process -in input.rdf -xsl rss2insert.xsl -out
output.nt
```

1.7.4 Exporting Semantic Data

To output semantic data to a file in N-Triple format, use the `NTripleConverter` Java class. The `NDM2NTriple(String, int)` method exports all the triples stored for the specified model.

For information about using the `NTriple` converter class, see the `README.txt` file in the `sdordf_converter.zip` file, which you can download from the Oracle Technology Network.

1.8 Using Semantic Network Indexes

Semantic network indexes are nonunique B-tree indexes that you can add, alter, and drop for use with models and entailments in a semantic network. You can use such indexes to tune the performance of SEM_MATCH queries on the models and entailments in the network. As with any indexes, semantic network indexes enable index-based access that suits your query workload. This can lead to substantial performance benefits, such as in the following example scenarios:

- If your graph pattern is '`{<John> ?p <Mary>}`', you may want to have a usable 'CSP' or 'SCP' index for the target model or models and on the corresponding entailment, if used in the query.
- If your graph pattern is '`{?x <talksTo> ?y . ?z ?p ?y}`', you may want to have a usable semantic network index on the relevant model or models and entailment, with C as the leading key (for example, 'C' or 'CPS').

However, using semantic network indexes can affect overall performance by increasing the time required for DML, load, and inference operations.

You can create and manage semantic network indexes using the following subprograms:

- [SEM_APIS.ADD_SEM_INDEX](#)
- [SEM_APIS.ALTER_SEM_INDEX_ON_MODEL](#)
- [SEM_APIS.ALTER_SEM_INDEX_ON_ENTAILMENT](#)
- [SEM_APIS.DROP_SEM_INDEX](#)

All of these subprograms have an `index_code` parameter, which can contain any sequence of the following letters (without repetition): P, C, S, M, O. These letters used in the `index_code` correspond to the following columns in the SEMM_* and SEMI_* views: P_VALUE_ID, CANON_END_NODE_ID, START_NODE_ID, MODEL_ID, and END_NODE_ID.

The [SEM_APIS.ADD_SEM_INDEX](#) procedure creates a semantic network index that results in creation of a nonunique B-tree index in UNUSABLE status for each of the existing models and entailments. The name of the index is `RDF_LNK_<index_code>_IDX` and the index is owned by MDSYS. This operation is allowed only if the invoker has DBA role. The following example shows creation of the PSCM index with the following key: `<P_VALUE_ID, START_NODE_ID, CANON_END_NODE_ID, MODEL_ID>`.

```
EXECUTE SEM_APIS.ADD_SEM_INDEX('PSCM');
```

After you create a semantic network index, each of the corresponding nonunique B-tree indexes is in the UNUSABLE status, because making it usable can cause significant time and resources to be used, and because subsequent index maintenance operations might involve performance costs that you do not want to incur. You can make a semantic network index usable or unusable for specific models or entailments that you own by calling the [SEM_APIS.ALTER_SEM_INDEX_ON_MODEL](#) and [SEM_APIS.ALTER_SEM_INDEX_ON_ENTAILMENT](#) procedures and specifying 'REBUILD' or 'UNUSABLE' as the command parameter. Thus, you can experiment by making different semantic network indexes usable and unusable, and checking for any differences in performance. For example, the following statement makes the PSCM index usable for the FAMILY model:

```
EXECUTE SEM_APIS.ALTER_SEM_INDEX_ON_MODEL('FAMILY', 'PSCM', 'REBUILD');
```

Also note the following:

- Independent of any semantic network indexes that you create, when a semantic network is created, one of the indexes that is automatically created is an index that you can manage by referring to the `index_code` as 'PSCF' when you call the subprograms mentioned in this section. (The "F" in PSCF stands for "function": a predefined function that returns NULL when `end_node_id` is equal to `canon_end_node_id`, and otherwise returns `end_node_id`. PSCF is very close to PSCO. However, because most triples have the same `canon_end_node_id` and `end_node_id`, using NULL for those cases can save resources when the index is built.)
- When you create a new model or a new entailment, a new nonunique B-tree index is created for each of the semantic network indexes, and each such B-tree index is in the USABLE status.
- Including the MODEL_ID column in a semantic network index key (by including 'M' in the `index_code` value) may improve query performance. This is particularly relevant when virtual models are used.

1.9 Quick Start for Using Semantic Data

To work with semantic data in an Oracle database, follow these general steps:

1. Create a tablespace for the system tables. You must be connected as a user with appropriate privileges to create the tablespace. The following example creates a tablespace named RDF_TBLSPACE:

```
CREATE TABLESPACE rdf_tblspace
  DATAFILE '/oradata/orcl/rdf_tblspace.dat' SIZE 1024M REUSE
  AUTOEXTEND ON NEXT 256M MAXSIZE UNLIMITED
  SEGMENT SPACE MANAGEMENT AUTO;
```

2. Create a semantic data network.

Creating a semantic data network adds semantic data support to an Oracle database. You must create a semantic data network as a user with DBA privileges, specifying a valid tablespace with adequate space. Create the network only once for an Oracle database.

The following example creates a semantic data network using a tablespace named RDF_TBLSPACE (which must already exist):

```
EXECUTE SEM_APIS.CREATE_SEM_NETWORK('rdf_tblspace');
```

3. Connect as the database user under whose schema you will store your semantic data; do not perform the following steps while connected as SYS, SYSTEM, or MDSYS.
4. Create a table to store references to the semantic data. (You do not need to be connected as a user with DBA privileges for this step and the remaining steps.)

This table must contain a column of type SDO_RDF_TRIPLE_S, which will contain references to all data associated with a single model.

The following example creates a table named ARTICLES_RDF_DATA:

```
CREATE TABLE articles_rdf_data (id NUMBER, triple SDO_RDF_TRIPLE_S);
```

5. Create a model.

When you create a model, you specify the model name, the table to hold references to semantic data for the model, and the column of type SDO_RDF_TRIPLE_S in that table.

The following command creates a model named ARTICLES, which will use the table created in the preceding step.

```
EXECUTE SEM_APIS.CREATE_SEM_MODEL('articles', 'articles_rdf_data', 'triple');
```

- Where possible, create Oracle database indexes on conditions that will be specified in the WHERE clause of SELECT statements, to provide better performance for direct queries against the application table's SDO_RDF_TRIPLE_S column. (These indexes are not relevant if the SEM_MATCH table function is being used.) The following example creates such indexes:

```
-- Create indexes on the subjects, properties, and objects
-- in the ARTICLES_RDF_DATA table.
CREATE INDEX articles_sub_idx ON articles_rdf_data (triple.GET_SUBJECT());
CREATE INDEX articles_prop_idx ON articles_rdf_data (triple.GET_PROPERTY());
CREATE INDEX articles_obj_idx ON articles_rdf_data (TO_CHAR(triple.GET_
OBJECT()));
```

After you create the model, you can insert triples into the table, as shown in the examples in [Section 1.10](#).

1.10 Semantic Data Examples (PL/SQL and Java)

This section contains the following PL/SQL examples:

- Section 1.10.1, "Example: Journal Article Information"
- Section 1.10.2, "Example: Family Information"

In addition to the examples in this guide, see the "Semantic Technologies Code Samples and Examples" page on the Oracle Technology Network (http://www.oracle.com/technology/tech/semantic_technologies/sample_code/). That page includes several Java examples.

1.10.1 Example: Journal Article Information

This section presents a simplified PL/SQL example of model for statements about journal articles. [Example 1–24](#) contains descriptive comments, refer to concepts that are explained in this chapter, and uses functions and procedures documented in [Chapter 9](#).

Example 1–24 Using a Model for Journal Article Information

```
-- Basic steps:
-- After you have connected as a privileged user and called
-- SEM_APIS.CREATE_SEM_NETWORK to add RDF support,
-- connect as a regular database user and do the following.
-- 1. For each desired model, create a table to hold its data.
-- 2. For each model, create a model (SEM_APIS.CREATE_RDF_MODEL).
-- 3. For each table to hold semantic data, insert data into the table.
-- 4. Use various subprograms and constructors.

-- Create the table to hold data for the model.
CREATE TABLE articles_rdf_data (id NUMBER, triple SDO_RDF_TRIPLE_S);

-- Create the model.
EXECUTE SEM_APIS.CREATE_RDF_MODEL('articles', 'articles_rdf_data', 'triple');

-- Information to be stored about some fictitious articles:
-- Article1, titled "All about XYZ" and written by Jane Smith, refers
```

```
-- to Article2 and Article3.
-- Article2, titled "A review of ABC" and written by Joe Bloggs,
-- refers to Article3.
-- Seven SQL statements to store the information. In each statement:
-- Each article is referred to by its complete URI The URIs in
-- this example are fictitious.
-- Each property is referred to by the URL for its definition, as
-- created by the Dublin Core Metadata Initiative.

-- Insert rows into the table.

-- Article1 has the title "All about XYZ".
INSERT INTO articles_rdf_data VALUES (1,
  SDO_RDF_TRIPLE_S ('articles', 'http://nature.example.com/Article1',
    'http://purl.org/dc/elements/1.1/title', 'All about XYZ'));

-- Article1 was created (written) by Jane Smith.
INSERT INTO articles_rdf_data VALUES (2,
  SDO_RDF_TRIPLE_S ('articles', 'http://nature.example.com/Article1',
    'http://purl.org/dc/elements/1.1/creator',
    'Jane Smith'));

-- Article1 references (refers to) Article2.
INSERT INTO articles_rdf_data VALUES (3,
  SDO_RDF_TRIPLE_S ('articles',
    'http://nature.example.com/Article1',
    'http://purl.org/dc/terms/references',
    'http://nature.example.com/Article2'));

-- Article1 references (refers to) Article3.
INSERT INTO articles_rdf_data VALUES (4,
  SDO_RDF_TRIPLE_S ('articles',
    'http://nature.example.com/Article1',
    'http://purl.org/dc/terms/references',
    'http://nature.example.com/Article3'));

-- Article2 has the title "A review of ABC".
INSERT INTO articles_rdf_data VALUES (5,
  SDO_RDF_TRIPLE_S ('articles',
    'http://nature.example.com/Article2',
    'http://purl.org/dc/elements/1.1/title',
    'A review of ABC'));

-- Article2 was created (written) by Joe Bloggs.
INSERT INTO articles_rdf_data VALUES (6,
  SDO_RDF_TRIPLE_S ('articles',
    'http://nature.example.com/Article2',
    'http://purl.org/dc/elements/1.1/creator',
    'Joe Bloggs'));

-- Article2 references (refers to) Article3.
INSERT INTO articles_rdf_data VALUES (7,
  SDO_RDF_TRIPLE_S ('articles',
    'http://nature.example.com/Article2',
    'http://purl.org/dc/terms/references',
    'http://nature.example.com/Article3'));

COMMIT;

-- Query semantic data.
```

```

SELECT SEM_APIS.GET_MODEL_ID('articles') AS model_id FROM DUAL;

SELECT SEM_APIS.GET_TRIPLE_ID(
  'articles',
  'http://nature.example.com/Article2',
  'http://purl.org/dc/terms/references',
  'http://nature.example.com/Article3') AS RDF_triple_id FROM DUAL;

SELECT SEM_APIS.IS_TRIPLE(
  'articles',
  'http://nature.example.com/Article2',
  'http://purl.org/dc/terms/references',
  'http://nature.example.com/Article3') AS is_triple FROM DUAL;

-- Use SDO_RDF_TRIPLE_S member functions in queries.

SELECT a.triple.GET_TRIPLE() AS triple
  FROM articles_rdf_data a WHERE a.id = 1;
SELECT a.triple.GET_SUBJECT() AS subject
  FROM articles_rdf_data a WHERE a.id = 1;
SELECT a.triple.GET_PROPERTY() AS property
  FROM articles_rdf_data a WHERE a.id = 1;
SELECT a.triple.GET_OBJECT() AS object
  FROM articles_rdf_data a WHERE a.id = 1;


```

1.10.2 Example: Family Information

This section presents a simplified PL/SQL example of a model for statements about family tree (genealogy) information. [Example 1-24](#) contains descriptive comments, refer to concepts that are explained in this chapter, and uses functions and procedures documented in [Chapter 9](#).

The family relationships in this example reflect the family tree shown in [Figure 1-3](#). This figure also shows some of the information directly stated in the example: Cathy is the sister of Jack, Jack and Tom are male, and Cindy is female.

Figure 1-3 Family Tree for RDF Example



Example 1-25 Using a Model for Family Information

```

-- Basic steps:
-- After you have connected as a privileged user and called
-- SEM_APIS.CREATE_SEM_NETWORK to enable RDF support,
-- connect as a regular database user and do the following.
-- 1. For each desired model, create a table to hold its data.
-- 2. For each model, create a model (SEM_APIS.CREATE_RDF_MODEL).
-- 3. For each table to hold semantic data, insert data into the table.

```

```
-- 4. Use various subprograms and constructors.

-- Create the table to hold data for the model.
CREATE TABLE family_rdf_data (id NUMBER, triple SDO_RDF_TRIPLE_S);

-- Create the model.
execute SEM_APIS.create_rdf_model('family', 'family_rdf_data', 'triple');

-- Insert rows into the table. These express the following information:
-----
-- John and Janice have two children, Suzie and Matt.
-- Matt married Martha, and they have two children:
--   Tom (male, height 5.75) and Cindy (female, height 06.00).
-- Suzie married Sammy, and they have two children:
--   Cathy (height 5.8) and Jack (male, height 6).

-- Person is a class that has two subclasses: Male and Female.
-- parentOf is a property that has two subproperties: fatherOf and motherOf.
-- siblingOf is a property that has two subproperties: brotherOf and sisterOf.
-- The domain of the fatherOf and brotherOf properties is Male.
-- The domain of the motherOf and sisterOf properties is Female.
-----

-- John is the father of Suzie.
INSERT INTO family_rdf_data VALUES (1,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/John',
'http://www.example.org/family/fatherOf',
'http://www.example.org/family/Suzie'));

-- John is the father of Matt.
INSERT INTO family_rdf_data VALUES (2,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/John',
'http://www.example.org/family/fatherOf',
'http://www.example.org/family/Matt'));

-- Janice is the mother of Suzie.
INSERT INTO family_rdf_data VALUES (3,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Janice',
'http://www.example.org/family/motherOf',
'http://www.example.org/family/Suzie'));

-- Janice is the mother of Matt.
INSERT INTO family_rdf_data VALUES (4,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Janice',
'http://www.example.org/family/motherOf',
'http://www.example.org/family/Matt'));

-- Sammy is the father of Cathy.
INSERT INTO family_rdf_data VALUES (5,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Sammy',
'http://www.example.org/family/fatherOf',
'http://www.example.org/family/Cathy'));

-- Sammy is the father of Jack.
INSERT INTO family_rdf_data VALUES (6,
```

```
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Sammy',
'http://www.example.org/family/fatherOf',
'http://www.example.org/family/Jack'));

-- Suzie is the mother of Cathy.
INSERT INTO family_rdf_data VALUES (7,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Suzie',
'http://www.example.org/family/motherOf',
'http://www.example.org/family/Cathy'));

-- Suzie is the mother of Jack.
INSERT INTO family_rdf_data VALUES (8,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Suzie',
'http://www.example.org/family/motherOf',
'http://www.example.org/family/Jack'));

-- Matt is the father of Tom.
INSERT INTO family_rdf_data VALUES (9,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Matt',
'http://www.example.org/family/fatherOf',
'http://www.example.org/family/Tom'));

-- Matt is the father of Cindy
INSERT INTO family_rdf_data VALUES (10,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Matt',
'http://www.example.org/family/fatherOf',
'http://www.example.org/family/Cindy'));

-- Martha is the mother of Tom.
INSERT INTO family_rdf_data VALUES (11,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Martha',
'http://www.example.org/family/motherOf',
'http://www.example.org/family/Tom'));

-- Martha is the mother of Cindy.
INSERT INTO family_rdf_data VALUES (12,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Martha',
'http://www.example.org/family/motherOf',
'http://www.example.org/family/Cindy'));

-- Cathy is the sister of Jack.
INSERT INTO family_rdf_data VALUES (13,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Cathy',
'http://www.example.org/family/sisterOf',
'http://www.example.org/family/Jack'));

-- Jack is male.
INSERT INTO family_rdf_data VALUES (14,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Jack',
'http://www.w3.org/1999/02/22-rdf-syntax-ns#type',
'http://www.example.org/family/Male'));
```

```
-- Tom is male.
INSERT INTO family_rdf_data VALUES (15,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Tom',
'http://www.w3.org/1999/02/22-rdf-syntax-ns#type',
'http://www.example.org/family/Male'));

-- Cindy is female.
INSERT INTO family_rdf_data VALUES (16,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Cindy',
'http://www.w3.org/1999/02/22-rdf-syntax-ns#type',
'http://www.example.org/family/Female'));

-- Person is a class.
INSERT INTO family_rdf_data VALUES (17,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Person',
'http://www.w3.org/1999/02/22-rdf-syntax-ns#type',
'http://www.w3.org/2000/01/rdf-schema#Class'));

-- Male is a subclass of Person.
INSERT INTO family_rdf_data VALUES (18,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Male',
'http://www.w3.org/2000/01/rdf-schema#subClassOf',
'http://www.example.org/family/Person'));

-- Female is a subclass of Person.
INSERT INTO family_rdf_data VALUES (19,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Female',
'http://www.w3.org/2000/01/rdf-schema#subClassOf',
'http://www.example.org/family/Person'));

-- siblingOf is a property.
INSERT INTO family_rdf_data VALUES (20,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/siblingOf',
'http://www.w3.org/1999/02/22-rdf-syntax-ns#type',
'http://www.w3.org/1999/02/22-rdf-syntax-ns#Property'));

-- parentOf is a property.
INSERT INTO family_rdf_data VALUES (21,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/parentOf',
'http://www.w3.org/1999/02/22-rdf-syntax-ns#type',
'http://www.w3.org/1999/02/22-rdf-syntax-ns#Property'));

-- brotherOf is a subproperty of siblingOf.
INSERT INTO family_rdf_data VALUES (22,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/brotherOf',
'http://www.w3.org/2000/01/rdf-schema#subPropertyOf',
'http://www.example.org/family/siblingOf'));

-- sisterOf is a subproperty of siblingOf.
INSERT INTO family_rdf_data VALUES (23,
SDO_RDF_TRIPLE_S('family',
```

```
'http://www.example.org/family/sisterOf',
'http://www.w3.org/2000/01/rdf-schema#subPropertyOf',
'http://www.example.org/family/siblingOf'));

-- A brother is male.
INSERT INTO family_rdf_data VALUES (24,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/brotherOf',
'http://www.w3.org/2000/01/rdf-schema#domain',
'http://www.example.org/family/Male'));

-- A sister is female.
INSERT INTO family_rdf_data VALUES (25,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/sisterOf',
'http://www.w3.org/2000/01/rdf-schema#domain',
'http://www.example.org/family/Female'));

-- fatherOf is a subproperty of parentOf.
INSERT INTO family_rdf_data VALUES (26,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/fatherOf',
'http://www.w3.org/2000/01/rdf-schema#subPropertyOf',
'http://www.example.org/family/parentOf'));

-- motherOf is a subproperty of parentOf.
INSERT INTO family_rdf_data VALUES (27,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/motherOf',
'http://www.w3.org/2000/01/rdf-schema#subPropertyOf',
'http://www.example.org/family/parentOf'));

-- A father is male.
INSERT INTO family_rdf_data VALUES (28,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/fatherOf',
'http://www.w3.org/2000/01/rdf-schema#domain',
'http://www.example.org/family/Male'));

-- A mother is female.
INSERT INTO family_rdf_data VALUES (29,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/motherOf',
'http://www.w3.org/2000/01/rdf-schema#domain',
'http://www.example.org/family/Female'));

-- Use SET ESCAPE OFF to prevent the caret (^) from being
-- interpreted as an escape character. Two carets (^) are
-- used to represent typed literals.
SET ESCAPE OFF;

-- Cathy's height is 5.8 (decimal).
INSERT INTO family_rdf_data VALUES (30,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Cathy',
'http://www.example.org/family/height',
'"5.8"^^xsd:decimal'));

-- Jack's height is 6 (integer).
INSERT INTO family_rdf_data VALUES (31,
```

```

SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Jack',
'http://www.example.org/family/height',
'6'^^xsd:integer));

-- Tom's height is 05.75 (decimal).
INSERT INTO family_rdf_data VALUES (32,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Tom',
'http://www.example.org/family/height',
'05.75'^^xsd:decimal));

-- Cindy's height is 06.00 (decimal).
INSERT INTO family_rdf_data VALUES (33,
SDO_RDF_TRIPLE_S('family',
'http://www.example.org/family/Cindy',
'http://www.example.org/family/height',
'06.00'^^xsd:decimal));

COMMIT;

-- RDFS inferencing in the family model
BEGIN
  SEM_APIS.CREATE_ENTAILMENT(
    'rdfs_rix_family',
    SEM_Models('family'),
    SEM_Rulebases('RDFS'));
END;
/

-- Select all males from the family model, without inferencing.
SELECT m
FROM TABLE(SEM_MATCH(
  '(?m rdf:type :Male)',
  SEM_Models('family'),
  null,
  SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/'),
  null));

-- Select all males from the family model, with RDFS inferencing.
SELECT m
FROM TABLE(SEM_MATCH(
  '(?m rdf:type :Male)',
  SEM_Models('family'),
  SDO_RDF_Rulebases('RDFS'),
  SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/'),
  null));

-- General inferencing in the family model

EXECUTE SEM_APIS.CREATE_RULEBASE('family_rb');

INSERT INTO mdsys.semr_family_rb VALUES(
  'grandparent_rule',
  '(?x :parentOf ?y) (?y :parentOf ?z)',
  NULL,
  '(?x :grandParentOf ?z)',
  SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/')));

COMMIT;

```

```

-- Because a new rulebase has been created, and it will be used in the
-- entailment, drop the preceding entailment and then re-create it.
EXECUTE SEM_APIS.DROP_ENTAILMENT ('rdfs_rix_family');

-- Re-create the entailment.
BEGIN
  SEM_APIS.CREATE_ENTAILMENT(
    'rdfs_rix_family',
    SEM_Models('family'),
    SEM_Rulebases('RDFS','family_rb'));
END;
/

-- Select all grandfathers and their grandchildren from the family model,
-- without inferencing. (With no inferencing, no results are returned.)
SELECT x grandfather, y grandchild
  FROM TABLE(SEM_MATCH(
    '?x :grandParentOf ?y' (?x rdf:type :Male)',
    SEM_Models('family'),
    null,
    SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/')),
    null));

-- Select all grandfathers and their grandchildren from the family model.
-- Use inferencing from both the RDFS and family_rb rulebases.
SELECT x grandfather, y grandchild
  FROM TABLE(SEM_MATCH(
    '?x :grandParentOf ?y' (?x rdf:type :Male)',
    SEM_Models('family'),
    SEM_Rulebases('RDFS','family_rb'),
    SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/')),
    null));

-- Set up to find grandfathers of tall (>= 6) grandchildren
-- from the family model, with RDFS inferencing and
-- inferencing using the "family_rb" rulebase.

UPDATE mdsys.semr_family_rb SET
  antecedents = '?x :parentOf ?y' (?y :parentOf ?z) (?z :height ?h)',
  filter = '(h >= 6)',
  aliases = SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/'))
WHERE rule_name = 'GRANDPARENT_RULE';

-- Because the rulebase has been updated, drop the preceding entailment,
-- and then re-create it.
EXECUTE SEM_APIS.DROP_ENTAILMENT ('rdfs_rix_family');

-- Re-create the entailment.
BEGIN
  SEM_APIS.CREATE_ENTAILMENT(
    'rdfs_rix_family',
    SEM_Models('family'),
    SEM_Rulebases('RDFS','family_rb'));
END;
/

-- Find the entailment that was just created (that is, the
-- one based on the specified model and rulebases).
SELECT SEM_APIS.LOOKUP_ENTAILMENT(SEM_MODELS('family'),

```

```

SEM_RULEBASES('RDFS','family_rb')) AS lookup_entailment FROM DUAL;

-- Select grandfathers of tall (>= 6) grandchildren, and their
-- tall grandchildren.
SELECT x grandfather, y grandchild
FROM TABLE(SEM_MATCH(
  '(?x :grandParentOf ?y) (?x rdf:type :Male)',
  SEM_Models('family'),
  SEM_RuleBases('RDFS','family_rb'),
  SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/')),
  null));

```

1.11 Software Naming Changes for Semantic Technologies

Because the support for semantic data has been expanded beyond the original focus on RDF, the names of many software objects (PL/SQL packages, functions and procedures, system tables and views, and so on) have been changed as of Oracle Database Release 11.1. In most cases, the change is to replace the string *RDF* with *SEM*, although in some cases it may be to replace *SDO_RDF* with *SEM*.

All valid code that used the pre-Release 11.1 names will continue to work; your existing applications will not be broken. However, it is suggested that you change old applications to use new object names, and you should use the new names for any new applications. This manual will document only the new names.

Table 1–13 lists the old and new names for some objects related to support for semantic technologies, in alphabetical order by old name.

Table 1–13 Semantic Technology Software Objects: Old and New Names

Old Name	New Name
RDF_ALIAS data type	SEM_ALIAS
RDF_MODEL\$ view	SEM_MODEL\$
RDF_RULEBASE_INFO view	SEM_RULEBASE_INFO
RDF_RULES_INDEX_DATASETS view	SEM_RULES_INDEX_DATASETS
RDF_RULES_INDEX_INFO view	SEM_RULES_INDEX_INFO
RDFI_rules-index-name view	SEMI_rules-index-name
RDFM_model-name view	SEMM_model-name
RDFR_rulebase-name view	SEMR_rulebase-name
SDO_RDF package	SEM_APIS
SDO_RDF_INFERENCE package	SEM_APIS
SDO_RDF_MATCH table function	SEM_MATCH
SDO_RDF_MODELS data type	SEM_MODELS
SDO_RDF_RULEBASES data type	SEM_RULEBASES

1.12 For More Information About Semantic Technologies

For more information about Oracle Database semantic technology support and related topics, you may find the following resources helpful:

- Semantic Technologies Center (OTN), which includes links for downloads, technical and business white papers, a discussion forum, and other sources of

information: http://www.oracle.com/technology/tech/semantic_technologies/

- World Wide Web Consortium (W3C) *RDF Primer*:
<http://www.w3.org/TR/rdf-primer/>
- World Wide Web Consortium (W3C) *OWL Web Ontology Language Reference*:
<http://www.w3.org/TR/owl-ref/>

OWL Concepts

This chapter describes concepts related to the support for a subset of the Web Ontology Language (OWL). It builds on the information in [Chapter 1](#), and it assumes that you are familiar with the major concepts associated with OWL, such as ontologies, properties, and relationships. For detailed information about OWL, see the *OWL Web Ontology Language Reference* at <http://www.w3.org/TR/owl-ref/>.

This chapter contains the following major sections:

- [Section 2.1, "Ontologies"](#)
- [Section 2.2, "Using OWL Inferencing"](#)
- [Section 2.3, "Using Semantic Operators to Query Relational Data"](#)

2.1 Ontologies

An **ontology** is a shared conceptualization of knowledge in a particular domain. It consists of a collection of classes, properties, and optionally instances. Classes are typically related by class hierarchy (subclass/ superclass relationship). Similarly, the properties can be related by property hierarchy (subproperty/ superproperty relationship). Properties can be symmetric or transitive, or both. Properties can also have domain, ranges, and cardinality constraints specified for them.

RDFS-based ontologies only allow specification of class hierarchies, property hierarchies, `instanceOf` relationships, and a domain and a range for properties.


OWL ontologies build on RDFS-based ontologies by additionally allowing specification of property characteristics. OWL ontologies can be further classified as OWL-Lite, OWL-DL, and OWL Full. OWL-Lite restricts the cardinality minimum and maximum values to 0 or 1. OWL-DL relaxes this restriction by allowing minimum and maximum values. OWL Full allows instances to be also defined as a class, which is not allowed in OWL-DL and OWL-Lite ontologies.

[Section 2.1.2](#) describes OWL capabilities that are supported and not supported with semantic data.

2.1.1 Example: Cancer Ontology

[Figure 2-1](#) shows part of a cancer ontology, which describes the classes and properties related to cancer. One requirement is to have a PATIENTS data table with a column named DIAGNOSIS, which must contain a value from the `Diseases_and_Disorders` class hierarchy.

Figure 2–1 Cancer Ontology Example



In the cancer ontology shown in [Figure 2–1](#), the diagnosis `Immune_System_Disorder` includes two subclasses, `Autoimmune_Disease` and `Immunodeficiency_Syndrome`. The `Autoimmune_Disease` diagnosis includes the subclass `Rheumatoid_Arthritis`; and the `Immunodeficiency_Syndrome` diagnosis includes the subclass `T_Cell_Immunodeficiency`, which includes the subclass `AIDS`.

The data in the PATIENTS table might include the PATIENT_ID and DIAGNOSIS column values shown in [Table 2–1](#).

Table 2–1 PATIENTS Table Example Data

PATIENT_ID	DIAGNOSIS
1234	Rheumatoid_Arthritis
2345	Immunodeficiency_Syndrome
3456	AIDS

To query ontologies, you can use the SEM_MATCH table function (described in [Section 1.6](#)) or the SEM_RELATED operator and its ancillary operators (described in [Section 2.3](#)).

2.1.2 Supported OWL Subsets

This section describes OWL vocabulary subsets that are supported.

Oracle Database supports the RDFS++, OWLSIF, and OWLPrime vocabularies, which have increasing expressivity. Each supported vocabulary has a corresponding rulebase; however, these rulebases do not need to be populated because the underlying entailment rules of these three vocabularies are internally implemented. The supported vocabularies are as follows:

- RDFS++: A minimal extension to RDFS; which is RDFS plus `owl:sameAs` and `owl:InverseFunctionalProperty`.
- OWLSIF: OWL with IF Semantic, with the vocabulary and semantics proposed for pD* semantics in *Completeness, decidability and complexity of entailment for RDF*

Schema and a semantic extension involving the OWL vocabulary, by H.J. Horst, Journal of Web Semantics 3, 2 (2005), 79–115.

- OWLPrime: The following OWL capabilities:
 - Basics: class, subclass, property, subproperty, domain, range, type
 - Property characteristics: transitive, symmetric, functional, inverse functional, inverse
 - Class comparisons: equivalence, disjointness
 - Property comparisons: equivalence
 - Individual comparisons: same, different
 - Class expressions: complement
 - Property restrictions: `hasValue`, `someValuesFrom`, `allValuesFrom`
As with pD^* , the supported semantics for these value restrictions are only intensional (IF semantics).

The following OWL capabilities are not yet supported in any Oracle-supported OWL subset:

- Property restrictions: cardinality
- Class expressions: set operations (union, intersection), enumeration

[Table 2–2](#) lists the RDFS/OWL vocabulary constructs included in each supported rulebase.

Table 2–2 RDFS/OWL Vocabulary Constructs Included in Each Supported Rulebase

Rulebase Name	RDFS/OWL Constructs Included
RDFS++	all RDFS vocabulary constructs <code>owl:InverseFunctionalProperty</code> <code>owl:sameAs</code>
OWLSIF	all RDFS vocabulary constructs <code>owl:FunctionalProperty</code> <code>owl:InverseFunctionalProperty</code> <code>owl:SymmetricProperty</code> <code>owl:TransitiveProperty</code> <code>owl:sameAs</code> <code>owl:inverseOf</code> <code>owl:equivalentClass</code> <code>owl:equivalentProperty</code> <code>owl:hasValue</code> <code>owl:someValuesFrom</code> <code>owl:allValuesFrom</code>

Table 2–2 (Cont.) RDFS/OWL Vocabulary Constructs Included in Each Supported

Rulebase Name	RDFS/OWL Constructs Included
OWLPrime	rdfs:subClassOf rdfs:subPropertyOf rdfs:domain rdfs:range owl:FunctionalProperty owl:InverseFunctionalProperty owl:SymmetricProperty owl:TransitiveProperty owl:sameAs owl:inverseOf owl:equivalentClass owl:equivalentProperty owl:hasValue owl:someValuesFrom owl:allValuesFrom owl:differentFrom owl:disjointWith owl:complementOf

2.2 Using OWL Inferencing

You can use entailment rules to perform native OWL inferencing. This section creates a simple ontology, performs native inferencing, and illustrates some more advanced features.

2.2.1 Creating a Simple OWL Ontology

[Example 2–1](#) creates a simple OWL ontology, inserts one statement that two URIs refer to the same entity, and performs a query using the SEM_MATCH table function

Example 2–1 Creating a Simple OWL Ontology

```
SQL> CREATE TABLE owlst(id number, triple sdo_rdf_triple_s);
Table created.

SQL> EXECUTE sem_apis.create_sem_model('owlst','owlst','triple');
PL/SQL procedure successfully completed.

SQL> INSERT INTO owlst VALUES (1, sdo_rdf_triple_s('owlst',
            'http://example.com/name/John', 'http://www.w3.org/2002/07/owl#sameAs',
            'http://example.com/name/JohnQ'));
1 row created.

SQL> commit;

SQL> -- Use SEM_MATCH to perform a simple query.
SQL> select s,p,o from table(SEM_MATCH('(s ?p ?o)', SEM_Models('OWLST'),
            null, null, null ));
```

2.2.2 Performing Native OWL inferencing

[Example 2-2](#) calls the `SEM_APIS.CREATE_ENTAILMENT` procedure. You do not need to create the rulebase and add rules to it, because the OWL rules are already built into the Oracle semantic technologies inferencing engine.

Example 2-2 Performing Native OWL Inferencing

```
SQL> -- Invoke the following command to run native OWL inferencing that
SQL> -- understands the vocabulary defined in the preceding section.
SQL>
SQL> EXECUTE sem_apis.create_entailment('owlstst_idx', sem_models('owlstst'), sem_
rulebases('OWLPRIME'));
PL/SQL procedure successfully completed.

SQL> -- The following view is generated to represent the entailed graph (rules
index).
SQL> desc mdsys.semi_owlstst_idx;

SQL> -- Run the preceding query with an additional rulebase parameter to list
SQL> -- the original graph plus the inferred triples.
SQL> SELECT s,p,o FROM table(SEM_MATCH('(s ?p ?o)', SEM_MODELS('OWLSTST'),
SEM_RULEBASES('OWLPRIME'), null, null ));
```

2.2.3 Performing OWL and User-Defined Rules inferencing

[Example 2-3](#) creates a user-defined rulebase, inserts a simplified `uncleOf` rule (stating that the brother of one's father is one's uncle), and calls the `SEM_APIS.CREATE_ENTAILMENT` procedure.

Example 2-3 Performing OWL and User-Defined Rules Inferencing

```
SQL> -- First, insert the following assertions.

SQL> INSERT INTO owlstst VALUES (1, sdo_rdf_triple_s('owlstst',
'http://example.com/name/John', 'http://example.com/rel/fatherOf',
'http://example.com/name/Mary'));

SQL> INSERT INTO owlstst VALUES (1, sdo_rdf_triple_s('owlstst',
'http://example.com/name/Jack', 'http://example.com/rel/brotherOf',
'http://example.com/name/John'));

SQL> -- Create a user-defined rulebase.

SQL> EXECUTE sem_apis.create_rulebase('user_rulebase');

SQL> -- Insert a simple "uncle" rule.

SQL> INSERT INTO mdsys.semr_user_rulebase VALUES ('uncle_rule',
'(?x <http://example.com/rel/brotherOf> ?y)(?y <http://example.com/rel/fatherOf>
?z)',
NULL, '(?x <http://example.com/rel/uncleOf> ?z)', null);

SQL> -- In the following statement, 'USER_RULES=T' is required, to
SQL> -- include the original graph plus the inferred triples.
SQL> EXECUTE sem_apis.create_entailment('owlstst2_idx', sem_models('owlstst'),
sem_rulebases('OWLPRIME', 'USER_RULEBASE'),
SEM_APIS.REACH_CLOSURE, null, 'USER_RULES=T');
```

```
SQL> -- In the result of the following query, :Jack :uncleOf :Mary is inferred.
SQL> SELECT s,p,o FROM table(SEM_MATCH('(s ?p ?o)',
      SEM_MODELS('OWLTST'),
      SEM_RULEBASES('OWLPRIME','USER_RULEBASE'), null, null ));
```

2.2.4 Generating OWL inferencing Proofs

OWL inference can be complex, depending on the size of the ontology, the actual vocabulary (set of language constructs) used, and the interactions among those language constructs. To enable you to find out how a triple is derived, you can use proof generation during inference. (Proof generation does require additional CPU time and disk resources.)

To generate the information required for proof, specify `PROOF=T` in the call to the [SEM_APIS.CREATE_ENTAILMENT](#) procedure, as shown in the following example:

```
EXECUTE sem_apis.create_entailment('owlstst_idx', sem_models('owlstst'), -
      sem_rulebases('owlprime'), SEM_APIS.REACH_CLOSURE, 'SAM', 'PROOF=T');
```

Specifying `PROOF=T` causes a view to be created containing proof for each inferred triple. The view name is the entailment name prefixed by `MDSYS.SEMI_`. Two relevant columns in this view are `LINK_ID` and `EXPLAIN` (the proof). The following example displays the `LINK_ID` value and proof of each generated triple (with `LINK_ID` values shortened for simplicity):

```
SELECT link_id || ' generated by ' || explain as
      triple_and_its_proof FROM mdsys.semi_owlstst_idx;
```

```
TRIPLE_AND_ITS_PROOF
```

```
-----
8_5_5_4 generated by 4_D_5_5 : SYMM_SAMH_SYMM
8_4_5_4 generated by 8_5_5_4 4_D_5_5 : SAM_SAMH
. . .
```

A proof consists of one or more triple (link) ID values and the name of the rule that is applied on those triples:

```
link-id1 [link-id2 ... link-idn] : rule-name
```

To get the full subject, predicate, and object URIs for proofs, you can query the model view and the entailment (rules index) view. [Example 2-4](#) displays the `LINK_ID` value and associated triple contents using the model view `MDSYS.SEMM_OWLTST` and the entailment view `MDSYS.SEMI_OWLTST_IDX`.

Example 2-4 Displaying Proof Information

```
SELECT to_char(x.triple.rdf_m_id, 'FMXXXXXXXXXXXXXXXXXX') || '-' ||
      to_char(x.triple.rdf_s_id, 'FMXXXXXXXXXXXXXXXXXX') || '-' ||
      to_char(x.triple.rdf_p_id, 'FMXXXXXXXXXXXXXXXXXX') || '-' ||
      to_char(x.triple.rdf_c_id, 'FMXXXXXXXXXXXXXXXXXX'),
      x.triple.get_triple()
FROM (
  SELECT sdo_rdf_triple_s(
        t.canon_end_node_id,
        t.model_id,
        t.start_node_id,
        t.p_value_id,
        t.end_node_id) triple
  FROM (select * from mdsys.semm_owlstst union all
        select * from mdsys.semi_owlstst_idx
       ) t
```

```

WHERE t.link_id IN ('4_D_5_5','8_5_5_4')
) x;

LINK_ID X.TRIPLE.GET_TRIPLE() (SUBJECT, PROPERTY, OBJECT)
-----
4_D_5_5 SDO_RDF_TRIPLE('<http://example.com/name/John>',
'<http://www.w3.org/2002/07/owl#sameAs>', '<http://example.com/name/JohnQ>')
8_5_5_4 SDO_RDF_TRIPLE('<http://example.com/name/JohnQ>',
'<http://www.w3.org/2002/07/owl#sameAs>', '<http://example.com/name/John>')

```

In [Example 2-4](#), for the proof entry 8_5_5_4 generated by 4_D_5_5: SYMM_SAMH_SYMM for the triple with LINK_ID = 8_5_5_4, it is inferred from the triple with 4_D_5_5 using the symmetry of owl:sameAs.

If the entailment status is INCOMPLETE and if the last entailment was generated without proof information, you cannot invoke SEM_APIS.CREATE_ENTAILMENT with PROOF=T. In this case, you must first drop the entailment and create it again specifying PROOF=T.

2.2.5 Validating OWL Models and Entailments

An OWL ontology may contain errors, such as unsatisfiable classes, instances belonging to unsatisfiable classes, and two individuals asserted to be same and different at the same time. You can use the SEM_APIS.VALIDATE_MODEL and SEM_APIS.VALIDATE_ENTAILMENT functions to detect inconsistencies in the original data model and in the entailment, respectively.

[Example 2-5](#) shows uses the SEM_APIS.VALIDATE_ENTAILMENT function, which returns a null value if no errors are detected or a VARRAY of strings if any errors are detected.

Example 2-5 Validating an Entailment

```

SQL> -- Insert an offending triple.
SQL> insert into owlst values (1, sdo_rdf_triple_s('owlst',
        'urn:C1', 'http://www.w3.org/2000/01/rdf-schema#subClassOf',
        'http://www.w3.org/2002/07/owl#Nothing'));

SQL> -- Drop entailment first.
SQL> exec sem_apis.drop_entailment('owlst_idx');
PL/SQL procedure successfully completed.

SQL> -- Perform OWL inferencing.
SQL> exec sem_apis.create_entailment('owlst_idx', sem_models('OWLSTST'), sem_
rulebases('OWLPRIME'));
PL/SQL procedure successfully completed.

SQL > set serveroutput on;
SQL > -- Now invoke validation API: sem_apis.validate_entailment
SQL >
declare
    lva mdsys.rdf_longVcharArray;
    idx int;
begin
    lva := sem_apis.validate_entailment(sem_models('OWLSTST'), sem_
rulebases('OWLPRIME')) ;

    if (lva is null) then
        dbms_output.put_line('No errors found.');
```

```

    for idx in 1..lva.count loop
        dbms_output.put_line('Offending entry := ' || lva(idx)) ;
    end loop ;
end if;
end ;
/

```

```

SQL> -- NOTE: The LINK_ID value and the numbers in the following
SQL> -- line are shortened for simplicity in this example. --

```

```

    Offending entry := 1 10001 (4_2_4_8 2 4 8) Unsatisfiable class.

```

Each item in the validation report array includes the following information:

- Number of triples that cause this error (1 in [Example 2-5](#))
- Error code (10001 [Example 2-5](#))
- One or more triples (shown in parentheses in the output; (4_2_4_8 2 4 8) in [Example 2-5](#)).

These numbers are the LINK_ID value and the ID values of the subject, predicate, and object.

- Descriptive error message (Unsatisfiable class. in [Example 2-5](#))

The output in [Example 2-5](#) indicates that the error is caused by one triple that asserts that a class is a subclass of an empty class owl:Nothing.

2.2.6 Using SEM_APIS.CREATE_ENTAILMENT for RDFS Inference

In addition to accepting OWL vocabularies, the `SEM_APIS.CREATE_ENTAILMENT` procedure accepts RDFS rulebases. The following example shows RDFS inference (all standard RDFS rules are defined in <http://www.w3.org/TR/rdf-mt/>):

```

EXECUTE sem_apis.create_entailment('rdfstst_idx', sem_models('my_model'), sem_
rulebases('RDFS'));

```

Because rules RDFS4A, RDFS4B, RDFS6, RDFS8, RDFS10, RDFS13 may not generate meaningful inference for your applications, you can deselect those components for faster inference. The following example deselects these rules.

```

EXECUTE sem_apis.create_entailment('rdfstst_idx', sem_models('my_model'), sem_
rulebases('RDFS'), SEM_APIS.REACH_CLOSURE, -
'RDFS4A-, RDFS4B-, RDFS6-, RDFS8-, RDFS10-, RDFS13-');

```

2.2.7 Enhancing Inference Performance

This section describes suggestions for improving the performance of inference operations.

- Collect statistics before inferencing. After you load a large RDF/OWL data model, you should execute the `SEM_PERF.GATHER_STATS` procedure. See the Usage Notes for that procedure (in [Chapter 10](#)) for important usage information.
- Allocate sufficient temporary tablespace for inference operations. OWL inference support in Oracle relies heavily on table joins, and therefore uses significant temporary tablespace.

See also [Section 2.2.8, "Optimizing owl:sameAs Inference"](#).

2.2.8 Optimizing owl:sameAs Inference

You can optimize inference performance for large owl:sameAs cliques by specifying 'OPT_SAMEAS=T' in the options parameter when performing OWLPrime entailment. (A **clique** is a graph in which every node of it is connected to, bidirectionally, every other node in the same graph.)

According to OWL semantics, the owl:sameAs construct is treated as an equivalence relation, so it is reflexive, symmetric, and transitive. As a result, during inference a full materialization of owl:sameAs-related entailments could significantly increase the size of the inferred graph. Consider the following example triple set:

```
:John owl:sameAs :John1 .
:John owl:sameAs :John2 .
:John2 :hasAge      "32" .
```

Applying OWLPrime inference (with the SAM component specified) to this set would generate the following new triples:

```
:John1 owl:sameAs :John .
:John2 owl:sameAs :John .
:John1 owl:sameAs :John2 .
:John2 owl:sameAs :John1 .
:John owl:sameAs :John .
:John1 owl:sameAs :John1 .
:John2 owl:sameAs :John2 .
:John :hasAge      "32" .
:John1 :hasAge     "32" .
```

In the preceding example, :John, :John1 and :John2 are connected to each other with the owl:sameAs relationship; that is, they are members of an owl:sameAs **clique**. To provide optimized inference for large owl:sameAs cliques, you can consolidate owl:sameAs triples without sacrificing correctness by specifying 'OPT_SAMEAS=T' in the options parameter when performing OWLPrime entailment. For example:

```
EXECUTE sem_apis.create_entailment('M_IDX', sem_models('M'),
  sem_rulebases('OWLPRIME'), null, null, 'OPT_SAMEAS=T');
```

When you specify this option, for each owl:sameAs clique, one resource from the clique is chosen as a canonical representative and all of the inferences for that clique are consolidated around that resource. Using the preceding example, if :John1 is the clique representative, after consolidation the inferred graph would contain only the following triples:

```
:John1 owl:sameAs :John1 .
:John1 :hasAge      "32" .
```

Some overhead is incurred with owl:sameAs consolidation. During inference, all asserted models are copied into the inference partition, where they are consolidated together with the inferred triples. Additionally, for very large asserted graphs, consolidating and removing duplicate triples incurs a large run-time overhead, so the OPT_SAMEAS=T option is recommended only for ontologies that have a large number of owl:sameAs relationships and large clique sizes.

After the OPT_SAMEAS=T option has been used for an entailment, all subsequent uses of [SEM_APIS.CREATE_ENTAILMENT](#) for that entailment must also use OPT_SAMEAS=T, or an error will be reported. To disable optimized sameAs handling, you must first drop the entailment.

Clique membership information is stored in a view named `MDSYS.SEMCL_entailment-name`, where *entailment-name* is the name of the entailment (rules index). Each `MDSYS.SEMCL_entailment-name` view has the columns shown in [Table 2–3](#).

Table 2–3 MDSYS.SEMCL_entailment_name View Columns

Column Name	Data Type	Description
MODEL_ID	NUMBER	ID number of the inferred model
VALUE_ID	NUMBER)	ID number of a resource that is a member of the <code>owl:sameAs</code> clique identified by CLIQUE_ID
CLIQUE_ID	NUMBER	ID number of the clique representative for the VALUE_ID resource

To save space, the `MDSYS.SEMCL_entailment-name` view does not contain reflexive rows like `(CLIQUE_ID, CLIQUE_ID)`.

2.2.8.1 Querying `owl:sameAs` Consolidated Inference Graphs

At query time, if the entailment queried was created using the `OPT_SAMEAS=T` option, the results are returned from an `owl:sameAs`-consolidated inference partition. The query results are not expanded to include the full `owl:sameAs` closure.

In the following example query, the only result returned would be `:John1`, which is the canonical clique representative.

```
SELECT A FROM TABLE (
  SEM_MATCH ('(?A :hasAge "32")', SEM_MODELS('M'),
    SEM_RULEBASES('OWLPRIME'), NULL, NULL));
```

With the preceding example, even though `:John2 :hasAge "32"` occurs in the model, it has been replaced during the inference consolidation phase where redundant triples are removed. However, you can expand the query results by performing a join with the `MDSYS.SEMCL_rules-index-name` view that contains the consolidated `owl:sameAs` information. For example, to get expanded result set for the preceding `SEM_MATCH` query, you can use the following expanded query:

```
SELECT V.VALUE_NAME A_VAL FROM TABLE (
  SEM_MATCH ('(?A :hasAge "32")', SEM_MODELS('M'),
    SEM_RULEBASES('OWLPRIME'), NULL, NULL)) Q,
  MDSYS.RDF_VALUE$ V, MDSYS.SEMCL_M_IDX C
WHERE V.VALUE_ID = C.VALUE_ID
  AND C.CLIQUE_ID = Q.A$RDFVID
UNION ALL
  SELECT A A_VAL FROM TABLE (
    SEM_MATCH ('(?A :hasAge "32")', SEM_MODELS('M'),
      SEM_RULEBASES('OWLPRIME'), NULL, NULL));
```

Or, you could rewrite the preceding expanded query using a left outer join, as follows:

```
SELECT V.VALUE_NAME A_VAL FROM TABLE (
  SEM_MATCH ('(?A <http://hasAge> "33")', SEM_MODELS('M'),
    SEM_RULEBASES('OWLPRIME'), NULL, NULL)) Q,
  MDSYS.RDF_VALUE$ V,
  (SELECT value_id, clique_id FROM MDSYS.SEMCL_M_IDX
  UNION ALL
  SELECT DISTINCT clique_id, clique_id
  FROM MDSYS.SEMCL_M_IDX) C
WHERE Q.A$RDFVID = c.clique_id (+)
  AND V.VALUE_ID = nvl(C.VALUE_ID, Q.A$RDFVID);
```

2.2.9 Performing Incremental Inference

Incremental inference can be used to update entailments (rules indexes) efficiently after triple additions. There are two ways to enable incremental inference for an entailment:

- Specify the `options` parameter value `INC=T` when creating the entailment. For example:

```
EXECUTE sem_apis.create_entailment ('M_IDX', sem_models('M'),
    sem_rulebases('OWLPRIME'), null, null, 'INC=T');
```

- Use the [SEM_APIS.ENABLE_INC_INFERENCE](#) procedure.

If you use this procedure, the entailment must have a `VALID` status. Before calling the procedure, if you do not own the models involved in the entailment, you must ensure that the respective model owners have used the [SEM_APIS.ENABLE_CHANGE_TRACKING](#) procedure to enable change tracking for those models.

When incremental inference is enabled for an entailment, the parameter `INC=T` must be specified when invoking the [SEM_APIS.CREATE_ENTAILMENT](#) procedure for that entailment.

Incremental inference for an entailment depends on triggers for the application tables of the models involved in creating the entailment. This means that incremental inference works only when triples are inserted in the application tables underlying the entailment using conventional path loads, unless you specify the triples by using the `delta_in` parameter in the call to the [SEM_APIS.CREATE_ENTAILMENT](#) procedure, as in the following example, in which the triples from model `M_NEW` will be added to model `M`, and entailment `M_IDX` will be updated with the new inferences:

```
EXECUTE sem_apis.create_entailment('M_IDX', sem_models('M'),
    sem_rulebases('OWLPRIME'), SEM_APIS.REACH_CLOSURE, null, null,
    sem_models('M_NEW'));
```

Another way to bypass the conventional path loading requirement when using incremental inference is to set the `UNDO_RETENTION` parameter to cover the intervals between entailments when you perform bulk loading. For example, if the last entailment was created 6 hours ago, the `UNDO_RETENTION` value should be set to greater than 6 hours; if it is less than that, then (given a heavy workload and limited undo space) it is not guaranteed that all relevant undo information will be preserved for incremental inference to apply. In such cases, the [SEM_APIS.CREATE_ENTAILMENT](#) procedure falls back to regular (non-incremental) inference.

To check if change tracking is enabled on a model, use the [SEM_APIS.GET_CHANGE_TRACKING_INFO](#) procedure. To get additional information about incremental inference for an entailment, use the [SEM_APIS.GET_INC_INF_INFO](#) procedure.

The following restrictions apply to incremental inference:

- It does not work with optimized `owl:sameAs` handling (`OPT_SAMEAS`), user-defined rules, VPD-enabled models, or version-enabled models.
- It supports only the addition of triples. With updates or deletions, the entailment will be completely rebuilt.
- It depends on triggers on application tables.
- Column types (`RAW8` or `NUMBER`) used in incremental inference must be consistent. For instance, if `RAW8=T` is used to build the entailment initially, then for every subsequent [SEM_APIS.CREATE_ENTAILMENT](#) call the same option must

be used. To change the column type to NUMBER, you must drop and rebuild the entailment.

2.2.10 Using Parallel Inference

Parallel inference can improve inference performance by taking advantage of the capabilities of a multi-core or multi-CPU architectures. To use parallel inference, specify the DOP (degree of parallelism) keyword and an appropriate value when using the [SEM_APIS.CREATE_ENTAILMENT](#) procedure. For example:

```
EXECUTE sem_apis.create_entailment('M_IDX', sem_models('M'),
    sem_rulebases('OWLPRIME'), sem_apis.REACH_CLOSURE, null, 'DOP=4');
```

Specifying the DOP keyword causes parallel execution to be enabled for an Oracle-chosen set of inference components

The success of parallel inference depends heavily on a good hardware configuration of the system on which the database is running. The key is to have a "balanced" system that implements the best practices for database performance tuning and Oracle SQL parallel execution. For example, do not use a single 1 TB disk for an 800 GB database, because executing SQL statements in parallel on a single physical disk can even be slower than executing SQL statements in serial mode. Parallel inference requires ample memory; for each CPU core, you should have at least 4 GB of memory.

Parallel inference is best suited for large ontologies; however, inference performance can also improve for small ontologies.

There is some transient storage overhead associated with using parallel inference. Parallel inference builds a source table that includes all triples based on all the source RDF/OWL models and existing inferred graph. This table might use an additional 10 to 30 percent of storage compared to the space required for storing data and index of the source models.

2.2.11 Performing Selective Inferencing (Advanced Information)

Selective inferencing is component-based inferencing, in which you limit the inferencing to specific OWL components that you are interested in. To perform selective inferencing, use the `inf_components_in` parameter to the [SEM_APIS.CREATE_ENTAILMENT](#) procedure to specify a comma-delimited list of components. The final inferencing is determined by the *union* of rulebases specified and the components specified.

[Example 2-6](#) limits the inferencing to the class hierarchy from subclass (SCOH) relationship and the property hierarchy from subproperty (SPOH) relationship. This example creates an empty rulebase and then specifies the two components ('SCOH, SPOH') in the call to the [SEM_APIS.CREATE_ENTAILMENT](#) procedure.

Example 2-6 Performing Selective Inferencing

```
EXECUTE sem_apis.create_rulebase('my_rulebase');

EXECUTE sem_apis.create_entailment('owlstst_idx', sem_models('owlstst'), sem_
rulebases('my_rulebase'), SEM_APIS.REACH_CLOSURE, 'SCOH, SPOH');
```

The following component codes are available: SCOH, COMPH, DISJH, SYMMH, INVH, SPIH, MBRH, SPOH, DOMH, RANH, EQCH, EQPH, FPH, IFPH, DOM, RAN, SCO, DISJ, COMP, INV, SPO, FP, IFP, SYMM, TRANS, DIF, SAM, CHAIN, HASKEY, ONEOF, INTERSECT, INTERSECTSCOH, MBRLST, PROPDISJH, SKOSAXIOMS, SNOMED, SVFH, THINGH, THINGSAM, UNION, RDFP1, RDFP2, RDFP3, RDFP4, RDFP6, RDFP7, RDFP8AX,

RDFP8BX, RDFP9, RDFP10, RDFP11, RDFP12A, RDFP12B, RDFP12C, RDFP13A, RDFP13B, RDFP13C, RDFP14A, RDFP14BX, RDFP15, RDFP16, RDFS2, RDFS3, RDFS4a, RDFS4b, RDFS5, RDFS6, RDFS7, RDFS8, RDFS9, RDFS10, RDFS11, RDFS12, RDFS13

The rules corresponding to components with a prefix of *RDFP* can be found in *Completeness, decidability and complexity of entailment for RDF Schema and a semantic extension involving the OWL vocabulary*, by H.J. Horst.

The syntax for deselecting a component is *component_name* followed by a minus (-) sign. For example, the following statement performs OWLPrime inference without calculating the `subClassOf` hierarchy:

```
EXECUTE sem_apis.create_entailment('owlstst_idx', sem_models('owlstst'), sem_rulebases('OWLPRIME'), SEM_APIS.REACH_CLOSURE, 'SCOH-');
```

By default, the OWLPrime rulebase implements the transitive semantics of `owl:sameAs`. OWLPrime does not include the following rules (semantics):

```
U owl:sameAs V .
U p X .          ==> V p X .

U owl:sameAs V .
X p U .          ==> X p V .
```

The reason for not including these rules is that they tend to generate many assertions. If you need to include these assertions, you can include the SAM component code in the call to the [SEM_APIS.CREATE_ENTAILMENT](#) procedure.

2.3 Using Semantic Operators to Query Relational Data

You can use semantic operators to query relational data in an ontology-assisted manner, based on the semantic relationship between the data in a table column and terms in an ontology. The `SEM_RELATED` semantic operator retrieves rows based on semantic relatedness. The `SEM_DISTANCE` semantic operator returns distance measures for the semantic relatedness, so that rows returned by the `SEM_RELATED` operator can be ordered or restricted using the distance measure. The index type `MDSYS.SEM_INDEXTYPE` allows efficient execution of such queries, enabling scalable performance over large data sets.

2.3.1 Using the SEM_RELATED Operator

Referring to the cancer ontology example in [Section 2.1.1](#), consider the following query that requires semantic matching: *Find all patients whose diagnosis is of the type 'Immune_System_Disorder'*. A typical database query of the `PATIENTS` table (described in [Section 2.1.1](#)) involving syntactic match will not return any rows, because no rows have a `DIAGNOSIS` column containing the exact value `Immune_System_Disorder`. For example the following query will not return any rows:

```
SELECT diagnosis FROM patients WHERE diagnosis = 'Immune_System_Disorder';
```

However, many rows in the patient data table are relevant, because their diagnoses fall under this class. [Example 2-7](#) uses the `SEM_RELATED` operator (instead of lexical equality) to retrieve all the relevant rows from the patient data table. (In this example, the term `Immune_System_Disorder` is prefixed with a namespace, and the default assumption is that the values in the table column also have a namespace prefix. However, that might not always be the case, as explained in [Section 2.3.5](#).)

Example 2-7 SEM_RELATED Operator

```
SELECT diagnosis FROM patients
WHERE SEM_RELATED (diagnosis,
  '<http://www.w3.org/2000/01/rdf-schema#subClassOf>',
  '<http://www.example.org/medical_terms/Immune_System_Disorder>',
  sem_models('medical_ontology'), sem_rulebases('owlprime')) = 1;
```

The SEM_RELATED operator has the following attributes:

```
SEM_RELATED(
  sub VARCHAR2,
  predExpr VARCHAR2,
  obj VARCHAR2,
  ontologyName SEM_MODELS,
  ruleBases SEM_RULEBASES,
  index_status VARCHAR2,
  lower_bound INTEGER,
  upper_bound INTEGER
) RETURN INTEGER;
```

The `sub` attribute is the name of table column that is being searched. The terms in the table column are typically the subject in a <subject, predicate, object> triple pattern.

The `predExpr` attribute represents the predicate that can appear as a label of the edge on the path from the subject node to the object node.

The `obj` attribute represents the term in the ontology for which related terms (related by the `predExpr` attribute) have to be found in the table (in the column specified by the `sub` attribute). This term is typically the object in a <subject, predicate, object> triple pattern. (In a query with the equality operator, this would be the query term.)

The `ontologyName` attribute is the name of the ontology that contains the relationships between terms.

The `rulebases` attribute identifies one or more rulebases whose rules have been applied to the ontology to infer new relationships. The query will be answered based both on relationships from the ontology and the inferred new relationships when this attribute is specified.

The `index_status` optional attribute lets you query the data even when the relevant entailment (created when the specified rulebase was applied to the ontology) does not have a valid status. If this attribute is null, the query returns an error if the entailment does not have a valid status. If this attribute is not null, it must be the string `VALID`, `INCOMPLETE`, or `INVALID`, to specify the minimum status of the entailment for the query to succeed. Because OWL does not guarantee monotonicity, the value `INCOMPLETE` should not be used when an OWL Rulebase is specified.

The `lower_bound` and `upper_bound` optional attributes let you specify a bound on the distance measure of the relationship between terms that are related. See [Section 2.3.2](#) for the description of the distance measure.

The SEM_RELATED operator returns 1 if the two input terms are related with respect to the specified `predExpr` relationship within the ontology, and it returns 0 if the two input terms are not related. If the lower and upper bounds are specified, it returns 1 if the two input terms are related with a distance measure that is greater than or equal to `lower_bound` and less than or equal to `upper_bound`.

2.3.2 Using the SEM_DISTANCE Ancillary Operator

The SEM_DISTANCE ancillary operator computes the distance measure for the rows filtered using the SEM_RELATED operator. The SEM_DISTANCE operator has the following format:

```
SEM_DISTANCE (number) RETURN NUMBER;
```

The `number` attribute can be any number, as long as it matches the number that is the last attribute specified in the call to the SEM_RELATED operator (see [Example 2-8](#)). The number is used to match the invocation of the ancillary operator SEM_DISTANCE with a specific SEM_RELATED (primary operator) invocation, because a query can have multiple invocations of primary and ancillary operators.

[Example 2-8](#) expands [Example 2-7](#) to show several statements that include the SEM_DISTANCE ancillary operator, which gives a measure of how closely the two terms (here, a patient's diagnosis and the term `Immune_System_Disorder`) are related by measuring the distance between the terms. Using the cancer ontology described in [Section 2.1.1](#), the distance between `AIDS` and `Immune_System_Disorder` is 3.

Example 2-8 SEM_DISTANCE Ancillary Operator

```
SELECT diagnosis, SEM_DISTANCE(123) FROM patients
WHERE SEM_RELATED (diagnosis,
  '<http://www.w3.org/2000/01/rdf-schema#subClassOf>',
  '<http://www.example.org/medical_terms/Immune_System_Disorder>',
  sem_models('medical_ontology'), sem_rulebases('owlprime'), 123) = 1;
```

```
SELECT diagnosis FROM patients
WHERE SEM_RELATED (diagnosis,
  '<http://www.w3.org/2000/01/rdf-schema#subClassOf>',
  '<http://www.example.org/medical_terms/Immune_System_Disorder>',
  sem_models('medical_ontology'), sem_rulebases('owlprime'), 123) = 1
ORDER BY SEM_DISTANCE(123);
```

```
SELECT diagnosis, SEM_DISTANCE(123) FROM patients
WHERE SEM_RELATED (diagnosis,
  '<http://www.w3.org/2000/01/rdf-schema#subClassOf>',
  '<http://www.example.org/medical_terms/Immune_System_Disorder>',
  sem_models('medical_ontology'), sem_rulebases('owlprime'), 123) = 1
WHERE SEM_DISTANCE(123) <= 3;
```

[Example 2-9](#) uses distance information to restrict the number of rows returned by the primary operator. All rows with a term related to the object attribute specified in the SEM_RELATED invocation, but with a distance of greater than or equal to 2 and less than or equal to 4, are retrieved.

Example 2-9 Using SEM_DISTANCE to Restrict the Number of Rows Returned

```
SELECT diagnosis FROM patients
WHERE SEM_RELATED (diagnosis,
  '<http://www.w3.org/2000/01/rdf-schema#subClassOf>',
  '<http://www.example.org/medical_terms/Immune_System_Disorder>',
  sem_models('medical_ontology'), sem_rulebases('owlprime'), 2, 4) = 1;
```

In [Example 2-9](#), the lower and upper bounds are specified using the `lower_bound` and `upper_bound` parameters in the SEM_RELATED operator instead of using the SEM_DISTANCE operator. The SEM_DISTANCE operator can be also be used for restricting the rows returned, as shown in the last SELECT statement in [Example 2-8](#).

2.3.2.1 Computation of Distance Information

Distances are generated for the following properties during inference (entailment): OWL properties defined as transitive properties, and RDFS `subClassOf` and RDFS `subPropertyOf` properties. The distance between two terms linked through these properties is computed as the shortest distance between them in a hierarchical class structure. Distances of two terms linked through other properties are undefined and therefore set to null.

Each transitive property link in the original model (viewed as a hierarchical class structure) has a distance of 1, and the distance of an inferred triple is generated according to the number of links between the two terms. Consider the following hypothetical sample scenarios:

- If the original graph contains `C1 rdfs:subClassOf C2` and `C2 rdfs:subClassOf C3`, then `C1 rdfs:subClassOf C3` will be derived. In this case:
 - `C1 rdfs:subClassOf C2`: distance = 1, because it exists in the model.
 - `C2 rdfs:subClassOf C3`: distance = 1, because it exists in the model.
 - `C1 rdfs:subClassOf C3`: distance = 2, because it is generated during inference.
- If the original graph contains `P1 rdfs:subPropertyOf P2` and `P2 rdfs:subPropertyOf P3`, then `P1 rdfs:subPropertyOf P3` will be derived. In this case:
 - `P1 rdfs:subPropertyOf P2`: distance = 1, because it exists in the model.
 - `P2 rdfs:subPropertyOf P3`: distance = 1, because it exists in the model.
 - `P1 rdfs:subPropertyOf P3`: distance = 2, because it is generated during inference.
- If the original graph contains `C1 owl:equivalentClass C2` and `C2 owl:equivalentClass C3`, then `C1 owl:equivalentClass C3` will be derived. In this case:
 - `C1 owl:equivalentClass C2`: distance = 1, because it exists in the model.
 - `C2 owl:equivalentClass C3`: distance = 1, because it exists in the model.
 - `C1 owl:equivalentClass C3`: distance = 2, because it is generated during inference.

The `SEM_RELATED` operator works with user-defined rulebases. However, using the `SEM_DISTANCE` operator with a user-defined rulebase is not yet supported, and will raise an error.

2.3.3 Creating a Semantic Index of Type `MDSYS.SEM_INDEXTYPE`

When using the `SEM_RELATED` operator, you can create a semantic index of type `MDSYS.SEM_INDEXTYPE` on the column that contains the ontology terms. Creating such an index will result in more efficient execution of the queries. The `CREATE INDEX` statement must contain the `INDEXTYPE IS MDSYS.SEM_INDEXTYPE` clause, to specify the type of index being created.

[Example 2–10](#) creates a semantic index named `DIAGNOSIS_SEM_IDX` on the `DIAGNOSIS` column of the `PATIENTS` table using the `Cancer_Ontology` ontology.

Example 2–10 Creating a Semantic Index

```
CREATE INDEX diagnosis_sem_idx
  ON patients (diagnosis)
  INDEXTYPE IS MDSYS.SEM_INDEXTYPE;
```

The column on which the index is built (DIAGNOSIS in [Example 2–10](#)) must be the first parameter to the SEM_RELATED operator, in order for the index to be used. If it not the first parameter, the index is not used during the execution of the query.

To improve the performance of certain semantic queries, you can cause statistical information to be generated for the semantic index by specifying one or more models and rulebases when you create the index. [Example 2–11](#) creates an index that will also generate statistics information for the specified model and rulebase. The index can be used with other models and rulebases during query, but the statistical information will be used only if the model and rulebase specified during the creation of the index are the same model and rulebase specified in the query.

Example 2–11 Creating a Semantic Index Specifying a Model and Rulebase

```
CREATE INDEX diagnosis_sem_idx
  ON patients (diagnosis)
  INDEXTYPE IS MDSYS.SEM_INDEXTYPE('ONTOLOGY_MODEL(medical_ontology),
  RULEBASE(OWLPrime)');
```

The statistical information is useful for queries that return top-k results sorted by semantic distance. [Example 2–12](#) shows such a query.

Example 2–12 Query Benefitting from Generation of Statistical Information

```
SELECT /*+ FIRST_ROWS */ diagnosis FROM patients
  WHERE SEM_RELATED (diagnosis,
    '<http://www.w3.org/2000/01/rdf-schema#subClassOf>',
    '<http://www.example.org/medical_terms/Immune_System_Disorder>',
    sem_models('medical_ontology'), sem_rulebases('owlprime'), 123) = 1
  ORDER BY SEM_DISTANCE(123);
```

2.3.4 Using SEM_RELATED and SEM_DISTANCE When the Indexed Column Is Not the First Parameter

If an index of type MDSYS.SEM_INDEXTYPE has been created on a table column that is the first parameter to the SEM_RELATED operator, the index will be used. For example, the following query retrieves all rows that have a value in the DIAGNOSIS column that is a subclass of (rdfs:subClassOf) Immune_System_Disorder.

```
SELECT diagnosis FROM patients
  WHERE SEM_RELATED (diagnosis,
    '<http://www.w3.org/2000/01/rdf-schema#subClassOf>',
    '<http://www.example.org/medical_terms/Immune_System_Disorder>',
    sem_models('medical_ontology'), sem_rulebases('owlprime')) = 1;
```

Assume, however, that this query instead needs to retrieve all rows that have a value in the DIAGNOSIS column for which Immune_System_Disorder is a subclass. You could rewrite the query as follows:

```
SELECT diagnosis FROM patients
  WHERE SEM_RELATED
    ('<http://www.example.org/medical_terms/Immune_System_Disorder>',
    '<http://www.w3.org/2000/01/rdf-schema#subClassOf>',
    diagnosis,
```

```
sem_models('medical_ontology'), sem_rulebases('owlprime')) = 1;
```

However, in this case a semantic index on the DIAGNOSIS column will not be used, because it is not the first parameter to the SEM_RELATED operator. To cause the index to be used, you can change the preceding query to use the `inverseOf` keyword, as follows:

```
SELECT diagnosis FROM patients
WHERE SEM_RELATED (diagnosis,
  'inverseOf(http://www.w3.org/2000/01/rdf-schema#subClassOf) ',
  '<http://www.example.org/medical_terms/Immune_System_Disorder>',
  sem_models('medical_ontology'), sem_rulebases('owlprime')) = 1;
```

This form causes the table column (on which the index is built) to be the first parameter to the SEM_RELATED operator, and it retrieves all rows that have a value in the DIAGNOSIS column for which `Immune_System_Disorder` is a subclass.

2.3.5 Using URIPREFIX When Values Are Not Stored as URIs

By default, the semantic operator support assumes that the values stored in the table are URIs. These URIs can be from different namespaces. However, if the values in the table do not have URIs, you can use the URIPREFIX keyword to specify a URI when you create the semantic index. In this case, the specified URI is prefixed to the value in the table and stored in the index structure. (One implication is that multiple URIs cannot be used).

[Example 2-13](#) creates a semantic index that uses a URI prefix.

Example 2-13 Specifying a URI Prefix During Semantic Index Creation

```
CREATE INDEX diagnosis_sem_idx
ON patients (diagnosis)
INDEXTYPE IS MDSYS.SEM_INDEXTYPE
PARAMETERS ('URIPREFIX(<http://www.example.org/medical/>');
```

Note that the slash (/) character at the end of the URI is important, because the URI is prefixed to the table value (in the index structure) without any parsing.

Simple Knowledge Organization System (SKOS) Support

You can perform inferencing based on a core subset of the Simple Knowledge Organization System (SKOS) data model, which is especially useful for representing thesauri, classification schemes, taxonomies, and other types of controlled vocabulary. SKOS is based on standard semantic web technologies including RDF and OWL, which makes it easy to define the formal semantics for those knowledge organization systems and to share the semantics across applications.

Support is provided for most, but not all, of the features of SKOS, the detailed specification of which is available at <http://www.w3.org/TR/skos-reference/>.

Around 40 SKOS-specific terms are included in the Oracle Database semantic technologies support, such as `skos:broader`, `skos:relatedMatch`, and `skos:Concept`. Over 100 SKOS axiomatic triples have been added, providing the basic coverage of SKOS semantics. However, support is not included for the integrity conditions described in the SKOS specification.

To perform SKOS-based inferencing, specify the system-defined `SKOSCORE` rulebase in the `rulebases_in` parameter in the call to the `SEM_APIS.CREATE_ENTAILMENT` procedure, as in the following example:

```
EXECUTE sem_apis.create_entailment('tstidx',sem_models('tst'), sem_
rulebases('skoscore'));
```

[Example 3-1](#) defines, in Turtle format, a simple electronics scheme and two relevant concepts, cameras and digital cameras. Its meaning is straightforward and its representation is in RDF. It can be managed by Oracle Database in the same way as other RDF and OWL data.

Example 3-1 SKOS Definition of an Electronics Scheme

```
ex1:electronicsScheme rdf:type skos:ConceptScheme;

ex1:cameras rdf:type skos:Concept;
  skos:prefLabel "cameras"@en;
  skos:inScheme ex1:electronicsScheme.

ex1:digitalCameras rdf:type skos:Concept;
  skos:prefLabel "digital cameras"@en;
  skos:inScheme ex1:electronicsScheme.

ex1:digitalCameras skos:broader ex1:cameras.
```

3.1 Supported and Unsupported SKOS Semantics

This section describes features of SKOS semantics that are and are not supported by Oracle Database.

3.1.1 Supported SKOS Semantics

All terms defined in SKOS and SKOS extension for labels are recognized. When the SKOSCORE rulebase is chosen for inference, the recognized terms include the following:

```
skos:altLabel
skos:broader
skos:broaderTransitive
skos:broadMatch
skos:changeNote
skos:closeMatch
skos:Collection
skos:Concept
skos:ConceptScheme
skos:definition
skos:editorialNote
skos:exactMatch
skos:example
skos:hasTopConcept
skos:hiddenLabel
skos:historyNote
skos:inScheme
skos:mappingRelation
skos:member
skos:memberList
skos:narrower
skos:narrowerTransitive
skos:narrowMatch
skos:notation
skos:note
skos:OrderedCollection
skos:prefLabel
skos:related
skos:relatedMatch
skos:scopeNote
skos:semanticRelation
skos:topConceptOf
skosxl:altLabel
skosxl:hiddenLabel
skosxl:Label
skosxl:labelRelation
skosxl:literalForm
skosxl:prefLabel
```

Most SKOS axioms and definitions are supported including the following: S1-S8, S10-S11, S15-S26, S28-S31, S33-S36, S38-S45, S47-S50, and S53-S54. (See the SKOS detailed specification for definitions.)

Most SKOS integrity conditions are supported, including S9, S13, S27, S37, and S46.

S52 is partially supported.

S55, S56, and S57 are not supported by default.

- S55, the property chain (`skosxl:prefLabel`, `skosxl:literalForm`), is a subproperty of `skos:prefLabel`.
- S56, the property chain (`skosxl:altLabel`, `skosxl:literalForm`), is a subproperty of `skos:altLabel`.
- S57, the property chain (`skosxl:hiddenLabel`, `skosxl:literalForm`), is a subproperty of `skos:hiddenLabel.chains`.

However, S55, S56, and S57 can be implemented using the OWL 2 subproperty chain construct. For information about property chain handling, see [Section 3.2.2](#).

3.1.2 Unsupported SKOS Semantics

The following features of SKOS semantics are not supported:

- S12 and S51: The `rdfs:range` of the relevant predicates is the class of RDF plain literals. There is no check that the object values of these predicates are indeed plain literals; however, applications can perform such a check.
- S14: A resource has no more than one value of `skos:prefLabel` per language tag. This integrity condition is even beyond OWL FULL semantics, and it is not enforced in the current release.
- S32: The `rdfs:range` of `skos:member` is the union of classes `skos:Concept` and `skos:Collection`. This integrity condition is not enforced.
- S55, S56, and S57 are not supported by default, but they can be implemented using the OWL 2 subproperty chain construct, as explained in [Section 3.1.1](#).

3.2 Performing Inference on SKOS Models

To create an SKOS model, use the same procedure ([SEM_APIS.CREATE_SEM_MODEL](#)) as for creating a semantic model. You can load data into an SKOS model in the same way as for semantic models.

To infer new relationships for one or more SKOS models, use the [SEM_APIS.CREATE_ENTAILMENT](#) procedure with the system-defined rulebase `SKOSCORE`. For example:

```
EXECUTE sem_apis.create_entailment('tstidx',sem_models('tst'), sem_
rulebases('skoscore'));
```

The inferred data will include many of the axioms defined in the SKOS detailed specification. Like other system-defined rulebases, `SKOSCORE` has no explicit rules; all the semantics supported are coded into the implementation.

3.2.1 Validating SKOS Models and Entailments

You can use the [SEM_APIS.VALIDATE_ENTAILMENT](#) and [SEM_APIS.VALIDATE_MODEL](#) procedures to validate the supported integrity conditions. The output will include any inconsistencies caused by the supported integrity conditions, such as OWL 2 `propertyDisjointWith` and S52.

[Example 3-2](#) validates an SKOS entailment.

Example 3-2 Validating an SKOS Entailment

```
set serveroutput on
declare
  lva mdsys.rdf_longVarcharArray;
  idx int;
```

```

begin
  lva := sem_apis.validate_entailment(sdo_rdf_models('tstskos'), sem_
rulebases('skoscore'));
  if (lva is null) then
    dbms_output.put_line('No conflicts');
  else
    for idx in 1..lva.count loop
      dbms_output.put_line('entry ' || idx || ' ' || lva(idx));
    end loop;
  end if;
end;
/

```

3.2.2 Property Chain Handling

The SKOS S55, S56, and S57 semantics are not supported by default. However, you can add support for them by using the OWL 2 subproperty chain construct.

[Example 3-3](#) inserts the necessary chain definition triples for S55 into an SKOS model. After the insertion, an invocation of [SEM_APIS.CREATE_ENTAILMENT](#) that specifies the SKOSCORE rulebase will include the semantics defined in S55.

Example 3-3 Property Chain Insertions to Implement S55

```

INSERT INTO tst VALUES(sdo_rdf_triple_
s('tst', '<http://www.w3.org/2004/02/skos/core#prefLabel>',
'<http://www.w3.org/2002/07/owl#propertyChainAxiom>', '_:jA1'));
INSERT INTO tst VALUES(sdo_rdf_triple_s('tst', '_:jA1',
'<http://www.w3.org/1999/02/22-rdf-syntax-ns#first>',
'<http://www.w3.org/2008/05/skos-xl#prefLabel>'));
INSERT INTO tst VALUES(sdo_rdf_triple_s('tst', '_:jA1',
'<http://www.w3.org/1999/02/22-rdf-syntax-ns#rest>', '_:jA2'));
INSERT INTO tst VALUES(sdo_rdf_triple_s('tst', '_:jA2',
'<http://www.w3.org/1999/02/22-rdf-syntax-ns#first>',
'<http://www.w3.org/2008/05/skos-xl#literalForm>'));
INSERT INTO tst VALUES(sdo_rdf_triple_s('tst', '_:jA2',
'<http://www.w3.org/1999/02/22-rdf-syntax-ns#rest>',
'<http://www.w3.org/1999/02/22-rdf-syntax-ns#nil>'));

```

Semantic Indexing for Documents

Information extractors locate and extract meaningful information from unstructured documents. The ability to search for documents based on this extracted information is a significant improvement over the keyword-based searches supported by the full-text search engines.

Semantic indexing for documents introduces an index type that can make use of information extractors and annotators to semantically index documents stored in relational tables. Documents indexed semantically can be searched using SEM_CONTAINS operator within a standard SQL query. The search criteria for these documents are expressed using SPARQL query patterns that operate on the information extracted from the documents, as in the following example.

```
SELECT docId
FROM   Newsfeed
WHERE  SEM_CONTAINS (article,
    ' { ?org    rdf:type          typ:Organization .
      ?org    pred:hasCategory   cat:BusinessFinance } ', ..) = 1
```

The key components that facilitate Semantic Indexing for documents in an Oracle Database include:

- Extensible information extractor framework, which allows third-party information extractors to be plugged into the database
- SEM_CONTAINS operator to identify documents of interest, based on their extracted information, using standard SQL queries
- SEM_CONTAINS_SELECT ancillary operator to return relevant information about the documents identified using SEM_CONTAINS operator
- SemContext index type to interact with the information extractor and manage the information extracted from a document set in an index structure and to facilitate semantically meaningful searches on the documents

Creating a first semantic index for documents in a database re-creates an index on the underlying triple store that holds data for all RDF models. Thus, the time needed to create a first semantic index depends on the amount of existing data in these models.

The application program interface (API) for managing extractor policies and semantic indexes created for documents is provided in the SEM_RDFCTX PL/SQL package. [Chapter 11](#) provides the reference information about the programs in SEM_RDFCTX package.

This chapter contains the following major sections:

- [Section 4.1, "Information Extractors for Semantically Indexing Documents"](#)
- [Section 4.2, "Extractor Policies"](#)

- [Section 4.3, "Semantically Indexing Documents"](#)
- [Section 4.4, "SEM_CONTAINS and SEM_CONTAINS_SELECT Syntax"](#)
- [Section 4.5, "Searching for Documents Using SPARQL Query Patterns"](#)
- [Section 4.6, "Bindings from Matched Documents \(SEM_CONTAINS_SELECT Ancillary Operator\)"](#)
- [Section 4.7, "Improving the Quality of Document Search Operations"](#)
- [Section 4.8, "Indexing External Documents"](#)
- [Section 4.9, "Configuring the Calais Extractor type"](#)
- [Section 4.10, "Working with General Architecture for Text Engineering \(GATE\)"](#)
- [Section 4.11, "Creating a New Extractor Type"](#)
- [Section 4.12, "Metadata Views for Semantic Indexing"](#)

4.1 Information Extractors for Semantically Indexing Documents

Information extractors process unstructured documents and extract meaningful information from them, often using natural-language processing engines with the aid of ontologies. The quality and the completeness of information extracted from a document vary from one extractor to the other. Some extractors simply identify the entities (such as names of persons, organizations, and geographic locations from a document), while the others attempt to identify the relationships among the identified entities and additional description for those entities. You can search for a specific document from a large set when the information extracted from the documents is maintained as a semantic index.

You can use an information extractor to create a semantic index on the documents stored in a column of a relational table. An extensible framework allows any third-party information extractor that is accessible from the database to be plugged into the database. An object type created for an extractor encapsulates the extraction logic, and has methods to configure the extractor and receive information extracted from a given document in RDF/XML format.

An abstract type `MDSYS.RDFCTX_EXTRACTOR` defines the common interfaces to all information extractors. An implementation of this abstract type interacts with a specific information extractor to produce RDF/XML for a given document. An implementation for this type can access a third-party information extractor that either is available as a database application or is installed on the network (accessed using Web service callouts). [Example 4–1](#) shows the definition of the `RDFCTX_EXTRACTOR` abstract type.

Example 4–1 *RDFCTX_EXTRACTOR Abstract Type Definition*

```
create or replace type rdfctx_extractor authid current_user as object (  
  extr_type          VARCHAR2(32),  
  member function   getDescription return VARCHAR2,  
  member function   rdfReturnType return VARCHAR2,  
  member procedure  startDriver,  
  member function   extractRDF(document CLOB,  
                               docId   VARCHAR2) return CLOB,  
  member procedure  closeDriver  
) not instantiable not final  
/
```

A specific implementation of the `RDFCTX_EXTRACTOR` type sets an identifier for the extractor type in the `extr_type` attribute, and it returns a short description for the extractor type using `getDescription` method. All implementations of this abstract type return the extracted information as RDF triples. In the current release, the RDF triples are expected to be serialized using RDF/XML format, and therefore the `rdfReturnType` method should return 'RDF/XML'.

An extractor type implementation uses the `extractRDF` method to encapsulate the extraction logic, possibly by invoking external information extractor using proprietary interfaces, and returns the extracted information in RDF/XML format. When a third-party extractor uses some proprietary XML Schema to capture the extracted information, an XML style sheet can be used to generate an equivalent RDF/XML. The `startDriver` and `closeDriver` methods can perform any housekeeping operations pertaining to the information extractor.

An extractor type for the General Architecture for Text Engineering (GATE) engine is defined as a subtype of the `RDFCTX_EXTRACTOR` type. The implementation of this extractor type sends the documents to a GATE engine over a TCP connection, receives annotations extracted by the engine in XML format, and converts this proprietary XML document to an RDF/XML document. For more information on configuring a GATE engine to work with Oracle Database, see [Section 4.10](#). For an example of creating a new information extractor, see [Section 4.11](#).

Information extractors that are deployed as Web services can be invoked from the database by extending the `RDFCTX_WS_EXTRACTOR` type, which is a subtype of the `RDFCTX_EXTRACTOR` type. The `RDFCTX_WS_EXTRACTOR` type encapsulates the Web service callouts in the `extractRDF` method; specific implementations for network-based extractors can reuse this implementation by setting relevant attribute values in the type constructor.

Thomson Reuters Calais is an example of a network-based information extractor that can be accessed using web-service callouts. The `CALAIS_EXTRACTOR` type, which is a subtype of the `RDFCTX_WS_EXTRACTOR` type, encapsulates the Calais extraction logic, and it can be used to semantically index the documents. The `CALAIS_EXTRACTOR` type must be configured for the database instance before it can be used to create semantic indexes, as explained in [Section 4.9](#).

4.2 Extractor Policies

An **extractor policy** is a named dictionary entity that determines the characteristics of a semantic index that is created using the policy. Each extractor policy refers, directly or indirectly, to an instance of an extractor type. An extractor policy with a direct reference to an extractor type instance can be used to compose other extractor policies that include additional RDF models for ontologies.

The following example creates a basic extractor policy created using the GATE extractor type:

```
begin
  sem_rdfctx.create_policy (policy_name => 'SEM_EXTR',
                          extractor    => mdsys.gatenlp_extractor());
end;
/
```

The following example creates a dependent extractor policy that combines the metadata extracted by the policy in the preceding example with a user-defined RDF model named `geo_ontology`:

```
begin
```

```

sem_rdfctx.create_policy (policy_name => 'SEM_EXTR_PLUS_GEOONT',
                        base_policy => 'SEM_EXTR',
                        user_models => SEM_MODELS ('geo_ontology'));
end;
/

```

You can use an extractor policy to create one or more semantic indexes on columns that store unstructured documents, as explained in [Section 4.3](#).

4.3 Semantically Indexing Documents

Textual documents stored in a CLOB or VARCHAR2 column of a relational table can be indexed using the MDSYS.SEMCONTEXT index type, to facilitate semantically meaningful searches. The extractor policy specified at index creation determines the information extractor used to semantically index the documents. The extracted information, captured as a set of RDF triples for each document, is managed in the semantic data store. Each instance of the semantic index is associated with a system-generated RDF model, which maintains the RDF triples extracted from the corresponding documents.

The following example creates a semantic index named `ArticleIndex` on the textual documents in the `ARTICLE` column of the `NEWSFEED` table, using the extractor policy named `SEM_EXTR`:

```

CREATE INDEX ArticleIndex on Newsfeed (article)
  INDEXTYPE IS mdsys.SemContext PARAMETERS ('SEM_EXTR');

```

The RDF model created for an index is managed internally and it is not associated with an application table. The triples stored in such model are automatically maintained for any modifications (such as update, insert, or delete) made to the documents stored in the table column. Although a single RDF model is used to index all documents stored in a table column, the triples stored in the model maintain references to the documents from which they are extracted; therefore, all the triples extracted from a specific document form an individual graph within the RDF model. The documents that are semantically indexed can then be searched using a SPARQL query pattern that operates on the triples extracted from the documents.

When creating a semantic index for documents, you can use a basic extractor policy or a dependent policy, which may include one or more user-defined RDF models. When you create an index with a dependent extractor policy, the document search pattern specified using SPARQL could span the triples extracted from the documents as well as those defined in user-defined models.

You can create an index using multiple extractor policies, in which case the triples extracted by the corresponding extractors are maintained separately in distinct RDF models. A document search query using one such index can select the specific policy to be used for answering the query. For example, an extractor policy named `CITY_EXTR` can be created to extract the names of the cities from a given document, and this extractor policy can be used in combination with the `SEM_EXTR` policy to create a semantic index, as in the following example:

```

CREATE INDEX ArticleIndex on Newsfeed (article)
  INDEXTYPE IS mdsys.SemContext PARAMETERS ('SEM_EXTR CITY_EXTR');

```

The first extractor policy in the `PARAMETERS` list is considered to be the default policy if a query does not refer to a specific policy; however, you can change the default extractor policy for a semantic index by using the `SEM_RDFCTX.SET_DEFAULT_POLICY` procedure, as in the following example:

```

begin
  sem_rdfctx.set_default_policy (index_name => 'ArticleIndex',
                                policy_name => 'CITY_EXTR');
end;
/

```

4.4 SEM_CONTAINS and SEM_CONTAINS_SELECT Syntax

You can use the SEM_CONTAINS operator in a standard SQL statement to search for documents or document references that are stored in relational tables. This operator has the following syntax:

```

SEM_CONTAINS(
  column  VARCHAR2 / CLOB,
  sparql  VARCHAR2,
  policy  VARCHAR2,
  aliases SEM_ALIASES,
  ancoper NUMBER
) RETURN NUMBER;

```

The `column` and `sparql` attributes are required. The other attributes are optional (that is, each can be a null value).

The `column` attribute identifies a VARCHAR2 or CLOB column in a relational table that stores the documents or references to documents that are semantically indexed. An index of type MDSYS.SEMCONTEXT must be defined in this column for the SEM_CONTAINS operator to use.

The `sparql` attribute is a string literal that defines the document search criteria, expressed in SPARQL format.

The optional `policy` attribute specifies the name of an extractor policy, usually to override the default policy. A semantic document index can have one or more extractor policies specified at index creation, and one of these policies is the default, which is used if the `policy` attribute is null in the call to SEM_CONTAINS.

The optional `aliases` attribute identifies one or more namespaces, including a default namespace, to be used for expansion of qualified names in the query pattern. Its data type is SEM_ALIASES, which has the following definition: TABLE OF SEM_ALIAS, where each SEM_ALIAS element identifies a namespace ID and namespace value. The SEM_ALIAS data type has the following definition: (namespace_id VARCHAR2(30), namespace_val VARCHAR2(4000))

The optional `ancoper` attribute specifies a number as the binding to be used when the SEM_CONTAINS_SELECT ancillary operator is used with this operator in a query. The number specified for the `ancoper` attribute should be the same as number specified for the `operbind` attribute in the SEM_CONTAINS_SELECT ancillary operator.

The SEM_CONTAINS operator returns 1 for each document instance matching the specified search criteria, and returns 0 for all other cases.

For more information about using the SEM_CONTAINS operator, including an example, see [Section 4.5](#).

You can use the SEM_CONTAINS_SELECT ancillary operator to return additional information about each document that matches some search criteria. This ancillary operator has a single numerical attribute (`operbind`) that associates an instance of the SEM_CONTAINS_SELECT ancillary operator with a SEM_CONTAINS operator by using the same value for the binding. This ancillary operator returns an object of type

CLOB that contains the additional information from the matching document, formatted in SPARQL Query Results XML format.

The SEM_CONTAINS_SELECT ancillary operator has the following syntax:

```
SEM_CONTAINS_SELECT (
  operbind NUMBER
) RETURN CLOB;
```

For more information about using the SEM_CONTAINS_SELECT ancillary operator, including examples, see [Section 4.6](#).

4.5 Searching for Documents Using SPARQL Query Patterns

Documents that are semantically indexed (that is, indexed using the mdsys.SemContext index type) can be searched using SEM_CONTAINS operator within a standard SQL query. In the query, the SEM_CONTAINS operator must have at least two parameters, the first specifying the column in which the documents are stored and the second specifying the document search criteria expressed as a SPARQL query pattern, as in the following example:

```
SELECT docId FROM Newsfeed
WHERE SEM_CONTAINS (article,
  '{ ?org rdf:type <http://www.example.com/classes/Organization> .
  ?org <http://example.com/pred/hasCategory>
  <http://www.example.com/category/BusinessFinance> }'
) = 1;
```

The SPARQL query pattern specified with the SEM_CONTAINS operator is matched against the individual graphs corresponding to each document, and a document is considered to match a search criterion if the triples from the corresponding graph satisfy the query pattern. In the preceding example, the SPARQL query pattern identifies the individual graphs (thus, the documents) that refer to an `Organization` that belong to `BusinessFinance` category. The SQL query returns the rows corresponding to the matching documents in its result set. The preceding example assumes that the URIs used in the query are generated by the underlying extractor, and that you (the user searching for documents) are aware of the properties and terms that are generated by the extractor in use.

When you create an index using a dependent extractor policy that includes one or more user-defined RDF models, the triples asserted in the user models are considered to be common to all the documents. Document searches involving such policies test the search criteria against the triples in individual graphs corresponding to the documents, combined with the triples in the user models. For example, the following query identifies all articles referring to organizations in the state of New Hampshire, using the geographical ontology (`geo_ontology` RDF Model from a preceding example) that maps cities to states:

```
SELECT docId FROM Newsfeed
WHERE SEM_CONTAINS (article,
  '{ ?org rdf:type class:Organization .
  ?org pred:hasLocation ?city .
  ?city geo:hasState state:NewHampshire }',
  'SEM_EXTR_PLUS_GEOONT',
  sem_aliases(
    sem_alias('class', 'http://www.myorg.com/classes/'),
    sem_alias('pred', 'http://www.myorg.com/pred/'),
    sem_alias('geo', 'http://geoont.org/rel/'),
    sem_alias('state', 'http://geoont.org/state/')) = 1;
```

The preceding query, with a reference to the extractor policy SEM_EXTR_PLUS_GEOONT (created in an example in [Section 4.2](#)), combines the triples extracted from the indexed documents and the triples in the user model to find matching documents. In this example, the name of the extractor policy is optional if the corresponding index is created with just this policy or if this is the default extractor policy for the index. When the query pattern uses some qualified names, an optional parameter to the SEM_CONTAINS operator can specify the namespaces to be used for expanding the qualified names.

SPARQL-based document searches can make use of the SPARQL syntax that is supported through SEM_MATCH queries.

4.6 Bindings from Matched Documents (SEM_CONTAINS_SELECT Ancillary Operator)

You can use the SEM_CONTAINS_SELECT ancillary operator to return additional information about each document matched using the SEM_CONTAINS operator. Specifically, the bindings for the variables used in SPARQL-based document search criteria can be returned using this operator. This operator is ancillary to the SEM_CONTAINS operator, and a literal number is used as an argument to this operator to associate it with a specific instance of SEM_CONTAINS operator, as in the following example:

```
SELECT docId, SEM_CONTAINS_SELECT(1) as result
FROM Newsfeed
WHERE SEM_CONTAINS (article,
  '{ ?org rdf:type class:Organization .
    ?org pred:hasCategory cat:BusinessFinance }', ..,
  1)= 1;
```

The SEM_CONTAINS_SELECT ancillary operator returns the bindings for the variables in SPARQL Query Results XML format, as CLOB data. The variables may be bound to multiple data instances from a single document, in which case all bindings for the variables are returned. The following example is an excerpt from the output of the preceding query: a value returned by the SEM_CONTAINS_SELECT ancillary operator for a document matching the specified search criteria.

```
<results>
  <result>
    <binding name="ORG">
      <uri>http://newscorp.com/Org/AcmeCorp</uri>
    </binding>
  </result>
  <result>
    <binding name="ORG">
      <uri>http://newscorp.com/Org/ABCCorp</uri>
    </binding>
  </result>
</results>
```

You can rank the search results by creating an instance of XMLType for the CLOB value returned by the SEM_CONTAINS_SELECT ancillary operator and applying an XPath expression to sort the results on some attribute values.

By default, the SEM_CONTAINS_SELECT ancillary operator returns bindings for all variables used in the SPARQL-based document search criteria. However, when the values for only a subset of the variables are relevant for a search, the SPARQL pattern

can include a SELECT clause with space-separated list of variables for which the values should be returned, as in the following example:

```
SELECT docId, SEM_CONTAINS_SELECT(1) as result
FROM   Newsfeed
WHERE  SEM_CONTAINS (article,
    'SELECT ?org ?city
    WHERE { ?org      rdf:type          class:Organization .
            ?org      pred:hasLocation ?city .
            ?city     geo:hasState     state:NewHampshire }', ...
    1) = 1;
```

4.7 Improving the Quality of Document Search Operations

The quality of a document search operation depends on the quality of the information produced by the extractor used to index the documents. If the information extracted is incomplete, you may want to add some annotations to a document. You can use the [SEM_RDFCTX.MAINTAIN_TRIPLES](#) procedure to add annotations, in the form of RDF triples, to specific documents in order to improve the quality of search, as shown in the following example:

```
begin
  sem_rdfctx.maintain_triples(
    index_name      => 'ArticleIndex',
    where_clause    => 'docid in (1,15,20)',
    rdfxml_content => sys.xmltype(
      '<rdf:RDF xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
        xmlns:rdfs="http://www.w3.org/2000/01/rdf-schema#"
        xmlns:pred="http://example.com/pred/">
        <rdf:Description rdf:about=" http://newscorp.com/Org/ExampleCorp">
          <pred:hasShortName
            rdf:datatype="http://www.w3.org/2001/XMLSchema#string">
            Example
          </pred:hasShortName>
        </rdf:Description>
      </rdf:RDF>');
end;
/
```

The index name and the WHERE clause specified in the preceding example identify specific instances of the document to be annotated, and the RDF/XML content passed in is used to add additional triples to the individual graphs corresponding to those documents. This allows domain experts and user communities to improve the quality of search by adding relevant triples to annotate some documents.

4.8 Indexing External Documents

You can use semantic indexing on documents that are stored in a file system or on the network. In such cases, you store the references to external documents in a table column, and you create a semantic index on the column using an appropriate extractor policy.

To index external documents, define an extractor policy with appropriate preferences, using an XML document that is assigned to the preferences parameter of the [SEM_RDFCTX.CREATE_POLICY](#) procedure, as in the following example:

```
begin
  sem_rdfctx.create_policy (
    policy_name => 'SEM_EXTR_FROM_FILE',
```

```

extractor => mdsys.gatenlp_extractor(),
preferences => sys.xmltype('<RDFCTXPreferences>
                        <Datastore type="FILE">
                          <Path>EXTFILES_DIR</Path>
                        </Datastore>
                        </RDFCTXPreferences>');

end;
/

```

The `<Datastore>` element in the preferences document specifies the type of repository used for the documents to be indexed. When the value for the `type` attribute is set to `FILE`, the `<Path>` element identifies a directory object in the database (created using the SQL statement `CREATE DIRECTORY`). A table column indexed using the specified extractor policy is expected to contain relative paths to individual files within the directory object, as shown in the following example:

```

CREATE TABLE newsfeed (docid      number,
                       articleLoc VARCHAR2(100));
INSERT INTO into newsfeed (docid, articleLoc) values
      (1, 'article1.txt');
INSERT INTO newsfeed (docid, articleLoc) values
      (2, 'folder/article2.txt');

CREATE INDEX ArticleIndex on newsfeed (articleLoc)
  INDEXTYPE IS mdsys.SemContext PARAMETERS ('SEM_EXTR_FROM_FILE');

```

To index documents that are accessed using HTTP protocol, create a extractor policy with preferences that set the `type` attribute of the `<Datastore>` element to `URL` and that list one or more hosts in the `<Path>` elements, as shown in the following excerpt:

```

<RDFCTXPreferences>
  <Datastore type="URL">
    <Path>http://cnn.com</Path>
    <Path>http://abc.com</Path>
  </Datastore>
</RDFCTXPreferences>

```

The schema in which a semantic index for external documents is created must have the necessary privileges to access the external objects, including access to any proxy server used to access documents outside the firewall, as shown in the following example:

```

-- Grant read access to the directory object for FILE data store --
grant read on directory EXTFILES_DIR to SEMUSR;

-- Grant connect access to set of hosts for URL data store --
begin
  dbms_network_acl_admin.create_acl (
    acl          => 'network_docs.xml',
    description  => 'Normal Access',
    principal    => 'SEMUSR',
    is_grant     => TRUE,
    privilege    => 'connect');

end;
/

begin
  dbms_network_acl_admin.assign_acl (
    acl          => 'network_docs.xml',
    host         => 'cnn.com',

```

```

        lower_port => 1,
        upper_port => 10000);
end;
/

```

External documents that are semantically indexed in the database may be in one of the well-known formats such as Microsoft Word, RTF, and PDF. This takes advantage of the Oracle Text capability to extract plain text version from formatted documents using filters (see the CTX_DOC.POLICY_FILTER procedure, described in *Oracle Text Reference*). To semantically index formatted documents, you must specify the name of a CTX policy in the extractor preferences, as shown in the following excerpt:

```

<RDFCTXPreferences>
  <Datastore type="FILE" filter="CTX_FILTER_POLICY">
    <Path>EXTFILES_DIR</Path>
  </Datastore>
</RDFCTXPreferences>

```

In the preceding example, the CTX_FILTER_POLICY policy, created using the CTX_DDL.CREATE_POLICY procedure, must exist in your schema. The table columns that are semantically indexed using this preferences document can store paths to formatted documents, from which plain text is extracted using the specified CTX policy. The information extractor associated with the extractor policy then processes the plain text further, to extract the semantics in RDF/XML format.

4.9 Configuring the Calais Extractor type

The CALAIS_EXTRACTOR type, which is a subtype of the RDFCTX_WS_EXTRACTOR type, enables you to access a Web service end point anywhere on the network, including the one that is publicly accessible (OpenCalais.com). To do so, you must connect with SYSDBA privileges and configure the Calais extractor type with Web service end point, the SOAP action, and the license key by setting corresponding parameters, as shown in the following example:

```

begin
  sem_rdfctx.set_extractor_param (
    param_key   => 'CALAIS_WS_ENDPOINT',
    param_value => 'http://api1.opencalais.com/enlighten/calais.asmx',
    param_desc  => 'Calais web service end-point');

  sem_rdfctx.set_extractor_param (
    param_key   => 'CALAIS_KEY',
    param_value => '<Calais license key goes here>',
    param_desc  => 'Calais extractor license key');

  sem_rdfctx.set_extractor_param (
    param_key   => 'CALAIS_WS_SOAPACTION',
    param_value => 'http://clearforest.com/Enlighten',
    param_desc  => 'Calais web service SOAP Action');
end;

```

To enable access to a Web service outside the firewall, you must also set the parameter for the proxy host, as in the following example:

```

begin
  sem_rdfctx.set_extractor_param (
    param_key   => 'HTTP_PROXY',
    param_value => 'www-proxy.acme.com',
    param_desc  => 'Proxy server');

```

```
end;
```

4.10 Working with General Architecture for Text Engineering (GATE)

General Architecture for Text Engineering (GATE) is an open source natural language processor and information extractor (see <http://gate.ac.uk>). You can use GATE to perform semantic indexing of documents stored in the database. The extractor type `mdsys.gatenlp_extractor` is defined as a subtype of the `RDFCTX_EXTRACTOR` type. The implementation of this extractor type sends an unstructured document to a GATE engine over a TCP connection, receives corresponding annotations, and converts them into RDF following a user-specified XML style sheet.

The requests for information extraction are handled by a server socket implementation, which instantiates the GATE components and listens to extraction requests at a pre-determined port. The host and the port for the GATE listener are recorded in the database, as shown in the following example, for all instances of the `mdsys.gatenlp_extractor` type to use.

```
begin
  sem_rdfctx.set_extractor_param (
    param_key   => 'GATE_NLP_HOST',
    param_value => 'gateserver.acme.com',
    param_desc  => 'Host for GATE NLP Listener ');

  sem_rdfctx.set_extractor_param (
    param_key   => 'GATE_NLP_PORT',
    param_value => '7687',
    param_desc  => 'Port for Gate NLP Listener');
end;
```

The server socket application receives an unstructured document and constructs an annotation set with the desired types of annotations. Each annotation in the set may be customized to include additional features, such as the relevant phrase from the input document and some domain specific features. The resulting annotation set is serialized into XML (using the `annotationSetToXml` method in the `gate.corpora.DocumentXmlUtils` Java package) and returned back to the socket client.

A sample Java implementation for the GATE listener is available for download from the code samples and examples page on OTN (see [Section 1.10, "Semantic Data Examples \(PL/SQL and Java\)"](#) for information about this page).

The `mdsys.gatenlp_extractor` implementation in the database receives the annotation set encoded in XML, and converts it to RDF/XML using an XML style sheet. You can replace the default style sheet (listed in [Section 4.13](#)) used by the `mdsys.gatenlp_extractor` implementation with a custom style sheet when you instantiate the type.

The following example creates an extractor policy that uses a custom style sheet to generate RDF from the annotation set produced by the GATE extractor:

```
begin
  sem_rdfctx.create_policy (policy_name => 'GATE_EXTR',
                           extractor   => mdsys.gatenlp_extractor(
    sys.XMLType('<?xml version="1.0"?>
<xsl:stylesheet version="2.0"
  xmlns:xsl="http://www.w3.org/1999/XSL/Transform" >
  ..
</xsl:stylesheet>')));
end;
```

/

4.11 Creating a New Extractor Type

You can create a new extractor type by extending the `RDFCTX_EXTRACTOR` or `RDFCTX_WS_EXTRACTOR` extractor type. The extractor type to be extended must be accessible using Web service calls. The schema in which the new extractor type is created must be granted additional privileges to allow creation of the subtype. For example, if a new extractor type is created in the schema `RDFCTXU`, you must enter the following commands to grant the `UNDER` and `RDFCTX_ADMIN` privileges to that schema:

```
GRANT under ON mdsys.rdfctx_extractor TO rdfctxu;
GRANT rdfctx_admin TO rdfctxu;
```

As an example, assume that an information extractor can process an incoming document and return an XML document that contains extracted information. To enable the information extractor to be invoked using a PL/SQL wrapper, you can create the corresponding extractor type implementation, as in the following example:

```
create or replace type rdfctxu.info_extractor under rdfctx_extractor (
  xsl_trans sys.XMLType,
  constructor function info_extractor (
    xsl_trans sys.XMLType ) return self as result,
  overriding member function getDescription return VARCHAR2,
  overriding member function rdfReturnType return VARCHAR2,
  overriding member function extractRDF(document CLOB,
                                       docId VARCHAR2) return CLOB
)
/

create or replace type body rdfctxu.info_extractor as
  constructor function info_extractor (
    xsl_trans sys.XMLType ) return self as result is
  begin
    self.extr_type := 'Info Extractor Inc.';
    -- XML style sheet to generate RDF/XML from proprietary XML documents
    self.xsl_trans := xsl_trans;
    return;
  end info_extractor;

  overriding member function getDescription return VARCHAR2 is
  begin
    return 'Extractor by Info Extractor Inc.';
  end getDescription;

  overriding member function rdfReturnType return VARCHAR2 is
  begin
    return 'RDF/XML';
  end rdfReturnType;

  overriding member function extractRDF(document CLOB,
                                       docId VARCHAR2) return CLOB is
  ce_xmlt sys.xmltype;
  begin
    EXECUTE IMMEDIATE
      'begin :1 = info_extract_xml(doc => :2); end;'
      USING IN OUT ce_xmlt, IN document;

    -- Now pass the ce_xmlt through RDF/XML transformation --
```

```

        return ce_xmlt.transform(self.xml_trans).getClobVal();
    end extractRdf;

end;

```

In the preceding example:

- The implementation for the created `info_extractor` extractor type relies on the XML style sheet, set in the constructor, to generate RDF/XML from the proprietary XML schema used by the underlying information extractor.
- The `extractRdf` function assumes that the `info_extract_xml` function contacts the desired information extractor and returns an XML document with the information extracted from the document that was passed in.
- The XML style sheet is applied on the XML document to generate equivalent RDF/XML, which is returned by the `extractRdf` function.

4.12 Metadata Views for Semantic Indexing

This section describes views that contain metadata about semantic indexing.

4.12.1 MDSYS.RDFCTX_POLICIES View

Information about extractor policies defined in the current schema is maintained in the `MDSYS.RDFCTX_POLICIES` view, which has the columns shown in [Table 4-1](#) and one row for each extractor policy.

Table 4-1 *MDSYS.RDFCTX_POLICIES View Columns*

Column Name	Data Type	Description
POLICY_OWNER	VARCHAR2(32)	Owner of the extractor policy
POLICY_NAME	VARCHAR2(32)	Name of the extractor policy
EXTRACTOR	MDSYS.RDFCTX_EXTRACTOR	Instance of extractor type
IS_DEPENDENT	VARCHAR2(3)	Contains YES if the extractor policy is dependent on a base policy; contains NO if the extractor policy is not dependent on a base policy.
BASE_POLICY	VARCHAR2(32)	For a dependent policy, the name of the base policy
USER_MODELS	MDSYS.RDF_MODELS	For a dependent policy, a list of the RDF models included in the policy

4.12.2 RDFCTX_INDEX_POLICIES View

Information about semantic indexes defined in the current schema and the extractor policies used to create the index is maintained in the `MDSYS.RDFCTX_POLICIES` view, which has the columns shown in [Table 4-2](#) and one row for each combination of semantic index and extractor policy.

Table 4-2 *MDSYS.RDFCTX_INDEX_POLICIES View Columns*

Column Name	Data Type	Description
INDEX_OWNER	VARCHAR2(32)	Owner of the semantic index
INDEX_NAME	VARCHAR2(32)	Name of the semantic index

Table 4–2 (Cont.) MDSYS.RDFCTX_INDEX_POLICIES View Columns

Column Name	Data Type	Description
POLICY_NAME	VARCHAR2(32)	Name of the extractor policy
IS_DEFAULT	VARCHAR2(3)	Contains YES if POLICY_NAME is the default extractor policy for the index; contains NO if POLICY_NAME is not the default extractor policy for the index.
STATUS	VARCHAR2(10)	Contains VALID if the index is valid, INPROGRESS if the index is being created, or FAILED if a system failure occurred during the creation of the index.
RDF_MODEL	VARCHAR2(32)	Name of the RDF model maintaining the index data

4.12.3 RDFCTX_INDEX_EXCEPTIONS View

Information about exceptions encountered while creating or maintaining semantic indexes in the current schema is maintained in the MDSYS.RDFCTX_INDEX_EXCEPTIONS view, which has the columns shown in Table 4–3 and one row for each exception.

Table 4–3 MDSYS.RDFCTX_INDEX_EXCEPTIONS View Columns

Column Name	Data Type	Description
INDEX_OWNER	VARCHAR2(32)	Owner of the semantic index associated with the exception
INDEX_NAME	VARCHAR2(32)	Name of the semantic index associated with the exception
POLICY_NAME	VARCHAR2(32)	Name of the extractor policy associated with the exception
DOC_IDENTIFIER	VARCHAR2(38)	Row identifier (rowid) of the document associated with the exception
EXCEPTION_TYPE	VARCHAR2(13)	Type of exception
EXCEPTION_CODE	NUMBER	Error code associated with the exception
EXCEPTION_TEXT	CLOB	Text associated with the exception
EXTRACTED_AT	TIMESTAMP	Time at which the exception occurred

4.13 Default Style Sheet for GATE Extractor Output

This section lists the default XML style sheet that the `mdsys.gatenlp_extractor` implementation uses to convert the annotation set (encoded in XML) into RDF/XML. (This extractor is explained in Section 4.10.)

```
<?xml version="1.0"?>
  <xsl:stylesheet version="2.0"
    xmlns:xsl="http://www.w3.org/1999/XSL/Transform" >
    <xsl:output encoding="utf-8" indent="yes"/>
    <xsl:param name="docbase">http://xmlns.oracle.com/rdfctx/</xsl:param>
    <xsl:param name="docident">0</xsl:param>
    <xsl:param name="classpfx">
      <xsl:value-of select="$docbase"/>
      <xsl:text>class/</xsl:text>
    </xsl:param>
```

```

<xsl:template match="/">
  <rdf:RDF xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
    xmlns:rdfs="http://www.w3.org/2000/01/rdf-schema#"
    xmlns:owl="http://www.w3.org/2002/07/owl#"
    xmlns:prop="http://xmlns.oracle.com/rdfctx/property/">
  <xsl:for-each select="AnnotationSet/Annotation">
    <rdf:Description>
      <xsl:attribute name="rdf:about">
        <xsl:value-of select="$docbase"/>
        <xsl:text>docref/</xsl:text>
        <xsl:value-of select="$docident"/>
        <xsl:text>/</xsl:text>
        <xsl:value-of select="@Id"/>
      </xsl:attribute>
      <xsl:for-each select="./Feature">
        <xsl:choose>
          <xsl:when test="./Name[text()='majorType']">
            <rdf:type>
              <xsl:attribute name="rdf:resource">
                <xsl:value-of select="$classpfx"/>
                <xsl:text>major/</xsl:text>
                <xsl:value-of select="translate(./Value/text(),
                  ' ', '\#')"/>
              </xsl:attribute>
            </rdf:type>
          </xsl:when>
          <xsl:when test="./Name[text()='minorType']">
            <xsl:element name="prop:hasMinorType">
              <xsl:attribute name="rdf:resource">
                <xsl:value-of select="$docbase"/>
                <xsl:text>minorType/</xsl:text>
                <xsl:value-of select="translate(./Value/text(),
                  ' ', '\#')"/>
              </xsl:attribute>
            </xsl:element>
          </xsl:when>
          <xsl:when test="./Name[text()='kind']">
            <xsl:element name="prop:hasKind">
              <xsl:attribute name="rdf:resource">
                <xsl:value-of select="$docbase"/>
                <xsl:text>kind/</xsl:text>
                <xsl:value-of select="translate(./Value/text(),
                  ' ', '\#')"/>
              </xsl:attribute>
            </xsl:element>
          </xsl:when>
          <xsl:when test="./Name[text()='locType']">
            <xsl:element name="prop:hasLocType">
              <xsl:attribute name="rdf:resource">
                <xsl:value-of select="$docbase"/>
                <xsl:text>locType/</xsl:text>
                <xsl:value-of select="translate(./Value/text(),
                  ' ', '\#')"/>
              </xsl:attribute>
            </xsl:element>
          </xsl:when>
          <xsl:when test="./Name[text()='entityValue']">
            <xsl:element name="prop:hasEntityValue">
              <xsl:attribute name="rdf:datatype">
                <xsl:text>

```

```
        http://www.w3.org/2001/XMLSchema#string
      </xsl:text>
    </xsl:attribute>
    <xsl:value-of select="./Value/text()"/>
  </xsl:element>
</xsl:when>
<xsl:otherwise>
  <xsl:element name="prop:has{translate(
    substring(./Name/text(),1,1),
    'abcdefghijklmnopqrstuvwxyz',
    'ABCDEFGHIJKLMNOPQRSTUVWXYZ')}{
    substring(./Name/text(),2)}">
    <xsl:attribute name="rdf:datatype">
      <xsl:text>
        http://www.w3.org/2001/XMLSchema#string
      </xsl:text>
    </xsl:attribute>
    <xsl:value-of select="./Value/text()"/>
  </xsl:element>
</xsl:otherwise>
</xsl:choose>
</xsl:for-each>
</rdf:Description>
</xsl:for-each>
</rdf:RDF>
</xsl:template>
</xsl:stylesheet>
```

Fine-Grained Access Control for RDF Data

The default control of access to the Oracle Database semantic data store is at the model level: the owner of a model may grant select, delete, and insert privileges on the model to other users by granting appropriate privileges on the view named `RDFM_<model_name>`. However, for applications with stringent security requirements, you can enforce a fine-grained access control mechanism by using either the Virtual Private Database feature or the Oracle Label Security option of Oracle Database:

- Virtual Private Database (VPD) for RDF data allows security administrators to define policies that conditionally restrict a user's access to triples that involve instances of a specific RDF class or property. Using VPD, the data stored in the RDF models is classified using its metadata and each user query is rewritten to include context-dependent data access constraints that enforce access restrictions.

For information about using VPD, see *Oracle Database Security Guide*. For information about support for VPD with semantic data, see [Section 5.1](#).

- Oracle Label Security (OLS) for RDF data allows sensitivity labels to be associated with individual triples stored in an RDF model. For each query, access to specific triples is granted by comparing their labels with the user's session labels. Furthermore, a minimum sensitivity label for all triple describing a specific resource or all triples defined with a specific predicate can be enforced by assigning a sensitivity label directly to the resource or the predicate, respectively.

For information about using OLS, see *Oracle Label Security Administrator's Guide*. For information about support for OLS with semantic data, see [Section 5.2](#)

Some factors to consider in choosing whether use VPD or OLS with RDF data include the following:

- OLS, when enabled for RDF data, is enforced at the network level, while VPD can be enforced for individual RDF models.
- You cannot use both VPD and OLS for RDF data at the same time in an Oracle instance.

The application programming interface (API) for implementing VPD or OLS with semantic data is provided in the `SEM_RDFSA` PL/SQL package. [Chapter 12](#) provides reference information about the programs in the `SEM_RDFSA` package.

VPD and OLS support for RDF data is included in the semantic technologies support for Release 11.2. (For information about enabling, downgrading, or removing semantic technologies support, see [Appendix A](#).)

This chapter contains the following major sections:

- [Section 5.1, "Virtual Private Database \(VPD\) for RDF Data"](#)
- [Section 5.2, "Oracle Label Security \(OLS\) for RDF Data"](#)

5.1 Virtual Private Database (VPD) for RDF Data

The Virtual Private Database (VPD) feature is a row-level security mechanism that restricts access to specific rows in a relational table or view using a security policy and an application context. The security policy includes a policy function that dynamically generates predicates that are enforced for each row returned for the user query. The security predicates returned by the policy function associated with a table are typically expressed using the columns in the table and are thus dependent on the table metadata. Effectively, the security predicates ensure that the rows returned for a user query satisfy additional conditions that are applied on the contents of the row.

When the relational data is mapped to RDF, the data stored in a specific relational table represent triples describing instances of a specific RDF class. In this representation, the columns in the relational table map to RDF properties that are used to describe a resource. This mapping may be further extended to the application of VPD policies.

A VPD policy applied to RDF data restricts users' access to instances of a specific RDF class or property by applying predicates, in the form of graph patterns and filter conditions, on the instance data. For example, a VPD policy may be defined to restrict access to instances of a `Contract` RDF class only to the users belonging to a specific department. Furthermore, access to the `hasContractValue` property for a resource identified as instance of the `Contract` RDF class may be restricted only to the manager of the contract. VPD support for RDF data allows security conditions or data access constraints to be associated with RDF classes and properties, so that access to corresponding instance data is restricted.

A data access constraint associated with an RDF class or property specifies a graph query pattern that must be enforced for all corresponding data instances that are returned as the query result. For example, a SPARQL query pattern to find the due dates for all instances of a `Contract` class, `{?contract :hasDueDate ?due}`, may activate a data access constraint that ensures that the information returned pertains to contracts belonging to a specific department. This is achieved by logically rewriting the user's graph query pattern to include additional graph patterns, as shown in the following example:

```
{ ?contract :hasDueDate ?due .
  ?contract :drivenBy dept:Dept1 }
```

Furthermore, the values bound into the rewritten graph query pattern may make use of session context to enforce dynamic access restrictions. In the following example, the `sys_context` function in the object position of the triple pattern binds the appropriate department value based on the session context:

```
{ ?contract :hasDueDate ?due .
  ?contract :drivenBy
    "sys_context('sa$appctx','user_dept')"^^orardf:instruction }
```

In a relational data model, the metadata, in the form of table definition, always exists along with the data (the rows stored in the table); thus, the VPD policies defined using the metadata are well formed and the security conditions are generated using a procedural logic in the policy function.

However, the RDF data model allows data with no accompanying metadata, and therefore the class information for instance data may not always be available for a given RDF graph. For example, in an RDF graph a resource known to be a `Contract` might not accompany a triple that asserts that the resource is an instance of `Contract` class. Usually such triples can be inferred using available domain and range specifications for the properties describing the resource.

Similarly, a VPD policy relies on the properties' domain and range specifications for deriving the class information for the instance data and for enforcing appropriate data access constraints. However, to avoid runtime dependencies on the user data, a VPD policy maintains the minimal metadata required to derive the class information in its dictionary, separate from the asserted and inferred triples. This also ensures that the metadata maintained by a VPD policy is complete even when some necessary information is missing from the asserted triples and that a VPD policy, with its data access constraints and the metadata, is self-contained and portable with no external dependencies.

A VPD policy with specific data access constraints and RDF metadata specifications can be used to enforce access restrictions for the data stored in an RDF model. Each SPARQL query issued on the model is analyzed to deduce the class information for the resources accessed in the query, and appropriate data access constraints are applied. To facilitate the compile-time analysis and derivation of class information for instance data, a graph query pattern with an unbound predicate is restricted when a VPD policy is in effect. For example, a graph pattern of the following form, anywhere in a SPARQL query pattern, raises an exception when any underlying model has a VPD policy:

```
{ <contract:projectHLS> ?pred ?obj }
```

VPD policies are only enforced for SEM_MATCH queries expressed in SPARQL syntax. All other forms of data access (such as classic syntax for graph pattern or direct query on the model view) are not permitted.

5.1.1 VPD Policy for RDF Data

A VPD policy for RDF data is a named dictionary entity that can be used to enforce access restrictions for the data stored in one or more RDF models. A VPD policy defined for RDF data has unique characteristics, and it cannot be reused to enforce security policies for relational data. An RDF-VPD policy defined in the database includes the following:

- The RDF Schema statements or metadata necessary for deriving class information for the data referenced in a SPARQL user query
- The data access constraints that enforce access restrictions for the instance data
- Application context that allows conditional inclusions of groups of data access constraints based on the runtime environment

An RDF-VPD policy is defined, owned, and maintained by a user with a security administrator role in an organization. This user must have at least EXECUTE privileges on the SYS.DBMS_RLS package. The owner of an RDF-VPD policy can maintain the metadata associated with the policy, define new data access constraints, and apply the policy to one or more RDF models.

A SPARQL query issued on an RDF model with a VPD policy is analyzed, and zero or more data access constraints defined in the policy are enforced such that the data instances that are returned as the query result also satisfy these constraints. The exact data access constraints enforced for a user query vary, based on the resources referenced in the query and the application context. For example, a policy that restricts a manager's access to the `hasContractValue` property may be relaxed for a user with the Vice President role.

Based on the role of the user, as captured in the application context, specific constraints to be applied are determined at runtime. To facilitate this dynamic inclusion of subsets of constraints defined in a VPD policy, the data access constraints

are arranged into named groups that can be activated and deactivated based on the application context. During query analysis, only the constraints defined in the active groups are considered for enforcement.

The constraint groups within a VPD policy are managed using an application context and its package implementation. Each VPD policy can specify the namespace for a context created with the CREATE CONTEXT command. Each attribute associated with the context is treated as the name of a constraint group that can be activated by initializing its value to 1. For example, setting the value for MANAGER attribute of the context associated with a VPD policy to 1 will activate the constraints associated with MANAGER group for the user session. The logic that initializes specific constraint groups based on the user context is typically embedded in the package associated with the context type. The following example shows an excerpt from a sample implementation for one such package:

```
CREATE CONTEXT contracts_constr_ctx using sec_admin.contracts_ctx_pack;

begin
  -- create the VPD policy with a context --
  sem_rdfsa.create_vpd_policy(policy_name => 'CONTRACTS_POLICY',
                             policy_context => 'contracts_constr_ctx');
end;
/

create or replace package sec_admin.contracts_ctx_pack as
  procedure init_constr_groups;
end;
/

create or replace package body sec_admin.contracts_ctx_pack as
  procedure init_contr_groups is
    hrdata EmpRole%rowtype;
  begin
    -- specific users with FULL access to the data associated with
    -- the policy --
    if (sys_context('userenv', 'session_user') = 'RDF_ADMIN') then
      dbms_session.set_context('contracts_constr_ctx',
                              sem_rdfsa.VPD_FULL_ACCESS, 1);

      return;
    end if;

    SELECT * into hrdata FROM EmpRole WHERE guid =
      sys_context('userenv', 'session_user');

    if (hrdata.emprole = 'VP') then
      -- if the user logged in has VP role, activate the constraint
      -- group named VP and keep all other groups inactive.
      dbms_session.set_context('contracts_constr_ctx', 'VP', '1');
    elsif (hrdata.emprole = 'MANAGER') then
      dbms_session.set_context('contracts_constr_ctx', 'MANAGER', '1');
    elsif ...
      ...
    else
      raise_application_error(-20010, 'unknown user role');
    end if;

    exception when others then
      -- enforce constraints for all groups --
      dbms_session.clear_all_context('contracts_constr_ctx');
    end init_contr_groups;
```

```
end;
/
```

By default, when a namespace is not associated with an RDF-VPD policy or when a specific constraint group is not activated in a session, all the constraints defined in the policy are active and they are enforced for each user query. However, when a specific constraint group is activated by setting the corresponding namespace-attribute value to 1, only the constraints belonging to the group and any other constraints that are not associated with any group are enforced. For a given session, one or more constraint groups may be activated, in which case all the applicable constraints are enforced conjunctively.

At the time of creation, the data access constraints defined in a RDF-VPD policy may specify the name of a constraint group (explained in [Section 5.1.3, "Data Access Constraints"](#)). Within a database session, appropriate groups of constraints are activated based on the session context set by the context package. For all subsequent SPARQL queries in the database session, the constraints belonging to the active groups are consulted for enforcing appropriate security policies.

Maintenance operations on an RDF model with a VPD policy require unconditional access to data in the model. These operations include creation of an entailment using at least one VPD protected model, and load or data manipulation operations. You can grant unconditional access to the data stored in an RDF model by initializing a reserved attribute for the namespace associated with the VPD policy. The reserved attribute is defined by the package constant `sem_rdfsa.VPD_FULL_ACCESS`, and the context package implementation shown in the preceding example grants FULL access to the RDF_ADMIN user.

DML operations on the application table are not validated for VPD constraint violations, so only a user with FULL access to the corresponding model can add or modify existing triples.

You can use the SEM_MATCH operator to query an RDF model with a VPD policy in a standard SQL query, and to perform a multi-model query on a combination of VPD-enabled models and models with no VPD policy. However, when more than one model in a multi-model query is VPD-enabled, they must all be associated with the same VPD policy. A VPD policy associated with an RDF model is automatically extended to any data inferred from the model. When multiple RDF models are specified during inference, all VPD-enabled models within the set should use the same VPD policy.

5.1.2 RDF Metadata for Enforcing VPD Policies

The types of RDF metadata used to enforce VPD policies include the following:

- Domain and range information for the properties used in the graph
- Subclass relationships in the graph
- Subproperty relationships in the graph
- Equivalent properties in the graph

The RDF metadata associated with a VPD policy is specified as one or more RDF Schema statements using one of the following property URIs:

- `http://www.w3.org/2000/01/rdf-schema#domain`
- `http://www.w3.org/2000/01/rdf-schema#range`
- `http://www.w3.org/2000/01/rdf-schema#subClassOf`

- <http://www.w3.org/2000/01/rdf-schema#subPropertyOf>
- <http://www.w3.org/2002/07/owl#equivalentProperty>

For example, the following RDF Schema statement associated with `contracts_policy` asserts that the domain of the `hasContractValue` property is a `Contract` class. Note that range specification for the predicates can be skipped if they are not relevant or if they are of literal type

```
begin
  sem_rdfsa.maint_vpd_metadata(
    policy_name => 'contracts_policy',
    t_subject   => '<http://www.myorg.com/pred/hasContractValue>',
    t_predicate => '<http://www.w3.org/2000/01/rdf-schema#domain>',
    t_object    => '<http://www.myorg.com/classes/Contract>');
end;
/
```

An RDF-VPD policy maintains its metadata separate from the asserted and inferred triples. You can derive this metadata programmatically from the RDF models and the corresponding entailments. For example, if the domain and range information for the properties and subclass and subproperty relationships are already established in the asserted or inferred triples, you can use a SQL query on the underlying model views to populate the metadata for an RDF-VPD policy.

The domain and range information for the properties aid the query analysis in determining the RDF class type for the terms and unbound variables referenced in the query. This information is further used to enforce appropriate data access constraints on the data accessed by the query. The metadata relating to the subclass property is used to ensure that a data access constraint defined for a specific class in a class hierarchy is automatically enforced for all its subclasses. Similarly, the subproperty specification in a VPD policy is used to enforce any constraints associated with a property to all its subproperties.

The RDF Schema statements associated with a VPD policy are not used to infer additional statements, and the security administrator should ensure that the metadata captured in a VPD policy is complete by cross checking it with inferred data. For example, a subproperty schema statement does not automatically infer the domain and range information for the property based on the domain and range specified for the super-property.

Certain owl and rdfs properties in the asserted triples, when left unchecked, may be used to infer data that may be used to circumvent the VPD policies. For example, when the new property is defined as a super-property of a property that has a specific data access constraint, the inferred data may duplicate all instances of the subproperty using the super-property. Unless the VPD policy explicitly defines access constraints for the super-property, the inferred data may be used to circumvent the access restrictions.

The ability to infer new data is only granted to users with FULL access, and such users should ensure that the metadata associated with the VPD policy is complete in light of newly inferred data. Specifically, the metadata associated with the VPD policy should be maintained if some new `rdfs:subClassOf`, `rdfs:superClassOf`, `rdfs:subPropertyOf`, `rdfs:superPropertyOf`, or `owl:equivalentProperty` assertions are generated during inference. Also, any new properties introduced by the rulebases used for inference may need domain and range specifications, as well as data access constraints, if they are associated with some sensitive information.

In a VPD policy, a property can be declared to be equivalent to another property so that the domain and range information, as well as any constraints defined for the

original property, are automatically duplicated for the equivalent property. However, within a VPD policy, additional metadata or data access constraints cannot be directly assigned to the property declared to be an equivalent of another property.

5.1.3 Data Access Constraints

The data access constraints associated with a VPD policy fall into two general categories, based on the types of access restrictions that they enforce:

- Those that restrict access to instances of specific RDF classes
- Those that restrict to assertions using specific RDF properties

The access restrictions are enforced conditionally, based on the application context and the characteristics of the resources being accessed in a SPARQL query. Data access constraints restrict access to instances of an RDF class or property using some properties associated with the resource. For example, access to a resource that is a member of the `Contract` class may be restricted only to the users who work on the contract, identified using the `hasMember` property associated with the resource. Similarly, access to the `hasContractValue` property for a resource may be restricted to a user identified as the manager of the contract using `hasManager` property associated with the same resource.

Each data access constraint is expressed using two graph patterns identified as a match pattern and an apply pattern. The **match pattern** of a constraint determines the type of access restriction it enforces and binds one or more variables to the corresponding data instances accessed in the user query. For example, the following match pattern is defined for instances of the `Contract` class, and it binds a variable to all such instances accessed through a SPARQL query:

```
{ ?contract rdf:type <http://www.myorg.com/classes/Contract> }
```

Similarly, a match pattern for a constraint involving an RDF property matches the instances of the property accessed in a SPARQL query, and binds two variables to the resources in the subject and object position of such instances. For example, the match pattern for a constraint on the `hasContractValue` property is defined as follows:

```
{ ?contract <http://www.myorg.com/pred/hasContractValue> ?cvalue }
```

The **apply pattern** of a data access constraint defines additional graph patterns to be applied on the resources that match the match pattern before they can be used to construct the query results. One or more variables defined in the match pattern of a data access constraint are used in the corresponding apply pattern to enforce the access restrictions on the identified resources. For example, the following match pattern and apply pattern combination ensures that the `hasContractValue` of a contract can be accessed only if `Andy` is the manager of the contract being accessed.:

```
Match: { ?contract pred:hasContractValue ?cvalue }
Apply: { ?contract pred:hasManager      emp:Andy }
```

A data access constraint with its match and apply patterns expressed in SPARQL syntax can be added to a VPD policy to enforce access restrictions on the data stored in RDF models that are associated with the VPD policy. The following example, which adds a constraint to the VPD policy, assumes that the VPD policy is defined with appropriate namespace map for the `pred` and `emp` namespace prefixes. (To associate a namespace map with a VPD policy, use the [SEM_RDFSA.CREATE_VPD_POLICY](#) procedure.)

```
begin
  sem_rdfsa.add_vpd_constraint(
```

```

policy_name => 'contracts_policy',
constr_name => 'andy_constraint_1',
match_pattern => '{?contract pred:hasContractValue ?cvalue }',
apply_pattern => '{?contract pred:hasManager emp:Andy }',
constr_group => 'andy');

end;
/

```

The ability to arrange data access constraints into groups could ensure that the previous constraint is applied only for the sessions associated with Andy. However, to avoid proliferation of structurally similar constraints for each user, you can define a common constraint that uses the application context in the object position of the apply graph patterns, as shown in the following example:

```

begin
  sem_rdfsa.add_vpd_constraint(
    policy_name => 'contracts_policy',
    constr_name => 'manager_constraint_1',
    match_pattern => '{?contract pred:hasContractValue ?cvalue }',
    apply_pattern => '{?contract pred:hasManager
      "sys_context('sa$appctx','app_user_uri')"^^orardf:instruction }',
    constr_group => 'manager');
end;
/

```

In the preceding example, the data access constraint, defined within the manager constraint group, can be activated for all sessions involving users with a manager role. In this case, the secure application context can be programmed to initialize the attribute `app_user_uri` of the `sa$appctx` namespace with the URI for the user logged in. For example, when user Andy logs into the application, the `app_user_uri` attribute can be initialized to `<http://www.myorg.com/employee/Andy>`, in which case the constraint will ensure that user Andy can view the value for a contract only if user Andy manages the contract. Generally, the `sys_context` function can be used in the object position of any graph pattern to allow dynamic URIs or literal values to be bound at the time of query execution. Note that if the context is not initialized properly, the preceding constraint will fail for all data instances and effectively restrict the user from accessing any data.

A SPARQL query issued on an RDF model with a VPD policy is analyzed using the match patterns of all the active data access constraints that are defined in the policy. In the next example, the SPARQL query refers to the `hasContractValue` property, thereby enforcing the constraint if the group is active. Logically, the enforcement of a constraint is equivalent to rewriting the original SPARQL graph pattern to include the apply patterns for all the relevant constraints, using appropriate variables and terms from the user query. With the previous access restriction on the `hasContractValue` property, the following SPARQL graph pattern passed to a `SEM_MATCH` operator is logically rewritten as shown in the following example:

```

Query:
{ ?contr pred:drivenBy      ?dept .
  ?contr pred:hasContractValue ?val }

Rewritten query:
{ ?contr pred:drivenBy      ?dept .
  ?contr pred:hasContractValue ?val .
  ?contr pred:hasManager
    "sys_context('sa$appctx','app_user_uri')"^^orardf:instruction }

```

When the match pattern of a data access constraint on an RDF property matches the pattern being accessed in a user query, the equivalent VPD-enforced query appends the corresponding apply patterns to the SPARQL query using the variables and terms appearing in the matched pattern. When a SPARQL query has nested graph patterns, the data access constraints are applied to appropriate basic query graph pattern block. In the following example, the `hasContractValue` property is referenced in the `OPTIONAL` graph pattern, and therefore the corresponding apply pattern is enforced just for this block of the graph pattern.

```
Query:
{ ?contr pred:drivenBy      ?dept .
  OPTIONAL { ?contr pred:hasContractValue ?val } }

Rewritten query:
{ ?contr pred:drivenBy      ?dept .
  OPTIONAL { ?contr pred:hasContractValue ?val .
            ?contr pred:hasManager
            "sys_context('sa$appctx','app_user_uri')""^^orardf:instruction }
```

The apply pattern for a data access constraint can be any valid basic graph pattern with multiple triple patterns and a `FILTER` clause. For example, the access constraint on the `hasContractValue` property for a user with `VP` role may stipulate that the user can access the property only if he or she is the Vice President of the department driving the contract. The match and apply patterns for such constraint can be defined as follows:

```
Match: { ?contract pred:hasContractValue ?cvalue }
Apply: { ?contract pred:drivenBy      ?dept .
        ?dept      pred:hasVP
        "sys_context('sa$appctx','app_user_uri')""^^orardf:instruction }
```

A match pattern defined for a data access constraint associated with an RDF class identifies all variables and terms that are known to be instances of the class. The RDF metadata defined in the VPD policy is used to determine the type for each variable and the term in a SPARQL query, and the appropriate access constraints are applied on these variables and terms. For example, the following VPD constraint ensures that a resource that is a member of the `Contract` class can only be accessed by a user who has a `hasMember` relationship with the resource:

```
Match: { ?contract rdf:type <http://www.myorg.com/classes/Contract> }
Apply: { ?contract pred:hasMember
        "sys_context('sa$appctx','app_user_uri')""^^orardf:instruction }
```

The class information for a variable or term appearing in a SPARQL query is derived using the domain and range information for the properties appearing in the query. In the SPARQL query in the next example, if the VPD policy has an RDF Schema statement that asserts that the domain of the `drivenBy` property is the `Contract` class, the variable `?contr` is known to hold instances of the `Contract` class. Therefore, with the previously defined access restriction for the `Contract` class, the user query is rewritten to include an appropriate apply pattern, as shown in the following example:

```
Query:
{ ?contr pred:drivenBy      ?dept .
  ?contr pred:hasDueDate    ?due }

Rewritten query:
{ ?contr pred:drivenBy      ?dept .
  ?contr pred:hasDueDate    ?due .
  ?contr pred:hasMember     }
```

```
?contr pred:hasMember
      "sys_context('sa$appctx','app_user_uri')"^^orrdf:instruction }
```

When a basic graph pattern in a SPARQL query matches multiple data access constraints, the corresponding apply patterns are combined to form a conjunctive graph pattern, which is subsequently enforced for the specific graph pattern by logically rewriting the SPARQL query. While considering the data access constraints to be enforced for a given SPARQL query, the class and property hierarchy associated with the VPD policy is consulted to automatically enforce all applicable constraints.

- A variable or term identified as an instance of a specific RDF class enforces constraints associated with the class and all its superclasses.
- A constraint associated with a property is enforced when the user query references the property or any property defined as its subproperty or an equivalent property.

You can use the `sys_context` function in a data access constraint to enforce context-dependent access restrictions with structurally similar graph patterns. You can dynamically activate and deactivate constraint groups, based on the application context, to enforce alternate access restrictions using structurally different graph patterns.

5.1.4 RDFVPD_POLICIES View

The `MDSYS.RDFVPD_POLICIES` view contains information about all VPD policies defined in the schema or the policies to which the user has FULL access. If the same policy is associated with multiple models, this view has one entry for each such association. This view exists only after the semantic network and a VPD policy have been created.

The `MDSYS.RDFVPD_POLICIES` view contains the columns shown in [Table 5-1](#).

Table 5-1 MDSYS.RDFVPD_POLICIES View Columns

Column Name	Data Type	Description
POLICY_OWNER	VARCHAR2(32)	Owner of the VPD policy.
POLICY_NAME	VARCHAR2(32)	Name of the VPD policy.
NAMESPACE_MAP	RDF_ALIASES	Mapping for namespace entries that are used in the VPD constraint definitions.
CONTEXT_NAME	VARCHAR2(32)	Name of the context used to manage constraint groups.

5.1.5 RDFVPD_MODELS View

The `MDSYS.RDFVPD_MODELS` view contains information about RDF models and their associated VPD policies. This view exists only after the semantic network and a VPD policy have been created.

The `MDSYS.RDFVPD_MODELS` view contains the columns shown in [Table 5-2](#).

Table 5-2 MDSYS.RDFVPD_MODELS View Columns

Column Name	Data Type	Description
MODEL_NAME	VARCHAR2(25)	Name of the model.
POLICY_OWNER	VARCHAR2(32)	Owner of the VPD policy.

Table 5–2 (Cont.) MDSYS.RDFVPD_MODELS View Columns

Column Name	Data Type	Description
POLICY_NAME	VARCHAR2(32)	Name of the VPD policy.
OPERATION_ TYPE	VARCHAR2(9)	Type of operation for which the VPD policy is enforced: QUERY or DML.

5.1.6 RDFVPD_POLICY_CONSTRAINTS View

The MDSYS.RDFVPD_POLICY_CONSTRAINTS view contains information about the constraints defined in the VPD policy that are accessible to the current user. This view exists only after the semantic network and a VPD policy have been created.

The MDSYS.RDFVPD_POLICY_CONSTRAINTS view contains the columns shown in [Table 5–3](#).

Table 5–3 MDSYS.RDFVPD_POLICY_CONSTRAINTS View Columns

Column Name	Data Type	Description
POLICY_ OWNER	VARCHAR2(32)	Owner of the VPD policy.
POLICY_NAME	VARCHAR2(32)	Name of the VPD policy.
CONSTRAINT_ NAME	VARCHAR2(32)	Name of the constraint.
MATCH_ PATTERN	VARCHAR2(1000)	Match pattern for the constraint.
APPLY_ PATTERN	VARCHAR2(4000)	Apply pattern for the constraint.
CONSTRAINT_ GROUP	VARCHAR2(32)	Name of the constraint group to which the constraint belongs. (Not case-sensitive.).

5.1.7 RDFVPD_PREDICATE_MDATA View

The MDSYS.RDFVPD_PREDICATE_MDATA view contains information about the predicate metadata associated with a VPD policy. This view exists only after the semantic network and a VPD policy have been created.

The MDSYS.RDFVPD_PREDICATE_MDATA view contains the columns shown in [Table 5–4](#).

Table 5–4 MDSYS.RDFVPD_PREDICATE_MDATA View Columns

Column Name	Data Type	Description
POLICY_ OWNER	VARCHAR2(32)	Owner of the VPD policy.
POLICY_NAME	VARCHAR2(32)	Name of the VPD policy.
PREDICATE	VARCHAR2(4000)	URI for the predicate for which the domain and range information is defined.
HASDOMAIN	VARCHAR2(4000)	URI representing the domain of the predicate.
HASRANGE	VARCHAR2(4000)	URI representing the range of the predicate.

5.1.8 RDFVPD_RESOURCE_REL View

The MDSYS.RDFVPD_RESOURCE_REL view contains information about the subclass, subproperty, and equivalence property relationships that are defined between resources in a VPD policy. This view exists only after the semantic network and a VPD policy have been created.

The MDSYS.RDFVPD_RESOURCE_REL view contains the columns shown in [Table 5-5](#).

Table 5-5 MDSYS.RDFVPD_RESOURCE_REL View Columns

Column Name	Data Type	Description
POLICY_OWNER	VARCHAR2(32)	Owner of the VPD policy.
POLICY_NAME	VARCHAR2(32)	Name of the VPD policy.
SUBJECT_RESOURCE	VARCHAR2(4000)	Subject resource.
OBJECT_RESOURCE	VARCHAR2(4000)	Object resource.
RELATIONSHIP_TYPE	VARCHAR2(4000)	Relationship that exists between the subject resource and the object resource.

5.2 Oracle Label Security (OLS) for RDF Data

Oracle Label Security (OLS) for RDF data provides two options for securing semantic data:

- Triple-level security (explained in [Section 5.2.1](#)), which is highly recommended for its performance and ease of use, but requires that a patch be installed
- Resource-level security (explained in [Section 5.2.2](#))

To specify an option, use the [SEM_RDFSA.APPLY_OLS_POLICY](#) procedure with the appropriate `rdfsa_options` parameter value.

To switch from one option to the other, remove the existing policy by using the [SEM_RDFSA.REMOVE_OLS_POLICY](#) procedure, and then apply the new policy by using the [SEM_RDFSA.APPLY_OLS_POLICY](#) procedure with the appropriate `rdfsa_options` parameter value.

5.2.1 Triple-Level Security

The triple-level security option provides a thin layer of RDF-specific capabilities on top of the Oracle Database native support for label security. This option provides better performance and is easier to use than the resource-level security (described in [Section 5.2.2](#)), especially for performing inference while using OLS. The main difference is that with triple-level security there is no need to assign labels, explicitly or implicitly, to individual triple resources (subjects, properties, objects).

Note: To use triple-level security, you *must* first install Patch 9819833 *SEMANTIC TECHNOLOGIES 11G R2 FIX BUNDLE 2* (available from My Oracle Support).

To use triple-level security, specify `SEM_RDFSA.TRIPLE_LEVEL_ONLY` as the `rdfsa_options` parameter value when you execute the [SEM_RDFSA.APPLY_OLS_POLICY](#) procedure. For example:

```
EXECUTE sem_rdfsa.apply_ols_policy('defense', SEM_RDFSA.TRIPLE_LEVEL_ONLY);
```

Do not specify any of the other available parameters for the [SEM_RDFSA.APPLY_OLS_POLICY](#) procedure.

When you use triple-level security, OLS is applied to each semantic model in the network. That is, label security is applied to the relevant internal tables and to all the application tables; there is no need to manually apply policies to the application tables of existing semantic models. However, if you need to create additional models after applying the OLS policy, you must use the `___??_SEM_OLS.APPLY_POLICY_TO_APP_TAB___` procedure to apply OLS to the application table before creating the model. Similarly, if you have dropped a semantic model and you no longer need to protect the application table, you can use the `___??_SEM_OLS.REMOVE_POLICY_FROM_APP_TAB___` procedure. (These procedures are described in [Chapter 12](#).)

With triple-level security, duplicate triples with different labels can be inserted in the semantic model. (Such duplicates are not allowed with resource-level security.) For example, assume that you have a triple with a very sensitive label, such as:

```
(<urn:X>, <urn:P>, <urn:Y>, "TOPSECRET")
```

This does not prevent a low-privileged (UNCLASSIFIED) user from inserting the triple (`<urn:X>, <urn:P>, <urn:Y>, "UNCLASSIFIED"`). Because SPARQL and `SEM_MATCH` do not return label information, a query will return both rows (assuming the user has appropriate privileges), and it will not be easy to distinguish between the TOPSECRET and UNCLASSIFIED triples.

To filter out such low-security triples when querying the semantic models, you can one or more the following options with `SEM_MATCH`:

- `POLICY_NAME` specifies the OLS policy name.
- `MIN_LABEL` specifies the minimum label for triples that are included in the query

In other words, every triple that contains a label that is strictly dominated by `MIN_LABEL` is not included in the query. For example, to filter out the “UNCLASSIFIED” triple, you could use the following query (assuming the OLS policy name is DEFENSE and that the query user has read privileges over UNCLASSIFIED and TOPSECRET triples):

```
SELECT s,p,y FROM table(sem_match('{?s ?p ?y}' ,
    sem_models(TEST'), null, null, null, null,
    'MIN_LABEL=TOPSECRET POLICY_NAME=DEFENSE'));
```

Note that the filtering in the preceding example occurs in addition to the security checks performed by the native OLS software.

After a triple has been inserted, you can view and update the label information can be done through the `CTXT1` column in the application table for the semantic model (assuming that you have the `WRITEUP` and `WRITEDOWN` privileges to modify the labels).

There are no restrictions on who can perform inference or bulk loading with triple-level security; all of the inferred or bulk loaded triples are inserted with the user’s session row label. Note that you can change the session labels by using the `SA_UTL` package. (For more information, see *Oracle Label Security Administrator’s Guide*.)

5.2.2 Resource-Level Security

The resource-level security option enables you to assign one or more security labels that define a security level for table rows. Conceptually, a table in a relational data model can be mapped to an equivalent RDF graph. Specifically, a row in a relational table can be mapped to a set of triples, each asserting some facts about a specific Subject. In this scenario, the subject represents the primary key for the row and each non-key column-value combination from the row is mapped to a predicate-object value combination for the corresponding triples.

A row in a relational data model is identified by its key, and OLS, as a row-level access control mechanism, effectively restricts access to the values associated with the key. With this conceptual mapping between relational and RDF data models, restricting access to a row in a relational table is equivalent to restricting access to a subgraph involving a specific subject. In a model that supports sensitivity labels for each triple, this is enforced by applying the same label to all the triples involving the given subject. However, you can also achieve greater flexibility by allowing the individual triples to have different labels, while maintaining a minimum bound for all the labels.

OLS support for RDF data employs a multilevel approach in which sensitivity labels associated with the triple components (subject, predicate, object) collectively form a minimum bound for the sensitivity label for the triple. With this approach, a data sensitivity label associated with an RDF resource (used as subject, predicate, or object) restricts unauthorized users from accessing any triples involving the resource and from creating new triples with the resource. For example, `projectHLS` as a subject may have a minimum sensitivity label, which ensures that all triples describing this subject have a sensitivity label that at least covers the label for `projectHLS`. Additionally, `hasContractValue` as a predicate may have a higher sensitivity label; and when this predicate is used with `projectHLS` to form a triple, that triple minimally has a label that covers both the subject and the predicate labels, as in the following example:

```
Triple 1: <http://www.myorg.com/contract/projectHLS> :ownedBy
                                                <http://www.myorg.com/department/Dept1>
Triple 2: <http://www.myorg.com/contract/projectHLS> :hasContractValue
                                                "100000"^^xsd:integer
```

Sensitivity labels are associated with the RDF resources (URIs) based on the position in which they appear in a triple. For example, the same RDF resource may appear in different positions (subject, predicate, or object) in different triples. Three unique labels can be assigned to each resource, so that the appropriate label is used to determine the label for a triple based on the position of the resource in the triple. You can choose the specific resource positions to be secured in a database instance when you apply an OLS policy to the RDF repository. You can secure subjects, objects, predicates, or any combination, as explained in separate sections to follow. The following example applies an OLS policy named `defense` to the RDF repository and allows sensitivity labels to be associated with RDF subjects and predicates.

```
begin
  sem_rdfsa.apply_ols_policy(
    policy_name => 'defense',
    rdfsa_options => sem_rdfsa.SECURE_SUBJECT+
                    sem_rdfsa.SECURE_PREDICATE);
end;
/
```

The same RDF resource can appear in both the subject and object positions (and sometime even as the predicate), and such a resource can have distinct sensitivity labels based on its position. A triple using the resource at a specific position should

have a label that covers the label corresponding to the resource's position. In such cases, the triple can be asserted or accessed only by the users with labels that cover the triple and the resource labels.

In a specific RDF repository, security based on data classification techniques can be turned on for subjects, predicates, objects, or a combination of these. This ensures that all the triples added to the repository automatically conform to the label relationships described above.

5.2.2.1 Securing RDF Subjects

An RDF resource (typically a URI) appears in the subject position of a triple when an assertion is made *about* the resource. In this case, a sensitivity label associated with the resource has following characteristics:

- The label represents the minimum sensitivity label for any triple using the resource as a subject. In other words, the sensitivity label for the triple should dominate or cover the label for the subject.
- The label for a newly added triple is initialized to the user initial row label or is generated using the label function, if one is specified. Such operations are successful only if the triple's label dominates the label associated with the triple's subject.
- Only a user with an access label that dominates the subject's label and the triple's label can read the triple.

By default, the sensitivity label for a subject is derived from the user environment when an RDF resource is used in the subject position of a triple for the first time. The default sensitivity label in this case is set to the user's initial row label (the default that is assigned to all rows inserted by the user).

However, you can categorize an RDF resource as a subject and assign a sensitivity label to it even before it is used in a triple. The following example assigns a sensitivity label named `SECRET:HLS:US` to the `projectHLS` resource, thereby restricting the users who are able to define new triples about this resource and who are able to access existing triples with this resource as the subject:

```
begin
  sem_rdfsa.set_resource_label(
    model_name => 'contracts',
    resource_uri => '<http://www.myorg.com/contract/projectHLS>',
    label_string => 'SECRET:HLS:US',
    resource_pos => 'S');
end;
```

5.2.2.2 Securing RDF Predicates

An RDF predicate defines the relationship between a subject and an object. You can use sensitivity labels associated with RDF predicates to restrict access to specific types of relationships with all subjects.

RDF predicates are analogous to columns in a relational table, and the ability to restrict access to specific predicates is equivalent to securing relational data at the column level. As in the case of securing the subject, the predicate's sensitivity label creates a minimum bound for any triples using this predicate. It is also the minimum authorization that a user must possess to define a triple with the predicate or to access a triple with the predicate.

The following example assigns the label `HSECRET:FIN` (in this scenario, a label that is Highly Secret and that also belongs to the Finance department) to triples with the

hasContractValue predicate, to ensure that only a user with such clearance can define the triple or access it:

```
begin
  sem_rdfsa.set_predicate_label(
    model_name => 'contracts',
    predicate  => '<http://www.myorg.com/pred/hasContractValue>',
    label_string => 'HSECRET:FIN');
end;
/
```

You can secure predicates in combination with subjects. In such cases, the triples using a subject and a predicate are ensured to have a sensitivity label that at least covers the labels for both the subject and the predicate. Extending the preceding example, if `projectHLS` as a subject is secured with label `SECRET:HLS:US` and if `hasContractValue` as a predicate is secured with label `HSECRET:FIN:`, a triple assigning a monetary value for `projectHLS` should at least have a label `HSECRET:HLS,FIN:US`. Effectively, a user's label must dominate this triple's label to be able to define or access the triple.

5.2.2.3 Securing RDF Objects

An RDF triple can have an URI or a literal in its object position. The URI in object position of a triple represents some resource. You can secure a resource in the object position by associating a sensitivity label to it, to restrict the ability to use the resource as an object in triples.

Typically, a resource (URI or non-literal) appearing in the object position of a triple may itself be described using additional RDF statements. Effectively, an RDF resource in the object position could appear in the subject position in some other triples. When the RDF resources are secured at the object position without explicit sensitivity labels, the label associated with the same resource in the subject position is used as the default label for the object.

5.2.2.4 Generating Labels for Inferred Triples

RDF data model allows for specification of declarative rules, enabling it to *infer* the presence of RDF statements that are not explicitly added to the repository. The following shows some simple declarative rules associated with the logic that projects can be owned by departments and departments have Vice Presidents, and in such cases the project leader is by default the Vice President of the department that owns the project.

```
RuleID -> projectLedBy
Antecedent Expression -> (?proj :ownedBy ?dept) (?dept :hasVP ?person)
Consequent Expression -> (?proj :isLedBy ?person)
```

An RDF rule uses some explicitly asserted triples as well as previously inferred triples as antecedents, and infers one or more consequent triples. Traditionally, the inference process is executed as an offline operation to pregenerate all the inferred triples and to make them available for subsequent query operations.

When the underlying RDF graph is secured using OLS, any additional data inferred from the graph should also be secured to avoid exposing the data to unauthorized users. Additionally, the inference process should run with higher privileges, specifically with full access to data, in order to ensure completeness.

OLS support for RDF data offers techniques to generate sensitivity labels for inferred triples based on labels associated with one or more RDF artifacts. It provides label generation techniques that you can invoke at the time of inference. Additionally, it

provides an extensibility framework, which allows an extensible implementation to receive a set of possible labels for a specific triple and determine the most appropriate sensitivity label for the triple based on some application-specific logic. The techniques that you can use for generating the labels for inferred triples include the following (each technique, except for Use Antecedent Labels, is associated with a SEM_RDFSA package constant):

- Use Rule Label (`SEM_RDFSA.LABELGEN_RULE`): An inferred triple is directly generated by a specific rule, and it may be indirectly dependent on other rules through its antecedents. Each rule may have a sensitivity label, which is used as the sensitivity label for all the triples directly inferred by the rule.
- Use Subject Label (`SEM_RDFSA.LABELGEN_SUBJECT`): Derives the label for the inferred triple by considering any sensitivity labels associated with the subject in the new triple. Each inferred triple has a subject, which could in turn be a subject, predicate, or object in any of the triple's antecedents. When such RDF resources are secured, the subject in the newly inferred triple may have one or more labels associated with it. With the Use Subject Label technique, the label for the inferred triple is set to the unique label associated with the RDF resource. When more than one label exists for the resource, you can implement the extensible logic to determine the most relevant label for the new triple.
- Use Predicate Label (`SEM_RDFSA.LABELGEN_PREDICATE`): Derives the label for the inferred triple by considering any sensitivity labels associated with the predicate in the new triple. Each inferred triple has a predicate, which could in turn be a subject, predicate, or object in any of the triple's antecedents. When such RDF resources are secured, the predicate in the newly inferred triple may have one or more labels associated with it. With the Use Predicate Label technique, the label for the inferred triple is set to the unique label associated with the RDF resource. When more than one label exists for the resource, you can implement the extensible logic to determine the most relevant label for the new triple.
- Use Object Label (`SEM_RDFSA.LABELGEN_OBJECT`): Derives the label for the inferred triple by considering any sensitivity labels associated with the object in the new triple. Each inferred triple has an object, which could in turn be a subject, predicate, or object in any of the triple's antecedents. When such RDF resources are secured, the object in the newly inferred triple may have one or more labels associated with it. With the Use Object Label technique, the label for the inferred triple is set to the unique label associated with the RDF resource. When more than one label exists for the resource, you can implement the extensible logic to determine the most relevant label for the new triple.
- Use Dominating Label (`SEM_RDFSA.LABELGEN_DOMINATING`): Each inferred triple minimally has four direct components: subject, predicate, object, and the rule that produced the triple. With the Use Dominating Label technique, at the time of inference the label generator computes the most dominating of the sensitivity labels associated with each of the component and assigns it as the sensitivity label for the inferred triple. Exception labels are assigned when a clear dominating relationship cannot be established between various labels.
- Use Antecedent Labels: In addition to the four direct components for each inferred triple (subject, predicate, object, and the rule that produced the triple), a triple may have one or more antecedent triples, which are instrumental in deducing the new triple. With the Use Antecedent Labels technique, the labels for all the antecedent triples are considered, and conflict resolution criteria are implemented to determine the most appropriate label for the new triple. Since an inferred triple may be dependent on other inferred triples, a strict order is followed while generating the labels for all the inferred triples.

The Use Antecedent Labels technique requires that you use a custom label generator. For information about creating and using a custom label generator, see [Section 5.2.2.5](#).

The following example creates an entailment (rules index) for the contracts data using a specific rule base. This operation can only be performed by a user with FULL access privilege with the OLS policy applied to the RDF repository. In this case, the labels generated for the inferred triples are based on the labels associated with their predicates, as indicated by the use of the `SEM_RDFSA.LABELGEN_PREDICATE` package constant in the `label_gen` parameter.

```
begin
  sem_rdfsa.create_entailment(
    index_name_in  => 'contracts_inf',
    models_in      => SDO_RDF_Models('contracts'),
    rulebases_in   => SDO_RDF_Rulebases('contracts_rb'),
    options        => 'USER_RULES=T',
    label_gen      => sem_rdfsa.LABELGEN_PREDICATE);
end;
```

When the predefined or extensible label generation implementation cannot compute a unique label to be applied to an inferred triple, an exception label is set for the triple. Such triples are not accessible by any user other than the user with full access to RDF data (also the user initiating the inference process). The triples with exception labels are clearly marked, so that a privileged user can access them and apply meaningful labels manually. After the sensitivity labels are applied to inferred triples, only users with compatible labels can access these triples. The following example updates the sensitivity label for triples for which an exception label was set:

```
update mdsys.rdfi_contracts_inf
  set ctxt1 = char_to_label('defense', 'SECRET:HLS:US')
  where ctxt1 = -1;
```

Inferred triples accessed through generated labels might not be same as conceptual triples inferred directly from the user accessible triples and rules. The labels generated using system-defined or custom implementations cannot be guaranteed to be precise. See the information about [Fine-Grained Access Control \(VPD and OLS\) Considerations](#) in the Usage Notes for the `SEM_APIS.CREATE_ENTAILMENT` procedure in [Chapter 9](#) for details.

5.2.2.5 Using Labels Based on Application Logic

The `MDSYS.RDFSA_LABELGEN` type is used to apply appropriate label generator logic at the time of index creation; however, you can also extend this type to implement a custom label generator and generate labels based on application logic. The label generator is specified using the `label_gen` parameter with the `SEM_APIS.CREATE_ENTAILMENT` procedure. To use a system-defined label generator, specify a `SEM_RDFSA` package constant, as explained in [Section 5.2.2.4](#); to use a custom label generator, you must implement a custom label generator type and specify an instance of that type instead of a `SEM_RDFSA` package constant.

To create a custom label generator type, you must have the UNDER privilege on the `RDFSA_LABELGEN` type. In addition, to create an index for RDF data, you must should have the EXECUTE privilege on this type. The following example grants these privileges to a user named `RDF_ADMIN`:

```
GRANT under, execute ON mdsys.rdfsa_labelgen TO rdf_admin;
```

The custom label generator type must implement a constructor, which should set the dependent resources and specify the `getNumericLabel` method to return the label computed from the information passed in, as shown in the following example:

```
CREATE OR REPLACE TYPE CustomSPORALabel UNDER mdsys.rdfsa_labelgen (
  constructor function CustomSPORALabel return self as result,
  overriding member function getNumericLabel (
    subject  rdfsa_resource,
    predicate rdfsa_resource,
    object   rdfsa_resource,
    rule     rdfsa_resource,
    anteced  rdfsa_resource)
    return number);
```

The label generator constructor uses a set of constants defined in the `SEM_RDFSA` package to indicate the list of resources on which the label generator relies. The dependent resources are identified as an inferred triple's subject, its predicate, its object, the rule that produced the triple, and its antecedents. A custom label generator can rely on any subset of these resources for generating the labels, and you can specify this in its constructor by using the constants defined in `SEM_RDFSA` package: `USE_SUBJECT_LABEL`, `USE_PREDICATE_LABEL`, `USE_OBJECT_LABEL`, `USE_RULE_LABEL`, `USE_ANTCED_LABEL`. The following example creates the type body and specifies the constructor:

[Example 5-1](#) creates the type body, specifying the constructor function and the `getNumericLabel` member function. (Application-specific logic is not included in this example.)

Example 5-1 Creating a Custom Label Generator Type

```
CREATE OR REPLACE TYPE BODY CustomSPORALabel AS

  constructor function CustomSPORALabel return self as result as
  begin
    self.setDepResources(sem_rdfsa.USE_SUBJECT_LABEL+
      sem_rdfsa.USE_PREDICATE_LABEL+
      sem_rdfsa.USE_OBJECT_LABEL+
      sem_rdfsa.USE_RULE_LABEL+
      sem_rdfsa.USE_ANTECED_LABELS);

    return;
  end CustomSPORALabel;

  overriding member function getNumericLabel (
    subject  rdfsa_resource,
    predicate rdfsa_resource,
    object   rdfsa_resource,
    rule     rdfsa_resource,
    anteced  rdfsa_resource)
    return number as
    labellst mdsys.int_array := mdsys.int_array();
  begin
    -- Find dominating label of S P O R A -
    -- Application specific logic for computing the triple label -
    -- Copy over all labels to labellst --
    for li in 1 .. subject.getLabelCount() loop
      labellst.extend;
      labellst(labellst.COUNT) = subject.getLabel(li);
    end loop;
    --- Copy over other labels as well ---
    --- Find a dominating of all the labels. Generates -1 if no
```

```

    --- dominating label within the set
    return self.findDominatingOf(labelList);
end getNumericLabel;
end CustomSPORALabel;
/

```

In [Example 5-1](#), the sample label generator implementation uses all the resources contributing to the inferred triple for generating a sensitivity label for the triple. Thus, the constructor uses the `setDepResources` method defined in the superclass to set all its dependent components. The list of dependent resources set with this step determines the exact list of values passed to the label generating routine.

The `getNumericLabel` method is the label generation routine that has one argument for each resource that an inferred triple may depend on. Some arguments may be null values if the corresponding dependent resource is not set in the constructor implementation.

The label generator implementation can make use of a general-purpose static routine defined in the `RDFSA_LABELGEN` type to find a domination label for a given set of labels. A set of labels is passed in an instance of `MDSYS.INT_ARRAY` type, and the method finds a dominating label among them. If no such label exists, an exception label `-1` is returned.

After you have implemented the custom label generator type, you can use the custom label generator for inferred data by assigning an instance of this type to the `label_gen` parameter in the [SEM_APIS.CREATE_ENTAILMENT](#) procedure, as shown in the following example:

```

begin
  sem_apis.create_entailment(
    index_name_in => 'contracts_rdfsinf',
    models_in     => SDO_RDF_Models('contracts'),
    rulebases_in  => SDO_RDF_Rulebases('RDFS'),
    options       => '',
    label_gen     => CustomSPORALabel();
end;
/

```

5.2.2.6 RDFOLS_SECURE_RESOURCE View

The `MDSYS.RDFOLS_SECURE_RESOURCE` view contains information about resources secured with Oracle Label Security (OLS) policies and the sensitivity labels associated with these resources.

Select privileges on this view can be granted to appropriate users. To view the resources associated with a specific model, you must also have select privileges on the model (or the corresponding `RDFM_model-name` view).

The `MDSYS.RDFOLS_SECURE_RESOURCE` view contains the columns shown in [Table 5-6](#).

Table 5-6 *MDSYS.RDFOLS_SECURE_RESOURCE View Columns*

Column Name	Data Type	Description
MODEL_NAME	VARCHAR2(25)	Name of the model.
MODEL_ID	NUMBER	Internal identifier for the model.
RESOURCE_ID	NUMBER	Internal identifier for the resource; to be joined with <code>MDSYS.RDF_VALUE\$.VALUE_ID</code> column for information about the resource.

Table 5–6 (Cont.) MDSYS.RDFOLS_SECURE_RESOURCE View Columns

Column Name	Data Type	Description
RESOURCE_ TYPE	VARCHAR2(16)	One of the following string values to indicate the resource type for which the label is assigned: SUBJECT, PREDICATE, OBJECT, GLOBAL.
CTXT1	NUMBER	Sensitivity label assigned to the resource.

Workspace Manager Support for RDF Data

RDF data stored in the Oracle Database semantic data store can be version-enabled using Oracle Database 11g Workspace Manager. Using Workspace Manager, you can create new versions of RDF data through data modification operations while maintaining a copy of the old data. For detailed usage and reference information about Workspace Manager, see *Oracle Database Workspace Manager Developer's Guide*.

The unit of versioning for the semantic data store is a model, which is in turn associated with an application table that resides in a user schema. Traditional Workspace Manager interfaces are used to manage a version-enabled RDF model. (However, you cannot use version-enabling on a model that participates in a virtual model. Virtual models are described in [Section 1.3.8](#))

Creating the first version-enabled RDF model in a database re-creates an index on the underlying triple store that holds data for all RDF models. Thus, the time needed to create the first version-enabled RDF model depends on the amount of existing data in these models.

This chapter discusses the key characteristics of a version-enabled RDF model and provides some examples. It contains the following major sections:

- [Section 6.1, "Enabling Workspace Manager Support for RDF Data"](#)
- [Section 6.2, "Version-Enabling an RDF Model"](#)
- [Section 6.3, "Inferring from Version-Enabled RDF Models"](#)
- [Section 6.4, "Merging and Refreshing Workspaces in Version-Enabled RDF Models"](#)

6.1 Enabling Workspace Manager Support for RDF Data

Workspace Manager support for RDF data is not installed in the database by default. Instead, you must run a script named `sdordfwm.sql` after you enable semantic technologies support in the database (explained in [Section A.1, "Enabling Semantic Technologies Support"](#)). You only need to run `sdordfwm.sql` once for the database. To run this script, connect to the database as SYSDBA and enter the following statement as appropriate for your operating system:

- Linux: SQL> @\$ORACLE_HOME/md/admin/sdordfwm.sql
- Windows: SQL> @%ORACLE_HOME%\md\admin\sdordfwm.sql

If you want to check whether Workspace Manager support is enabled for RDF data, enter the following query and see if the value returned is `INSTALLED`:

```
SELECT value FROM mdsys.rdf_parameter
WHERE namespace = 'COMPONENT' and attribute = 'RDFOWM';
```

6.1.1 Removing Workspace Manager Support for RDF Data

After you have enabled Workspace Manager support for RDF data, you might need to remove that support in certain circumstances. For example, before you downgrade or remove semantic technologies support in the database, you must remove the Workspace Manager support for RDF data. (For information about downgrading and removing semantic technologies support, see [Appendix A, "Enabling, Downgrading, or Removing Semantic Technologies Support"](#).)

To remove Workspace Manager support for RDF data, perform the following steps:

1. Connect to the database as the SYS user with SYSDBA privileges (SYS AS SYSDBA, and enter the SYS account password when prompted).
2. Start SQL*Plus, and enter the following statement:
 - Linux: @\$ORACLE_HOME/md/admin/sdordfwm_rm.sql
 - Windows: @%ORACLE_HOME%\md\admin\sdordfwm_rm.sql

After the `sdordfwm_rm.sql` script completes successfully, you can downgrade or remove semantic technologies support in the database.

6.2 Version-Enabling an RDF Model

To version-enable an RDF model, you version-enable its associated application table. For example, if an RDF model named `contracts` is associated with an application table named `CONTRACTS_RDF_DATA`, you can perform the version enabling as shown in the following example:

```
begin
  dbms_wm.enableVersioning (table_name => 'contracts_rdf_data');
end;
/
```

The application table must have a primary key, and you cannot specify the `HISTORY` or `VALID TIME` options.

The data stored in the application table and the corresponding RDF data in the semantic data store are versioned logically. The standard data manipulation operations (insert, update, delete) on a version-enabled application table maintain the version information for both the affected application table rows and the corresponding RDF triples in the semantic data store. Queries accessing the RDF data using the `SEM_MATCH` operator take the state of the active workspace and the relevant versions of data into account when constructing the result set.

You cannot use continually refreshed workspaces and multiparent workspaces when working with RDF data. However, other workspace operations (such as creating new workspaces, creating savepoints, setting access modes, and refreshing and merging workspaces) proceed as you would expect.


You can use Workspace Manager locks on the application table rows to avoid conflicting data manipulation operations in concurrent workspaces. The conflicts in such cases are detected based on the primary keys for the locked rows, and they may not directly translate to any meaningful locks on the RDF data, such as a lock on a sub-graph or a node. (See [Section 6.4](#) for best practices involving version-enabled RDF data.)

6.3 Inferring from Version-Enabled RDF Models

You can use an RDF model to create one or more entailments through inference using system-defined and user-defined rulebases. When such a model is version-enabled, the associated entailments that store the inferred data are also version-enabled.

However, unlike the RDF models, which are versioned logically, the entailments are versioned physically. Thus, a workspace with some unmerged changes to an RDF model may maintain a private version of the entailment, which duplicates all the inferred triples that may already exist in the entailment corresponding to the parent workspace. [Figure 6-1](#) shows a physically versioned entailment where private copies of the index are maintained for workspaces W1 and W2, which are child workspaces of the LIVE workspace.

Figure 6-1 Physical Versioning of Entailment (Rules Index)



A workspace created from a parent workspace with a valid entailment will share the entailment with its parent until some workspace-specific data manipulation operations occur on the corresponding models. The first data manipulation operation within a workspace creates a private copy of the entailment and marks it INVALID.

Workspace-private versions of inference data can be rebuilt using the [SEM_APIS.CREATE_ENTAILMENT](#) procedure, as shown in the following example:

```
begin
  sem_apis.create_entailment(
    index_name_in   => 'contracts_rdfs',
    models_in       => SDO_RDF_Models('contracts'),
    rulebases_in    => SDO_RDF_Rulebases('RDFS'));
end;
/
```

Any subsequent additions to the RDF model within the workspace will mark the entailment as INCOMPLETE, although you can return it to a VALID status using the [SEM_APIS.CREATE_ENTAILMENT](#) procedure. When a workspace is merged, the workspace-private entailment is dropped, and the corresponding index in the parent workspace is marked INVALID.

6.4 Merging and Refreshing Workspaces in Version-Enabled RDF Models

A workspace modifying data stored in a version-enabled RDF model may contain additional changes to other RDF models or relational tables. The semantics for the merging or refreshing relational data modified in a workspace remain unchanged. Similarly, the merging or refreshing of the application table is subject to conflict

analysis based on the primary key defined in the application table. Triples added and deleted in concurrent workspaces are not flagged as conflicts unless they are associated with the same primary key in the application table. For example, a parent and a child workspace may assert the same triple with different primary keys, and during a workspace merge both the triples are accepted. You can avoid such conflicts by generating the application table primary keys from the triple components.

When you work with RDF data, the types of conflicts that must be flagged vary depending on the application requirements. The conflicts include physical conflicts that exist between two triples, and logical conflicts that exist in a graph to which the triples belong. For example, two concurrent workspaces asserting a triple that captures the value of a specific contract physically conflict with each other. Similarly, a workspace that assigned a new project to a department (with an appropriate triple) may logically conflict with other workspace that reduced the budget for the department.

You can avoid these conflicts by acquiring appropriate Workspace Manager locks on the application table rows using the DBMS_WM.lockRows subprogram. For example, while adding a new triple that describes a specific resource, the application logic may acquire row locks for all application table rows that describe the same resource; in this case, failure to acquire the lock indicates a conflict.

If business conflicts between concurrent workspaces can be manually detected and reconciled, you can use the `<application table name>_DIFF` Workspace Manager view to obtain a summary of all the changes in two workspaces. For a version-enabled application table named `contracts_rdf_data`, the query in following example fetches the triples for all the rows that are modified either in `W2` workspace or the `LIVE` workspace:

```
begin
  dbms_wm.SetDiffVersions(workspace1 => 'W2',
                          workspace2 => 'LIVE');
end;
/

SELECT appt.apptable_pkey, appt.triple.get_triple() triple,
       wm_diffver, wm_code FROM contracts_rdf_data_diff appt;
```

For an explanation of the possible values for the `WM_DIFFVER` and `WM_CODE` columns, see the section about `xxx_DIFF` views in *Oracle Database Workspace Manager Developer's Guide*.

For any conflicts detected using this technique, you can resolve them by executing compensating data manipulation operations for the conflicting data modifications.

Jena Adapter for Oracle Database

The Jena Adapter for Oracle Database (referred to here as the Jena Adapter) provides a Java-based interface to Oracle Database Semantic Technologies by implementing the well-known Jena Graph and Model APIs. (Jena is an open source framework developed by Hewlett-Packard and is available under a BSD-style license.)

This chapter assumes that you are familiar with major concepts explained in [Chapter 1, "Oracle Database Semantic Technologies Overview"](#) and [Chapter 2, "OWL Concepts"](#). It also assumes that you are familiar with the overall capabilities and use of the Jena Java framework. For information about the Jena framework, see <http://jena.sourceforge.net/>, especially the Jena Documentation page.

The Jena Adapter extends the semantic data management capabilities of Oracle Database Release 11.2 RDF/OWL.

This chapter includes the following major topics:

- [Section 7.1, "Setting Up the Software Environment"](#)
- [Section 7.2, "Setting Up the SPARQL Service"](#)
- [Section 7.3, "Setting Up the Semantic Technologies Environment"](#)
- [Section 7.4, "SEM_MATCH and Jena Adapter Queries Compared"](#)
- [Section 7.5, "Optimized Handling of SPARQL Queries"](#)
- [Section 7.6, "Additions to the SPARQL Syntax to Support Other Features"](#)
- [Section 7.7, "Functions Supported in SPARQL Queries through the Jena Adapter"](#)
- [Section 7.8, "Support for Server-Side APIs"](#)
- [Section 7.9, "Bulk Loading Using the Jena Adapter"](#)
- [Section 7.10, "Example Queries Using the Jena Adapter"](#)

Disclaimer: The current Jena Adapter release has been tested against Jena 2.6.3, ARQ 2.8.5, and Joseki 3.4.2. Because of the nature of open source projects, you should not use this Jena Adapter with later versions of Jena, ARQ, or Joseki.

7.1 Setting Up the Software Environment

To use the Jena Adapter, you must first ensure that the system environment has the necessary software, including Oracle Database 11g Release 2 with the Spatial and Partitioning options and with Semantic Technologies support enabled, Jena version

2.6.3, the Jena Adapter, and JDK 1.6. You can set up the software environment by performing these actions:

1. Install Oracle Database Release 11.2 Enterprise Edition with the Oracle Spatial and Partitioning Options.
2. Install the 11.2.0.2 Patch Set for Oracle Database Server (https://updates.oracle.com/ARULink/PatchDetails/process_form?patch_num=10098816).
3. Enable the support for Semantic Technologies, as explained in [Section A.1](#).
4. Install Jena (version 2.6.3): download the .zip file from <http://sourceforge.net/projects/jena/files/Jena/Jena-2.6.3/jena-2.6.3.zip/download> and unzip it. (The directory or folder into which you unzip it will be referred to as *<Jena_DIR>*.)

The Java package will be unpacked into *<Jena_DIR>*.

Note that Jena 2.6.3 comes with ARQ version 2.8.4 (*arq-2.8.4.jar*); however, this version of the Jena Adapter actually requires a newer ARQ version (*arq-2.8.5.jar*). You can download *arq-2.8.5.jar* from <http://sourceforge.net/projects/jena/files/ARQ/ARQ-2.8.5/arq-2.8.5.zip/download> and unzip it to a temporary directory. Remove the *arq-2.8.4.jar* file from *<Jena_DIR>/Jena-2.6.3/lib/*, and copy *arq-2.8.5.jar* from the temporary directory into *<Jena_DIR>/Jena-2.6.3/lib/*.

5. Download the Jena Adapter (*jena_adaptor_for_release11.2.0.2.zip*) from the Oracle Database Semantic Technologies page (http://www.oracle.com/technology/tech/semantic_technologies/), and unzip it into a temporary directory, such as (on a Linux system) */tmp/jena_adapter*. (If this temporary directory does not already exist, create it before the unzip operation.)

The Jena Adapter directories and files have the following structure:

```
examples/
  examples/Test10.java
  examples/Test11.java
  examples/Test12.java
  examples/Test13.java
  examples/Test14.java
  examples/Test15.java
  examples/Test16.java
  examples/Test17.java
  examples/Test18.java
  examples/Test19.java
  examples/Test20.java
  examples/Test6.java
  examples/Test7.java
  examples/Test8.java
  examples/Test9.java
  examples/Test.java
jar/
  jar/sdordfclient.jar
javadoc/
  javadoc/javadoc.zip
joseki/
  joseki/index.html
  joseki/application.xml
  joseki/update.html
```

```

joseki/xml-to-html.xsl
joseki/joseki-config.ttl
web/
web/web.xml

```

6. Copy `ojdbc5.jar` into `<Jena_DIR>/lib` (Linux) or `<Jena_DIR>\lib` (Windows). (`ojdbc5.jar` is in `$ORACLE_HOME/jdbc/lib` or `%ORACLE_HOME%\jdbc\lib`.)
7. Copy `sdordf.jar` into `<Jena_DIR>/lib` (Linux) or `<Jena_DIR>\lib` (Windows). (`sdordf.jar` is in `$ORACLE_HOME/md/jlib` or `%ORACLE_HOME%\md\jlib`.)
8. If JDK 1.6 is not already installed, install it.
9. If the `JAVA_HOME` environment variable does not already refer to the JDK 1.6 installation, define it accordingly. For example:

```
setenv JAVA_HOME /usr/local/packages/jdk16/
```
10. If the SPARQL service to support the SPARQL protocol is not set up, set it up as explained in [Section 7.2](#).

After setting up the software environment, ensure that your Semantic Technologies environment can enable you to use the Jena Adapter to perform queries, as explained in [Section 7.3](#).

7.2 Setting Up the SPARQL Service

Setting up a SPARQL endpoint using the Jena Adapter involves downloading Joseki, an open source HTTP engine that supports the SPARQL protocol and SPARQL queries. This section explains how to set up a SPARQL service using a servlet deployed in WebLogic Server. The number and complexity of the steps reflect the fact that Oracle is not permitted to bundle all the dependent third-party libraries in a `.war` or `.ear` file.

1. Download and Install Oracle WebLogic Server 11g Release 1 (10.3.1). For details, see <http://www.oracle.com/technology/products/weblogic/> and <http://www.oracle.com/technetwork/middleware/ias/downloads/wls-main-097127.html>.
2. Ensure that you have Java 6 installed, because it is required by Joseki 3.4.2.
3. Download Joseki 3.4.2 (`joseki-3.4.2.zip`) from <http://sourceforge.net/projects/joseki/files/Joseki-SPARQL/>.
4. Unpack `joseki-3.4.2.zip` into a temporary directory. For example:

```
mkdir /tmp/joseki
cp joseki-3.4.2.zip /tmp/joseki
cd /tmp/joseki
unzip joseki-3.4.2.zip
```
5. Ensure that you have downloaded and unzipped the Jena Adapter for Oracle Database, as explained in [Section 7.1](#).
6. Create a directory named `joseki.war` at the same level as the `jena_adapter` directory, and go to it. For example:

```
mkdir /tmp/joseki.war
cd /tmp/joseki.war
```
7. Copy necessary files into the directory created in the preceding step:

```
cp /tmp/jena_adapter/joseki/* /tmp/joseki.war
```

```
cp -rf /tmp/joseki/Joseki-3.4.2/webapps/joseki/StyleSheets /tmp/joseki.war
```

8. Create directories and copy necessary files into them, as follows:

```
mkdir /tmp/joseki.war/WEB-INF
cp /tmp/jena_adapter/web/* /tmp/joseki.war/WEB-INF

mkdir /tmp/joseki.war/WEB-INF/lib
cp /tmp/joseki/Joseki-3.4.2/lib/*.jar /tmp/joseki.war/WEB-INF/lib
cp /tmp/jena_adapter/jar/*.jar /tmp/joseki.war/WEB-INF/lib
##
## Assume ORACLE_HOME points to the home directory of a Release 11.2 Oracle
Database.
##
cp $ORACLE_HOME/md/jlib/sdordf.jar /tmp/joseki.war/WEB-INF/lib
cp $ORACLE_HOME/jdbc/lib/ojdbc5.jar /tmp/joseki.war/WEB-INF/lib
```

Note that in the last command, you can specify `ojdbc6.jar` instead of `ojdbc5.jar`.

9. Using the WebLogic Server Administration console, create a J2EE data source named *OracleSemDS*. During the data source creation, you can specify a user and password for the database schema that contains the relevant semantic data against which SPARQL queries are to be executed.

If you need help in creating this data source, see [Section 7.2.1, "Creating the Required Data Source Using WebLogic Server"](#).

10. Go to the `autodeploy` directory of WebLogic Server and copy files, as follows. (For information about auto-deploying applications in development domains, see: http://download.oracle.com/docs/cd/E11035_01/wls100/deployment/autodeploy.html)

```
cd <domain_name>/autodeploy
cp -rf /tmp/joseki.war <domain_name>/autodeploy
```

In the preceding example, `<domain_name>` is the name of a WebLogic Server domain.

Note that while you can run a WebLogic Server domain in two different modes, development and production, only development mode allows you use the auto-deployment feature.

11. Check the files and the directory structure, as in the following example:

```
autodeploy/% ls -lR ./joseki.war/

./joseki.war:
application.xml
index.html
joseki-config.ttl
StyleSheets/
update.html
WEB-INF/
xml-to-html.xsl

./joseki.war/StyleSheets:
joseki.css

./joseki.war/WEB-INF:
lib/
web.xml
```

```

./joseki.war/WEB-INF/lib:
ojdbc5.jar
sdordfclient.jar
sdordf.jar
arg-2.8.5.jar
arg-2.8.5-sources.jar
arg-2.8.5-tests.jar
arg-2.8.5-test-sources.jar
icu4j-3.4.4.jar
iri-0.8.jar
iri-0.8-sources.jar
jena-2.6.3.jar
jena-2.6.3-sources.jar
jena-2.6.3-tests.jar
jena-2.6.3-test-sources.jar
jetty-6.1.10.jar
jetty-util-6.1.10.jar
joseki-3.4.2.jar
junit-4.5.jar
log4j-1.2.14.jar
lucene-core-2.3.1.jar
sdb-1.3.2.jar
servlet-api-2.5-6.1.10.jar
servlet-api-2.5.jar
slf4j-api-1.5.8.jar
slf4j-log4j12-1.5.8.jar
stax-api-1.0.1.jar
tdb-0.8.7.jar
wstx-asl-3.2.9.jar
xercesImpl-2.7.1.jar

```

- 12.** If you want to build a .war file from the /tmp/joseki.war directory (note that a .war file is required if you want to deploy Joseki to an OC4J container), enter the following commands:

```

cd /tmp/joseki.war
jar cvf /tmp/joseki_app.war *

```

- 13.** Start or restart WebLogic Server.

- 14.** Verify your deployment by using your Web browser to connect to a URL in the following format (assume that the Web application is deployed at port 7001):
<http://<hostname>:7001/joseki>

You should see a page titled *Oracle SPARQL Service Endpoint using Joseki*, and the first text box should contain an example SPARQL query.

- 15.** Click **Submit Query**.

You should see a page titled *Oracle SPARQL Endpoint Query Results*. There may or may not be any results, depending on the underlying semantic model against which the query is executed.

7.2.1 Creating the Required Data Source Using WebLogic Server

If you need help creating the required J2EE data source using the WebLogic Server admin console, you can follow these steps:

1. Login to: <http://<hostname>:7001/console>
2. In the Domain Structure panel, click **Services**.

3. Click **JDBC**
4. Click **Data Services**.
5. In the Summary of JDBC Data Sources panel, click **New** under the Data Sources table.
6. In the Create a New JDBC Data Source panel, enter or select the following values.
Name: OracleSemDS
JNDI Name: OracleSemDS
Database Type: Oracle
Database Driver: Oracle's Driver (Thin) Versions:
9.0.1, 9.2.0, 10, 11
7. Click **Next** twice.
8. In the Connection Properties panel, enter the appropriate values for the **Database Name**, **Host Name**, **Port**, **Database User Name** (schema that contains semantic data), **Password** fields.
9. Click **Next**.
10. Select (check) the target server or servers to which you want to deploy this OracleSemDS data source.
11. Click **Finish**.
You should see a message that all changes have been activated and no restart is necessary.

7.2.2 Configuring the SPARQL Service

By default, the SPARQL Service endpoint assumes that the queries are to be executed against a semantic model with a pre-set name. This semantic model is owned by the schema specified in the J2EE data source with JNDI name *OracleSemDS*. Note that you do not need to create this model explicitly using PL/SQL or Java; if the model does not exist in the network, it will be automatically created, along with the necessary application table and index.

Note: Effective with the Jena Adapter release in November 2010, the default name of the application table index is changed from *<model_name>_triple_idx* to *<model_name>_idx*, and a compressed index is created on the leading model ID column in the application table to save storage.

For existing models created by an older version of the Jena Adapter, you can migrate the application table index name and definition by using the `OracleUtils.migrateApplicationTableIndex(oracle, graph, dop)` method in the `oracle.spatial.rdf.client.jena` package. (See the Javadoc for more information.)

However, you must configure the SPARQL service by editing the `joseki-config.ttl` configuration file, which is in `<domain_name>/autodeploy/joseki.war`.

The supplied `joseki-config.ttl` file includes a section similar to the following for the Oracle data set:

```
#
## Datasets
#
[] ja:loadClass "oracle.spatial.rdf.client.jena.assembler.OracleAssemblerVocab" .

oracle:Dataset rdfs:subClassOf ja:RDFDataset .

<#oracle> rdf:type oracle:Dataset;
  joseki:poolSize 1 ;          ## Number of concurrent connections allowed to
this dataset.
  oracle:connection
  [ a oracle:OracleConnection ;
  ];
  oracle:defaultModel [ oracle:firstModel "TEST_MODEL" ] .
```

In this section of the file, you can:

- Modify the `joseki:poolSize` value, which specifies the number of concurrent connections allowed to this Oracle data set (`<#oracle> rdf:type oracle:Dataset;`), which points to various RDF models in the database.
- Modify the name (or the object value of `oracle:firstModel` predicate) of the `defaultModel`, to use a different semantic model for queries. You can also specify multiple models, and one or more rulebases for this `defaultModel`.

For example, the following specifies two models (named ABOX and TBOX) and an OWLPRIME rulebase for the default model. Note that models specified using the `oracle:modelName` predicate must exist; they *will not* be created automatically.

```
<#oracle> rdf:type oracle:Dataset;
  joseki:poolSize 1 ;          ## Number of concurrent connections allowed
to this dataset.
  oracle:connection
  [ a oracle:OracleConnection ;
  ];
  oracle:defaultModel [ oracle:firstModel "ABOX";
                        oracle:modelName "TBOX";
                        oracle:rulebaseName "OWLPRIME" ] .
```

- Use a virtual model for queries by adding `oracle:useVM "TRUE"`, as shown in the following example. Note that if the specified virtual model does not exist, it *will* automatically be created on demand.

```
<#oracle> rdf:type oracle:Dataset;
  joseki:poolSize 1 ;          ## Number of concurrent connections allowed
to this dataset.
  oracle:connection
  [ a oracle:OracleConnection ;
  ];
  oracle:defaultModel [ oracle:firstModel "ABOX";
                        oracle:modelName "TBOX";
                        oracle:rulebaseName "OWLPRIME";
                        oracle:useVM "TRUE"
  ] .
```

For more information, see [Section 7.8.1, "Virtual Models Support"](#).

- Set the `queryOptions` and `inferenceMaintenance` properties to change the query behavior and inference update mode. (See the Javadoc for information about `QueryOptions` and `InferenceMaintenanceMode`.)

By default, `QueryOptions.ALLOW_QUERY_INVALID_AND_DUP` and `InferenceMaintenanceMode.NO_UPDATE` are set, for maximum query flexibility and efficiency.

7.2.2.1 Client Identifiers

For every database connection created or used by the Jena Adapter, a client identifier is associated with the connection. The client identifier can be helpful, especially in a Real Application Cluster (RAC) environment, for isolating Jena Adapter-related activities from other database activities when you are doing performance analysis and tuning.

By default, the client identifier assigned is `JenaAdapter`. However, you can specify a different value by setting the Java VM `clientIdentifier` property using the following format:

```
-Doracle.spatial.rdf.client.jena.clientIdentifier=<identificationString>
```

To start the tracing of only Jena Adapter-related activities on the database side, you can use the `DBMS_MONITOR.CLIENT_ID_TRACE_ENABLE` procedure. For example:

```
SQL> EXECUTE DBMS_MONITOR.CLIENT_ID_TRACE_ENABLE('JenaAdapter', true, true);
```

7.2.3 Terminating Long-Running SPARQL Queries

Because some applications need to be able to terminate long-running SPARQL queries, an abort framework has been introduced with the Jena Adapter and the Joseki setup. Basically, for queries that may take a long time to run, you must stamp each with a unique query ID (`qid`) value.

For example, the following SPARQL query selects out the subject of all triples. A query ID (`qid`) is set so that this query can be terminated upon request.

```
PREFIX ORACLE_SEM_FS_NS: <http://example.com/semtech#qid=8761>
SELECT ?subject WHERE {?subject ?property ?object }
```

The `qid` attribute value is of long integer type. You can choose a value for the `qid` for a particular query based on your own application needs.

To terminate a SPARQL query that has been submitted with a `qid` value, applications can send an abort request to a servlet in the following format and specify a matching QID value

```
http://<hostname>:7001/joseki/querymgt?abortqid=8761
```

7.2.4 N-Triples Encoding for Non-ASCII Characters

For any non-ASCII characters in the lexical representation of RDF resources, `\uHHHH` N-Triples encoding is used when the characters are inserted into the Oracle database. (For details about N-Triples encoding, see http://www.w3.org/TR/rdf-testcases/#ntrip_grammar.) Encoding of the constant resources in a SPARQL query is handled in a similar fashion.

Using `\uHHHH` N-Triples encoding enables support for international characters, such as a mix of Norwegian and Swedish characters, in the Oracle database even if a supported Unicode character set is not being used.

7.3 Setting Up the Semantic Technologies Environment

To use the Jena Adapter to perform queries, you can connect as any user (with suitable privileges) and use any models in the semantic network. If your Semantic Technologies environment already meets the requirements, you can go directly to compiling and running Java code that uses the Jena Adapter. If your Semantic Technologies environment is not yet set up to be able to use the Jena Adapter, you can perform actions similar to the following example steps:

1. Connect as SYS with the SYSDBA role:

```
sqlplus sys/<password-for-sys> as sysdba
```

2. Create a tablespace for the system tables. For example:

```
CREATE TABLESPACE rdf_users datafile 'rdf_users01.dbf'
  size 128M reuse autoextend on next 64M
  maxsize unlimited segment space management auto;
```

3. Create the semantic network. For example:

```
EXECUTE sem_apis.create_sem_network('RDF_USERS');
```

4. Create a database user (for connecting to the database to use the semantic network and the Jena Adapter). For example:

```
CREATE USER rdfusr IDENTIFIED BY <password-for-udfusr>
  DEFAULT TABLESPACE rdf_users;
```

5. Grant the necessary privileges to this database user. For example:

```
GRANT connect, resource TO rdfusr;
```

6. To use the Jena Adapter with your own semantic data, perform the appropriate steps to store data, create a model, and create database indexes, as explained in [Section 1.9, "Quick Start for Using Semantic Data"](#). Then perform queries by compiling and running Java code; see [Section 7.10](#) for information about example queries.

To use the Jena Adapter with supplied example data, see [Section 7.10](#).

7.4 SEM_MATCH and Jena Adapter Queries Compared

There are two ways to query semantic data stored in Oracle Database: SEM_MATCH-based SQL statements and SPARQL queries through the Jena Adapter. Queries using each approach are similar in appearance, but there are important behavioral differences. To ensure consistent application behavior, you must understand the differences and use care when dealing with query results coming from SEM_MATCH queries and SPARQL queries.

The following simple examples show the two approaches.

Query 1 (SEM_MATCH-based)

```
select s, p, o
  from table(sem_match('{s ?p ?o}', sem_models('Test_Model'), ...))
```

Query 2 (SPARQL query through the Jena Adapter)

```
select ?s ?p ?o
where {?s ?p ?o}
```

These two queries perform the same kind of functions; however, there are some important differences. Query 1 (SEM_MATCH-based):

- Reads all triples out of `Test_Model`.
- Does not differentiate among URI, bNode, plain literals, and typed literals, and it does not handle long literals.
- Does not unescape certain characters (such as `'\n'`).

Query 2 (SPARQL query executed through the Jena Adapter) also reads all triples out of `Test_Model` (assume it executed a call to `ModelOracleSem` referring to the same underlying `Test_Model`). However, Query 2:

- Reads out additional columns (as opposed to just the `s`, `p`, and `o` columns with the SEM_MATCH table function), to differentiate URI, bNodes, plain literals, typed literals, and long literals. This is to ensure proper creation of Jena Node objects.
- Unescapes those characters that are escaped when stored in Oracle Database

Blank node handling is another difference between the two approaches:

- In a SEM_MATCH-based query, blank nodes are always treated as constants.
- In a SPARQL query, a blank node that *is not* wrapped inside `<` and `>` is treated as a variable when the query is executed through the Jena Adapter. This matches the SPARQL standard semantics. However, a blank node that *is* wrapped inside `<` and `>` is treated as a constant when the query is executed, and the Jena Adapter adds a proper prefix to the blank node label as required by the underlying data modeling.

The maximum length for the name of a semantic model created using the Jena Adapter API is 22 characters.

7.5 Optimized Handling of SPARQL Queries

This section describes some performance-related features of the Jena Adapter that can enhance SPARQL query processing. These features are performed automatically by default.

This section assumes that you are familiar with SPARQL, including the CONSTRUCT feature and property paths.

7.5.1 Compilation of SPARQL queries to a single SEM_MATCH Call

SPARQL queries involving DISTINCT, OPTIONAL, FILTER, UNION, ORDER BY, and LIMIT are converted to a single Oracle SEM_MATCH table function. If a query cannot be converted directly to SEM_MATCH because it uses SPARQL features not supported by SEM_MATCH (for example, CONSTRUCT), the Jena Adapter employs a hybrid approach and tries to execute the largest portion of the query using a single SEM_MATCH function while executing the rest using the Jena ARQ query engine.

For example, the following SPARQL query is directly translated to a single SEM_MATCH table function:

```
PREFIX dc: <http://purl.org/dc/elements/1.1/>
PREFIX rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#>
PREFIX foaf: <http://xmlns.com/foaf/0.1/>
SELECT ?person ?name
  WHERE {
    {?alice foaf:knows ?person . }
    UNION {
      ?person ?p ?name. OPTIONAL { ?person ?x ?name1 }
    }
  }
```

```

    }
}

```

However, the following example query is not directly translatable to a single SEM_MATCH table function because of the CONSTRUCT keyword:

```

PREFIX vcard: <http://www.w3.org/2001/vcard-rdf/3.0#>
CONSTRUCT { <http://example.org/person#Alice> vcard:FN ?obj }
  WHERE { { ?x <http://pred/a> ?obj.}
          UNION
          { ?x <http://pred/b> ?obj.} }

```

In this case, the Jena Adapter converts the inner UNION query into a single SEM_MATCH table function, and then passes on the result set to the Jena ARQ query engine for further evaluation.

7.5.2 Optimized Handling of Property Paths

As defined in Jena, a property path is a possible route through an RDF graph between two graph nodes. Property paths are an extension of SPARQL and are more expressive than basic graph pattern queries, because regular expressions can be used over properties for pattern matching RDF graphs. For more information about property paths, see the documentation for the Jena ARQ query engine.

The Jena Adapter supports all Jena property path types through the integration with the Jena ARQ query engine, but it converts some common path types directly to native SQL hierarchical queries (not based on SEM_MATCH) to improve performance. The following types of property paths are directly converted to SQL by the Jena Adapter:

- Predicate alternatives: (p1 | p2 | ... | pn) where pi is a property URI
- Predicate sequences: (p1 / p2 / ... / pn) where pi is a property URI
- Reverse paths : (^ p) where p is a predicate URI
- Complex paths: p+, p*, p{0, n} where p could be an alternative, sequence, reverse path, or property URI

Path expressions that cannot be captured in this grammar are not translated directly to SQL by the Jena Adapter, and they are answered using the Jena query engine.

The following example contains a code snippet using a property path expression with path sequences:

```

String m = "PROP_PATH";

ModelOracleSem model = ModelOracleSem.createOracleSemModel(oracle, m);

GraphOracleSem graph = new GraphOracleSem(oracle, m);

// populate the RDF Graph
graph.add(Triple.create(Node.createURI("http://a"),
    Node.createURI("http://p1"),
    Node.createURI("http://b")));

graph.add(Triple.create(Node.createURI("http://b"),
    Node.createURI("http://p2"),
    Node.createURI("http://c")));

graph.add(Triple.create(Node.createURI("http://c"),
    Node.createURI("http://p5"),
    Node.createURI("http://d")));

```

```
String query =
" SELECT ?s " +
" WHERE {?s (<http://p1>/<http://p2>/<http://p5>)+ <http://d>}";

QueryExecution qexec =
    QueryExecutionFactory.create(QueryFactory.create(query),
    Syntax.syntaxARQ), model);

try {
    ResultSet results = qexec.execSelect();
    ResultSetFormatter.out(System.out, results);
}
finally {
    if (qexec != null)
        qexec.close();
}

OracleUtils.dropSemanticModel(oracle, m);
model.close();
```

7.5.3 Optimized Handling of Plain BGP and OPTIONAL Queries

The Jena Adapter automatically translates basic graph pattern (BGP) and parallel OPTIONAL queries directly to native SQL (not based on SEM_MATCH). The advantage of this approach is that you can specify directives such as RESULT_CACHE in the query to improve performance.

The following queries are translated directly to SQL:

- Plain BGP queries. For example:

```
SELECT ?x ?y WHERE {?x urn:a ?o. ?o ?p ?y}
```

- Queries using parallel OPTIONAL clauses. For example:

```
SELECT ?x ?y
WHERE {?x urn:a ?o.
      OPTIONAL {?x urn:b ?b}
      OPTIONAL {?x urn:c ?c} }
```

- Queries using property paths (see [Section 7.5.2, "Optimized Handling of Property Paths"](#)). For example:

```
SELECT ?x ?y
WHERE {?x urn:a ?o. OPTIONAL {?x urn:b* ?b} }
```

7.6 Additions to the SPARQL Syntax to Support Other Features

The Jena Adapter allows you to pass in hints and additional query options. It implements these capabilities by overloading the SPARQL namespace prefix syntax by using Oracle-specific namespaces that contain query options. The namespaces are in the form *PREFIX ORACLE_SEM_XX_NS*, where *xx* indicates the type of feature (such as HT for hint or AP for additional predicate)

7.6.1 SQL Hints

SQL hints can be passed to a SEM_MATCH query including a line in the following form:

```
PREFIX ORACLE_SEM_HT_NS: <http://oracle.com/semtech#hint>
```

Where *hint* can be any hint supported by SEM_MATCH. For example:

```
PREFIX ORACLE_SEM_HT_NS: <http://oracle.com/semtech#leading(t0,t1)>
SELECT ?book ?title ?isbn
WHERE { ?book <http://title> ?title. ?book <http://ISBN> ?isbn }
```

In this example, *t0*, *t1* refers to the first and second patterns in the query.

Note the slight difference in specifying hints when compared to SEM_MATCH. Due to restrictions of namespace value syntax, a comma (,) must be used to separate *t0* and *t1* (or other hint components) instead of a space.

For more information about using SQL hints, see [Section 1.6, "Using the SEM_MATCH Table Function to Query Semantic Data"](#), specifically the material about the HINT0 keyword in the options attribute.

7.6.2 Using Bind Variables in SPARQL Queries

In Oracle Database, using bind variables can reduce query parsing time and increase query efficiency and concurrency. Bind variable support in SPARQL queries is provided through namespace pragma specifications similar to ORACLE_SEM_FS_NS.

Consider a case where an application runs two SPARQL queries, where the second (Query 2) depends on the partial or complete results of the first (Query 1). Some approaches that do not involve bind variables include:

- Iterating through results of Query 1 and generating a set of queries. (However, this approach requires as many queries as the number of results of Query 1.)
- Constructing a SPARQL filter expression based on results of Query 1.
- Treating Query 1 as a subquery.

Another approach in this case is to use bind variables, as in the following sample scenario:

Query 1:

```
SELECT ?x
WHERE { ... <some complex query> ... };
```

Query 2:

```
SELECT ?subject ?x
WHERE {?subject <urn:related> ?x .};
```

The following example shows Query 2 with the syntax for using bind variables with the Jena Adapter:

```
PREFIX ORACLE_SEM_FS_NS: <http://oracle.com/semtech#no_fall_back,s2s>
PREFIX ORACLE_SEM_UEAP_NS: <http://oracle.com/semtech#x$RDFVID%20in(?,?,?)>
PREFIX ORACLE_SEM_UEPJ_NS: <http://oracle.com/semtech#x$RDFVID>
PREFIX ORACLE_SEM_UEBV_NS: <http://oracle.com/semtech#1,2,3>
SELECT ?subject ?x
WHERE {
    ?subject <urn:related> ?x
};
```

This syntax includes using the following namespaces:

- ORACLE_SEM_UEAP_NS is like ORACLE_SEM_AP_NS, but the value portion of ORACLE_SEM_UEAP_NS is URL Encoded. Before the value portion is used, it must be URL decoded, and then it will be treated as an additional predicate to the SPARQL query.

In this example, after URL decoding, the value portion (following the # character) of this ORACLE_SEM_UEAP_NS prefix becomes "x\$RDFVID in(?, ?, ?)". The three question marks imply a binding to three values coming from Query 1.

- ORACLE_SEM_UEPJ_NS specifies the additional projections involved. In this case, because ORACLE_SEM_UEAP_NS references the x\$RDFVID column, which does not appear in the SELECT clause of the query, it must be specified. Multiple projections are separated by commas.
- ORACLE_SEM_UEBV_NS specifies the list of bind values that are URL encoded first, and then concatenated and delimited by commas.

Conceptually, the preceding example query is equivalent to the following non-SPARQL syntax query, in which 1, 2, and 3 are treated as bind values:

```
SELECT ?subject ?x
  WHERE {
    ?subject <urn:related> ?x
  }
  AND ?x$RDFVID in (1,2,3);
```

In the preceding SPARQL example of Query 2, the three integers 1, 2, and 3 come from Query 1. You can use the `oext:build-uri-for-id` function to generate such internal integer IDs for RDF resources. The following example gets the internal integer IDs from Query 1:

```
PREFIX oext: <http://oracle.com/semtech/jena-adaptor/ext/function#>
SELECT ?x (oext:build-uri-for-id(?x) as ?xid)
WHERE { ... <some complex query> ... };
```

The values of `?xid` have the form of `<rdfvid:integer-value>`. The application can strip out the angle brackets and the "rdfvid:" strings to get the integer values and pass them to Query 2.

Consider another case, with a single query structure but potentially many different constants. For example, the following SPARQL query finds the hobby for each user who has a hobby and who logs in to an application. Obviously, different users will provide different `<uri>` values to this SPARQL query, because users of the application are represented using different URIs.

```
SELECT ?hobby
  WHERE { <uri> <urn:hasHobby> ?hobby };
```

One approach, which would not use bind variables, is to generate a different SPARQL query for each different `<uri>` value. For example, user Jane Doe might trigger the execution of the following SPARQL query:

```
SELECT ?hobby WHERE {
<http://www.example.com/Jane_Doe> <urn:hasHobby> ?hobby };
```

However, another approach is to use bind variables, as in the following example specifying user Jane Doe:

```
PREFIX ORACLE_SEM_FS_NS: <http://oracle.com/semtech#no_fall_back,s2s>
PREFIX ORACLE_SEM_UEAP_NS: <http://oracle.com/semtech#subject$RDFVID%20in(ORACLE_
ORARDF_RES2VID(?)>
PREFIX ORACLE_SEM_UEPJ_NS: <http://oracle.com/semtech#subject$RDFVID>
```

```

PREFIX ORACLE_SEM_UEBV_NS:
<http://oracle.com/semtech#http%3a%2f%2fwww.example.com%2fJohn_Doe>
SELECT ?subject ?hobby
  WHERE {
    ?subject <urn:hasHobby> ?hobby
  };

```

Conceptually, the preceding example query is equivalent to the following non-SPARQL syntax query, in which `http://www.example.com/Jane_Doe` is treated as a bind variable:

```

SELECT ?subject ?hobby
WHERE {
  ?subject <urn:hasHobby> ?hobby
}
AND ?subject$RDFVID in (ORACLE_ORARDF_RES2VID('http://www.example.com/Jane_Doe'));

```

In this example, `ORACLE_ORARDF_RES2VID` is a function that translates URIs and literals into their internal integer ID representation. This function is created automatically when the Jena Adapter is used to connect to an Oracle database.

7.6.3 Additional WHERE Clause Predicates

The `SEM_MATCH filter` attribute can specify additional selection criteria as a string in the form of a WHERE clause without the WHERE keyword. Additional WHERE clause predicates can be passed to a `SEM_MATCH` query including a line in the following form:

```
PREFIX ORACLE_SEM_AP_NS: <http://oracle.com/semtech#pred>
```

Where *pred* reflects the WHERE clause content to be appended to the query. For example:

```

PREFIX rdfs: <http://www.w3.org/2000/01/rdf-schema#>
PREFIX ORACLE_SEM_AP_NS:<http://www.oracle.com/semtech#label$RDFLANG='fr'>
SELECT DISTINCT ?inst ?label
  WHERE { ?inst a <http://someClass>. ?inst rdfs:label ?label . }
  ORDER BY (?label) LIMIT 20

```

In this example, a restriction is added to the query that the language type of the label variable must be 'fr'.

7.6.4 Additional Query Options

Additional query options can be passed to a `SEM_MATCH` query including a line in the following form:

```
PREFIX ORACLE_SEM_FS_NS: <http://oracle.com/semtech#option>
```

Where *option* reflects a query option (or multiple query options delimited by commas) to be appended to the query. For example:

```

PREFIX ORACLE_SEM_FS_NS:
<http://oracle.com/semtech#timeout=3,dop=4,INF_ONLY,ORDERED,ALLOW_DUP=T>
SELECT * WHERE {?subject ?property ?object }

```

The following query options are supported:

- `ALLOW_DUP=t` chooses a faster way to query multiple semantic models, although duplicate results may occur.

- `BEST_EFFORT_QUERY=t`, when used with the `TIMEOUT=n` option, returns all matches found in n seconds for the SPARQL query.
- `DEGREE=n` specifies, at the statement level, the degree of parallelism (n) for the query. With multi-core or multi-CPU processors, experimenting with different DOP values (such as 4 or 8) may improve performance.

Contrast `DEGREE` with `DOP`, which specifies parallelism at the session level. `DEGREE` is recommended over `DOP` for use with the Jena Adapter, because `DEGREE` involves less processing overhead.

- `DOP=n` specifies, at the session level, the degree of parallelism (n) for the query. With multi-core or multi-CPU processors, experimenting with different DOP values (such as 4 or 8) may improve performance.
- `INF_ONLY` causes only the inferred model to be queried.
- `JENA_EXECUTOR` disables the compilation of SPARQL queries to `SEM_MATCH` (or native SQL); instead, the Jena native query executor will be used.
- `JOIN=n` specifies how results from a SPARQL SERVICE call to a federated query can be joined with other parts of the query. For information about federated queries and the `JOIN` option, see [Section 7.6.4.1](#).
- `NO_FALL_BACK` causes the underlying query execution engine not to fall back on the Jena execution mechanism if a SQL exception occurs.
- `ODS=n` specifies, at the statement level, the level of dynamic sampling. (For an explanation of dynamic sampling, see the section about estimating statistics with dynamic sampling in *Oracle Database Performance Tuning Guide*.) Valid values for n are 1 through 10. For example, you could try `ODS=3` for complex queries.
- `ORDERED` is translated to a `LEADING SQL` hint for the query triple pattern joins, while performing the necessary `RDF_VALUE$` joins last.
- `PLAIN_SQL_OPT=F` disables the native compilation of queries directly to SQL.
- `QID=n` specifies a query ID number; this feature can be used to cancel the query if it is not responding.
- `RESULT_CACHE` uses the Oracle `RESULT_CACHE` directive for the query.
- `REWRITE=F` disables `ODCI_Table_Rewrite` for the `SEM_MATCH` table function.
- `SKIP_CLOB=T` causes CLOB values not to be returned for the query.
- `S2S` (SPARQL to pure SQL) causes the underlying `SEM_MATCH`-based query or queries generated based on the SPARQL query to be further converted into SQL queries *without* using the `SEM_MATCH` table function. The resulting SQL queries are executed by the Oracle cost-based optimizer, and the results are processed by the Jena Adapter before being passed on to the client. For more information about the `S2S` option, including benefits and usage information, see [Section 7.6.4.2](#).
- `TIMEOUT=n` (query timeout) specifies the number of seconds (n) that the query will run until it is terminated. The underlying SQL generated from a SPARQL query can return many matches and can use features like subqueries and assignments, all of which can take considerable time. The `TIMEOUT` and `BEST_EFFORT_QUERY=t` options can be used to prevent what you consider excessive processing time for the query.

7.6.4.1 JOIN Option and Federated Queries

A SPARQL federated query, as described in W3C documents, is a query "over distributed data" that entails "querying one source and using the acquired information

to constrain queries of the next source." For more information, see *SPARQL 1.1 Federation Extensions* (<http://www.w3.org/2009/sparql/docs/fed/service>).

You can use the JOIN option (described in [Section 7.6.4](#)) and the SERVICE keyword in a federated query that uses the Jena Adapter. For example, assume the following query:

```
SELECT ?s ?s1 ?o
WHERE { ?s1 ?p1 ?s .
      {
        SERVICE <http://sparql.org/books> { ?s ?p ?o }
      }
}
```

If the *local* query portion (`?s1 ?p1 ?s`;) is very selective, you can specify `join=2`, as shown in the following query:

```
PREFIX ORACLE_SEM_FS_NS: <http://oracle.com/semtech#join=2>
SELECT ?s ?s1 ?o
WHERE { ?s1 ?p1 ?s .
      {
        SERVICE <http://sparql.org/books> { ?s ?p ?o }
      }
}
```

In this case, the local query portion (`?s1 ?p1 ?s`;) is executed locally against the Oracle database. Each binding of `?s` from the results is then pushed into the SERVICE part (remote query portion), and a call is made to the service endpoint specified. Conceptually, this approach is somewhat like nested loop join.

If the *remote* query portion (`?s ?s1 ?o`) is very selective, you can specify `join=3`, as shown in the following query, so that the remote portion is executed first and results are used to drive the execution of local portion:

```
PREFIX ORACLE_SEM_FS_NS: <http://oracle.com/semtech#join=3>
SELECT ?s ?s1 ?o
WHERE { ?s1 ?p1 ?s .
      {
        SERVICE <http://sparql.org/books> { ?s ?p ?o }
      }
}
```

In this case, a single call is made to the remote service endpoint and each binding of `?s` triggers a local query. As with `join=2`, this approach is conceptually a nested loop based join, but the difference is that the order is switched.

If neither the local query portion nor the remote query portion is very selective, then we can choose `join=1`, as shown in the following query:

```
PREFIX ORACLE_SEM_FS_NS: <http://oracle.com/semtech#join=1>
SELECT ?s ?s1 ?o
WHERE { ?s1 ?p1 ?s .
      {
        SERVICE <http://sparql.org/books> { ?s ?p ?o }
      }
}
```

In this case, the remote query portion and the local portion are executed independently, and the results are joined together by Jena. Conceptually, this approach is somewhat like a hash join.

For debugging or tracing federated queries, you can use the HTTP Analyzer in Oracle JDeveloper to see the underlying SERVICE calls.

7.6.4.2 S2S Option Benefits and Usage Information

The S2S option, described in [Section 7.6.4](#), provides the following potential benefits:

- It works well with the RESULT_CACHE option to improve query performance. Using the S2S and RESULT_CACHE options is especially helpful for queries that are executed frequently.
- It reduces the parsing time of the SEM_MATCH table function, which can be helpful for applications that involve many dynamically generated SPARQL queries.
- It eliminates the limit of 4000 bytes for the query body (the first parameter of the SEM_MATCH table function), which means that longer, more complex queries are supported.

The S2S option causes an internal in-memory cache to be used for translated SQL query statements. The default size of this internal cache is 1024 (that is, 1024 SQL queries); however, you can adjust the size by using the following Java VM property:

```
-Doracle.spatial.rdf.client.jena.queryCacheSize=<size>
```

7.6.5 Midtier Resource Caching

When semantic data is stored, all of the resource values are hashed into IDs, which are stored in the triples table. The mappings from value IDs to full resource values are stored in the MDSYS.RDF_VALUE\$ table. At query time, for each selected variable, Oracle Database must perform a join with the RDF_VALUE\$ table to retrieve the resource.

However, to reduce the number of joins, you can use the midtier cache option, which causes an in-memory cache on the middle tier to be used for storing mappings between value IDs and resource values. To use this feature, include the following PREFIX pragma in the SPARQL query:

```
PREFIX ORACLE_SEM_FS_NS: <http://oracle.com/semtech#midtier_cache>
```

To control the maximum size (in bytes) of the in-memory cache, use the `oracle.spatial.rdf.client.jena.cacheMaxSize` system property. The default cache maximum size is 1GB.

Note that midtier resource caching is most effective for queries using ORDER BY or DISTINCT (or both) constructs. Midtier cache can be combined with the other options specified in [Section 7.6.4](#).

If you want to pre-populate the cache with all of the resources in a model, use the `GraphOracleSem.populateCache` method.

7.7 Functions Supported in SPARQL Queries through the Jena Adapter

SPARQL queries through the Jena Adapter can use the following kinds of functions:

- Functions in the function library of the Jena ARQ query engine
- Native Oracle Database functions for projected variables
- User-defined functions

7.7.1 Functions in the ARQ Function Library

SPARQL queries through the Jena Adapter can use functions in the function library of the Jena ARQ query engine. These queries are executed in the middle tier.

The following examples use the upper-case and namespace functions. In these examples, the prefix `fn` is `<http://www.w3.org/2005/xpath-functions#>` and the prefix `afn` is `<http://jena.hpl.hp.com/ARQ/function#>`.

```
PREFIX fn: <http://www.w3.org/2005/xpath-functions#>
PREFIX afn: <http://jena.hpl.hp.com/ARQ/function#>
SELECT (fn:upper-case(?object) as ?object1)
WHERE { ?subject dc:title ?object }
```

```
PREFIX fn: <http://www.w3.org/2005/xpath-functions#>
PREFIX afn: <http://jena.hpl.hp.com/ARQ/function#>
SELECT ?subject (afn:namespace(?object) as ?object1)
WHERE { ?subject <http://www.w3.org/1999/02/22-rdf-syntax-ns#type> ?object }
```

7.7.2 Native Oracle Database Functions for Projected Variables

SPARQL queries through the Jena Adapter can use native Oracle Database functions for projected variables. These queries and the functions are executed inside the database. Note that the functions described in this section should not be used together with ARQ functions (described in [Section 7.7.1](#)).

This section lists the supported native functions and provides some examples. In the examples, the prefix `oext` is

`<http://oracle.com/semtech/jena-adaptor/ext/function#>`.

Note: In the preceding URL, note the spelling `jena-adaptor`, which is retained for compatibility with existing applications and which must be used in queries. The *adapter* spelling is used in regular text, to follow Oracle documentation style guidelines.

- **`oext:upper-literal`** converts literal values (except for long literals) to uppercase. For example:

```
PREFIX oext: <http://oracle.com/semtech/jena-adaptor/ext/function#>
SELECT (oext:upper-literal(?object) as ?object1)
WHERE { ?subject dc:title ?object }
```

- **`oext:lower-literal`** converts literal values (except for long literals) to lowercase. For example:

```
PREFIX oext: <http://oracle.com/semtech/jena-adaptor/ext/function#>
SELECT (oext:lower-literal(?object) as ?object1)
WHERE { ?subject dc:title ?object }
```

- **`oext:build-uri-for-id`** converts the value ID of a URI, `bNode`, or literal into a URI form. For example:

```
PREFIX oext: <http://oracle.com/semtech/jena-adaptor/ext/function#>
SELECT (oext:build-uri-for-id(?object) as ?object1)
WHERE { ?subject dc:title ?object }
```

An example of the output might be: `<rdfvid:1716368199350136353>`

One use of this function is to allow Java applications to maintain in memory a mapping of those value IDs to the lexical form of URIs, bNodes, or literals. The MDSYS.RDF_VALUE\$ table provides such a mapping in Oracle Database.

For a given variable ?var, if only oext:build-uri-for-id(?var) is projected, the query performance is likely to be faster because fewer internal table join operations are needed to answer the query.

- **oext:literal-strlen** returns the length of literal values (except for long literals). For example:

```
PREFIX oext: <http://oracle.com/semtech/jena-adaptor/ext/function#>
SELECT (oext:literal-strlen(?object) as ?objlen)
WHERE { ?subject dc:title ?object }
```

7.7.3 User-Defined Functions

SPARQL queries through the Jena Adapter can use user-defined functions that are stored in the database.

In the following example, assume that you want to define a string length function (my_strlen) that handles long literals (CLOB) as well as short literals. On the SPARQL query side, this function can be referenced under the namespace of ouext, which is

http://oracle.com/semtech/jena-adaptor/ext/user-def-function#.

```
PREFIX ouext: <http://oracle.com/semtech/jena-adaptor/ext/user-def-function#>
SELECT ?subject ?object (ouext:my_strlen(?object) as ?obj1)
WHERE { ?subject dc:title ?object }
```

Inside the database, functions including my_strlen, my_strlen_cl, my_strlen_la, my_strlen_lt, and my_strlen_vt are defined to implement this capability. Conceptually, the return values of these functions are mapped as shown in [Table 7-1](#).

Table 7-1 Functions and Return Values for my_strlen Example

Function Name	Return Value
my_strlen	<VAR>
my_strlen_cl	<VAR>\$RDFCLOB
my_strlen_la	<VAR>\$RDFLANG
my_strlen_lt	<VAR>\$RDFLTYP
my_strlen_vt	<VAR>\$RDFVTYP

A set of functions (five in all) is used to implement a user-defined function that can be referenced from SPARQL, because this aligns with the internal representation of an RDF resource (in MDSYS.RDF_VALUE\$). There are five major columns describing an RDF resource in terms of its value, language, literal type, long value, and value type, and these five columns can be selected out using SEM_MATCH. In this context, a user-defined function simply converts one RDF resource that is represented by five columns to another RDF resource.

These functions are defined as follows:

```
create or replace function my_strlen(rdfvtyp in varchar2,
                                   rdfltyp in varchar2,
                                   rdflang in varchar2,
                                   rdfclob in clob,
                                   value in varchar2
```

```

        ) return varchar2
    as
        ret_val varchar2(4000);
    begin
        -- value
        if (rdfvtyp = 'LIT') then
            if (rdfclob is null) then
                return length(value);
            else
                return dbms_lob.getlength(rdfclob);
            end if;
        else
            -- Assign -1 for non-literal values so that application can
            -- easily differentiate
            return '-1';
        end if;
    end;
/

create or replace function my_strlen_cl(rdfvtyp in varchar2,
        rdfltyp in varchar2,
        rdflang in varchar2,
        rdfclob in clob,
        value in varchar2
    ) return clob

as
begin
    return null;
end;
/

create or replace function my_strlen_la(rdfvtyp in varchar2,
        rdfltyp in varchar2,
        rdflang in varchar2,
        rdfclob in clob,
        value in varchar2
    ) return varchar2

as
begin
    return null;
end;
/

create or replace function my_strlen_lt(rdfvtyp in varchar2,
        rdfltyp in varchar2,
        rdflang in varchar2,
        rdfclob in clob,
        value in varchar2
    ) return varchar2

as
        ret_val varchar2(4000);
    begin
        -- literal type
        return 'http://www.w3.org/2001/XMLSchema#integer';
    end;
/

create or replace function my_strlen_vt(rdfvtyp in varchar2,
        rdfltyp in varchar2,
        rdflang in varchar2,

```

```

                                rdfclob in clob,
                                value   in varchar2
                                ) return varchar2

as
  ret_val varchar2(3);
begin
  return 'LIT';
end;
/

```

User-defined functions can also accept a parameter of VARCHAR2 type. The following five functions together define a `my_shorten_str` function that accepts an integer (in VARCHAR2 form) for the substring length and returns the substring. (The substring in this example is 12 characters, and it must not be greater than 4000 bytes.)

```

-- SPARQL query that returns the first 12 characters of literal values.
--
PREFIX ouext: <http://oracle.com/semtech/jena-adaptor/ext/user-def-function#>
SELECT (ouext:my_shorten_str(?object, "12") as ?obj1) ?subject
WHERE { ?subject dc:title ?object }

```

```

create or replace function my_shorten_str(rdfvtyp in varchar2,
                                rdfltyp in varchar2,
                                rdflang in varchar2,
                                rdfclob in clob,
                                value   in varchar2,
                                arg     in varchar2
                                ) return varchar2

```

```

as
  ret_val varchar2(4000);
begin
  -- value
  if (rdfvtyp = 'LIT') then
    if (rdfclob is null) then
      return substr(value, 1, to_number(arg));
    else
      return dbms_lob.substr(rdfclob, to_number(arg), 1);
    end if;
  else
    return null;
  end if;
end;
/

```

```

create or replace function my_shorten_str_cl(rdfvtyp in varchar2,
                                rdfltyp in varchar2,
                                rdflang in varchar2,
                                rdfclob in clob,
                                value   in varchar2,
                                arg     in varchar2
                                ) return clob

```

```

as
  ret_val clob;
begin
  -- lob
  return null;
end;
/

```

```

create or replace function my_shorten_str_la(rdfvtyp in varchar2,

```

```

        rdfltyp in varchar2,
        rdflang in varchar2,
        rdfclob in clob,
        value   in varchar2,
        arg     in varchar2
    ) return varchar2

as
    ret_val varchar2(4000);
begin
    -- lang
    if (rdfvtyp = 'LIT') then
        return rdflang;
    else
        return null;
    end if;
end;
/

create or replace function my_shorten_str_lt(rdfvtyp in varchar2,
        rdfltyp in varchar2,
        rdflang in varchar2,
        rdfclob in clob,
        value   in varchar2,
        arg     in varchar2
    ) return varchar2

as
    ret_val varchar2(4000);
begin
    -- literal type
    ret_val := rdfltyp;
    return ret_val;
end;
/

create or replace function my_shorten_str_vt(rdfvtyp in varchar2,
        rdfltyp in varchar2,
        rdflang in varchar2,
        rdfclob in clob,
        value   in varchar2,
        arg     in varchar2
    ) return varchar2

as
    ret_val varchar2(3);
begin
    return 'LIT';
end;
/

```

7.8 Support for Server-Side APIs

This section describes some of the Oracle Database Semantic Technologies features that are exposed by the Jena Adapter. For comprehensive documentation of the API calls that support the available features, see the Jena Adapter reference information (Javadoc). For additional information about the server-side features exposed by the Jena Adapter, see the relevant chapters in this manual.

7.8.1 Virtual Models Support

Virtual models (explained in [Section 1.3.8](#)) are specified in the `GraphOracleSem` constructor, and they are handled transparently. If a virtual model exists for the model-rulebase combination, it is used in query answering; if such a virtual model does not exist, it is created in the database.

Note: Virtual model support through the Jena Adapter is available only with Oracle Database Release 11.2 or later.

The following example reuses an existing virtual model.

```
String modelName = "EX";
String m1 = "EX_1";

ModelOracleSem defaultModel =
    ModelOracleSem.createOracleSemModel(oracle, modelName);

// create these models in case they don't exist
ModelOracleSem model1 = ModelOracleSem.createOracleSemModel(oracle, m1);

String vmName = "VM_" + modelName;

//create a virtual model containing EX and EX_1
oracle.executeCall(
    "begin sem_apis.create_virtual_model(?,sem_models('" + m1 + "', '" +
    modelName + "'),null); end;",vmName);

String[] modelNames = {m1};
String[] rulebaseNames = {};

Attachment attachment = Attachment.createInstance(modelNames, rulebaseNames,
    InferenceMaintenanceMode.NO_UPDATE, QueryOptions.ALLOW_QUERY_VALID_AND_DUP);

// vmName is passed to the constructor, so GraphOracleSem will use the virtual
// model named vmname (if the current user has read privileges on it)
GraphOracleSem graph = new GraphOracleSem(oracle, modelName, attachment, vmName);
graph.add(Triple.create(Node.createURI("urn:alice"),
    Node.createURI("http://xmlns.com/foaf/0.1/mbox"),
    Node.createURI("mailto:alice@example")));
ModelOracleSem model = new ModelOracleSem(graph);

String queryString =

    " SELECT ?subject ?object WHERE { ?subject ?p ?object } ";

Query query = QueryFactory.create(queryString) ;
QueryExecution qexec = QueryExecutionFactory.create(query, model) ;

try {
    ResultSet results = qexec.execSelect() ;
    for ( ; results.hasNext() ; ) {
        QuerySolution soln = results.nextSolution() ;
        psOut.println("soln " + soln);
    }
}
finally {
    qexec.close() ;
}
```

```

}

OracleUtils.dropSemanticModel(oracle, modelName);
OracleUtils.dropSemanticModel(oracle, m1);

oracle.dispose();

```

You can also use the `GraphOracleSem` constructor to create a virtual model, as in the following example:

```
GraphOracleSem graph = new GraphOracleSem(oracle, modelName, attachment, true);
```

In this example, the fourth parameter (`true`) specifies that a virtual model needs to be created for the specified `modelName` and `attachment`.

7.8.2 Connection Pooling Support

Oracle Database Connection Pooling is provided through the Jena Adapter `OraclePool` class. Once this class is initialized, it can return Oracle objects out of its pool of available connections. Oracle objects are essentially database connection wrappers. After `dispose` is called on the Oracle object, the connection is returned to the pool. More information about using `OraclePool` can be found in the API reference information (Javadoc).

The following example sets up an `OraclePool` object with five (5) initial connections.

```

public static void main(String[] args) throws Exception
{
    String szJdbcURL = args[0];
    String szUser    = args[1];
    String szPasswd  = args[2];
    String szModelName = args[3];

    // test with connection properties
    java.util.Properties prop = new java.util.Properties();
    prop.setProperty("MinLimit", "2"); // the cache size is 2 at least
    prop.setProperty("MaxLimit", "10");
    prop.setProperty("InitialLimit", "2"); // create 2 connections at startup
    prop.setProperty("InactivityTimeout", "1800"); // seconds
    prop.setProperty("AbandonedConnectionTimeout", "900"); // seconds
    prop.setProperty("MaxStatementsLimit", "10");
    prop.setProperty("PropertyCheckInterval", "60"); // seconds

    System.out.println("Creating OraclePool");
    OraclePool op = new OraclePool(szJdbcURL, szUser, szPasswd, prop,
        "OracleSemConnPool");
    System.out.println("Done creating OraclePool");

    // grab an Oracle and do something with it
    System.out.println("Getting an Oracle from OraclePool");
    Oracle oracle = op.getOracle();
    System.out.println("Done");
    System.out.println("Is logical connection:" +
        oracle.getConnection().isLogicalConnection());
    GraphOracleSem g = new GraphOracleSem(oracle, szModelName);
    g.add(Triple.create(Node.createURI("u:John"),
        Node.createURI("u:parentOf"),
        Node.createURI("u:Mary")));
    g.close();
    // return the Oracle back to the pool

```

```

oracle.dispose();

// grab another Oracle and do something else
System.out.println("Getting an Oracle from OraclePool");
oracle = op.getOracle();
System.out.println("Done");
System.out.println("Is logical connection:" +
    oracle.getConnection().isLogicalConnection());
g = new GraphOracleSem(oracle, szModelName);
g.add(Triple.create(Node.createURI("u:John"),
    Node.createURI("u:parentOf"),
    Node.createURI("u:Jack")));

g.close();

OracleUtils.dropSemanticModel(oracle, szModelName);

// return the Oracle object back to the pool
oracle.dispose();
}

```

7.8.3 Semantic Model PL/SQL Interfaces

Several semantic PL/SQL subprograms are available through the Jena Adapter. [Table 7-2](#) lists the subprograms and their corresponding Java class and methods.

Table 7-2 PL/SQL Subprograms and Corresponding Jena Adapter Java Class and Methods

PL/SQL Subprogram	Corresponding Java Class and Methods
SEM_APIS.DROP_SEM_MODEL	OracleUtils.dropSemanticModel
SEM_APIS.MERGE_MODELS	OracleUtils.mergeModels
SEM_APIS.SWAP_NAMES	OracleUtils.swapNames
SEM_APIS.REMOVE_DUPLICATES	OracleUtils.removeDuplicates
SEM_APIS.RENAME_MODEL	OracleUtils.renameModels

For information about these PL/SQL utility subprograms, see the reference information in [Chapter 9](#). For information about the corresponding Java class and methods, see the Jena Adapter API Reference documentation (Javadoc).

7.8.4 Inference Options

You can add options to entailment calls by using the `setInferenceOption(String options)` procedure with the `GraphOracleSem` constructor. The following example enables incremental inference and specifies a parallelism value of 4 when creating an entailment.

```
graph.setInferenceOption("INC=T,DOP=4");
```

For information about inference options, see [Section 2.2](#).

7.8.5 PelletInfGraph Class Support Deprecated

The support for the `PelletInfGraph` class within the Jena Adapter is deprecated. You should instead use the more optimized Oracle/Pellet integration through the PelletDb OWL 2 reasoner for Oracle Database 11g. (For information about PelletDb, see <http://clarkparsia.com/pelletdb/>.)

7.9 Bulk Loading Using the Jena Adapter

To load thousands to hundreds of thousands of RDF/OWL data files into an Oracle database, you can use the `prepareBulk` and `completeBulk` methods in the `OracleBulkUpdateHandler` Java class to simplify the task.

The `addInBulk` method in the `OracleBulkUpdateHandler` class can load triples of a graph or model into an Oracle database in bulk loading style. If the graph or model is a Jena in-memory graph or model, the operation is limited by the size of the physical memory. The `prepareBulk` method bypasses the Jena in-memory graph or model and takes a direct input stream to an RDF data file, parses the data, and load the triples into an underlying staging table. If the staging table and an accompanying table for storing long literals do not already exist, they are created automatically.

The `prepareBulk` method can be invoked multiple times to load multiple data files into the same underlying staging table. It can also be invoked concurrently, assuming the hardware system is balanced and there are multiple CPU cores and sufficient I/O capacity.

Once all the data files are processed by the `prepareBulk` method, you can invoke `completeBulk` to load all the data into the semantic network.

[Example 7-1](#) shows how to load all data files in directory `dir_1` into the underlying staging table. Long literals are supported and will be stored in a separate table. The data files can be compressed using GZIP to save storage space, and the `prepareBulk` method can detect automatically if a data file is compressed using GZIP or not.

Example 7-1 Loading Data into the Staging Table (`prepareBulk`)

```
Oracle oracle = new Oracle(szJdbcURL, szUser, szPasswd);
GraphOracleSem graph = new GraphOracleSem(oracle, szModelName);

PrintStream psOut = System.out;

String dirname = "dir_1";
File fileDir = new File(dirname);
String[] szAllFiles = fileDir.list();

// loop through all the files in a directory
for (int idx = 0; idx < szAllFiles.length; idx++) {
    String szIndFileName = dirname + File.separator + szAllFiles[idx];
    psOut.println("process to [ID = " + idx + " ] file " + szIndFileName);
    psOut.flush();

    try {
        InputStream is = new FileInputStream(szIndFileName);
        graph.getBulkUpdateHandler().prepareBulk(
            is,                // input stream
            "http://example.com", // base URI
            "RDF/XML",         // data file type: can be RDF/XML, N-TRIPLE, etc.
            "SEMTS",           // tablespace
            null,               // flags
            null,               // listener
            null                // staging table name.
        );
        is.close();
    }
    catch (Throwable t) {
        psOut.println("Hit exception " + t.getMessage());
    }
}
```

```
graph.close();
oracle.dispose();
```

The code in [Example 7-1](#), starting from creating a new Oracle object and ending with disposing of the Oracle object, can be executed in parallel. Assume there is a quad-core CPU and enough I/O capacity on the database hardware system; you can divide up all the data files and save them into four separate directories: `dir_1`, `dir_2`, `dir_3`, and `dir_4`. Four Java threads or processes can be started to work on those directories separately and concurrently.

After all data files are processed, you can invoke, just once, the `completeBulk` method to load the data from staging table into the semantic network, as shown in [Example 7-2](#). Triples with long literals will be loaded also.

Example 7-2 Loading Data from the Staging Table into the Semantic Network (completeBulk)

```
graph.getBulkUpdateHandler().completeBulk(
    null, // flags for invoking SEM_APIS.bulk_load_from_staging_table
    null // staging table name
);
```

The `prepareBulk` method can also take a Jena model as an input data source, in which case triples in that Jena model are loaded into the underlying staging table. For more information, see the Javadoc.

In addition to loading triples from Jena models and data files, the `prepareBulk` method supports RDFa, as shown in [Example 7-3](#). (RDFa is explained in <http://www.w3.org/TR/xhtml-rdfa-primer/>.)

Example 7-3 Using prepareBulk with RDFa

```
graph.getBulkUpdateHandler().prepareBulk(
    rdfaUrl, // url to a web page using RDFa
    "SEMTS", // tablespace
    null, // flags
    null, // listener
    null // staging table name
);
```

To parse RDFa, the relevant `java-rdfa` libraries must be included in the classpath. No additional setup or API calls are required. (For information about `java-rdfa`, see <http://www.rootdev.net/maven/projects/java-rdfa/> and the other topics there under Project Information.)

Note that if the `rdfaUrl` is located outside a firewall, you may need to set the following HTTP Proxy-related Java VM properties:

```
-Dhttp.proxyPort=...
-Dhttp.proxyHost=...
```

7.10 Example Queries Using the Jena Adapter

This section includes example queries using the Jena Adapter. Each example is self-contained: it typically creates a model, creates triples, performs a query that may involve inference, displays the result, and drops the model.

This section includes queries that do the following:

- Count asserted triples and asserted plus inferred triples in an example "university" ontology, both by referencing the ontology by a URL and by bulk loading the ontology from a local file
- Run several SPARQL queries using a "family" ontology, including features such as LIMIT, OFFSET, TIMEOUT, DOP (degree of parallelism), ASK, DESCRIBE, CONSTRUCT, GRAPH, ALLOW_DUP (duplicate triples with multiple models), SPARUL (inserting data)
- Use the ARQ built-in function
- Use a SELECT cast query
- Instantiate Oracle Database using OracleConnection
- Use Oracle Database connection pooling

To run a query, you must do the following:

1. Include the code in a Java source file. The examples used in this section are supplied in files in the `examples` directory of the Jena Adapter download.
2. Compile the Java source file. For example:

```
> javac -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4
j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar Test.java
```

Note: The `javac` and `java` commands must each be on a single command line.

3. Run the compiled file. For example:

```
> java -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf
4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar:/iri-0.8.jar:/icu
4j-3.4.4.jar:/log4j-1.2.14.jar Test jdbc:oracle:thin:@localhost:1521:orcl
scott <password-for-scott> M1
```

7.10.1 Test.java: Query Family Relationships

[Example 7-4](#) specifies that John is the father of Mary, and it selects and displays the subject and object in each `fatherOf` relationship

Example 7-4 Query Family Relationships

```
import oracle.spatial.rdf.client.jena.*;
import com.hp.hpl.jena.rdf.model.Model;
import com.hp.hpl.jena.graph.*;
import com.hp.hpl.jena.query.*;
public class Test {

    public static void main(String[] args) throws Exception
    {
        String szJdbcURL = args[0];
        String szUser    = args[1];
        String szPasswd  = args[2];
        String szModelName = args[3];

        Oracle oracle = new Oracle(szJdbcURL, szUser, szPasswd);
```

```

Model model = ModelOracleSem.createOracleSemModel(
    oracle, szModelName);

model.getGraph().add(Triple.create(
    Node.createURI("http://example.com/John"),
    Node.createURI("http://example.com/fatherOf"),
    Node.createURI("http://example.com/Mary")));
Query query = QueryFactory.create(
    "select ?f ?k WHERE {?f <http://example.com/fatherOf> ?k .}");
QueryExecution qexec = QueryExecutionFactory.create(query, model);
ResultSet results = qexec.execSelect();
ResultSetFormatter.out(System.out, results, query);
model.close();
oracle.dispose();
}
}

```

The following are the commands to compile and run [Example 7-4](#), as well as the expected output of the java command.

```

javac -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar Test.java
java -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar:/iri-0.8.jar:/icu4j-3.4.4.jar:/log4j-1.2.14.jar Test jdbc:oracle:thin:@localhost:1521:orcl scott
<password-for-scott> M1

```

```

-----
| f                               | k                               |
-----
| <http://example.com/John>     | <http://example.com/Mary>     |
-----

```

7.10.2 Test6.java: Load OWL Ontology and Perform OWLPrime inference

[Example 7-5](#) loads an OWL ontology and performs OWLPrime inference. Note that the OWL ontology is in RDF/XML format, and after it is loaded into Oracle it will be serialized out in N-TRIPLE form. The example also queries for the number of asserted and inferred triples.

The ontology in this example can be retrieved from <http://www.lehigh.edu/~zhp2/2004/0401/univ-bench.owl>, and it describes roles, resources, and relationships in a university environment.

Example 7-5 Load OWL Ontology and Perform OWLPrime inference

```

import java.io.*;
import com.hp.hpl.jena.query.*;
import com.hp.hpl.jena.rdf.model.Model;
import com.hp.hpl.jena.util.FileManager;
import oracle.spatial.rdf.client.jena.*;
public class Test6 {
    public static void main(String[] args) throws Exception
    {
        String szJdbcURL = args[0];
        String szUser    = args[1];
        String szPasswd  = args[2];
        String szModelName = args[3];

```

```

Oracle oracle = new Oracle(szJdbcURL, szUser, szPasswd);
Model model = ModelOracleSem.createOracleSemModel(oracle, szModelName);

// load UNIV ontology
InputStream in = FileManager.get().open("./univ-bench.owl" );
model.read(in, null);
OutputStream os = new FileOutputStream("./univ-bench.nt");
model.write(os, "N-TRIPLE");
os.close();

String queryString =
    " SELECT ?subject ?prop ?object WHERE { ?subject ?prop ?object } ";

Query query = QueryFactory.create(queryString) ;
QueryExecution qexec = QueryExecutionFactory.create(query, model) ;

try {
    int iTriplesCount = 0;
    ResultSet results = qexec.execSelect() ;
    for ( ; results.hasNext() ; ) {
        QuerySolution soln = results.nextSolution() ;
        iTriplesCount++;
    }
    System.out.println("Asserted  triples count: " + iTriplesCount);
}
finally {
    qexec.close() ;
}

Attachment attachment = Attachment.createInstance(
    new String[] {}, "OWLPRIME",
    InferenceMaintenanceMode.NO_UPDATE, QueryOptions.DEFAULT);

GraphOracleSem graph = new GraphOracleSem(oracle, szModelName, attachment);
graph.analyze();
graph.performInference();

query = QueryFactory.create(queryString) ;
qexec = QueryExecutionFactory.create(query,new ModelOracleSem(graph)) ;

try {
    int iTriplesCount = 0;
    ResultSet results = qexec.execSelect() ;
    for ( ; results.hasNext() ; ) {
        QuerySolution soln = results.nextSolution() ;
        iTriplesCount++;
    }
    System.out.println("Asserted + Infered triples count: " + iTriplesCount);
}
finally {
    qexec.close() ;
}
model.close();

OracleUtils.dropSemanticModel(oracle, szModelName);
oracle.dispose();
}
}

```

The following are the commands to compile and run [Example 7-5](#), as well as the expected output of the java command.

```
javac -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar Test6.java
java -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar:/iri-0.8.jar:/icu4j-3.4.4.jar:/log4j-1.2.14.jar Test6 jdbc:oracle:thin:@localhost:1521:orcl scott
<password-for-scott> M1
Asserted triples count: 294
Asserted + Inferred triples count: 341
```

Note that this output reflects an older version of the LUBM ontology. The latest version of the ontology has more triples.

7.10.3 Test7.java: Bulk Load OWL Ontology and Perform OWLPrime inference

[Example 7-6](#) loads the same OWL ontology as in [Section 7.10.2](#), but stored in a local file using Bulk Loader. Ontologies can also be loaded using an incremental and batch loader; these two methods are also listed in the example for completeness.

Example 7-6 Bulk Load OWL Ontology and Perform OWLPrime inference

```
import java.io.*;
import com.hp.hpl.jena.query.*;
import com.hp.hpl.jena.graph.*;
import com.hp.hpl.jena.rdf.model.*;
import com.hp.hpl.jena.util.*;
import oracle.spatial.rdf.client.jena.*;

public class Test7
{
    public static void main(String[] args) throws Exception
    {
        String szJdbcURL = args[0];
        String szUser = args[1];
        String szPasswd = args[2];
        String szModelName = args[3];
        // in memory Jena Model
        Model model = ModelFactory.createDefaultModel();
        InputStream is = FileManager.get().open("./univ-bench.owl");
        model.read(is, "", "RDF/XML");
        is.close();

        Oracle oracle = new Oracle(szJdbcURL, szUser, szPasswd);
        ModelOracleSem modelDest = ModelOracleSem.createOracleSemModel(oracle,
szModelName);

        GraphOracleSem g = modelDest.getGraph();
        g.dropApplicationTableIndex();

        int method = 2; // try bulk loader
        String tbs = "SYSAUX"; // can be customized
        if (method == 0) {
            System.out.println("start incremental");
            modelDest.add(model);
            System.out.println("end size " + modelDest.size());
        }
    }
}
```

```

else if (method == 1) {
    System.out.println("start batch load");
    g.getBulkUpdateHandler().addInBatch(
        GraphUtil.findAll(model.getGraph()), tbs);
    System.out.println("end size " + modelDest.size());
}
else {
    System.out.println("start bulk load");
    g.getBulkUpdateHandler().addInBulk(
        GraphUtil.findAll(model.getGraph()), tbs);
    System.out.println("end size " + modelDest.size());
}
g.rebuildApplicationTableIndex();

long lCount = g.getCount(Triple.ANY);
System.out.println("Asserted triples count: " + lCount);
model.close();
OracleUtils.dropSemanticModel(oracle, szModelName);
oracle.dispose();
}
}

```

The following are the commands to compile and run [Example 7-6](#), as well as the expected output of the `java` command.

```

javac -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar Test7.java
java -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar:/iri-0.8.jar:/icu4j-3.4.4.jar:/log4j-1.2.14.jar Test7 jdbc:oracle:thin:@localhost:1521:orcl scott
<password-for-scott> M1
start bulk load
end size 293
Asserted triples count: 293

```

Note that this output reflects an older version of the LUBM ontology. The latest version of the ontology has more triples.

7.10.4 Test8.java: SPARQL OPTIONAL Query

[Example 7-7](#) shows a SPARQL OPTIONAL query. It inserts triples that postulate the following:

- John is a parent of Mary.
- John is a parent of Jack.
- Mary is a parent of Jill.

It then finds parent-child relationships, optionally including any grandchild (gkid) relationships.

Example 7-7 SPARQL OPTIONAL Query

```

import java.io.*;
import com.hp.hpl.jena.query.*;
import com.hp.hpl.jena.rdf.model.Model;
import com.hp.hpl.jena.util.FileManager;
import oracle.spatial.rdf.client.jena.*;

```

```

import com.hp.hpl.jena.graph.*;

public class Test8
{
    public static void main(String[] args) throws Exception
    {
        String szJdbcURL = args[0];
        String szUser    = args[1];
        String szPasswd  = args[2];
        String szModelName = args[3];

        Oracle oracle = new Oracle(szJdbcURL, szUser, szPasswd);
        ModelOracleSem model = ModelOracleSem.createOracleSemModel(oracle,
szModelName);
        GraphOracleSem g = model.getGraph();

        g.add(Triple.create(
            Node.createURI("u:John"), Node.createURI("u:parentOf"),
Node.createURI("u:Mary")));
        g.add(Triple.create(
            Node.createURI("u:John"), Node.createURI("u:parentOf"),
Node.createURI("u:Jack")));
        g.add(Triple.create(
            Node.createURI("u:Mary"), Node.createURI("u:parentOf"),
Node.createURI("u:Jill")));

        String queryString =
" SELECT ?s ?o ?gkid " +
" WHERE { ?s <u:parentOf> ?o . OPTIONAL {?o <u:parentOf> ?gkid } } ";

        Query query = QueryFactory.create(queryString) ;
        QueryExecution qexec = QueryExecutionFactory.create(query, model) ;

        try {
            int iMatchCount = 0;
            ResultSet results = qexec.execSelect() ;
            ResultSetFormatter.out(System.out, results, query);
        }
        finally {
            qexec.close() ;
        }
        model.close();

        OracleUtils.dropSemanticModel(oracle, szModelName);
        oracle.dispose();
    }
}

```

The following are the commands to compile and run [Example 7-7](#), as well as the expected output of the java command.

```

javac -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-l
og4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar Test8.java
java -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-
log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar:/iri-0.8.jar:/icu4j-3.4
.4.jar:/log4j-1.2.14.jar Test8 jdbc:oracle:thin:@localhost:1521:orcl scott
<password-for-scott> M1
-----
| s          | o          | gkid       |

```

```

=====
| <u:John> | <u:Mary> | <u:Jill> |
| <u:Mary> | <u:Jill> |           |
| <u:John> | <u:Jack> |           |
-----

```

7.10.5 Test9.java: SPARQL Query with LIMIT and OFFSET

[Example 7–8](#) shows a SPARQL query with LIMIT and OFFSET. It inserts triples that postulate the following:

- John is a parent of Mary.
- John is a parent of Jack.
- Mary is a parent of Jill.

It then finds one parent-child relationship (LIMIT 1), skipping the first two parent-child relationships encountered (OFFSET 2), and optionally includes any grandchild (gkid) relationships for the one found.

Example 7–8 SPARQL Query with LIMIT and OFFSET

```

import java.io.*;
import com.hp.hpl.jena.query.*;
import com.hp.hpl.jena.rdf.model.Model;
import com.hp.hpl.jena.util.FileManager;
import oracle.spatial.rdf.client.jena.*;
import com.hp.hpl.jena.graph.*;

public class Test9
{
    public static void main(String[] args) throws Exception
    {
        String szJdbcURL = args[0];
        String szUser    = args[1];
        String szPasswd  = args[2];
        String szModelName = args[3];

        Oracle oracle = new Oracle(szJdbcURL, szUser, szPasswd);
        ModelOracleSem model = ModelOracleSem.createOracleSemModel(oracle,
szModelName);
        GraphOracleSem g = model.getGraph();

        g.add(Triple.create(Node.createURI("u:John"), Node.createURI("u:parentOf"),
            Node.createURI("u:Mary")));
        g.add(Triple.create(Node.createURI("u:John"), Node.createURI("u:parentOf"),
            Node.createURI("u:Jack")));
        g.add(Triple.create(Node.createURI("u:Mary"), Node.createURI("u:parentOf"),
            Node.createURI("u:Jill")));

        String queryString =
            " SELECT ?s ?o ?gkid " +
            " WHERE { ?s <u:parentOf> ?o . OPTIONAL {?o <u:parentOf> ?gkid } } " +
            " LIMIT 1 OFFSET 2";

        Query query = QueryFactory.create(queryString) ;
        QueryExecution qexec = QueryExecutionFactory.create(query, model) ;

        int iMatchCount = 0;
        ResultSet results = qexec.execSelect() ;
        ResultSetFormatter.out(System.out, results, query);
    }
}

```

```

    qexec.close() ;
    model.close();

    OracleUtils.dropSemanticModel(oracle, szModelName);
    oracle.dispose();
}
}

```

The following are the commands to compile and run [Example 7–8](#), as well as the expected output of the `java` command.

```

javac -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-
log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar Test9.java
java -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-
log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar:/iri-0.8.jar:/icu4j-3.4
.4.jar:/log4j-1.2.14.jar Test9 jdbc:oracle:thin:@localhost:1521:orcl scott
<password-for-scott> M1
-----
| s          | o          | gkid |
=====
| <u:John>  | <u:Jack>  |      |
-----

```

7.10.6 Test10.java: SPARQL Query with TIMEOUT and DOP

[Example 7–9](#) shows the SPARQL query from [Section 7.10.5](#) with additional features, including a timeout setting (TIMEOUT=1, in seconds) and parallel execution setting (DOP=4).

Example 7–9 SPARQL Query with TIMEOUT and DOP

```

import java.io.*;
import com.hp.hpl.jena.query.*;
import com.hp.hpl.jena.rdf.model.Model;
import com.hp.hpl.jena.util.FileManager;
import oracle.spatial.rdf.client.jena.*;
import com.hp.hpl.jena.graph.*;

public class Test10 {
    public static void main(String[] args) throws Exception {
        String szJdbcURL = args[0];
        String szUser    = args[1];
        String szPasswd  = args[2];
        String szModelName = args[3];

        Oracle oracle = new Oracle(szJdbcURL, szUser, szPasswd);
        ModelOracleSem model = ModelOracleSem.createOracleSemModel(oracle,
szModelName);
        GraphOracleSem g = model.getGraph();

        g.add(Triple.create(Node.createURI("u:John"), Node.createURI("u:parentOf"),
Node.createURI("u:Mary")));
        g.add(Triple.create(Node.createURI("u:John"), Node.createURI("u:parentOf"),
Node.createURI("u:Jack")));
        g.add(Triple.create(Node.createURI("u:Mary"), Node.createURI("u:parentOf"),
Node.createURI("u:Jill")));
        String queryString =
            " PREFIX ORACLE_SEM_FS_NS: <http://oracle.com/semtech#dop=4,timeout=1> "

```

```

+ " SELECT ?s ?o ?gkid WHERE { ?s <u:parentOf> ?o . "
+ " OPTIONAL {?o <u:parentOf> ?gkid }} "
+ " LIMIT 1 OFFSET 2";

Query query = QueryFactory.create(queryString) ;
QueryExecution qexec = QueryExecutionFactory.create(query, model) ;

int iMatchCount = 0;
ResultSet results = qexec.execSelect() ;
ResultSetFormatter.out(System.out, results, query);
qexec.close() ;
model.close();

OracleUtils.dropSemanticModel(oracle, szModelName);
oracle.dispose();
}
}

```

The following are the commands to compile and run [Example 7-9](#), as well as the expected output of the java command.

```

javac -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-1
og4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar Test10.java
java -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-
log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar:/iri-0.8.jar:/icu4j-3.4
.4.jar:/log4j-1.2.14.jar Test10 jdbc:oracle:thin:@localhost:1521:orcl scott
<password-for-scott> M1
-----
| s          | o          | gkid |
-----
| <u:Mary>  | <u:Jill>  |      |
-----

```

7.10.7 Test11.java: Query Involving Named Graphs

[Example 7-10](#) shows a query involving named graphs. It involves a default model that has information about named graph URLs and their publishers. The query finds graph names, their publishers, and within each named graph finds the mailbox value using the `foaf:mbox` predicate.

Example 7-10 Named Graph Based Query

```

import java.io.*;
import com.hp.hpl.jena.query.*;
import com.hp.hpl.jena.rdf.model.Model;
import com.hp.hpl.jena.util.FileManager;
import oracle.spatial.rdf.client.jena.*;
import com.hp.hpl.jena.graph.*;

public class Test11
{
    public static void main(String[] args) throws Exception
    {
        String szJdbcURL = args[0];
        String szUser    = args[1];
        String szPasswd  = args[2];
        String szModelName = args[3];

```

```

Oracle oracle = new Oracle(szJdbcURL, szUser, szPasswd);
DataSource ds = DatasetFactory.create();
ModelOracleSem model = ModelOracleSem.createOracleSemModel(oracle,
szModelName);
model.getGraph().add(Triple.create(Node.createURI("http://example.org/bob"),
Node.createURI("http://purl.org/dc/elements/1.1/publisher"),
Node.createLiteral("Bob Hacker")));
model.getGraph().add(Triple.create(Node.createURI("http://example.org/alice"),
Node.createURI("http://purl.org/dc/elements/1.1/publisher"),
Node.createLiteral("alice Hacker")));

ModelOracleSem model1 = ModelOracleSem.createOracleSemModel(oracle,
szModelName+"1");

model1.getGraph().add(Triple.create(Node.createURI("urn:bob"),
Node.createURI("http://xmlns.com/foaf/0.1/name"),
Node.createLiteral("Bob")));
model1.getGraph().add(Triple.create(Node.createURI("urn:bob"),
Node.createURI("http://xmlns.com/foaf/0.1/mbox"),
Node.createURI("mailto:bob@example"))));

ModelOracleSem model2 = ModelOracleSem.createOracleSemModel(oracle,
szModelName+"2");
model2.getGraph().add(Triple.create(Node.createURI("urn:alice"),
Node.createURI("http://xmlns.com/foaf/0.1/name"),
Node.createLiteral("Alice")));
model2.getGraph().add(Triple.create(Node.createURI("urn:alice"),
Node.createURI("http://xmlns.com/foaf/0.1/mbox"),
Node.createURI("mailto:alice@example"))));

ds.setDefaultModel(model);
ds.addNamedModel("http://example.org/bob",model1);
ds.addNamedModel("http://example.org/alice",model2);

String queryString =
    " PREFIX foaf: <http://xmlns.com/foaf/0.1/> "
+ " PREFIX dc: <http://purl.org/dc/elements/1.1/> "
+ " SELECT ?who ?graph ?mbox "
+ " FROM NAMED <http://example.org/alice> "
+ " FROM NAMED <http://example.org/bob> "
+ " WHERE "
+ " { "
+ "     ?graph dc:publisher ?who . "
+ "     GRAPH ?graph { ?x foaf:mbox ?mbox } "
+ " } ";

Query query = QueryFactory.create(queryString) ;
QueryExecution qexec = QueryExecutionFactory.create(query, ds) ;

ResultSet results = qexec.execSelect() ;
ResultSetFormatter.out(System.out, results, query);

qexec.close();
model.close();
model1.close();

```

```

model2.close();

OracleUtils.dropSemanticModel(oracle, szModelName);
OracleUtils.dropSemanticModel(oracle, szModelName + "1");
OracleUtils.dropSemanticModel(oracle, szModelName + "2");
oracle.dispose();
}
}

```

The following are the commands to compile and run [Example 7–10](#), as well as the expected output of the java command.

```

javac -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar Test11.java
java -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar:/iri-0.8.jar:/icu4j-3.4.4.jar:/log4j-1.2.14.jar Test11 jdbc:oracle:thin:@localhost:1521:orcl scott
<password-for-scott> M1
-----
| who          | graph          | mbox          |
=====
| "alice Hacker" | <http://example.org/alice> | <mailto:alice@example> |
| "Bob Hacker"  | <http://example.org/bob>  | <mailto:bob@example>  |
-----

```

7.10.8 Test12.java: SPARQL ASK Query

[Example 7–11](#) shows a SPARQL ASK query. It inserts a triple that postulates that John is a parent of Mary. It then finds whether John is a parent of Mary.

Example 7–11 SPARQL ASK Query

```

import java.io.*;
import com.hp.hpl.jena.query.*;
import com.hp.hpl.jena.rdf.model.Model;
import com.hp.hpl.jena.util.FileManager;
import oracle.spatial.rdf.client.jena.*;
import com.hp.hpl.jena.graph.*;
public class Test12
{
    public static void main(String[] args) throws Exception
    {
        String szJdbcURL = args[0];
        String szUser    = args[1];
        String szPasswd  = args[2];
        String szModelName = args[3];

        Oracle oracle = new Oracle(szJdbcURL, szUser, szPasswd);
        ModelOracleSem model = ModelOracleSem.createOracleSemModel(oracle,
            szModelName);
        GraphOracleSem g = model.getGraph();

        g.add(Triple.create(Node.createURI("u:John"), Node.createURI("u:parentOf"),
            Node.createURI("u:Mary")));
        String queryString = " ASK { <u:John> <u:parentOf> <u:Mary> } ";

        Query query = QueryFactory.create(queryString) ;
        QueryExecution qexec = QueryExecutionFactory.create(query, model) ;
    }
}

```

```

boolean b = qexec.execAsk();
System.out.println("ask result = " + ((b)?"TRUE":"FALSE"));
qexec.close() ;

model.close();
OracleUtils.dropSemanticModel(oracle, szModelName);
oracle.dispose();
}
}

```

The following are the commands to compile and run [Example 7–11](#), as well as the expected output of the `java` command.

```

javac -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar Test12.java
java -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar:/iri-0.8.jar:/icu4j-3.4.4.jar:/log4j-1.2.14.jar Test12 jdbc:oracle:thin:@localhost:1521:orcl scott
<password-for-scott> M1
ask result = TRUE

```

7.10.9 Test13.java: SPARQL DESCRIBE Query

[Example 7–12](#) shows a SPARQL DESCRIBE query. It inserts triples that postulate the following:

- John is a parent of Mary.
- John is a parent of Jack.
- Amy is a parent of Jack.

It then finds all relationships that involve any parents of Jack.

Example 7–12 SPARQL DESCRIBE Query

```

import java.io.*;
import com.hp.hpl.jena.query.*;
import com.hp.hpl.jena.rdf.model.Model;
import com.hp.hpl.jena.util.FileManager;
import oracle.spatial.rdf.client.jena.*;
import com.hp.hpl.jena.graph.*;

public class Test13
{
    public static void main(String[] args) throws Exception
    {
        String szJdbcURL = args[0];
        String szUser    = args[1];
        String szPasswd  = args[2];
        String szModelName = args[3];

        Oracle oracle = new Oracle(szJdbcURL, szUser, szPasswd);
        ModelOracleSem model = ModelOracleSem.createOracleSemModel(oracle,
szModelName);
        GraphOracleSem g = model.getGraph();

        g.add(Triple.create(Node.createURI("u:John"), Node.createURI("u:parentOf"),
Node.createURI("u:Mary")));
        g.add(Triple.create(Node.createURI("u:John"), Node.createURI("u:parentOf"),

```

```

Node.createURI("u:Jack"));
    g.add(Triple.create(Node.createURI("u:Amy"), Node.createURI("u:parentOf"),
Node.createURI("u:Jack"));
    String queryString = " DESCRIBE ?x WHERE {?x <u:parentOf> <u:Jack>}";

    Query query = QueryFactory.create(queryString) ;
    QueryExecution qexec = QueryExecutionFactory.create(query, model) ;
    Model m = qexec.execDescribe();
    System.out.println("describe result = " + m.toString());

    qexec.close() ;
    model.close();
    OracleUtils.dropSemanticModel(oracle, szModelName);
    oracle.dispose();
}
}

```

The following are the commands to compile and run [Example 7–12](#), as well as the expected output of the java command.

```

javac -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-
og4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar Test13.java
java -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-
log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar:/iri-0.8.jar:/icu4j-3.4
.4.jar:/log4j-1.2.14.jar Test13 jdbc:oracle:thin:@localhost:1521:orcl scott
<password-for-scott> M1
describe result = <ModelCom {u:Amy @u:parentOf u:Jack; u:John @u:parentOf
u:Jack; u:John @u:parentOf u:Mary} | >

```

7.10.10 Test14.java: SPARQL CONSTRUCT Query

[Example 7–13](#) shows a SPARQL CONSTRUCT query. It inserts triples that postulate the following:

- John is a parent of Mary.
- John is a parent of Jack.
- Amy is a parent of Jack.
- Each parent loves all of his or her children.

It then constructs an RDF graph with information about who loves whom.

Example 7–13 SPARQL CONSTRUCT Query

```

import java.io.*;
import com.hp.hpl.jena.query.*;
import com.hp.hpl.jena.rdf.model.Model;
import com.hp.hpl.jena.util.FileManager;
import oracle.spatial.rdf.client.jena.*;
import com.hp.hpl.jena.graph.*;

public class Test14
{
    public static void main(String[] args) throws Exception
    {
        String szJdbcURL = args[0];
        String szUser = args[1];
        String szPasswd = args[2];

```

```

String szModelName = args[3];

Oracle oracle = new Oracle(szJdbcURL, szUser, szPasswd);
ModelOracleSem model = ModelOracleSem.createOracleSemModel(oracle,
szModelName);
GraphOracleSem g = model.getGraph();

g.add(Triple.create(Node.createURI("u:John"), Node.createURI("u:parentOf"),
Node.createURI("u:Mary")));
g.add(Triple.create(Node.createURI("u:John"), Node.createURI("u:parentOf"),
Node.createURI("u:Jack")));
g.add(Triple.create(Node.createURI("u:Amy"), Node.createURI("u:parentOf"),
Node.createURI("u:Jack")));
String queryString = " CONSTRUCT { ?s <u:loves> ?o } WHERE {?s <u:parentOf>
?o}";

Query query = QueryFactory.create(queryString) ;
QueryExecution qexec = QueryExecutionFactory.create(query, model) ;
Model m = qexec.execConstruct();
System.out.println("Construct result = " + m.toString());

qexec.close() ;
model.close();
OracleUtils.dropSemanticModel(oracle, szModelName);
oracle.dispose();
}
}

```

The following are the commands to compile and run [Example 7-13](#), as well as the expected output of the `java` command.

```

javac -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-l
og4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar Test14.java
java -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-
log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar:/iri-0.8.jar:/icu4j-3.4
.4.jar:/log4j-1.2.14.jar Test14 jdbc:oracle:thin:@localhost:1521:orcl scott
<password-for-scott> M1
Construct result = <ModelCom {u:Amy @u:loves u:Jack; u:John @u:loves u:Jack;
u:John @u:loves u:Mary} | >

```

7.10.11 Test15.java: Query Multiple Models and Specify "Allow Duplicates"

[Example 7-14](#) queries multiple models and uses the "allow duplicates" option. It inserts triples that postulate the following:

- John is a parent of Jack (in Model 1).
- Mary is a parent of Jack (in Model 2).
- Each parent loves all of his or her children.

It then finds out who loves whom. It searches both models and allows for the possibility of duplicate triples in the models (although there are no duplicates in this example).

Example 7-14 Query Multiple Models and Specify "Allow Duplicates"

```

import java.io.*;
import com.hp.hpl.jena.query.*;
import com.hp.hpl.jena.rdf.model.Model;

```

```

import com.hp.hpl.jena.util.FileManager;
import oracle.spatial.rdf.client.jena.*;
import com.hp.hpl.jena.graph.*;

public class Test15
{
    public static void main(String[] args) throws Exception
    {
        String szJdbcURL = args[0];
        String szUser    = args[1];
        String szPasswd  = args[2];
        String szModelName1 = args[3];
        String szModelName2 = args[4];

        Oracle oracle = new Oracle(szJdbcURL, szUser, szPasswd);
        ModelOracleSem model1 = ModelOracleSem.createOracleSemModel(oracle,
szModelName1);
        model1.getGraph().add(Triple.create(Node.createURI("u:John"),
Node.createURI("u:parentOf"), Node.createURI("u:Jack")));
        model1.close();

        ModelOracleSem model2 = ModelOracleSem.createOracleSemModel(oracle,
szModelName2);
        model2.getGraph().add(Triple.create(Node.createURI("u:Mary"),
Node.createURI("u:parentOf"), Node.createURI("u:Jack")));
        model2.close();

        String[] modelNamesList = {szModelName2};
        String[] rulebasesList = {};
        Attachment attachment = Attachment.createInstance(modelNamesList,
rulebasesList,
InferenceMaintenanceMode.NO_UPDATE,
QueryOptions.ALLOW_QUERY_VALID_AND_DUP);

        GraphOracleSem graph = new GraphOracleSem(oracle, szModelName1, attachment);
        ModelOracleSem model = new ModelOracleSem(graph);

        String queryString = " CONSTRUCT { ?s <u:loves> ?o } WHERE {?s <u:parentOf>
?o}";
        Query query = QueryFactory.create(queryString) ;
        QueryExecution qexec = QueryExecutionFactory.create(query, model) ;
        Model m = qexec.execConstruct();
        System.out.println("Construct result = " + m.toString());

        qexec.close() ;
        model.close();
        OracleUtils.dropSemanticModel(oracle, szModelName1);
        OracleUtils.dropSemanticModel(oracle, szModelName2);
        oracle.dispose();
    }
}

```

The following are the commands to compile and run [Example 7-14](#), as well as the expected output of the java command.

```

javac -classpath
./../jena-2.6.3.jar:./sdordfclient.jar:./ojdbc5.jar:./slf4j-api-1.5.8.jar:./slf4j-log4j12-1.5.8.jar:./arq-2.8.5.jar:./xercesImpl-2.7.1.jar Test15.java
java -classpath
./../jena-2.6.3.jar:./sdordfclient.jar:./ojdbc5.jar:./slf4j-api-1.5.8.jar:./slf4j-log4j12-1.5.8.jar:./arq-2.8.5.jar:./xercesImpl-2.7.1.jar:./iri-0.8.jar:./icu4j-3.4

```

```
.4.jar:./log4j-1.2.14.jar Test15 jdbc:oracle:thin:@localhost:1521:orcl scott
<password-for-scott> M1 M2
Construct result = <ModelCom {u:Mary @u:loves u:Jack; u:John @u:loves u:Jack} |
>
```

7.10.12 Test16.java: SPARUL (SPARQL Update) Example

[Example 7–15](#) inserts two triples into a model.

Example 7–15 SPARUL (SPARQL Update) Example

```
import java.io.*;
import com.hp.hpl.jena.query.*;
import com.hp.hpl.jena.rdf.model.Model;
import com.hp.hpl.jena.util.FileManager;
import com.hp.hpl.jena.util.iterator.*;
import oracle.spatial.rdf.client.jena.*;
import com.hp.hpl.jena.graph.*;
import com.hp.hpl.jena.update.*;

public class Test16
{
    public static void main(String[] args) throws Exception
    {
        String szJdbcURL = args[0];
        String szUser    = args[1];
        String szPasswd  = args[2];
        String szModelName = args[3];

        Oracle oracle = new Oracle(szJdbcURL, szUser, szPasswd);
        ModelOracleSem model = ModelOracleSem.createOracleSemModel(oracle,
szModelName);
        GraphOracleSem g = model.getGraph();
        String insertString =
            " PREFIX dc: <http://purl.org/dc/elements/1.1/> "          +
            " INSERT DATA "                                          +
            " { <http://example/book3> dc:title    \"A new book\" ; " +
            "   \"                                     dc:creator \"A.N.Other\" . " +
            " } ";

        UpdateAction.parseExecute(insertString, model);
        ExtendedIterator ei = GraphUtil.findAll(g);
        while (ei.hasNext()) {
            System.out.println("Triple " + ei.next().toString());
        }
        model.close();
        OracleUtils.dropSemanticModel(oracle, szModelName);
        oracle.dispose();
    }
}
```

The following are the commands to compile and run [Example 7–15](#), as well as the expected output of the java command.

```
javac -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-l
og4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar Test16.java
java -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-
log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar:/iri-0.8.jar:/icu4j-3.4
```

```
.4.jar:./log4j-1.2.14.jar Test16 jdbc:oracle:thin:@localhost:1521:orcl scott
<password-for-scott> M1
Triple http://example/book3 @dc:title "A new book"
Triple http://example/book3 @dc:creator "A.N.Other"
```

7.10.13 Test17.java: SPARQL Query with ARQ Built-In Functions

[Example 7–16](#) inserts data about two books, and it displays the book titles in all uppercase characters and the length of each title string.

Example 7–16 SPARQL Query with ARQ Built-In Functions

```
import java.io.*;
import com.hp.hpl.jena.query.*;
import com.hp.hpl.jena.rdf.model.Model;
import com.hp.hpl.jena.util.FileManager;
import com.hp.hpl.jena.util.iterator.*;
import oracle.spatial.rdf.client.jena.*;
import com.hp.hpl.jena.graph.*;
import com.hp.hpl.jena.update.*;

public class Test17 {
    public static void main(String[] args) throws Exception {
        String szJdbcURL = args[0];
        String szUser = args[1];
        String szPasswd = args[2];
        String szModelName = args[3];

        Oracle oracle = new Oracle(szJdbcURL, szUser, szPasswd);
        ModelOracleSem model = ModelOracleSem.createOracleSemModel(oracle,
szModelName);
        GraphOracleSem g = model.getGraph();
        String insertString =
            " PREFIX dc: <http://purl.org/dc/elements/1.1/> " +
            " INSERT DATA " +
            " { <http://example/book3> dc:title \"A new book\" ; " +
            "   dc:creator \"A.N.Other\" . " +
            "   <http://example/book4> dc:title \"Semantic Web Rocks\" ; " +
            "   dc:creator \"TB\" . " +
            " } ";

        UpdateAction.parseExecute(insertString, model);
        String queryString = "PREFIX dc: <http://purl.org/dc/elements/1.1/> " +
            " PREFIX fn: <http://www.w3.org/2005/xpath-functions#> " +
            " SELECT ?subject (fn:upper-case(?object) as ?object1) " +
            "   (fn:string-length(?object) as ?strlen) " +
            " WHERE { ?subject dc:title ?object } "
            ;
        Query query = QueryFactory.create(queryString, Syntax.syntaxARQ);
        QueryExecution qexec = QueryExecutionFactory.create(query, model);
        ResultSet results = qexec.execSelect();
        ResultSetFormatter.out(System.out, results, query);
        model.close();
        OracleUtils.dropSemanticModel(oracle, szModelName);
        oracle.dispose();
    }
}
```

The following are the commands to compile and run [Example 7–16](#), as well as the expected output of the java command.

```
javac -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar Test17.java
java -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar:/iri-0.8.jar:/icu4j-3.4.4.jar:/log4j-1.2.14.jar Test17 jdbc:oracle:thin:@localhost:1521:orcl scott
<password-for-scott> M1
```

```
-----
| subject                | object1                | strlen |
=====
| <http://example/book3> | "A NEW BOOK"           | 10     |
| <http://example/book4> | "SEMANTIC WEB ROCKS"  | 18     |
-----
```

7.10.14 Test18.java: SELECT Cast Query

Example 7-17 "converts" two Fahrenheit temperatures (18.1 and 32.0) to Celsius temperatures.

Example 7-17 SELECT Cast Query

```
import java.io.*;
import com.hp.hpl.jena.query.*;
import com.hp.hpl.jena.rdf.model.Model;
import com.hp.hpl.jena.util.FileManager;
import com.hp.hpl.jena.util.iterator.*;
import oracle.spatial.rdf.client.jena.*;
import com.hp.hpl.jena.graph.*;
import com.hp.hpl.jena.update.*;

public class Test18 {
    public static void main(String[] args) throws Exception {
        String szJdbcURL = args[0];
        String szUser    = args[1];
        String szPasswd  = args[2];
        String szModelName = args[3];

        Oracle oracle = new Oracle(szJdbcURL, szUser, szPasswd);
        ModelOracleSem model = ModelOracleSem.createOracleSemModel(oracle,
szModelName);
        GraphOracleSem g = model.getGraph();
        String insertString =
            " PREFIX xsd: <http://www.w3.org/2001/XMLSchema#> " +
            " INSERT DATA " +
            " { <u:Object1> <u:temp>    \"18.1\"^^xsd:float ; " +
            "           <u:name>        \"Foo... \" . " +
            "   <u:Object2> <u:temp>    \"32.0\"^^xsd:float ; " +
            "           <u:name>        \"Bar... \" . " +
            " } ";

        UpdateAction.parseExecute(insertString, model);
        String queryString =
            " PREFIX fn: <http://www.w3.org/2005/xpath-functions#> " +
            " SELECT ?subject ((?temp - 32.0)*5/9 as ?celsius_temp) " +
            " WHERE { ?subject <u:temp> ?temp } "
            ;
        Query query = QueryFactory.create(queryString, Syntax.syntaxARQ);
        QueryExecution qexec = QueryExecutionFactory.create(query, model);
        ResultSet results = qexec.execSelect();
```

```

ResultSetFormatter.out(System.out, results, query);

model.close();
OracleUtils.dropSemanticModel(oracle, szModelName);
oracle.dispose();
}
}

```

The following are the commands to compile and run [Example 7-17](#), as well as the expected output of the java command.

```

javac -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar Test18.java
java -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar:/iri-0.8.jar:/icu4j-3.4.4.jar:/log4j-1.2.14.jar Test18 jdbc:oracle:thin:@localhost:1521:orcl scott
<password-for-scott> M1
-----
| subject      | celsius_temp      |
=====
| <u:Object1> | "-7.7222223"^^<http://www.w3.org/2001/XMLSchema#float> |
| <u:Object2> | "0.0"^^<http://www.w3.org/2001/XMLSchema#float>      |
-----

```

7.10.15 Test19.java: Instantiate Oracle Database Using OracleConnection

[Example 7-18](#) shows a different way to instantiate an Oracle object using a given `OracleConnection` object. (In a J2EE Web application, users can normally get an `OracleConnection` object from a J2EE data source.)

Example 7-18 *Instantiate Oracle Database Using OracleConnection*

```

import java.io.*;
import com.hp.hpl.jena.query.*;
import com.hp.hpl.jena.rdf.model.Model;
import com.hp.hpl.jena.util.FileManager;
import com.hp.hpl.jena.util.iterator.*;
import com.hp.hpl.jena.graph.*;
import com.hp.hpl.jena.update.*;
import oracle.spatial.rdf.client.jena.*;
import oracle.jdbc.pool.*;
import oracle.jdbc.*;

public class Test19 {
    public static void main(String[] args) throws Exception {
        String szJdbcURL = args[0];
        String szUser    = args[1];
        String szPasswd  = args[2];
        String szModelName = args[3];

        OracleDataSource ds = new OracleDataSource();
        ds.setURL(szJdbcURL);
        ds.setUser(szUser);
        ds.setPassword(szPasswd);
        OracleConnection conn = (OracleConnection) ds.getConnection();
        Oracle oracle = new Oracle(conn);

        ModelOracleSem model = ModelOracleSem.createOracleSemModel(oracle,

```

```

szModelName);
    GraphOracleSem g = model.getGraph();

    g.add(Triple.create(Node.createURI("u:John"), Node.createURI("u:parentOf"),
        Node.createURI("u:Mary")));
    g.add(Triple.create(Node.createURI("u:John"), Node.createURI("u:parentOf"),
        Node.createURI("u:Jack")));
    g.add(Triple.create(Node.createURI("u:Mary"), Node.createURI("u:parentOf"),
        Node.createURI("u:Jill")));
    String queryString =
        " SELECT ?s ?o WHERE { ?s <u:parentOf> ?o .} ";
    Query query = QueryFactory.create(queryString) ;
    QueryExecution qexec = QueryExecutionFactory.create(query, model) ;

    ResultSet results = qexec.execSelect() ;
    ResultSetFormatter.out(System.out, results, query);
    qexec.close() ;
    model.close();
    OracleUtils.dropSemanticModel(oracle, szModelName);
    oracle.dispose();
}
}

```

The following are the commands to compile and run [Example 7–18](#), as well as the expected output of the java command.

```

javac -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar Test19.java
java -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar:/iri-0.8.jar:/icu4j-3.4.4.jar:/log4j-1.2.14.jar Test19 jdbc:oracle:thin:@localhost:1521:orcl scott
<password-for-scott> M1
-----
| s          | o          |
=====
| <u:John>  | <u:Mary>  |
| <u:John>  | <u:Jack>  |
| <u:Mary>  | <u:Jill>  |
-----

```

7.10.16 Test20.java: Oracle Database Connection Pooling

[Example 7–19](#) uses Oracle Database connection pooling.

Example 7–19 Oracle Database Connection Pooling

```

import java.io.*;
import com.hp.hpl.jena.query.*;
import com.hp.hpl.jena.rdf.model.Model;
import com.hp.hpl.jena.util.FileManager;
import com.hp.hpl.jena.util.iterator.*;
import com.hp.hpl.jena.graph.*;
import com.hp.hpl.jena.update.*;
import oracle.spatial.rdf.client.jena.*;
import oracle.jdbc.pool.*;
import oracle.jdbc.*;

public class Test20

```

```

{
public static void main(String[] args) throws Exception
{
    String szJdbcURL = args[0];
    String szUser    = args[1];
    String szPasswd  = args[2];
    String szModelName = args[3];

    // test with connection properties (taken from some example)
    java.util.Properties prop = new java.util.Properties();
    prop.setProperty("MinLimit", "2"); // the cache size is 2 at least
    prop.setProperty("MaxLimit", "10");
    prop.setProperty("InitialLimit", "2"); // create 2 connections at startup
    prop.setProperty("InactivityTimeout", "1800"); // seconds
    prop.setProperty("AbandonedConnectionTimeout", "900"); // seconds
    prop.setProperty("MaxStatementsLimit", "10");
    prop.setProperty("PropertyCheckInterval", "60"); // seconds

    System.out.println("Creating OraclePool");
    OraclePool op = new OraclePool(szJdbcURL, szUser, szPasswd, prop,
        "OracleSemConnPool");
    System.out.println("Done creating OraclePool");

    // grab an Oracle and do something with it
    System.out.println("Getting an Oracle from OraclePool");
    Oracle oracle = op.getOracle();
    System.out.println("Done");
    System.out.println("Is logical connection:" +
        oracle.getConnection().isLogicalConnection());
    GraphOracleSem g = new GraphOracleSem(oracle, szModelName);
    g.add(Triple.create(Node.createURI("u:John"), Node.createURI("u:parentOf"),
        Node.createURI("u:Mary")));
    g.close();
    // return the Oracle back to the pool
    oracle.dispose();

    // grab another Oracle and do something else
    System.out.println("Getting an Oracle from OraclePool");
    oracle = op.getOracle();
    System.out.println("Done");
    System.out.println("Is logical connection:" +
        oracle.getConnection().isLogicalConnection());
    g = new GraphOracleSem(oracle, szModelName);
    g.add(Triple.create(Node.createURI("u:John"), Node.createURI("u:parentOf"),
        Node.createURI("u:Jack")));
    g.close();

    OracleUtils.dropSemanticModel(oracle, szModelName);

    // return the Oracle back to the pool
    oracle.dispose();
}
}

```

The following are the commands to compile and run [Example 7-19](#), as well as the expected output of the java command.

```

javac -classpath
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-l
og4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar Test20.java
java -classpath

```

```
./:/jena-2.6.3.jar:/sdordfclient.jar:/ojdbc5.jar:/slf4j-api-1.5.8.jar:/slf4j-  
log4j12-1.5.8.jar:/arq-2.8.5.jar:/xercesImpl-2.7.1.jar:/iri-0.8.jar:/icu4j-3.4  
.4.jar:/log4j-1.2.14.jar Test20 jdbc:oracle:thin:@localhost:1521:orcl scott  
<password-for-scott> M1  
Creating OraclePool  
Done creating OraclePool  
Getting an Oracle from OraclePool  
Done  
Is logical connection:true  
Getting an Oracle from OraclePool  
Done  
Is logical connection:true
```

Sesame Adapter for Oracle Database

The Sesame Adapter for Oracle Database (referred to here as the Sesame Adapter) integrates the popular Sesame Java APIs with Oracle Semantic Technologies support. Sesame, created by OpenRDF (<http://www.openrdf.org/>), "is an open source framework for storage, inferencing and querying of RDF data."

This chapter assumes that you are familiar with major concepts explained in [Chapter 1, "Oracle Database Semantic Technologies Overview"](#) and [Chapter 2, "OWL Concepts"](#). It also assumes that you are familiar with the overall capabilities and use of the Sesame Java framework. For information about the Sesame framework, see the Sesame Documentation page at <http://www.openrdf.org/documentation.jsp>.

The Sesame Adapter extends the semantic data management capabilities of Oracle Database Release 11.2 RDF/OWL.

This chapter includes the following major topics:

- [Section 8.1, "Sesame Adapter Overview"](#)
- [Section 8.2, "Setup and Configuration for the Sesame Adapter"](#)
- [Section 8.3, "SEM_MATCH and Sesame Adapter Queries Compared"](#)
- [Section 8.4, "Optimized Handling of SPARQL Queries"](#)
- [Section 8.5, "Recommendations for Best Performance"](#)
- [Section 8.6, "Additions to the SPARQL Syntax to Support Other Features"](#)
- [Section 8.7, "Support for Server-Side APIs"](#)
- [Section 8.8, "Oracle-Specific Extensions to Sesame APIs"](#)
- [Section 8.9, "Using the Sesame Console with the Sesame Adapter"](#)
- [Section 8.10, "Example Queries Using the Sesame Adapter"](#)

8.1 Sesame Adapter Overview

Like the Jena Adapter (described in [Chapter 7](#)), the Sesame Adapter provides a Java-based interface to Oracle semantic data through an open source framework and related tools. However, the Sesame Adapter adds support for **context** to the data:

- Jena statements deal with triples (subject, predicate, object).
- Sesame statements deal with triples and contexts; a Sesame statement is a quad consisting of a triple and a context. For example, with hospital patient data, the context might contain the patient's URI.

The Sesame Adapter provides a Java API for interacting with semantic data stored in Oracle Database. It also provides integration with the following Sesame tools:

- Sesame Server, which provides an HTTP SPARQL endpoint.
- Sesame Console, a command-line tool for creating and managing repositories. The available commands include the following:

```

connect  Connects to a (local or remote) set of repositories
disconnect Disconnects from the current set of repositories
create    Creates a new repository
drop      Drops a repository
open      Opens a repository to work on, takes a repository ID as argument
close     Closes the current repository
show      Displays an overview of various resources
load    Loads a data file into a repository, takes a file path or URL as argument
verify    Verifies the syntax of an RDF data file, takes a file path or URL as
argument
clear     Removes data from a repository
serql     Evaluates the SerQL query, takes a query as argument
sparql  Evaluates the SPARQL query, takes a query as argument
set       Allows various console parameters to be set
exit, quit Exits the console

```

- OpenRDF Workbench, a graphical user interface to the Sesame Server.

The features provided by the Sesame Adapter include:

- Loading (bulk and incremental), exporting, and removing statements, with and without context
- Querying of data, with and without context
- Inferencing, where inferred data is considered during query execution (if `includeInferred=true`), and where inferred triples have a null context
- Managing namespaces

The Sesame Adapter for Oracle Database implements various interfaces of the Sesame Storage and Inference Layer (SAIL) API. For example, the class `OracleSailConnection` is an Oracle implementation of the Sesame `SailConnection` interface, and the class `OracleSailStore` is an Oracle implementation of the Sesame `Sail` interface.

A typical usage flow for the Sesame Adapter might include the excerpt shown in [Example 8-1](#).

Example 8-1 Sample Usage flow for Sesame Adapter

```

String query =
" PREFIX foaf: <http://xmlns.com/foaf/0.1/> "
" PREFIX dc: <http://purl.org/dc/elements/1.1/> "
" select ?s ?p ?o ?name WHERE {?s ?p ?o . OPTIONAL {?o foaf:name ?name .} } ";

SailRepository sr = new SailRepository(
    new OracleSailStore(oracle, modelName,...attachmentForInference));
RepositoryConnection repConn = sr.getConnection();
// Data loading can happen here.
repConn.add(alice, friendOf, bob, context1);

TupleQuery tq = repConn.prepareTupleQuery(QueryLanguage.SPARQL, query);
TupleQueryResult tqr = tq.evaluate();
while(tqr.hasNext()) {

```

```

        psOut.print((tqr.next().toString()));
    };
    tqr.close()
    repConn.close();
    sr.shutdown();

```

8.2 Setup and Configuration for the Sesame Adapter

Setting up and configuring the Sesame Adapter for Oracle Database involves the following actions:

1. [Setting Up the Software Environment](#)
2. [Setting Up the SPARQL Service](#)
3. [Setting Up the Semantic Technologies Environment](#)

8.2.1 Setting Up the Software Environment

To use the Sesame Adapter, you must first ensure that the system environment has the necessary software, including Oracle Database 11g Release 2 with the Spatial and Partitioning options and with Semantic Technologies support enabled, Sesame version 2.3.1, the Sesame Adapter, and JDK 6. You can set up the software environment by performing these actions:

1. Install Oracle Database Release 11.2 Enterprise Edition with the Oracle Spatial and Partitioning Options.
2. Enable the support for Semantic Technologies, as explained in [Section A.1](#).
3. Download the Sesame 2.3.1 onejar library and include it in your classpath, as explained in the "Setting up to use the Sesame libraries" chapter of the *User Guide for Sesame 2.2*. (See <http://www.openrdf.org/doc/sesame2/users/ch04.html>, or a more recent version if available.)
4. Install the Sesame 2.3.1 Server, as explained in the "Server software installation" chapter of the *User Guide for Sesame 2.2*. (See <http://www.openrdf.org/doc/sesame2/users/ch06.html>, or a more recent version if available.)
5. Download the Sesame Adapter (`sesame_adapter_for_release11.2.zip`) from the Oracle Database Semantic Technologies page (http://www.oracle.com/technology/tech/semantic_technologies/), and unzip it into a temporary directory, such as (on a Linux system) `/tmp/sesame_adapter`. (If this temporary directory does not already exist, create it before the unzip operation.)

The Sesame Adapter directories and files have the following structure:

```

examples/
  examples/Example1.java
  examples/Example2.java
  .
  .
  .
lib/
  lib/sdordfsesame.jar
web/
  web/web.xml
javadoc/

```

```
javadoc/javadoc.zip
```

6. Copy `ojdbc5.jar` into `<Sesame_DIR>/lib` (Linux) or `<Sesame_DIR>\lib` (Windows). (`ojdbc5.jar` is in `$ORACLE_HOME/jdbc/lib` or `%ORACLE_HOME%\jdbc\lib`.)
7. Copy `sdordf.jar` into `<Sesame_DIR>/lib` (Linux) or `<Sesame_DIR>\lib` (Windows). (`sdordf.jar` is in `$ORACLE_HOME/md/jlib` or `%ORACLE_HOME%\md\jlib`.)
8. If JDK 6 is not already installed, install it.
9. If the `JAVA_HOME` environment variable does not already refer to the JDK 6 installation, define it accordingly. For example:


```
setenv JAVA_HOME /usr/local/packages/jdk16/
```
10. If the SPARQL service to support the SPARQL protocol is not set up, set it up as explained in [Section 8.2.2](#).

After setting up the software environment, ensure that your Semantic Technologies environment can enable you to use the Sesame Adapter to perform queries, as explained in [Section 8.2.3](#).

8.2.2 Setting Up the SPARQL Service

Setting up a SPARQL endpoint using the Sesame Adapter involves downloading the Sesame Server, with which client applications can communicate over HTTP protocol. The Sesame Server (and OpenRDF Workbench) is bundled with the Sesame 2.3.1 release package. This section explains how to set up a SPARQL service using a servlet deployed in WebLogic Server. The number and complexity of the steps reflect the fact that Oracle is not permitted to bundle all the dependent third-party libraries in a `.war` or `.ear` file.

1. Download and Install Oracle WebLogic Server 11g Release 1 (10.3.1). For details, see <http://www.oracle.com/technology/products/weblogic/>.
2. Ensure that you have Java 6 installed, because it is required by Sesame.
3. Download the Sesame 2.3.1 release package (in `.zip` format) from <http://sourceforge.net/projects/sesame/files/Sesame%20/>.
4. Unpack the `.zip` file into a temporary directory. For example:

```
mkdir /tmp/sesame
cp openrdf-sesame-2.3.1-sdk.zip /tmp/sesame/
cd /tmp/sesame
unzip openrdf-sesame-2.3.1-sdk.zip
```

5. Ensure that you have downloaded and unzipped the Sesame Adapter for Oracle Database, as explained in [Section 8.2.1](#).
6. Create a directory named `openrdf-sesame.war` at the same level as the `Sesame_adapter` directory, and go to it. For example:

```
/tmp/openrdf-sesame.war
cd /tmp/openrdf-sesame.war
```

7. Unzip necessary files into the directory created in the preceding step:

```
cd /tmp/openrdf-sesame.war
unzip /tmp/sesame/openrdf-sesame-2.3.1/war/openrdf-sesame.war
```

8. Copy necessary files, as follows. (Assume that ORACLE_HOME points to the home directory of a Release 11.2 Oracle Database.)

```
cp /tmp/Sesame_adapter/web/web.xml /tmp/openrdf-sesame.war/WEB-INF/web.xml
cp /tmp/Sesame_adapter/lib/*.jar /tmp/openrdf-sesame.war/WEB-INF/lib
cp $ORACLE_HOME/rd/jlib/sdordf.jar /tmp/openrdf-sesame.war/WEB-INF/lib
cp $ORACLE_HOME/jdbc/lib/ojdbc5.jar /tmp/openrdf-sesame.war/WEB-INF/lib
```

Note that in the last command, you can specify `ojdbc6.jar` instead of `ojdbc5.jar`.

9. Using the WebLogic Server Administration console, create a J2EE data source named *OracleSemDS*. During the data source creation, you can specify a user and password for the database schema that contains the relevant semantic data against which SPARQL queries are to be executed.

If you need help in creating this data source, see [Section 8.2.2.1, "Creating the Required Data Source Using WebLogic Server"](#).

10. Go to the `autodeploy` directory of WebLogic Server and copy files, as follows. (For information about auto-deploying applications in development domains, see: http://download.oracle.com/docs/cd/E11035_01/wls100/deployment/autodeploy.html)

```
cd <domain_name>/autodeploy
cp -rf /tmp/openrdf-sesame.war <domain_name>/autodeploy
```

In the preceding example, `<domain_name>` is the name of a WebLogic Server domain.

Note that while you can run a WebLogic Server domain in two different modes, development and production, only development mode allows you use the auto-deployment feature.

11. Check the files and the directory structure, as in the following example:

```
autodeploy/% ls -lR ./openrdf-sesame.war/
```

```
openrdf-sesame.war/:
favicon.ico
favicon.png
images
META-INF
styles
WEB-INF

openrdf-sesame.war/images:
DEBUG.png
ERROR.png
INFO.png
logo.png
productgroup.png
transparent.png
WARN.png

openrdf-sesame.war/META-INF:
MANIFEST.MF
maven

openrdf-sesame.war/META-INF/maven:
info.aduna.appbase
org.openrdf.sesame
```

```
openrdf-sesame.war/META-INF/maven/info.aduna.appbase:
aduna-appbase-webapp-system

openrdf-sesame.war/META-INF/maven/info.aduna.appbase/aduna-appbase-webapp-system:
pom.properties
pom.xml

openrdf-sesame.war/META-INF/maven/org.openrdf.sesame:
sesame-http-server

openrdf-sesame.war/META-INF/maven/org.openrdf.sesame/sesame-http-server:
pom.properties
pom.xml

openrdf-sesame.war/styles:
basic
default
msie-png-alpha.css
msie-png-alpha.png
w3-html40-recommended.css

openrdf-sesame.war/styles/basic:
all.css

openrdf-sesame.war/styles/default:
images
msie-minheight.css
print.css
screen.css

openrdf-sesame.war/styles/default/images:
bg_body.png
bg_header.png
bg_html.png
hr_menu.png

openrdf-sesame.war/WEB-INF:
aduna-webapp-servlet.xml
aduna-webapp-system-servlet.xml
classes
includes
lib
openrdf-http-server-servlet.xml
sample-web.xml
taglibs
tags
urlrewrite.xml
views
web.xml

openrdf-sesame.war/WEB-INF/classes:
logback.xml

openrdf-sesame.war/WEB-INF/includes:
components
stylesheets.html.jspf
taglibs.jspf
```

```
openrdf-sesame.war/WEB-INF/includes/components:  
bodyStart.html.jspf  
bodyStop.html.jspf  
ContentHeader.html.jspf  
Footer.html.jspf  
Header.html.jspf  
head.html.jspf  
htmlStart.html.jspf  
htmlStop.html.jspf  
logfilterform.html.jspf  
logpaginationfooter.html.jspf  
logpaginationheader.html.jspf  
Message.html.jspf  
Navigation.html.jspf  
page.html.jspf  
tabs.html.jspf
```

```
openrdf-sesame.war/WEB-INF/lib:  
activation-1.1.jar  
aduna-appbase-core-3.9.0.jar  
aduna-appbase-logging-api-3.9.0.jar  
aduna-appbase-logging-file-3.9.0.jar  
aduna-appbase-webapp-base-core-3.9.0.jar  
aduna-appbase-webapp-system-core-3.9.0.jar  
aduna-commons-collections-2.7.0.jar  
aduna-commons-concurrent-2.6.0.jar  
aduna-commons-i18n-1.3.0.jar  
aduna-commons-io-2.8.0.jar  
aduna-commons-iteration-2.7.0.jar  
aduna-commons-lang-2.8.0.jar  
aduna-commons-net-2.6.0.jar  
aduna-commons-platform-info-2.8.0.jar  
aduna-commons-text-2.6.0.jar  
aduna-commons-webapp-core-2.8.0.jar  
aduna-commons-xml-2.6.0.jar  
aopalliance-1.0.jar  
asm-1.5.3.jar  
cglib-2.1_3.jar  
commons-codec-1.3.jar  
commons-dbcp-1.2.2.jar  
commons-httpclient-3.1.jar  
commons-pool-1.3.jar  
jcl-over-slf4j-1.5.10.jar  
jstl-1.1.2.jar  
logback-classic-0.9.18.jar  
logback-core-0.9.18.jar  
ojdbc5.jar  
sdordf.jar  
sdordfsesame.jar  
sesame-http-client-2.3.1.jar  
sesame-http-protocol-2.3.1.jar  
sesame-http-server-2.3.1.jar  
sesame-http-server-spring-2.3.1.jar  
sesame-model-2.3.1.jar  
sesame-query-2.3.1.jar  
sesame-queryalgebra-evaluation-2.3.1.jar  
sesame-queryalgebra-model-2.3.1.jar  
sesame-queryparser-api-2.3.1.jar  
sesame-queryparser-serql-2.3.1.jar  
sesame-queryparser-sparql-2.3.1.jar
```

```
sesame-queryresultio-api-2.3.1.jar
sesame-queryresultio-binary-2.3.1.jar
sesame-queryresultio-sparqljson-2.3.1.jar
sesame-queryresultio-sparqlxml-2.3.1.jar
sesame-queryresultio-text-2.3.1.jar
sesame-repository-api-2.3.1.jar
sesame-repository-contextaware-2.3.1.jar
sesame-repository-dataset-2.3.1.jar
sesame-repository-event-2.3.1.jar
sesame-repository-http-2.3.1.jar
sesame-repository-manager-2.3.1.jar
sesame-repository-sail-2.3.1.jar
sesame-rio-api-2.3.1.jar
sesame-rio-n3-2.3.1.jar
sesame-rio-ntriples-2.3.1.jar
sesame-rio-rdfxml-2.3.1.jar
sesame-rio-trig-2.3.1.jar
sesame-rio-trix-2.3.1.jar
sesame-rio-turtle-2.3.1.jar
sesame-runtime-2.3.1.jar
sesame-sail-api-2.3.1.jar
sesame-sail-inferencer-2.3.1.jar
sesame-sail-memory-2.3.1.jar
sesame-sail-nativerdf-2.3.1.jar
sesame-sail-rdbms-2.3.1.jar
slf4j-api-1.5.10.jar
spring-aop-2.5.6.jar
spring-beans-2.5.6.jar
spring-context-2.5.6.jar
spring-context-support-2.5.6.jar
spring-core-2.5.6.jar
spring-web-2.5.6.jar
spring-webmvc-2.5.6.jar
standard-1.1.2.jar
urlrewritefilter-3.0.4.jar

openrdf-sesame.war/WEB-INF/taglibs:
navigation.tld

openrdf-sesame.war/WEB-INF/tags:
errors.tag

openrdf-sesame.war/WEB-INF/views:
home
overview.jsp
system

openrdf-sesame.war/WEB-INF/views/home:
overview.jsp

openrdf-sesame.war/WEB-INF/views/system:
info
logging
overview.jsp

openrdf-sesame.war/WEB-INF/views/system/info:
debug.jsp
overview.jsp

openrdf-sesame.war/WEB-INF/views/system/logging:
```

```
overview.jsp
```

12. Start or restart WebLogic Server.
13. Verify your deployment by using your Web browser to connect to a URL in the following format (assume that the Web application is deployed at port 7001):

```
http://<hostname>:7001/openrdf-sesame/querymgt?abortqid=0
```

You should see an XML response, which indicates a successful deployment of the Sesame Server with the Sesame Adapter query management servlet.

You can also install the OpenRDF Workbench, which is a graphical user interface (GUI) for communicating with the Sesame Server. To deploy the OpenRDF Workbench into the Oracle WebLogic Server, you must have performed at least the first 7 steps in the preceding instructions for setting up the SPARQL endpoint (explained earlier in this section); then, follow these steps:

1. Go to the `autodeploy` directory of WebLogic Server and copy files, as follows. (For information about auto-deploying applications in development domains, see: http://download.oracle.com/docs/cd/E11035_01/wls100/deployment/autodeploy.html)

```
cd <domain_name>/autodeploy
cp -rf /tmp/openrdf-workbench.war <domain_name>/autodeploy
```

In the preceding example, `<domain_name>` is the name of a WebLogic Server domain.

2. Check the files and the directory structure, as in the following example:

```
autodeploy/% ls -lR ./openrdf-workbench.war/
openrdf-workbench.war/:
```

```
favicon.ico
favicon.png
images
locale
META-INF
scripts
styles
transformations
WEB-INF
```

```
openrdf-workbench.war/images:
affirmative.png
edit.png
logo.png
negative.png
productgroup.png
server_network.png
server.png
view.png
```

```
openrdf-workbench.war/locale:
messages.xsl
```

```
openrdf-workbench.war/META-INF:
MANIFEST.MF
maven
```

```
openrdf-workbench.war/META-INF/maven:
org.openrdf.sesame
```

```
openrdf-workbench.war/META-INF/maven/org.openrdf.sesame:  
sesame-http-workbench  
  
openrdf-workbench.war/META-INF/maven/org.openrdf.sesame/sesame-http-workbench:  
pom.properties  
pom.xml  
  
openrdf-workbench.war/scripts:  
cookies.html  
  
openrdf-workbench.war/styles:  
basic  
default  
msie-png-alpha.css  
msie-png-alpha.png  
w3-html40-recommended.css  
  
openrdf-workbench.war/styles/basic:  
all.css  
  
openrdf-workbench.war/styles/default:  
images  
msie-minheight.css  
print.css  
screen.css  
  
openrdf-workbench.war/styles/default/images:  
bg_body.png  
bg_header.png  
bg_html.png  
hr_menu.png  
  
openrdf-workbench.war/transformations:  
add.xsl  
boolean.xsl  
clear.xsl  
contexts.xsl  
create-memory-rdfs-dt.xsl  
create-memory-rdfs.xsl  
create-memory.xsl  
create-mysql.xsl  
create-native-rdfs-dt.xsl  
create-native-rdfs.xsl  
create-native.xsl  
create-pgsql.xsl  
create-remote.xsl  
create.xsl  
delete.xsl  
explore.xsl  
export.xsl  
graph.xsl  
information.xsl  
list.xsl  
namespaces.xsl  
query.xsl  
remove.xsl  
repositories.xsl  
server.xsl  
summary.xsl
```

```
table.xsl
template.xsl
tuple.xsl
types.xsl
url-encode.xsl

openrdf-workbench.war/WEB-INF:
classes
lib
web.xml

openrdf-workbench.war/WEB-INF/classes:
org

openrdf-workbench.war/WEB-INF/classes/org:
openrdf

openrdf-workbench.war/WEB-INF/classes/org/openrdf:
workbench

openrdf-workbench.war/WEB-INF/classes/org/openrdf/workbench:
base
commands
exceptions
proxy
RepositoryServlet.class
util

openrdf-workbench.war/WEB-INF/classes/org/openrdf/workbench/base:
BaseRepositoryServlet.class
BaseServlet.class
TransformationServlet.class
TupleServlet.class

openrdf-workbench.war/WEB-INF/classes/org/openrdf/workbench/commands:
AddServlet.class
ClearServlet.class
ContextsServlet.class
CreateServlet.class
DeleteServlet.class
ExploreServlet.class
ExportServlet.class
InformationServlet.class
InfoServlet.class
NamespacesServlet.class
QueryServlet.class
RemoveServlet.class
RepositoriesServlet.class
SummaryServlet.class
TypesServlet.class

openrdf-workbench.war/WEB-INF/classes/org/openrdf/workbench/exceptions:
BadRequestException.class
MissingInitParameterException.class

openrdf-workbench.war/WEB-INF/classes/org/openrdf/workbench/proxy:
CookieCacheControlFilter$CacheAwareRequest.class
CookieCacheControlFilter$CacheAwareResponse.class
CookieCacheControlFilter.class
ProxyRepositoryServlet.class
```

```
RedirectFilter.class
WorkbenchGateway.class
WorkbenchServlet.class

openrdf-workbench.war/WEB-INF/classes/org/openrdf/workbench/util:
BasicServletConfig.class
ConfigTemplate.class
DynamicHttpRequest.class
TupleResultBuilder.class
WorkbenchRequest.class

openrdf-workbench.war/WEB-INF/lib:
aduna-appbase-core-3.9.0.jar
aduna-appbase-logging-api-3.9.0.jar
aduna-appbase-logging-file-3.9.0.jar
aduna-commons-collections-2.7.0.jar
aduna-commons-concurrent-2.6.0.jar
aduna-commons-il8n-1.3.0.jar
aduna-commons-io-2.8.0.jar
aduna-commons-iteration-2.7.0.jar
aduna-commons-lang-2.8.0.jar
aduna-commons-net-2.6.0.jar
aduna-commons-platform-info-2.8.0.jar
aduna-commons-text-2.6.0.jar
aduna-commons-xml-2.6.0.jar
commons-cli-1.1.jar
commons-codec-1.3.jar
commons-logging-1.2.2.jar
commons-fileupload-1.2.1.jar
commons-httpclient-3.1.jar
commons-io-1.3.2.jar
commons-pool-1.3.jar
jcl-over-slf4j-1.5.10.jar
sesame-console-2.3.1.jar
sesame-http-client-2.3.1.jar
sesame-http-protocol-2.3.1.jar
sesame-model-2.3.1.jar
sesame-query-2.3.1.jar
sesame-queryalgebra-evaluation-2.3.1.jar
sesame-queryalgebra-model-2.3.1.jar
sesame-queryparser-api-2.3.1.jar
sesame-queryparser-serql-2.3.1.jar
sesame-queryparser-sparql-2.3.1.jar
sesame-queryresultio-api-2.3.1.jar
sesame-queryresultio-binary-2.3.1.jar
sesame-queryresultio-sparqljson-2.3.1.jar
sesame-queryresultio-sparqlxml-2.3.1.jar
sesame-queryresultio-text-2.3.1.jar
sesame-repository-api-2.3.1.jar
sesame-repository-contextaware-2.3.1.jar
sesame-repository-dataset-2.3.1.jar
sesame-repository-event-2.3.1.jar
sesame-repository-http-2.3.1.jar
sesame-repository-manager-2.3.1.jar
sesame-repository-sail-2.3.1.jar
sesame-rio-api-2.3.1.jar
sesame-rio-n3-2.3.1.jar
sesame-rio-ntriples-2.3.1.jar
sesame-rio-rdfxml-2.3.1.jar
sesame-rio-trig-2.3.1.jar
```

```

sesame-rio-trix-2.3.1.jar
sesame-rio-turtle-2.3.1.jar
sesame-runtime-2.3.1.jar
sesame-sail-api-2.3.1.jar
sesame-sail-inferencer-2.3.1.jar
sesame-sail-memory-2.3.1.jar
sesame-sail-nativerdf-2.3.1.jar
sesame-sail-rdbms-2.3.1.jar
slf4j-api-1.5.10.jar
slf4j-jdk14-1.5.10.jar

```

3. Start or restart WebLogic Server.
4. Verify your deployment by using your Web browser to connect to a URL in the following format (assume that the Web application is deployed at port 7001):
`http://<hostname>:7001/openrdf-workbench`
 You should see a Web page with the OpenRDF Workbench logo. Click the **Repositories** link on the left to see a list of repositories.

8.2.2.1 Creating the Required Data Source Using WebLogic Server

If you need help creating the required J2EE data source using the WebLogic Server admin console, you can follow these steps:

1. Login to: `http://<hostname>:7001/console`
2. In the Domain Structure panel, click **Services**.
3. Click **JDBC**
4. Click **Data Services**.
5. In the Summary of JDBC Data Sources panel, click **New** under the Data Sources table.
6. In the Create a New JDBC Data Source panel, enter or select the following values.
Name: OracleSemDS
JNDI Name: OracleSemDS
Database Type: Oracle
Database Driver: Oracle's Driver (Thin) Versions:
`9.0.1,9.2.0,10,11`
7. Click **Next** twice.
8. In the Connection Properties panel, enter the appropriate values for the **Database Name**, **Host Name**, **Port**, **Database User Name** (schema that contains semantic data), **Password** fields.
9. Click **Next**.
10. Select (check) the target server or servers to which you want to deploy this OracleSemDS data source.
11. Click **Finish**.

You should see a message that all changes have been activated and no restart is necessary.

8.2.2.2 Configuring the SPARQL Service

You can use the `OracleSailStore` API and other relevant APIs to create semantic models, load data (incrementally or in bulk), and perform logical inference.

After the semantic models are in the Oracle database, you can use the Sesame Console (described in [Section 8.9](#)) to connect to the Sesame Server and create an Oracle semantic model-backed repository. For example, you might create a repository with the repository ID `myOracleRepos` that uses a semantic model named `LUBM` and the `OWLPRIME` rulebase.

This newly created repository provides a new service endpoint on the Sesame Server.

8.2.2.3 Terminating Long-Running SPARQL Queries

Because some applications need to be able to terminate long-running SPARQL queries, an abort framework has been introduced with the Sesame Adapter and the Sesame Server setup. Basically, for queries that may take a long time to run, you must stamp each with a unique query ID (`qid`) value.

For example, the following SPARQL query selects out the subject of all triples. A query ID (`qid`) is set so that this query can be terminated upon request.

```
PREFIX ORACLE_SEM_FS_NS: <http://example.com/semtech#qid=8761>
SELECT ?subject WHERE {?subject ?property ?object }
```

The `qid` attribute value is of long integer type. You can choose a value for the `qid` for a particular query based on your own application needs.

To terminate a SPARQL query that has been submitted with a `qid` value, applications can send an abort request to a servlet in the following format and specify a matching QID value

```
http://<hostname>:7001/openrdf-sesame/querymgmt?abortqid=8761
```

8.2.3 Setting Up the Semantic Technologies Environment

To use the Sesame Adapter to perform queries, you can connect as any user (with suitable privileges) and use any models in the semantic network. If your Semantic Technologies environment already meets the requirements, you can go directly to compiling and running Java code that uses the Sesame Adapter. If your Semantic Technologies environment is not yet set up to be able to use the Sesame Adapter, you can perform actions similar to the following example steps:

1. Connect as SYS with the SYSDBA role:

```
sqlplus sys/<password-for-sys> as sysdba
```

2. Create a tablespace for the system tables. For example:

```
CREATE TABLESPACE rdf_users datafile 'rdf_users01.dbf'
      size 128M reuse autoextend on next 64M
      maxsize unlimited segment space management auto;
```

3. Create the semantic network. For example:

```
EXECUTE sem_apis.create_sem_network('RDF_USERS');
```

4. Create a database user (for connecting to the database to use the semantic network and the Sesame Adapter). For example:

```
CREATE USER rdfusr IDENTIFIED BY <password-for-udfusr>
      DEFAULT TABLESPACE rdf_users;
```

- Grant the necessary privileges to this database user. For example:

```
GRANT connect, resource TO rdfusr;
```

- To use the Sesame Adapter with your own semantic data, perform the appropriate steps to store data, create a model, and create database indexes, as explained in [Section 1.9, "Quick Start for Using Semantic Data"](#). Then perform queries by compiling and running Java code; see [Section 8.10](#) for information about example queries.

To use the Sesame Adapter with supplied example data, see [Section 8.10](#).

8.3 SEM_MATCH and Sesame Adapter Queries Compared

There are two ways to query semantic data stored in Oracle Database: SEM_MATCH-based SQL statements and SPARQL queries through the Sesame Adapter. Queries using each approach are similar in appearance, but there are important behavioral differences. To ensure consistent application behavior, you must understand the differences and use care when dealing with query results coming from SEM_MATCH queries and SPARQL queries.

The following simple examples show the two approaches.

Query 1 (SEM_MATCH-based)

```
select s, p, o
  from table(sem_match('{?s ?p ?o}', sem_models('Test_Model'), ...))
```

Query 2 (SPARQL query through the Sesame Adapter)

```
select ?s ?p ?o
where {?s ?p ?o}
```

These two queries perform the same kind of functions; however, there are some important differences. Query 1 (SEM_MATCH-based):

- Reads all triples out of `Test_Model`.
- Does not differentiate among URI, bNode, plain literals, and typed literals, and it does not handle long literals.
- Does not unescape certain characters (such as `'\n'`).

Query 2 (SPARQL query executed through the Sesame Adapter) also reads all triples out of `Test_Model` (assume it executed a call to `ModelOracleSem` referring to the same underlying `Test_Model`). However, Query 2:

- Reads out additional columns (as opposed to just the `s`, `p`, and `o` columns with the SEM_MATCH table function), to differentiate URI, bNodes, plain literals, typed literals, and long literals. This is to ensure proper creation of Sesame Node objects.
- Unescapes those characters that are escaped when stored in Oracle Database

Blank node handling is another difference between the two approaches:

- In a SEM_MATCH-based query, blank nodes are always treated as constants.
- In a SPARQL query, a blank node that *is not* wrapped inside `<` and `>` is treated as a variable when the query is executed through the Sesame Adapter. This matches the SPARQL standard semantics. However, a blank node that *is* wrapped inside `<` and `>` is treated as a constant when the query is executed, and the Sesame Adapter

adds a proper prefix to the blank node label as required by the underlying data modeling.

The maximum length for the name of a semantic model created using the Sesame Adapter API is 22 characters.

8.4 Optimized Handling of SPARQL Queries

This section describes some performance-related features of the Sesame Adapter that can enhance SPARQL query processing. These features are performed automatically by default.

8.4.1 Compilation of SPARQL Queries to a Single SEM_MATCH Call

SPARQL queries involving `DISTINCT`, `OPTIONAL`, `GRAPH`, `FILTER`, `UNION`, `ORDER BY`, and `LIMIT` are converted to a single SQL query based on the `SEM_MATCH` table function. For SPARQL `ASK`, `DESCRIBE`, and `CONSTRUCT` queries, the Sesame Adapter employs additional query transformation logic and mid-tier processing.

If the SQL query based on `SEM_MATCH` fails to execute, the Sesame Adapter employs the Sesame evaluation strategy to execute the query.

8.5 Recommendations for Best Performance

The following are recommendations for enhancing the performance of queries using the Sesame Adapter:

- Put only relevant triple patterns in the `GRAPH` clause of a SPARQL query, to reduce the number of additional joins with the application table. (For an explanation, see [Section 8.5.1](#).)
- For the triple patterns inside `GRAPH` clause of a named graph query, do not use variables with null bindings. A null binding will not match any row in the join with the relevant application table, and therefore this binding will be dropped.
- Because of the preceding item, do not put an `OPTIONAL` clause in a `GRAPH` clause, or a `GRAPH` clause in an `OPTIONAL` clause.
- Do not use blank nodes for the `CONTEXT` column in the application table (see [Section 8.5.1](#)), because blank nodes in named graphs from two different semantic models will be treated as the same resource if they have the same label. This is not the case for blank nodes in triples (they are stored separately if coming from different models).

8.5.1 Statement Storage and Implications for Sesame Adapter Queries

Because the `MDSYS.SEMM_model-name` view (described in [Table 1–2](#) in [Section 1.3.1](#)) does not have columns for the graph name or context for each model, these two pieces of information are not stored inside that Oracle semantic model. Rather, this information is kept in the `CONTEXT` column in the user's application table.

When an `OracleSailStore` object is created for the first time using a model name that does not exist in the semantic network, a new application table is created automatically, and it includes these columns:

- `TRIPLE`, of type `SDO_RDF_TRIPLE_S`
- `CONTEXT`, of type `VARCHAR2`

A semantic model with the specified model name is then created. To enhance the performance of named graph queries and statement-oriented operations, a default index is created on the application table, and this index covers the CONTEXT column (leading column) as well as the three numeric ID attributes for triple's subject, predicate, and object field of the TRIPLE column.

When a SPARQL query runs against a semantic model, if the query does not use a named graph (that is, does not contain a GRAPH clause), the generated SQL statement will not use the model's application table. However, if the query has a GRAPH clause, the generated SQL statement will join a SEM_MATCH-based subquery with the model's application table to scope the results down to relevant contexts or named graphs. The number of joins with the application table depends on how many triple patterns are in the GRAPH clause, and therefore it is best to put only relevant triple patterns in the GRAPH clause, to reduce the number of additional joins with the application table.

8.6 Additions to the SPARQL Syntax to Support Other Features

The Sesame Adapter allows you to pass in hints and additional query options. It implements these capabilities by overloading the SPARQL namespace prefix syntax by using Oracle-specific namespaces that contain query options. The namespaces are in the form `PREFIX ORACLE_SEM_XX_NS`, where `xx` indicates the type of feature (such as HT for hint or AP for additional predicate)

8.6.1 SQL Hints

SQL hints can be passed to a SEM_MATCH query including a line in the following form:

```
PREFIX ORACLE_SEM_HT_NS: <http://oracle.com/semtech#hint>
```

Where *hint* can be any hint supported by SEM_MATCH. For example:

```
PREFIX ORACLE_SEM_HT_NS: <http://oracle.com/semtech#leading(t0,t1)>
SELECT ?book ?title ?isbn
WHERE { ?book <http://title> ?title. ?book <http://ISBN> ?isbn }
```

In this example, `t0`, `t1` refers to the first and second patterns in the query.

Note the slight difference in specifying hints when compared to SEM_MATCH. Due to restrictions of namespace value syntax, a comma (,) must be used to separate `t0` and `t1` (or other hint components) instead of a space.

For more information about using SQL hints, see [Section 1.6, "Using the SEM_MATCH Table Function to Query Semantic Data"](#), specifically the material about the HINTO keyword in the `options` attribute.

8.6.2 Additional WHERE Clause Predicates

The SEM_MATCH `filter` attribute can specify additional selection criteria as a string in the form of a WHERE clause without the WHERE keyword. Additional WHERE clause predicates can be passed to a SEM_MATCH query including a line in the following form:

```
PREFIX ORACLE_SEM_AP_NS: <http://oracle.com/semtech#pred>
```

Where *pred* reflects the WHERE clause content to be appended to the query. For example:

```

PREFIX rdfs: <http://www.w3.org/2000/01/rdf-schema#>
PREFIX ORACLE_SEM_AP_NS: <http://www.oracle.com/semtech#label$RDFLANG='fr'>
SELECT DISTINCT ?inst ?label
  WHERE { ?inst a <http://someClass>. ?inst rdfs:label ?label . }
  ORDER BY (?label) LIMIT 20

```

In this example, a restriction is added to the query that the language type of the label variable must be 'fr'.

8.6.3 Additional Query Options

Additional query options can be passed to a SEM_MATCH query including a line in the following form:

```
PREFIX ORACLE_SEM_FS_NS: <http://oracle.com/semtech#option>
```

Where *option* reflects a query option (or multiple query options delimited by commas) to be appended to the query. For example:

```

PREFIX ORACLE_SEM_FS_NS:
<http://oracle.com/semtech#timeout=3,dop=4,INF_ONLY,ORDERED,ALLOW_DUP=T>
SELECT * WHERE {?subject ?property ?object }

```

The following query options are supported:

- ALLOW_DUP=t chooses a faster way to query multiple semantic models, although duplicate results may occur.
- DOP=n specifies the degree of parallelism (*n*) for the query. With multi-core or multi-CPU processors, experimenting with different DOP values (such as 4 or 8) may improve performance.
- INF_ONLY causes only the inferred model to be queried. (For this option, you should also specify the includeInferred=true option for the query.)
- ORDERED is translated to a LEADING SQL hint for the query triple pattern joins, while performing the necessary RDF_VALUE\$ joins last.
- QID=n specifies a query ID number; this feature can be used to cancel the query if it is not responding.
- REWRITE=F disables ODCI_Table_Rewrite for the SEM_MATCH table function.
- SKIP_CLOB=T causes CLOB values not to be returned for the query.
- TIMEOUT=n (query timeout) specifies the number of seconds (*n*) that the query will run until it is terminated.
- USE_BIND_VAR(*n*) specifies that a bind variable be used during query parsing for the *n*th constant in triple patterns. (Do not apply this feature to constants inside an OPTIONAL clause.)

8.7 Support for Server-Side APIs

This section describes some of the Oracle Database Semantic Technologies features that are exposed by the Sesame Adapter. For comprehensive documentation of the API calls that support the available features, see the Sesame Adapter reference information (Javadoc). For additional information about the server-side features exposed by the Sesame Adapter, see the relevant chapters in this manual.

8.7.1 Virtual Models Support

Virtual models (explained in [Section 1.3.8](#)) are specified in the `OracleSailStore` constructor, and they are handled transparently. If a virtual model exists for the model-rulebase combination, it is used in query answering; if such a virtual model does not exist, it is created in the database.

Note: Virtual model support through the Sesame Adapter is available only with Oracle Database Release 11.2 or later.

The following example reuses an existing virtual model.

```
public void vm(String jdbcUrl,
              String user,
              String password,
              String model,
              PrintStream psOut)
{
    String m1 = "TEST_1";
    String m2 = "TEST_2";
    OraclePool op = new OraclePool(
        OraclePool.getOracleDataSource(jdbcUrl, user, password));

    // create the attachment semantic model in case it doesn't exist
    // (constructor handles it)
    OracleSailStore store = new OracleSailStore(op, m1);
    store.shutdown();

    store= new OracleSailStore(op, m2);
    store.shutdown();

    String vmName = "VM_" + m1;

    // create a virtual model with name vmName that will be used in the
    // OracleSailStore
    Oracle oracle = op.getOracle();
    oracle.executeCall(
        "begin sem_apis.create_virtual_model(?,sem_models(?,?), null); end;",
        vmName, m1, m2);
    op.returnOracle(oracle);

    String[] modelNames = {m2};
    String[] rulebaseNames = {};

    Attachment attachment = Attachment.createInstance(modelNames,
        rulebaseNames);

    store = new OracleSailStore(op, m1, attachment, vmName);

    OracleSailConnection conn = store.getConnection();
    conn.clear();
    conn.addStatement(
        store.getValueFactory().createURI("http://a1"),
        store.getValueFactory().createURI("http://p1"),
        store.getValueFactory().createURI("http://b1"));

    CloseableIteration res = conn.getStatements(null, null, null, false);
    while (res.hasNext()) {
        Statement stmt = (Statement) res.next();
    }
}
```

```
        System.out.println(stmt);
    }
    conn.close();
    store.shutdown();
}
```

You can also use the `OracleSailStore` constructor to create a virtual model, as in the following example:

```
OracleSailStore store = new OracleSailStore(oracle, modelName, attachment, true);
```

In this example, the fourth parameter (`true`) specifies that a virtual model needs to be created for the specified `modelName` and `attachment`.

8.7.2 Connection Pooling Support

Oracle Database Connection Pooling is provided through the Sesame Adapter `OraclePool` class. Usually, `OraclePool` is initialized with a `DataSource`, using the `OraclePool (DataSource ods)` constructor. In this case, `OraclePool` acts as an extended wrapper for the `DataSource`, while using the connection pooling capabilities of the data source. When you create an `OracleSailStore` object, it is sufficient to specify the `OraclePool` object in the `store` constructor; the database connections will then be managed automatically by the Sesame Adapter.

If you need to retrieve Oracle connection objects (which are essentially database connection wrappers) explicitly, you can invoke the `OraclePool.getOracle` method. After finishing with the connection, you can invoke the `OraclePool.returnOracle` method to return the object to the connection pool.

`OraclePool` can also be initialized with an `OracleConnection` object. In this case, only a single database connection is used when referring to this `OraclePool`; and because multiple Sesame `SailConnection` objects will use the same database connection, you must be aware that "dirty" reads across different `SailConnection` objects are possible.

More information about using `OraclePool` can be found in the Sesame Adapter API reference information (Javadoc).

The following example sets up an `OracleSailStore` object using the `OraclePool` class, with two initial connections.

```
public void op(String jdbcUrl,
              String user,
              String password,
              String model,
              PrintStream psOut)
    throws Exception
{
    // test with connection properties
    java.util.Properties prop = new java.util.Properties();
    prop.setProperty("MinLimit", "2"); // the cache size is 2 at least
    prop.setProperty("MaxLimit", "10");
    prop.setProperty("InitialLimit", "2"); // create 2 connections at startup
    prop.setProperty("InactivityTimeout", "1800"); // seconds
    prop.setProperty("AbandonedConnectionTimeout", "900"); // seconds
    prop.setProperty("MaxStatementsLimit", "10");
    prop.setProperty("PropertyCheckInterval", "60"); // seconds

    System.out.println("Creating Data Source");
    OracleDataSource ods =
OraclePool.getOracleDataSource(jdbcUrl, user, password,
```

```

        prop, "OracleSemConnPool");
System.out.println("Done creating Data Source");

OraclePool op = new OraclePool(ods);

// create an OracleSailStore with the OraclePool
OracleSailStore store = new OracleSailStore(op, model);
store.shutdown();
op.close();
ods.close();
}

```

8.7.3 Semantic Model PL/SQL Interfaces

Several semantic PL/SQL subprograms are available through the Sesame Adapter. [Table 8–1](#) lists the subprograms and their corresponding Java class and methods.

Table 8–1 PL/SQL Subprograms and Corresponding Sesame Adapter Java Class and Methods

PL/SQL Subprogram	Corresponding Java Class and Methods
SEM_APIS.DROP_SEM_MODEL	OracleUtils.dropSemanticModel
SEM_APIS.MERGE_MODELS	OracleUtils.mergeModels
SEM_APIS.SWAP_NAMES	OracleUtils.swapNames
SEM_APIS.REMOVE_DUPLICATES	OracleUtils.removeDuplicates
SEM_APIS.RENAME_MODEL	OracleUtils.renameModels

For information about these PL/SQL utility subprograms, see the reference information in [Chapter 9](#). For information about the corresponding Java class and methods, see the Sesame Adapter API Reference documentation (Javadoc).

8.7.4 Inference Options

You can add options to entailment calls by using the `setInferenceOption(String options)` procedure with the `OracleSailConnection` object. The following example enables incremental inference and specifies a parallelism value of 4 when creating an entailment.

```
conn.setInferenceOption("INC=T,DOP=4");
```

For information about inference options, see [Section 2.2](#).

8.8 Oracle-Specific Extensions to Sesame APIs

This section describes the extensions that the Sesame Adapter for Oracle Database provides to the Sesame `SailConnection` and `Sail` APIs.

8.8.1 Statement Uniqueness

In Sesame 2.3.0, statement uniqueness is enforced at the context level: the same triple cannot occur twice in a single context. In the Oracle Sesame Adapter, such uniqueness is enforced through a unique index on the context, predicate, subject, and object. However, in the Sesame Adapter, statement uniqueness is not enabled by default. When constructing an `OracleSailStore` object, the default value for statement

uniqueness is `DONTCARE`, meaning that if such a unique index does not already exist, it will not be created.

You can explicitly enable and disable the requirement for statement uniqueness either through the `OracleSailStore` constructor, or through the `enableUniquenessConstraint` and `disableUniquenessConstraint` methods.

8.8.2 Indexes and Interoperability with the Jena Adapter

Indexes on the application table are critical for good performance when performing DML operations (especially deletes) and named graph queries against an `OracleSailStore` object. When creating a new `OracleSailStore` object, a default CPSO index is created (where C,P,S,O stands for the context, predicate, subject, and object columns).

There are some storage differences between Oracle semantic models created using the Sesame Adapter and the Jena Adapter. For example, the default application table index is different in Jena Adapter. To access data in a Jena Adapter model from the Sesame Adapter (and vice versa), you can use the `OracleUtils.migrateFromJena` and `OracleUtils.migrateToJena` methods. These methods preserve the semantic data while making changes to the underlying storage structures. In particular, all triples along with their context information are preserved when migrating from Sesame Adapter to Jena Adapter and back.

[Example 8-2](#) illustrates migration between models created using the Sesame Adapter and the Jena Adapter:

Example 8-2 Migration Between Jena Adapter and Sesame Adapter Models

```
public void migrate(String jdbcUrl,
                   String user,
                   String password,
                   String model,
                   PrintStream psOut)
    throws Exception
{
    OraclePool oraclePool= new OraclePool(
        OraclePool.getOracleDataSource(jdbcUrl, user, password));

    OracleSailStore store = new OracleSailStore(oraclePool, model);

    OracleSailConnection conn = store.getConnection();
    conn.clear();

    // create a statement and add it to the store
    URI subject =
store.getValueFactory().createURI("http://example.org/foo");
    URI object = store.getValueFactory().createURI("http://example.org/bar");
    URI ngURI = store.getValueFactory().createURI("http://example.org/bar");

    conn.addStatement(subject, RDF.TYPE, object, ngURI);
    conn.commit();

    // convert it to a jena model
OracleUtils.migrateToJena(oraclePool, model);

    Oracle newOra = oraclePool.getOracle();
    oracle.spatial.rdf.client.jena.Oracle ora =
        new oracle.spatial.rdf.client.jena.Oracle(newOra.getConnection());
```

```

GraphOracleSem graph = new GraphOracleSem(ora, model);

// check size of jena graph
System.out.print("GraphOracleSem size:" + graph.getSize());

store.shutdown();

// now convert it back to an Oracle sailstore.
OracleUtils.migrateFromJena(oraclePool, model);
conn = store.getConnection();

// check overall store size
System.out.println("Size of store :" + conn.size());
// check context size, should be 1
System.out.println("Size of context " + ngURI + ":" + conn.size(ngURI));
store.shutdown();
ora.dispose();
oraclePool.returnOracle(newOra);
}

```

8.8.3 Inference

You can perform inference using the `OracleSailConnection.performInference` method. This method builds an entailment for the `OracleSailStore` object, given the models and rulebases that were specified in the attachment when constructing the store.

For information about creating entailments, see [Section 1.3.7, "Entailments \(Rules Indexes\)"](#).

8.8.4 Performing Analysis Operations

It is strongly recommended that you analyze the application table, semantic model, and inferred graph (if it exists) before performing inference and after loading a significant amount of semantic data into the database. Performing the analysis operations causes statistics to be gathered, which will help the Oracle optimizer select efficient execution plans when answering queries.

To gather relevant statistics, you can use the following methods in the `OracleSailConnection` and `OracleSailStore` classes:

- `OracleSailConnection.analyze`
- `OracleSailConnection.analyzeApplicationTable`
- `OracleSailConnection.analyzeInferredGraph`

For information about these methods, including their parameters, see the Sesame Adapter reference information (Javadoc).

8.9 Using the Sesame Console with the Sesame Adapter

The Sesame Console is, as OpenRDF.org explains, "a command-line application for interacting with Sesame. For now, the best way to create and manage repositories in a SYSTEM repository is to use the Sesame Console." For basic usage and reference information about the Sesame Console, see the documentation at <http://www.openrdf.org/doc/sesame2/users/ch07.html>.

This section describes how to use the Sesame Console with the Sesame Adapter for Oracle Database.

To create a new SAIL repository (`OracleSailStore` object) using the Sesame Console command-line tool, use the following command:

```
create oracle.
```

When you are prompted for parameters, you can specify the following:

Repository ID

ID string associated with the repository. Example: `myOracleRepos`

Repository Title

Title string associated with the repository. Example: `My Oracle Repository`

Model Name

Name of the Oracle semantic model that corresponds to this repository. All DML operations are performed against this model.

Additional Models

Comma-separated list of any additional semantic models to be included in this repository. Any additional models are used only for inference and query operations.

Rulebases

Comma-separated list of rulebases to be considered when building the entailment closure for this repository. The default is no rulebases, which means that no inference will be performed.

Use Virtual Model (TRUEIFALSE) [TRUE]

Specifies whether to use a virtual model when answering queries. The default is `TRUE`, which means to use a virtual model.

Virtual Model Name

If `Use Virtual Model` is `TRUE`, specify the name of the virtual model to be used to answer queries, if the database user that owns the repository has read permission on the specified virtual model.

Inference Maintenance Mode (NO_UPDATE|UPDATE_WHEN_COMMIT) [NO_UPDATE]

Specifies whether to update the entailment closure on each commit operation (`UPDATE_WHEN_COMMIT`) or only when the `OracleSailConnection.performInference` method is invoked (`NO_UPDATE`). The default is `NO_UPDATE`.

Allow Duplicates in Query (TRUEIFALSE) [TRUE]

Specifies whether, when querying a repository that has additional models, the query response can include duplicates across the different models. The default is `TRUE`, allows duplicates to be included, and which speeds query performance.

Allow Query with Non-Valid Inference status (INVALID|VALID|INCOMPLETE) [INVALID]

Specifies whether to allow queries when the entailment is not updated, that is, when the inference status is not valid. The default value is `INVALID`, which means that the entailment status can be `INVALID` when querying.

To allow queries only when entailments have a valid status, specify `VALID`. To allow queries when entailments have either a valid or incomplete status, specify `INCOMPLETE`.

Application Table Indexes [CPSO]

Specifies the custom index to be created on the application table for this repository. You can specify the columns to be included (and their order) by using a string of up to 4 of the following characters: *C* (*context*), *P* (*property*), *S* (*subject*), *O* (*object*). (You can use only those characters and cannot repeat any characters.) The default is *CPSO*, which creates an index on all four columns with context as the leading column.

Index Option: Degree of Parallelism [1]

Specifies the DOP (degree of parallelism) value for the application table indexes. With multi-core or multi-CPU processors, experimenting with different DOP values (such as 4 or 8) may improve performance. The default is 1 (no parallelism).

Index Option: Prefix Length to Compress [2]

Specifies whether to use key compression on the application table indexes. The default is 2, which specifies compression on the first two columns. A value of 0 (zero) means that no compression will be used.

Enforce Uniqueness (FALSE|TRUE) []

Specifies whether to enforce statement uniqueness across multiple contexts in the repository. Note that statement uniqueness is enforced by a unique index on the application table. The default is [] (that is, no value specified), which means that if the model exists, the uniqueness setting will be inherited from that model; and if the model does not already exist, a non-unique index will be created.

If you specify *FALSE* and if a unique index exists, that index is dropped and it is re-created as a non-unique index.

Data Source Name [OracleSemDS]

Name of the JDBC data source that provides the database connection setting for accessing the Oracle semantic models and application tables for this repository. The default is *OracleSemDS*.

[Example 8-3](#) shows a sample scenario of using the Sesame Console.

Example 8-3 Using the Sesame Console

```
> connect http://localhost:8080/openrdf-sesame.
Disconnecting from default data directory
Connected to http://localhost:8080/openrdf-sesame
> create oracle.
Please specify values for the following variables:
Repository ID: model2Repos
Repository title: Repository for Model 2
Model Name: model2
Additional Models (comma separated):
Rulebases (comma separated): OWLPRIME    -- OWLPRIME inference will be performed
when this model is created
Use Virtual Model (TRUE|FALSE) [TRUE]: TRUE
Virtual Model Name:    -- a new virtual model will be created if nonexistent
Inference Maintenance Mode (UPDATE_WHEN_COMMIT|NO_UPDATE) [UPDATE_WHEN_COMMIT]:
NO_UPDATE
Allow duplicates in query (TRUE|FALSE) [TRUE]: TRUE
Allow query with non-valid inference status (NONE|INCOMPLETE|INVALID) [NONE]: NONE
- inference must be up to date before query
Application Table Index [CPSO]: CPSO    -- default, recommended index
Index option: Degree of parallelism [1]: 1
Index option: Leading columns to compress [2]: 2
Enforce Uniqueness (|FALSE|TRUE) []: FALSE
DataSource Name [OracleSemDS]: OracleSemDS
```

```
Repository created
> open model2Repos.
Opened repository 'model2Repos'
model2Repos> show c.
--no contexts found--
model2Repos>
```

8.10 Example Queries Using the Sesame Adapter

This section includes example queries using the Sesame Adapter. Each example is self-contained: it typically starts an `OraclePool` object, creates an `OracleSailStore` object, adds and perhaps removes statements, performs a query that may involve inference, displays the result, shuts down the `OracleSailStore` object, and closes the `OraclePool` object.

For these examples, the following libraries must be included in the CLASSPATH definition:

```
sesame-console-2.3.1.jar
sesame-http-client-2.3.1.jar
sesame-http-protocol-2.3.1.jar
sesame-http-server-spring-2.3.1.jar
sesame-model-2.3.1.jar
sesame-query-2.3.1.jar
sesame-queryalgebra-evaluation-2.3.1.jar
sesame-queryalgebra-model-2.3.1.jar
sesame-queryparser-api-2.3.1.jar
sesame-queryparser-serql-2.3.1.jar
sesame-queryparser-sparql-2.3.1.jar
sesame-queryresultio-api-2.3.1.jar
sesame-queryresultio-binary-2.3.1.jar
sesame-queryresultio-sparqljson-2.3.1.jar
sesame-queryresultio-sparqlxml-2.3.1.jar
sesame-queryresultio-text-2.3.1.jar
sesame-repository-api-2.3.1.jar
sesame-repository-contextaware-2.3.1.jar
sesame-repository-dataset-2.3.1.jar
sesame-repository-event-2.3.1.jar
sesame-repository-http-2.3.1.jar
sesame-repository-manager-2.3.1.jar
sesame-repository-sail-2.3.1.jar
sesame-rio-api-2.3.1.jar
sesame-rio-n3-2.3.1.jar
sesame-rio-ntriples-2.3.1.jar
sesame-rio-rdfxml-2.3.1.jar
sesame-rio-trig-2.3.1.jar
sesame-rio-trix-2.3.1.jar
sesame-rio-turtle-2.3.1.jar
sesame-runtime-2.3.1.jar
sesame-sail-api-2.3.1.jar
sesame-sail-inferencer-2.3.1.jar
sesame-sail-memory-2.3.1.jar
sesame-sail-nativerdf-2.3.1.jar
sesame-sail-rdbms-2.3.1.jar
sdordf.jar
sdordfsesame.jar
ojdbc5.jar
```

To simplify the examples, an environment variable named `CP` was defined, as follows:

```

setenv CP
./:sesame-console-2.3.1.jar:sesame-http-client-2.3.1.jar:sesame-http-protocol-2.3.1.jar:sesame-http-server-spring-2.3.1.jar:sesame-model-2.3.1.jar:sesame-query-2.3.1.jar:sesame-queryalgebra-evaluation-2.3.1.jar:sesame-queryalgebra-model-2.3.1.jar:sesame-queryparser-api-2.3.1.jar:sesame-queryparser-serql-2.3.1.jar:sesame-queryparser-sparql-2.3.1.jar:sesame-queryresultio-api-2.3.1.jar:sesame-queryresultio-binary-2.3.1.jar:sesame-queryresultio-sparqljson-2.3.1.jar:sesame-queryresultio-sparqlxml-2.3.1.jar:sesame-queryresultio-text-2.3.1.jar:sesame-repository-api-2.3.1.jar:sesame-repository-contextaware-2.3.1.jar:sesame-repository-dataset-2.3.1.jar:sesame-repository-event-2.3.1.jar:sesame-repository-http-2.3.1.jar:sesame-repository-manager-2.3.1.jar:sesame-repository-sail-2.3.1.jar:sesame-rio-api-2.3.1.jar:sesame-rio-n3-2.3.1.jar:sesame-rio-ntriples-2.3.1.jar:sesame-rio-rdfxml-2.3.1.jar:sesame-rio-trig-2.3.1.jar:sesame-rio-trix-2.3.1.jar:sesame-rio-turtle-2.3.1.jar:sesame-runtime-2.3.1.jar:sesame-sail-api-2.3.1.jar:sesame-sail-inferencer-2.3.1.jar:sesame-sail-memory-2.3.1.jar:sesame-sail-nativerdf-2.3.1.jar:sesame-sail-rdbms-2.3.1.jar:sdordf.jar:sdordfsesame.jar:ojdbc5.jar

```

Note: Enter the `setenv` command, as well as each `javac` and `java` command, on a single command line.

To run a query, you must do the following:

1. Include the code in a Java source file. The examples used in this section are supplied in files in the `examples` directory of the Sesame Adapter download.

2. Compile the Java source file. For example:

```
> javac -classpath $CP Example1.java
```

3. Run the compiled file. For example:

```
> java -classpath $CP Test jdbc:oracle:thin:@localhost:1521:orcl scott
<password-for-scott> M1
```

8.10.1 Example1.java: Basic Operations

[Example 8-4](#) shows the `Example1.java` file, which performs some basic operations.

Example 8-4 Basic Operations

```

import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;

import org.openrdf.sail.SailConnection;
import org.openrdf.sail.SailException;
import org.openrdf.model.vocabulary.RDFS;

public class Example1
{
    public static void main(String[] args) throws SQLException, SailException
    {
        PrintStream psOut = System.out;

```

```

String jdbcUrl = args[0];
String user    = args[1];
String password = args[2];
String model   = args[3];

OraclePool op = new OraclePool(
    OraclePool.getOracleDataSource(jdbcUrl, user, password));
OracleSailStore store = new OracleSailStore(op, model);

OracleSailConnection conn = store.getConnection();

ValueFactory vf = store.getValueFactory();
URI p = vf.createURI("http://p");
URI cls = vf.createURI("http://cls");
URI a = vf.createURI("http://a");
URI b = vf.createURI("http://b");
URI ng1 = vf.createURI("http://ng1");

conn.clear();
conn.addStatement(p, RDFS.DOMAIN, cls);
conn.addStatement(a, p, b, ng1);

psOut.println("size of context " + ng1 + ":" + conn.size(ng1));

// returns OracleStatements
CloseableIteration<? extends Statement, SailException> it =
    conn.getStatements(null, null, null, false);

while (it.hasNext()) {
    Statement stmt = it.next();
    psOut.println("getStatements: stmt: " + stmt.toString());
}

conn.removeStatements(null, null, null, ng1);

psOut.println("size of context " + ng1 + ":" + conn.size(ng1));

conn.removeAll();

psOut.println("size of store: " + conn.size());

conn.close();
store.shutdown();
op.close();
}
}

```

To compile this example, enter the following command:

```
/usr/local/packages/jdk16/bin/javac -classpath $CP Example1.java
```

To run this example, enter a command in the following format:

```
/usr/local/packages/jdk16/bin/java -classpath $CP Example1
jdbc:oracle:thin:@localhost:1521:ORCL scott <password-for-scott> TestModel
```

The expected output of the java command might appear as follows:

```
size of context http://ng1:1
getStatements: stmt: 0: (http://a, http://p, http://b) [http://ng1]
getStatements: stmt: 0: (http://p, http://www.w3.org/2000/01/rdf-schema#domain,
```

```

http://cls) [null]
size of context http://ng1:0
size of store: 0

```

8.10.2 Example2.java: Add a Data File (in TRIG format)

[Example 8-5](#) shows the `Example2.java` file, which adds a data file in TRIG format.

Example 8-5 Add a Data File (in TRIG format)

```

import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;
import org.openrdf.rio.RDFFormat;
import org.openrdf.sail.SailConnection;
import org.openrdf.sail.SailException;
import org.openrdf.model.vocabulary.RDFS;
import org.openrdf.repository.RepositoryConnection;
import org.openrdf.repository.sail.SailRepository;
import org.openrdf.repository.RepositoryException;
import org.openrdf.rio.RDFParseException;

public class Example2
{
    public static void main(String[] args) throws SQLException, SailException,
        RepositoryException, IOException, RDFParseException
    {
        PrintStream psOut = System.out;
        String jdbcUrl = args[0];
        String user = args[1];
        String password = args[2];
        String model = args[3];
        String trigFile = args[4];

        OraclePool op = new OraclePool(
            OraclePool.getOracleDataSource(jdbcUrl, user, password));
        OracleSailStore store = new OracleSailStore(op, model);
        SailRepository sr = new SailRepository(store);
        RepositoryConnection repConn = sr.getConnection();

        repConn.setAutoCommit(false);
        repConn.add(new File(trigFile), "http://my.com/", RDFFormat.TRIG);
        repConn.commit();

        psOut.println("size " + Long.toString(repConn.size()));

        repConn.close();
        store.shutdown();
        op.close();
    }
}

```

To compile this example, enter the following command:

```
usr/local/packages/jdk16/bin/javac -classpath $CP Example2.java
```

For running this example, assume that a sample TRIG data file named `test.trig` was created as:

```
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .
@prefix xsd: <http://www.w3.org/2001/XMLSchema#> .
@prefix swp: <http://www.w3.org/2004/03/trix/swp-1/> .
@prefix dc: <http://purl.org/dc/elements/1.1/> .
@prefix foaf: <http://xmlns.com/foaf/0.1/> .
@prefix ex: <http://example.org/> .
@prefix : <http://example.org/> .

# default graph
{
<http://example.org/bob>    dc:publisher  "Bob Hacker" .
<http://example.org/alice> dc:publisher  "Alice Hacker" .
}

:bob {
_:a foaf:mbox <mailto:bob@oldcorp.example.org> .
}

:alice {
_:a foaf:name "Alice" .
_:a foaf:mbox <mailto:alice@work.example.org> .
}

:jack {
_:a foaf:name "Jack" .
_:a foaf:mbox <mailto:jack@oracle.example.org> .
}
```

To run this example using the `test.trig` data file, enter the following command:

```
/usr/local/packages/jdk16/bin/java -classpath $CP Example2
jdbc:oracle:thin:@localhost:1521:ORCL scott <password> TestModel ./test.trig
```

The expected output of the `java` command might appear as follows:

```
size 7
```

8.10.3 Example3.java: Simple Query

[Example 8–6](#) shows the `Example3.java` file, which performs a simple query.

Example 8–6 Simple Query

```
import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;
import org.openrdf.rio.RDFFormat;
import org.openrdf.sail.SailConnection;
import org.openrdf.sail.SailException;
import org.openrdf.model.vocabulary.RDFS;
```

```

import org.openrdf.repository.RepositoryConnection;
import org.openrdf.repository.sail.SailRepository;
import org.openrdf.repository.RepositoryException;
import org.openrdf.rio.RDFParseException;
import org.openrdf.model.Literal;
import org.openrdf.query.BindingSet;
import org.openrdf.query.QueryLanguage;
import org.openrdf.query.TupleQuery;
import org.openrdf.query.TupleQueryResult;
import org.openrdf.model.vocabulary.RDF;
import org.openrdf.query.QueryEvaluationException;
import org.openrdf.query.MalformedQueryException;

public class Example3
{
    public static void main(String[] args) throws SQLException, SailException,
        RepositoryException, IOException, RDFParseException, QueryEvaluationException,
        MalformedQueryException
    {
        PrintStream psOut = System.out;
        String jdbcUrl = args[0];
        String user = args[1];
        String password = args[2];
        String model = args[3];

        OraclePool op = new OraclePool(
            OraclePool.getOracleDataSource(jdbcUrl, user, password));
        OracleSailStore store = new OracleSailStore(op, model);
        SailRepository myRepository = new SailRepository(store);

        ValueFactory f = myRepository.getValueFactory();
        RepositoryConnection conn = myRepository.getConnection();

        // create some resources and literals to make statements out of
        URI alice = f.createURI("http://example.org/people/alice");
        URI name = f.createURI("http://example.org/ontology/name");
        URI person = f.createURI("http://example.org/ontology/Person");
        Literal alicesName = f.createLiteral("Alice");

        conn.clear(); // to start from scratch
        conn.add(alice, RDF.TYPE, person);
        conn.add(alice, name, alicesName);
        conn.commit();

        store.analyze();
        store.analyzeApplicationTable();

        try {
            //run a query against the repository
            String queryString = " SELECT * WHERE {?x ?p ?y} LIMIT 1 ";
            TupleQuery tupleQuery = conn.prepareTupleQuery(QueryLanguage.SPARQL,
queryString);
            TupleQueryResult result = tupleQuery.evaluate();
            try {
                while (result.hasNext()) {
                    BindingSet bindingSet = result.next();
                    psOut.println("value of x: " + bindingSet.getValue("x"));
                }
            }
            finally {

```

```

        result.close();
    }
}
finally {
    conn.clear();
    if (conn != null && conn.isOpen()) {
        conn.close();
    }

    myRepository.shutdown();
    op.close();
}
}
}

```

To compile this example, enter the following command:

```
/usr/local/packages/jdk16/bin/javac -classpath $CP Example3.java
```

To run this example, enter a command in the following format:

```
/usr/local/packages/jdk16/bin/java -classpath $CP Example3
jdbc:oracle:thin:@localhost:1521:ORCL scott <password-for-scott> TestModel
```

The expected output of the java command might appear as follows:

```
value of x: http://example.org/people/alice
```

8.10.4 Example4.java: Simple Bulk Load

[Example 8-7](#) shows the `Example4.java` file, which performs a simple bulk load operation.

Example 8-7 Simple Bulk Load

```

import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import org.openrdf.model.Resource;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;
import org.openrdf.rio.RDFFormat;
import org.openrdf.sail.SailConnection;
import org.openrdf.sail.SailException;
import org.openrdf.model.vocabulary.RDFS;
import org.openrdf.repository.RepositoryConnection;
import org.openrdf.repository.sail.SailRepository;
import org.openrdf.repository.RepositoryException;
import org.openrdf.rio.RDFParseException;
import org.openrdf.model.Literal;
import org.openrdf.query.BindingSet;
import org.openrdf.query.QueryLanguage;
import org.openrdf.query.TupleQuery;
import org.openrdf.query.TupleQueryResult;
import org.openrdf.model.vocabulary.RDF;
import org.openrdf.query.QueryEvaluationException;
import org.openrdf.query.MalformedQueryException;

```

```

public class Example4
{
    public static void main(String[] args) throws SQLException, SailException,
        RepositoryException, IOException, RDFParseException, QueryEvaluationException,
        MalformedQueryException
    {
        PrintStream psOut = System.out;
        String jdbcUrl = args[0];
        String user = args[1];
        String password = args[2];
        String model = args[3];
        String filename = args[4]; // N-TRIPLES file

        OraclePool op = new OraclePool(OraclePool.getOracleDataSource(jdbcUrl, user,
            password));

        psOut.println("testBulkLoad: start");

        OracleSailStore store = new OracleSailStore(op, model);
        OracleSailConnection osc = store.getConnection();
        FileInputStream fis = new FileInputStream(filename);

        long loadBegin = System.currentTimeMillis();
        osc.getBulkUpdateHandler().addInBulk(
            fis,
            "http://abc",           // baseURI
            RDFFormat.NTRIPLES,    // dataFormat
            null,                   // tablespaceName
            null,                   // flags
            null,                   // StatusListener
            (Resource[]) null      // Resource... for contexts
        );

        long loadEnd = System.currentTimeMillis();
        psOut.println("testBulkLoad: " + (loadEnd - loadBegin) + "ms.\n");

        osc.close();
        store.shutdown();
        op.close();
    }
}

```

To compile this example, enter the following command:

```
usr/local/packages/jdk16/bin/javac -classpath $CP Example4.java
```

For running this example, assume that a sample ntriples data file named `test.ntriples` was created as:

```

<http://example.org/bob>    <http://purl.org/dc/elements/1.1/publisher> "Bob
Hacker" .
<http://example.org/alice>  <http://purl.org/dc/elements/1.1/publisher> "Alice
Hacker" .

```

To run this example using the `test.ntriples` file, enter the following command:

```

/usr/local/packages/jdk16/bin/java -classpath $CP Example4
jdbc:oracle:thin:@localhost:1521:ORCL scott <password> TestModel ./test.ntriples

```

The expected output of the `java` command might appear as follows:

```
testBulkLoad: start
testBulkLoad: 756ms
```

8.10.5 Example5.java: Bulk Load RDF/XML and Application Table Index Maintenance

[Example 8–8](#) shows the `Example5.java` file, which disables indexes on the application table, performs a bulk load operation from an RDF file in XML format, and re-enables the indexes.

Example 8–8 Bulk Load RDF/XML and Application Table Index Maintenance

```
import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import org.openrdf.model.Resource;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;
import org.openrdf.rio.RDFFormat;
import org.openrdf.sail.SailConnection;
import org.openrdf.sail.SailException;
import org.openrdf.model.vocabulary.RDFS;
import org.openrdf.repository.RepositoryConnection;
import org.openrdf.repository.sail.SailRepository;
import org.openrdf.repository.RepositoryException;
import org.openrdf.rio.RDFParseException;
import org.openrdf.model.Literal;
import org.openrdf.query.BindingSet;
import org.openrdf.query.QueryLanguage;
import org.openrdf.query.TupleQuery;
import org.openrdf.query.TupleQueryResult;
import org.openrdf.model.vocabulary.RDF;
import org.openrdf.query.QueryEvaluationException;
import org.openrdf.query.MalformedQueryException;

public class Example5
{
    public static void main(String[] args) throws SQLException, SailException,
        RepositoryException, IOException, RDFParseException, QueryEvaluationException,
        MalformedQueryException
    {
        PrintStream psOut = System.out;
        String jdbcUrl = args[0];
        String user = args[1];
        String password = args[2];
        String model = args[3];
        String filename = args[4]; // RDF/XML

        OraclePool op = new OraclePool(OraclePool.getOracleDataSource(jdbcUrl, user,
            password));

        psOut.println("testBulkLoad: start");

        OracleSailStore store = new OracleSailStore(op, model);
        OracleSailConnection osc = store.getConnection();

        // disable indexes on application table
```

```

store.disableAllAppTabIndexes();

// NOTE: can be a gzipped file!
FileInputStream fis = new FileInputStream(filename);

long loadBegin = System.currentTimeMillis();
osc.getBulkUpdateHandler().addInBulk(
    fis,
    "http://abc",           // baseURI
    RDFFormat.RDFXML,     // dataFormat
    null,                  // tableName
    null,                  // flags
    null,                  // StatusListener
    (Resource[]) null     // Resource... for contexts
);

long loadEnd = System.currentTimeMillis();
opsOut.println("testBulkLoad: " + (loadEnd - loadBegin) + "ms.\n");

// enable indexes on application table
// Note: one can also specify to rebuild indexes in parallel.
store.enableAllAppTabIndexes();

osc.close();
store.shutdown();
op.close();
}
}

```

To compile this example, enter the following command:

```
usr/local/packages/jdk16/bin/javac -classpath $CP Example5.java
```

For running this example, assume that a sample file named `test.rdfxml` was created as:

```

<?xml version="1.0"?>
<!DOCTYPE owl [
  <!ENTITY owl "http://www.w3.org/2002/07/owl#" >
  <!ENTITY xsd "http://www.w3.org/2001/XMLSchema#" >
]>

<rdf:RDF
  xmlns      = "http://a/b#" xml:base = "http://a/b#" xmlns:my  = "http://a/b#"
  xmlns:owl  = "http://www.w3.org/2002/07/owl#"
  xmlns:rdf  = "http://www.w3.org/1999/02/22-rdf-syntax-ns#"
  xmlns:rdfs = "http://www.w3.org/2000/01/rdf-schema#"
  xmlns:xsd  = "http://www.w3.org/2001/XMLSchema#">
  <owl:Class rdf:ID="Color">
    <owl:oneOf rdf:parseType="Collection">
      <owl:Thing rdf:ID="Red"/>
      <owl:Thing rdf:ID="Blue"/>
    </owl:oneOf>
  </owl:Class>
</rdf:RDF>

```

To run this example using the `test.rdfxml` file, enter the following command:

```

/usr/local/packages/jdk16/bin/java -classpath $CP Example5
jdbc:oracle:thin:@localhost:1521:ORCL scott <password> EX5 ./test.rdfxml

```

The expected output of the java command might appear as follows:

```
testBulkLoad: start
testBulkLoad: 825ms
```

8.10.6 Example6.java: Bulk Load With StatusListener to Handle Loading with Bad Data

[Example 8-9](#) shows the `Example6.java` file, which performs the bulk load and index maintenance operations shown in [Example 8-7](#), but also registers and implements a `StatusListener` class to check for and report any data errors.

Example 8-9 Bulk Load With StatusListener to Handle Loading with Bad Data

```
import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import org.openrdf.model.Resource;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;
import org.openrdf.rio.RDFFormat;
import org.openrdf.sail.SailConnection;
import org.openrdf.sail.SailException;
import org.openrdf.model.vocabulary.RDFS;
import org.openrdf.model.Statement;
import org.openrdf.repository.RepositoryConnection;
import org.openrdf.repository.sail.SailRepository;
import org.openrdf.repository.RepositoryException;
import org.openrdf.rio.RDFParseException;
import org.openrdf.model.Literal;
import org.openrdf.query.BindingSet;
import org.openrdf.query.QueryLanguage;
import org.openrdf.query.TupleQuery;
import org.openrdf.query.TupleQueryResult;
import org.openrdf.model.vocabulary.RDF;
import org.openrdf.query.QueryEvaluationException;
import org.openrdf.query.MalformedQueryException;

public class Example6
{
    public static void main(String[] args) throws SQLException, SailException,
        RepositoryException, IOException, RDFParseException, QueryEvaluationException,
        MalformedQueryException
    {
        PrintStream psOut = System.out;
        String jdbcUrl = args[0];
        String user = args[1];
        String password = args[2];
        String model = args[3];
        String filename = args[4]; // RDF/XML

        OraclePool op = new OraclePool(OraclePool.getOracleDataSource(jdbcUrl, user,
            password));

        psOut.println("testBulkLoad: start");

        OracleSailStore store = new OracleSailStore(op, model);
```

```

OracleSailConnection osc = store.getConnection();

// disable indexes on application table
store.disableAllAppTabIndexes();

// NOTE: can be a gzipped file!
FileInputStream fis = new FileInputStream(filename);

long loadBegin = System.currentTimeMillis();
osc.getBulkUpdateHandler().addInBulk(
    fis,
    "http://abc",           // baseURI
    RDFFormat.NTRIPLES,    // dataFormat
    null,                  // tablespaceName
    null,                  // flags
    new MyListener(psOut), // register a StatusListener
    (Resource[]) null      // Resource... for contexts
);

long loadEnd = System.currentTimeMillis();
psOut.println("testBulkLoad: " + (loadEnd - loadBegin) + "ms.\n");

// enable indexes on application table
// Note: one can also specify to rebuild indexes in parallel.
store.enableAllAppTabIndexes();

osc.close();
store.shutdown();
op.close();
}

static class MyListener implements StatusListener {
    PrintStream m_ps = null;
    public MyListener(PrintStream ps) { m_ps = ps; }

    public void statusChanged(long count)
    {
        m_ps.println("process to " + Long.toString(count));
    }

    public int illegalStmtEncountered(Statement statement, long count)
    {
        m_ps.println("hit illegal statement with object " +
statement.getObject().toString());
        return 0; // skip it
    }
}
}

```

To compile this example, enter the following command:

```
usr/local/packages/jdk16/bin/javac -classpath $CP Example6.java
```

For running this example, assume that a sample N-TRIPLES file named `test-include-badtriple.ntriples` was created as follows. In this file, the first and last triples have illegal typed literal values for objects.

```

<http://example.org/x>      <http://my.com/#age>
"123.3456"^^<http://www.w3.org/2001/XMLSchema#integer> .
<http://example.org/bob>   <http://purl.org/dc/elements/1.1/publisher> "Bob
Hacker" .

```

```
<http://example.org/alice> <http://purl.org/dc/elements/1.1/publisher> "Alice
Hacker" .
<http://example.org/y> <http://my.com/#age>
"hello"^^<http://www.w3.org/2001/XMLSchema#float> .
```

To run this example using the `test-include-badtriple.ntriples` file, enter a command in the following format:

```
/usr/local/packages/jdk16/bin/java -classpath $CP Example6
jdbc:oracle:thin:@localhost:1521:ORCL scott <password> EX6
./test-include-badtriple.ntriples
```

The expected output of the `java` command might appear as follows:

```
testBulkLoad: start
hit illegal statement with object
"123.3456"^^<http://www.w3.org/2001/XMLSchema#integer>
process to 2
process to 3
hit illegal statement with object
"hello"^^<http://www.w3.org/2001/XMLSchema#float>
testBulkLoad: 725ms.
```

8.10.7 Example7.java: Load Data from Sesame Store into Oracle Database

[Example 8–10](#) shows the `Example7.java` file, disables indexes on the application table, loads an RDF file in XML format into an in-memory Sesame store, loads the data into the Oracle database, and re-enables the indexes.

Example 8–10 Load Data from Sesame Store into Oracle Database

```
import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import org.openrdf.model.Resource;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;
import org.openrdf.rio.RDFFormat;
import org.openrdf.sail.SailConnection;
import org.openrdf.sail.SailException;
import org.openrdf.sail.memory.MemoryStore;
import org.openrdf.model.vocabulary.RDFS;
import org.openrdf.model.Statement;
import org.openrdf.repository.RepositoryConnection;
import org.openrdf.repository.sail.SailRepository;
import org.openrdf.repository.RepositoryException;
import org.openrdf.rio.RDFParseException;
import org.openrdf.model.Literal;
import org.openrdf.query.BindingSet;
import org.openrdf.query.QueryLanguage;
import org.openrdf.query.TupleQuery;
import org.openrdf.query.TupleQueryResult;
import org.openrdf.model.vocabulary.RDF;
import org.openrdf.query.QueryEvaluationException;
import org.openrdf.query.MalformedQueryException;

public class Example7
```

```

{
    public static void main(String[] args) throws SQLException, SailException,
        RepositoryException, IOException, RDFParseException, QueryEvaluationException,
        MalformedQueryException
    {
        PrintStream psOut = System.out;
        String jdbcUrl = args[0];
        String user = args[1];
        String password = args[2];
        String model = args[3];
        String filename = args[4]; // RDF/XML

        OraclePool op = new OraclePool(OraclePool.getOracleDataSource(jdbcUrl, user,
            password));

        psOut.println("testBulkLoad: start");

        SailRepository srInMem = null;
        RepositoryConnection repConnInMem = null;
        { // build an in memory Sesame store for testing purpose
            srInMem = new SailRepository(new MemoryStore());
            srInMem.initialize();
            repConnInMem = srInMem.getConnection();
            File file = new File(filename);
            repConnInMem.setAutoCommit(false);
            repConnInMem.add(file, "http://my.com", RDFFormat.RDFXML);
            repConnInMem.commit();
        }

        OracleSailStore store = new OracleSailStore(op, model);
        OracleSailConnection osc = store.getConnection();

        // disable indexes on application table
        store.disableAllAppTabIndexes();

        long loadBegin = System.currentTimeMillis();
        // load all statements from in memory store to Oracle
        osc.getBulkUpdateHandler().addInBulk(
            repConnInMem.getStatements(null, null, null, false),
            null // tablespaceName
        );

        long loadEnd = System.currentTimeMillis();
        psOut.println("testBulkLoad: " + (loadEnd - loadBegin) + "ms.\n");

        // enable indexes on application table
        // Note: one can also specify to rebuild indexes in parallel.
        store.enableAllAppTabIndexes();

        repConnInMem.close();
        srInMem.shutdown();

        osc.close();
        store.shutdown();
        op.close();
    }
}

```

To compile this example, enter the following command:

```
usr/local/packages/jdk16/bin/javac -classpath $CP Example7.java
```

For running this example, assume that a file (to be loaded into memory) with the same format and content as the file described in [Section 8.10.5, "Example5.java: Bulk Load RDF/XML and Application Table Index Maintenance"](#) has been created.

To run this example, enter a command in the following format:

```
/usr/local/packages/jdk16/bin/java -classpath $CP Example7
jdbc:oracle:thin:@localhost:1521:ORCL scott <password> EX7 ./test.rdfxml
```

The expected output of the `java` command might appear as follows:

```
testBulkLoad: start
testBulkLoad: 720ms
```

8.10.8 Example8.java: SPARQL ASK Query

[Example 8–11](#) shows the `Example8.java` file, which performs a SPARQL ASK query.

Example 8–11 SPARQL ASK Query

```
import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;
import org.openrdf.rio.RDFFormat;
import org.openrdf.sail.SailConnection;
import org.openrdf.sail.SailException;
import org.openrdf.model.vocabulary.RDFS;
import org.openrdf.repository.RepositoryConnection;
import org.openrdf.repository.sail.SailRepository;
import org.openrdf.repository.RepositoryException;
import org.openrdf.rio.RDFParseException;
import org.openrdf.model.Literal;
import org.openrdf.query.BindingSet;
import org.openrdf.query.QueryLanguage;
import org.openrdf.query.BooleanQuery;
import org.openrdf.query.TupleQuery;
import org.openrdf.query.TupleQueryResult;
import org.openrdf.model.vocabulary.RDF;
import org.openrdf.query.QueryEvaluationException;
import org.openrdf.query.MalformedQueryException;

public class Example8
{
    public static void main(String[] args) throws SQLException, SailException,
        RepositoryException, IOException, RDFParseException, QueryEvaluationException,
        MalformedQueryException
    {
        PrintStream psOut = System.out;
        String jdbcUrl = args[0];
        String user = args[1];
        String password = args[2];
        String model = args[3];

        OraclePool op = new OraclePool(
```

```

        OraclePool.getOracleDataSource(jdbcUrl, user, password));
    OracleSailStore store = new OracleSailStore(op, model);

    SailRepository sr = new SailRepository(store);
    RepositoryConnection repConn = sr.getConnection();

    ValueFactory vf = sr.getValueFactory();
    URI p = vf.createURI("http://p");
    URI cls = vf.createURI("http://cls");

    repConn.clear();
    repConn.add(p, RDFS.DOMAIN, cls);
    repConn.commit();

    store.analyze(); // analyze the semantic model
    store.analyzeApplicationTable(); // and then the application table

    BooleanQuery tq = null;
    tq = repConn.prepareBooleanQuery(QueryLanguage.SPARQL, "ASK { ?x ?p
<http://cls> }" );
    boolean b = tq.evaluate();
    psOut.print("\nAnswer is " + Boolean.toString(b));

    repConn.close();
    sr.shutdown();
    op.close();
}
}

```

To compile this example, enter the following command:

```
usr/local/packages/jdk16/bin/javac -classpath $CP Example8.java
```

To run this example, enter a command in the following format:

```
/usr/local/packages/jdk16/bin/java -classpath $CP Example4
jdbc:oracle:thin:@localhost:1521:ORCL scott <password> EX8
```

The expected output of the java command might appear as follows:

```
Answer is true
```

8.10.9 Example9.java: SPARQL CONSTRUCT and DESCRIBE

[Example 8–12](#) shows the `Example9.java` file, which performs SPARQL CONSTRUCT and DESCRIBE queries.

Example 8–12 SPARQL CONSTRUCT and DESCRIBE

```

import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;
import org.openrdf.rio.RDFFormat;
import org.openrdf.sail.SailConnection;
import org.openrdf.sail.SailException;

```

```

import org.openrdf.model.vocabulary.RDFS;
import org.openrdf.repository.RepositoryConnection;
import org.openrdf.repository.sail.SailRepository;
import org.openrdf.repository.RepositoryException;
import org.openrdf.rio.RDFParseException;
import org.openrdf.model.Literal;
import org.openrdf.query.BindingSet;
import org.openrdf.query.QueryLanguage;
import org.openrdf.query.BooleanQuery;
import org.openrdf.query.TupleQuery;
import org.openrdf.query.GraphQuery;
import org.openrdf.query.GraphQueryResult;
import org.openrdf.query.TupleQueryResult;
import org.openrdf.model.vocabulary.RDF;
import org.openrdf.query.QueryEvaluationException;
import org.openrdf.query.MalformedQueryException;

public class Example9
{
    public static void main(String[] args) throws SQLException, SailException,
        RepositoryException, IOException, RDFParseException, QueryEvaluationException,
        MalformedQueryException
    {
        PrintStream psOut = System.out;
        String jdbcUrl = args[0];
        String user = args[1];
        String password = args[2];
        String model = args[3];

        OraclePool op = new OraclePool(
            OraclePool.getOracleDataSource(jdbcUrl, user, password));
        OracleSailStore store = new OracleSailStore(op, model);

        SailRepository sr = new SailRepository(store);
        RepositoryConnection repConn = sr.getConnection();

        ValueFactory vf = sr.getValueFactory();
        URI p = vf.createURI("http://p");
        URI cls = vf.createURI("http://cls");

        repConn.clear();
        repConn.add(p, RDFS.DOMAIN, cls);
        repConn.commit();

        store.analyze(); // analyze the semantic model
        store.analyzeApplicationTable(); // and then the application table

        GraphQuery tq = null;
        tq = repConn.prepareGraphQuery(QueryLanguage.SPARQL,
            "CONSTRUCT {?x <http://new_eq_p> ?o } WHERE { ?x ?p ?o }" );
        {
            psOut.println("Start construct query");
            GraphQueryResult result = tq.evaluate();
            while (result.hasNext()) {
                Statement stmt = (Statement) result.next();
                psOut.println(stmt.toString());
                // do something interesting with the values here...
            }
            result.close();
        }
    }
}

```

```

    tq = repConn.prepareStatement(QueryLanguage.SPARQL,
        "DESCRIBE <http://p> ");
    {
        psOut.println("Start describe query");
        GraphQueryResult result = tq.evaluate();
        while (result.hasNext()) {
            Statement stmt = (Statement) result.next();
            psOut.println(stmt.toString());
            // do something interesting with the values here...
        }
        result.close();
    }

    repConn.close();
    sr.shutdown();
    op.close();
}
}

```

To compile this example, enter the following command:

```
usr/local/packages/jdk16/bin/javac -classpath $CP Example9.java
```

To run this example, enter a command in the following format:

```
/usr/local/packages/jdk16/bin/java -classpath $CP Example9
jdbc:oracle:thin:@localhost:1521:ORCL scott <password> EX9
```

The expected output of the java command might appear as follows:

```

Start construct query
(http://p, http://new_eq_p, http://cls)
Start describe query
(http://p, http://www.w3.org/2000/01/rdf-schema#domain, http://cls)

```

8.10.10 Example10.java: Inference

[Example 8–13](#) shows the `Example10.java` file, which performs OWLPrime inference using the incremental (INC) and degree of parallelism (DOP) options.

Example 8–13 Inference

```

import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;
import org.openrdf.rio.RDFFormat;
import org.openrdf.sail.SailConnection;
import org.openrdf.sail.SailException;
import org.openrdf.model.vocabulary.RDFS;
import org.openrdf.repository.RepositoryConnection;
import org.openrdf.repository.sail.SailRepository;
import org.openrdf.repository.RepositoryException;
import org.openrdf.rio.RDFParseException;
import org.openrdf.model.Literal;

```

```
import org.openrdf.query.BindingSet;
import org.openrdf.query.QueryLanguage;
import org.openrdf.query.BooleanQuery;
import org.openrdf.query.TupleQuery;
import org.openrdf.query.GraphQuery;
import org.openrdf.query.GraphQueryResult;
import org.openrdf.query.TupleQueryResult;
import org.openrdf.model.vocabulary.RDF;
import org.openrdf.query.QueryEvaluationException;
import org.openrdf.query.MalformedQueryException;

public class Example10
{
    public static void main(String[] args) throws SQLException, SailException,
        RepositoryException, IOException, RDFParseException, QueryEvaluationException,
        MalformedQueryException
    {
        PrintStream psOut = System.out;
        String jdbcUrl = args[0];
        String user = args[1];
        String password = args[2];
        String model = args[3];

        OraclePool op = new OraclePool(
            OraclePool.getOracleDataSource(jdbcUrl, user, password));
        String[] rulebaseNames = new String[1];
        rulebaseNames[0] = "owlprime";

        Attachment attachment = Attachment.createInstance(
            Attachment.NO_ADDITIONAL_MODELS, rulebaseNames,
            InferenceMaintenanceMode.NO_UPDATE,
            QueryOptions.DEFAULT);

        OracleSailStore store = new OracleSailStore(op, model, attachment);
        OracleSailConnection osc = store.getConnection();

        ValueFactory vf = osc.getValueFactory();

        URI sub, pred, obj;
        {
            sub = vf.createURI("http://C1");
            pred = vf.createURI("http://www.w3.org/2000/01/rdf-schema#subClassOf");
            obj = vf.createURI("http://C2");
            osc.addStatement(sub, pred, obj);

            sub = vf.createURI("http://C2");
            pred = vf.createURI("http://www.w3.org/2000/01/rdf-schema#subClassOf");
            obj = vf.createURI("http://C3");
            osc.addStatement(sub, pred, obj);
        }

        osc.commit();
        osc.analyze(); // analyze the semantic model
        osc.analyzeApplicationTable(); // and then the application table

        // parallel inference is certainly an overkill for this ontology
        osc.setInferenceOption("INC=T,DOP=4,RAW8=T");
        osc.performInference();
        osc.analyzeInferredGraph();
    }
}
```

```

TupleQuery tq = null;
RepositoryConnection repConn = osc.asRepositoryConnection();
tq = repConn.prepareTupleQuery(QueryLanguage.SPARQL,
    "SELECT ?s ?p ?o WHERE {?s ?p ?o } ");
{
    TupleQueryResult result = tq.evaluate();
    int idx = 0;
    try {
        psOut.print("\nStart printing solution\n");
        while (result.hasNext()) {
            idx++;
            BindingSet bindingSet = result.next();
        }
    }
    finally {
        psOut.println("\ntotal # of solution " + Integer.toString(idx));
        result.close();
    }
}

{
    sub = vf.createURI("http://C3");
    pred = vf.createURI("http://www.w3.org/2000/01/rdf-schema#subClassOf");
    obj = vf.createURI("http://C4");
    osc.addStatement(sub, pred, obj);
}

// make a small change and then perform inference again
osc.commit();
osc.analyze(); // analyze the semantic model
osc.analyzeApplicationTable(); // and then the application table
osc.performInference();
osc.analyzeInferredGraph();

{
    TupleQueryResult result = tq.evaluate();
    int idx = 0;
    try {
        psOut.print("\nStart printing solution\n");
        while (result.hasNext()) {
            idx++;
            BindingSet bindingSet = result.next();
        }
    }
    finally {
        psOut.println("\ntotal # of solution " + Integer.toString(idx));
        result.close();
    }
}

osc.close();
store.shutdown();
op.close();
}
}

```

To compile this example, enter the following command:

```
usr/local/packages/jdk16/bin/javac -classpath $CP Example10.java
```

To run this example, enter a command in the following format:

```
/usr/local/packages/jdk16/bin/java -classpath $CP Example10  
jdbc:oracle:thin:@localhost:1521:ORCL scott <password> EX10
```

The expected output of the `java` command might appear as follows:

```
Start printing solution
```

```
total # of solution 3
```

```
Start printing solution
```

```
total # of solution 6
```

8.10.11 Example11.java: Named Graph Query

[Example 8–14](#) shows the `Example9.java` file, which performs a named graph query.

Example 8–14 Named Graph Query

```
import org.openrdf.model.Statement;  
import org.openrdf.model.URI;  
import org.openrdf.model.ValueFactory;  
import info.aduna.iteration.CloseableIteration;  
  
import java.io.*;  
import java.sql.SQLException;  
  
import oracle.spatial.rdf.client.sesame.*;  
import org.openrdf.rio.RDFFormat;  
import org.openrdf.sail.SailConnection;  
import org.openrdf.sail.SailException;  
import org.openrdf.model.vocabulary.RDFS;  
import org.openrdf.repository.RepositoryConnection;  
import org.openrdf.repository.sail.SailRepository;  
import org.openrdf.repository.RepositoryException;  
import org.openrdf.rio.RDFParseException;  
import org.openrdf.model.Literal;  
import org.openrdf.query.BindingSet;  
import org.openrdf.query.QueryLanguage;  
import org.openrdf.query.BooleanQuery;  
import org.openrdf.query.TupleQuery;  
import org.openrdf.query.GraphQuery;  
import org.openrdf.query.GraphQueryResult;  
import org.openrdf.query.TupleQueryResult;  
import org.openrdf.model.vocabulary.RDF;  
import org.openrdf.query.QueryEvaluationException;  
import org.openrdf.query.MalformedQueryException;  
  
public class Example11  
{  
    public static void main(String[] args) throws SQLException, SailException,  
        RepositoryException, IOException, RDFParseException, QueryEvaluationException,  
        MalformedQueryException  
    {  
        PrintStream psOut = System.out;  
        String jdbcUrl = args[0];  
        String user = args[1];  
        String password = args[2];  
        String model = args[3];
```

```

String trigFile = args[4];

OraclePool op = new OraclePool(
    OraclePool.getOracleDataSource(jdbcUrl, user, password));

OracleSailStore store = new OracleSailStore(op, model);
OracleSailConnection osc = store.getConnection();
RepositoryConnection repConn = osc.asRepositoryConnection();
repConn.setAutoCommit(false);

// load the data incrementally since it is very small file
repConn.add(new File(trigFile), "http://my.com/", RDFFormat.TRIG);

osc.commit();
osc.analyze(); // analyze the semantic model
osc.analyzeApplicationTable(); // and then the application table

TupleQuery tq = null;
tq = repConn.prepareTupleQuery(QueryLanguage.SPARQL,
    "SELECT ?g ?s ?p ?o WHERE {?g <http://purl.org/dc/elements/1.1/publisher>
?o1 . GRAPH ?g {?s ?p ?o}}");
{
    TupleQueryResult result = tq.evaluate();
    int idx = 0;
    try {
        while (result.hasNext()) {
            idx++;
            BindingSet bindingSet = result.next();
            psOut.print("\nsolution " + bindingSet.toString());
        }
    }
    finally {
        psOut.println("\ntotal # of solution " + Integer.toString(idx));
        result.close();
    }
}

osc.close();
store.shutdown();
op.close();
}
}

```

To compile this example, enter the following command:

```
usr/local/packages/jdk16/bin/javac -classpath $CP Example9.java
```

For running this example, assume that the `test.trig` file described in [Section 8.10.2, "Example2.java: Add a Data File \(in TRIG format\)"](#) has been created.

To run this example using the `test.trig` data file, enter the following command:

```
/usr/local/packages/jdk16/bin/java -classpath $CP Example11
jdbc:oracle:thin:@localhost:1521:ORCL scott <password> EX11 ./test.trig
```

The expected output of the `java` command might appear as follows:

```

solution [g=http://example.org/alice;s=_
:node14r2238h1x1;p=http://xmlns.com/foaf/0.1/mbox;o=mailto:alice@work.example.org]
solution [g=http://example.org/alice;s=_
:node14r2238h1x1;p=http://xmlns.com/foaf/0.1/name;o="Alice"]
solution [g=http://example.org/bob;s=_

```

```

:nodel4r2238h1x1;p=http://xmlns.com/foaf/0.1/mbox;o=mailto:bob@oldcorp.example.org
]
total # of solution 3

```

8.10.12 Example12.java: Indexes on Application Table *[Advanced]*

[Example 8–15](#) shows the `Example12.java` file, an advanced example that creates indexes on the application table.

Example 8–15 Indexes on Application Table *[Advanced]*

```

import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;
import org.openrdf.rio.RDFFormat;
import org.openrdf.sail.SailConnection;
import org.openrdf.sail.SailException;
import org.openrdf.model.vocabulary.RDFS;
import org.openrdf.repository.RepositoryConnection;
import org.openrdf.repository.sail.SailRepository;
import org.openrdf.repository.RepositoryException;
import org.openrdf.rio.RDFParseException;
import org.openrdf.model.Literal;
import org.openrdf.query.BindingSet;
import org.openrdf.query.QueryLanguage;
import org.openrdf.query.BooleanQuery;
import org.openrdf.query.TupleQuery;
import org.openrdf.query.GraphQuery;
import org.openrdf.query.GraphQueryResult;
import org.openrdf.query.TupleQueryResult;
import org.openrdf.model.vocabulary.RDF;
import org.openrdf.query.QueryEvaluationException;
import org.openrdf.query.MalformedQueryException;

public class Example12
{
    public static void main(String[] args) throws SQLException, SailException,
        RepositoryException, IOException, RDFParseException, QueryEvaluationException,
        MalformedQueryException
    {
        PrintStream psOut = System.out;
        String jdbcUrl = args[0];
        String user = args[1];
        String password = args[2];
        String model = args[3];

        OraclePool op = new OraclePool(
            OraclePool.getOracleDataSource(jdbcUrl, user, password));

        OracleSailStore store = new OracleSailStore(op, model);

        // create an index with compress 2, parallel 4
        store.createAppTabIndex("spoc", 2, 4);
    }
}

```

```

// create another index w/o parallel or compression
store.createAppTabIndex("cspo", 0, 1);

// will print out the default index (cpso) as well
psOut.println("index signatures before dropping indexes:");
for (String sig : store.getAppTabIndexSignatures()) {
    psOut.println("index signature:" + sig);
}

store.dropAllAppTabIndexes();
psOut.println("index signatures after dropping indexes...");
for (String sig : store.getAppTabIndexSignatures()) {
    psOut.println("index signature:" + sig);
}

store.shutdown();

// clean up oracle tables and models
OracleUtils.dropSemanticModelAndTables(op, model);

store.shutdown();
op.close();
}
}

```

To compile this example, enter the following command:

```
usr/local/packages/jdk16/bin/javac -classpath $CP Example12.java
```

To run this example, enter a command in the following format:

```
/usr/local/packages/jdk16/bin/java -classpath $CP Example12
jdbc:oracle:thin:@localhost:1521:ORCL scott <password> EX12
```

The expected output of the java command might appear as follows:

```

index signatures before dropping indexes:
index signature:spoc
index signature:cpso
index signature:cspo
index signatures after dropping indexes...

```

8.10.13 Example13.java: Uniqueness Constraint on Application Table [Advanced]

[Example 8–16](#) shows the `Example13.java` file, an advanced example that enables and disables the uniqueness constraint on the application table.

Example 8–16 Uniqueness Constraint on Application Table [Advanced]

```

import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;
import org.openrdf.rio.RDFFormat;
import org.openrdf.sail.SailConnection;
import org.openrdf.sail.SailException;

```

```

import org.openrdf.model.vocabulary.RDFS;
import org.openrdf.repository.RepositoryConnection;
import org.openrdf.repository.sail.SailRepository;
import org.openrdf.repository.RepositoryException;
import org.openrdf.rio.RDFParseException;
import org.openrdf.model.Literal;
import org.openrdf.query.BindingSet;
import org.openrdf.query.QueryLanguage;
import org.openrdf.query.BooleanQuery;
import org.openrdf.query.TupleQuery;
import org.openrdf.query.GraphQuery;
import org.openrdf.query.GraphQueryResult;
import org.openrdf.query.TupleQueryResult;
import org.openrdf.model.vocabulary.RDF;
import org.openrdf.query.QueryEvaluationException;
import org.openrdf.query.MalformedQueryException;

public class Example13
{
    public static void main(String[] args) throws SQLException, SailException,
        RepositoryException, IOException, RDFParseException, QueryEvaluationException,
        MalformedQueryException
    {
        PrintStream psOut = System.out;
        String jdbcUrl = args[0];
        String user = args[1];
        String password = args[2];
        String model = args[3];

        OraclePool op = new OraclePool(
            OraclePool.getOracleDataSource(jdbcUrl, user, password));

        OracleSailStore store = new OracleSailStore(op, model);
        store.enableUniquenessConstraint(); ValueFactory f =
store.getValueFactory();

        OracleSailConnection osc = store.getConnection();

        // create some resources and literals to make statements out of
        URI alice = f.createURI("http://example.org/people/alice");
        URI name = f.createURI("http://example.org/ontology/name");
        URI person = f.createURI("http://example.org/ontology/Person");

        osc.addStatement(alice, name, person);
        osc.addStatement(alice, name, person);
        psOut.println("size of store after adding duplicate triple with uniqueness ON
:" + osc.size());

        osc.clear();
        store.disableUniquenessConstraint(); osc.addStatement(alice, name, person);
        osc.addStatement(alice, name, person);
        psOut.println("size of store after adding duplicate triple with uniqueness
OFF:" + osc.size());

        osc.close();

        store.shutdown();
        op.close();
    }
}

```

To compile this example, enter the following command:

```
usr/local/packages/jdk16/bin/javac -classpath $CP Example13.java
```

To run this example, enter a command in the following format:

```
/usr/local/packages/jdk16/bin/java -classpath $CP Example13  
jdbc:oracle:thin:@localhost:1521:ORCL scott <password> EX13
```

The expected output of the java command might appear as follows:

```
size of store after adding duplicate triple with uniqueness ON :1  
size of store after adding duplicate triple with uniqueness OFF:2
```

8.10.14 Example14.java: Query Timeout and Parallel Execution *[Advanced]*

[Example 8-17](#) shows the `Example14.java` file, an advanced example that specifies a query timeout and parallel execution (`TIMEOUT` and `DOP` options).

Example 8-17 Query Timeout and Parallel Execution *[Advanced]*

```
import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;
import org.openrdf.rio.RDFFormat;
import org.openrdf.sail.SailConnection;
import org.openrdf.sail.SailException;
import org.openrdf.model.vocabulary.RDFS;
import org.openrdf.repository.RepositoryConnection;
import org.openrdf.repository.sail.SailRepository;
import org.openrdf.repository.RepositoryException;
import org.openrdf.rio.RDFParseException;
import org.openrdf.model.Literal;
import org.openrdf.query.BindingSet;
import org.openrdf.query.QueryLanguage;
import org.openrdf.query.TupleQuery;
import org.openrdf.query.TupleQueryResult;
import org.openrdf.model.vocabulary.RDF;
import org.openrdf.query.QueryEvaluationException;
import org.openrdf.query.MalformedQueryException;

public class Example14
{
    public static void main(String[] args) throws SQLException, SailException,
        RepositoryException, IOException, RDFParseException, QueryEvaluationException,
        MalformedQueryException
    {
        PrintStream psOut = System.out;
        String jdbcUrl = args[0];
        String user = args[1];
        String password = args[2];
        String model = args[3];

        OraclePool op = new OraclePool(
```

```

        OraclePool.getOracleDataSource(jdbcUrl, user, password));
OracleSailStore store = new OracleSailStore(op, model);

OracleSailConnection osc = store.getConnection();
ValueFactory f = osc.getValueFactory();

// create some resources and literals to make statements out of
URI alice = f.createURI("http://example.org/people/alice");
URI name = f.createURI("http://example.org/ontology/name");
URI person = f.createURI("http://example.org/ontology/Person");
Literal alicesName = f.createLiteral("Alice");

osc.addStatement(alice, RDF.TYPE, person);
osc.addStatement(alice, name, alicesName);
osc.commit();

osc.analyze();
osc.analyzeApplicationTable();

// Run a query while specifying parallel execution (through DOP=2)
// and max query execution time (through timeout=3)
String queryString =
    " PREFIX ORACLE_SEM_FS_NS: <http://oracle.com/semtech#> " +
    " SELECT * WHERE {?x ?p ?y} ";

TupleQuery tupleQuery = osc.asRepositoryConnection().prepareTupleQuery(
    QueryLanguage.SPARQL, queryString);

TupleQueryResult result = tupleQuery.evaluate();
try {
    while (result.hasNext()) {
        BindingSet bindingSet = result.next();
        psOut.println("value of x: " + bindingSet.getValue("x"));
    }
} finally {
    result.close();
}

osc.close();
store.shutdown();
op.close();
}
}

```

To compile this example, enter the following command:

```
usr/local/packages/jdk16/bin/javac -classpath $CP Example14.java
```

To run this example, enter a command in the following format:

```
/usr/local/packages/jdk16/bin/java -classpath $CP Example14
jdbc:oracle:thin:@localhost:1521:ORCL scott <password> EX14
```

The expected output of the `java` command might appear as follows:

```
value of x: http://example.org/people/alice
value of x: http://example.org/people/alice
```

8.10.15 Example15.java: Get COUNT of Matches *[Advanced]*

[Example 8–18](#) shows the `Example15.java` file, an advanced example that returns the total number (COUNT) of matches (and only of matches).

Example 8–18 Get COUNT of Matches *[Advanced]*

```
import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;
import org.openrdf.rio.RDFFormat;
import org.openrdf.sail.SailConnection;
import org.openrdf.sail.SailException;
import org.openrdf.model.vocabulary.RDFS;
import org.openrdf.repository.RepositoryConnection;
import org.openrdf.repository.sail.SailRepository;
import org.openrdf.repository.RepositoryException;
import org.openrdf.rio.RDFParseException;
import org.openrdf.model.Literal;
import org.openrdf.query.BindingSet;
import org.openrdf.query.QueryLanguage;
import org.openrdf.query.TupleQuery;
import org.openrdf.query.TupleQueryResult;
import org.openrdf.model.vocabulary.RDF;
import org.openrdf.query.QueryEvaluationException;
import org.openrdf.query.MalformedQueryException;

public class Example15
{
    public static void main(String[] args) throws SQLException, SailException,
        RepositoryException, IOException, RDFParseException, QueryEvaluationException,
        MalformedQueryException
    {
        PrintStream psOut = System.out;
        String jdbcUrl = args[0];
        String user = args[1];
        String password = args[2];
        String model = args[3];

        OraclePool op = new OraclePool(
            OraclePool.getOracleDataSource(jdbcUrl, user, password));
        OracleSailStore store = new OracleSailStore(op, model);

        OracleSailConnection osc = store.getConnection();
        ValueFactory f = osc.getValueFactory();

        // create some resources and literals to make statements out of
        URI alice = f.createURI("http://example.org/people/alice");
        URI name = f.createURI("http://example.org/ontology/name");
        URI person = f.createURI("http://example.org/ontology/Person");
        Literal alicesName = f.createLiteral("Alice");

        osc.addStatement(alice, RDF.TYPE, person);
        osc.addStatement(alice, name, alicesName);
        osc.commit();
    }
}
```

```

osc.analyze();
osc.analyzeApplicationTable();

// Run a query and only return the number of matches (the count!)
String queryString =
    " PREFIX ORACLE_SEM_FS_NS: <http://oracle.com/semtech#count_only> " +
    " SELECT ?totalCount WHERE {?s ?p ?y} ";

TupleQuery tupleQuery = osc.asRepositoryConnection().prepareTupleQuery(
    QueryLanguage.SPARQL, queryString);

TupleQueryResult result = tupleQuery.evaluate();
try {
    if (result.hasNext()) {
        BindingSet bindingSet = result.next();
        posOut.println("number of matches: " + bindingSet.getValue("totalCount"));
    }
}
finally {
    result.close();
}

osc.close();
store.shutdown();
op.close();
}
}

```

To compile this example, enter the following command:

```
usr/local/packages/jdk16/bin/javac -classpath $CP Example15.java
```

To run this example, enter a command in the following format:

```
/usr/local/packages/jdk16/bin/java -classpath $CP Example15
jdbc:oracle:thin:@localhost:1521:ORCL scott <password> EX15
```

The expected output of the java command might appear as follows:

```
number of matches: "2"^^<http://www.w3.org/2001/XMLSchema#integer>
```

8.10.16 Example16.java: Specify Bind Variable for Constant in Query Pattern [Advanced]

[Example 8–19](#) shows the `Example16.java` file, an advanced example that specifies a bind variable for a constant in the SPARQL query pattern.

Example 8–19 Specify Bind Variable for Constant in Query Pattern [Advanced]

```

import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;
import org.openrdf.rio.RDFFormat;
import org.openrdf.sail.SailConnection;

```

```

import org.openrdf.sail.SailException;
import org.openrdf.model.vocabulary.RDFS;
import org.openrdf.repository.RepositoryConnection;
import org.openrdf.repository.sail.SailRepository;
import org.openrdf.repository.RepositoryException;
import org.openrdf.rio.RDFParseException;
import org.openrdf.model.Literal;
import org.openrdf.query.BindingSet;
import org.openrdf.query.QueryLanguage;
import org.openrdf.query.TupleQuery;
import org.openrdf.query.TupleQueryResult;
import org.openrdf.model.vocabulary.RDF;
import org.openrdf.query.QueryEvaluationException;
import org.openrdf.query.MalformedQueryException;

public class Example16
{
    public static void main(String[] args) throws SQLException, SailException,
        RepositoryException, IOException, RDFParseException, QueryEvaluationException,
        MalformedQueryException
    {
        PrintStream psOut = System.out;
        String jdbcUrl = args[0];
        String user = args[1];
        String password = args[2];
        String model = args[3];

        OraclePool op = new OraclePool(
            OraclePool.getOracleDataSource(jdbcUrl, user, password));
        OracleSailStore store = new OracleSailStore(op, model);

        OracleSailConnection osc = store.getConnection();
        ValueFactory f = osc.getValueFactory();

        // create some resources and literals to make statements out of
        URI alice = f.createURI("http://example.org/people/alice");
        URI name = f.createURI("http://example.org/ontology/name");
        URI person = f.createURI("http://example.org/ontology/Person");
        Literal alicesName = f.createLiteral("Alice");

        osc.addStatement(alice, RDF.TYPE, person);
        osc.addStatement(alice, name, alicesName);
        osc.commit();

        osc.analyze();
        osc.analyzeApplicationTable();

        String queryString =
            " PREFIX ORACLE_SEM_FS_NS: <http://oracle.com/semtech#use_bind_var(1)> " +
            " SELECT ?p WHERE { <http://example.org/people/alice> " +
            "<http://www.w3.org/1999/02/22-rdf-syntax-ns#type> ?p} ";

        TupleQuery tupleQuery = osc.asRepositoryConnection().prepareTupleQuery(
            QueryLanguage.SPARQL, queryString);

        TupleQueryResult result = tupleQuery.evaluate();
        try {
            if (result.hasNext()) {
                BindingSet bindingSet = result.next();
                psOut.println("solution " + bindingSet.toString());
            }
        }
    }
}

```

```

    }
  }
  finally {
    result.close();
  }

  osc.close();
  store.shutdown();
  op.close();
}
}
}

```

To compile this example, enter the following command:

```
usr/local/packages/jdk16/bin/javac -classpath $CP Example16.java
```

To run this example, enter a command in the following format:

```
/usr/local/packages/jdk16/bin/java -classpath $CP Example16
jdbc:oracle:thin:@localhost:1521:ORCL scott <password> EX16
```

The expected output of the java command might appear as follows:

```
solution [p=http://example.org/ontology/Person]
```

8.10.17 Example17.java: Specify Bind Variable for Constant in Different Position in Query Pattern *[Advanced]*

[Example 8–20](#) shows the `Example17.java` file, an advanced example that specifies a bind variable for a constant in a different position in the SPARQL query pattern than in `Example16.java` ([Example 8–19](#)).

Example 8–20 Specify Bind Variable for Constant in Different Position in Query Pattern [Advanced]

```
import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;
import org.openrdf.rio.RDFFormat;
import org.openrdf.sail.SailConnection;
import org.openrdf.sail.SailException;
import org.openrdf.model.vocabulary.RDFS;
import org.openrdf.repository.RepositoryConnection;
import org.openrdf.repository.sail.SailRepository;
import org.openrdf.repository.RepositoryException;
import org.openrdf.rio.RDFParseException;
import org.openrdf.model.Literal;
import org.openrdf.query.BindingSet;
import org.openrdf.query.QueryLanguage;
import org.openrdf.query.TupleQuery;
import org.openrdf.query.TupleQueryResult;
import org.openrdf.model.vocabulary.RDF;
import org.openrdf.query.QueryEvaluationException;
import org.openrdf.query.MalformedQueryException;

```

```

public class Example17
{
    public static void main(String[] args) throws SQLException, SailException,
        RepositoryException, IOException, RDFParseException, QueryEvaluationException,
        MalformedQueryException
    {
        PrintStream psOut = System.out;
        String jdbcUrl = args[0];
        String user = args[1];
        String password = args[2];
        String model = args[3];

        OraclePool op = new OraclePool(
            OraclePool.getOracleDataSource(jdbcUrl, user, password));
        OracleSailStore store = new OracleSailStore(op, model);

        OracleSailConnection osc = store.getConnection();
        ValueFactory f = osc.getValueFactory();

        // create some resources and literals to make statements out of
        URI alice = f.createURI("http://example.org/people/alice");
        URI name = f.createURI("http://example.org/ontology/name");
        URI person = f.createURI("http://example.org/ontology/Person");
        Literal alicesName = f.createLiteral("Alice");

        osc.addStatement(alice, RDF.TYPE, person);
        osc.addStatement(alice, name, alicesName);
        osc.commit();

        osc.analyze();
        osc.analyzeApplicationTable();

        String queryString =
            " PREFIX ORACLE_SEM_FS_NS: <http://oracle.com/semtech#use_bind_var(2)> " +
            " SELECT ?s WHERE { ?s <http://example.org/ontology/name> \"Alice\" } ";

        TupleQuery tupleQuery = osc.asRepositoryConnection().prepareTupleQuery(
            QueryLanguage.SPARQL, queryString);

        TupleQueryResult result = tupleQuery.evaluate();
        try {
            if (result.hasNext()) {
                BindingSet bindingSet = result.next();
                psOut.println("solution " + bindingSet.toString());
            }
        }
        finally {
            result.close();
        }

        osc.close();
        store.shutdown();
        op.close();
    }
}

```

To compile this example, enter the following command:

```
usr/local/packages/jdk16/bin/javac -classpath $CP Example17.java
```

To run this example, enter a command in the following format:

```
/usr/local/packages/jdk16/bin/java -classpath $CP Example17
jdbc:oracle:thin:@localhost:1521:ORCL scott <password> EX17
```

The expected output of the `java` command might appear as follows:

```
solution [s=http://example.org/people/alice]
```

8.10.18 Example18.java: Build URIs from Internal Numeric IDs *[Advanced]*

[Example 8–21](#) shows the `Example18.java` file, an advanced example that builds URIs from internal numeric IDs.

Example 8–21 Build URIs from Internal Numeric IDs *[Advanced]*

```
import org.openrdf.model.Statement;
import org.openrdf.model.URI;
import org.openrdf.model.ValueFactory;
import info.aduna.iteration.CloseableIteration;

import java.io.*;
import java.sql.SQLException;

import oracle.spatial.rdf.client.sesame.*;
import org.openrdf.rio.RDFFormat;
import org.openrdf.sail.SailConnection;
import org.openrdf.sail.SailException;
import org.openrdf.model.vocabulary.RDFS;
import org.openrdf.repository.RepositoryConnection;
import org.openrdf.repository.sail.SailRepository;
import org.openrdf.repository.RepositoryException;
import org.openrdf.rio.RDFParseException;
import org.openrdf.model.Literal;
import org.openrdf.query.BindingSet;
import org.openrdf.query.QueryLanguage;
import org.openrdf.query.TupleQuery;
import org.openrdf.query.TupleQueryResult;
import org.openrdf.model.vocabulary.RDF;
import org.openrdf.query.QueryEvaluationException;
import org.openrdf.query.MalformedQueryException;

public class Example18
{
    public static void main(String[] args) throws SQLException, SailException,
        RepositoryException, IOException, RDFParseException, QueryEvaluationException,
        MalformedQueryException
    {
        PrintStream psOut = System.out;
        String jdbcUrl = args[0];
        String user = args[1];
        String password = args[2];
        String model = args[3];

        OraclePool op = new OraclePool(
            OraclePool.getOracleDataSource(jdbcUrl, user, password));
        OracleSailStore store = new OracleSailStore(op, model);

        OracleSailConnection osc = store.getConnection();
        ValueFactory f = osc.getValueFactory();

        // create some resources and literals to make statements out of
```

```

URI alice = f.createURI("http://example.org/people/alice");
URI name = f.createURI("http://example.org/ontology/name");
URI person = f.createURI("http://example.org/ontology/Person");
Literal alicesName = f.createLiteral("Alice");

osc.addStatement(alice, RDF.TYPE, person);
osc.addStatement(alice, name, alicesName);
osc.commit();

osc.analyze();
osc.analyzeApplicationTable();

String queryString =
    " PREFIX ORACLE_SEM_FS_NS: <http://oracle.com/semtech#build-uri-for-id(?p)>
" +
    " SELECT ?p WHERE { <http://example.org/people/alice>
<http://www.w3.org/1999/02/22-rdf-syntax-ns#type> ?p } ";

TupleQuery tupleQuery = osc.asRepositoryConnection().prepareTupleQuery(
    QueryLanguage.SPARQL, queryString);

TupleQueryResult result = tupleQuery.evaluate();
try {
    if (result.hasNext()) {
        BindingSet bindingSet = result.next();
        psOut.println("solution " + bindingSet.toString());
    }
}
finally {
    result.close();
}

osc.close();
store.shutdown();
op.close();
}
}

```

To compile this example, enter the following command:

```
usr/local/packages/jdk16/bin/javac -classpath $CP Example18.java
```

To run this example, enter a command in the following format:

```
/usr/local/packages/jdk16/bin/java -classpath $CP Example18
jdbc:oracle:thin:@localhost:1521:ORCL scott <password> EX18
```

The expected output of the java command might appear as follows:

```
solution [p=rdfvid:428072448720587401]
```

SEM_APIS Package Subprograms

The SEM_APIS package contains subprograms (functions and procedures) for working with the Resource Description Framework (RDF) and Web Ontology Language (OWL) in an Oracle database. To use the subprograms in this chapter, you must understand the conceptual and usage information in [Chapter 1, "Oracle Database Semantic Technologies Overview"](#) and [Chapter 2, "OWL Concepts"](#).

This chapter provides reference information about the subprograms, listed in alphabetical order.

SEM_APIS.ADD_SEM_INDEX

Format

```
SEM_APIS.ADD_SEM_INDEX(  
    index_code IN VARCHAR2);
```

Description

Creates a semantic network index that results in creation of a nonunique B-tree index in UNUSABLE status for each of the existing models and entailments of the semantic network.

Parameters

index_code
Index code string.

Usage Notes

You must have DBA privileges to call this procedure.

For an explanation of semantic network indexes, see [Section 1.8](#).

Examples

The following example creates a semantic network index with the index code string `pCSM` on the models and entailments of the semantic network.

```
EXECUTE SEM_APIS.ADD_SEM_INDEX('pCSM');
```

SEM_APIS.ALTER_ENTAILMENT

Format

```
SEM_APIS.ALTER_ENTAILMENT(  
    entailment_name IN VARCHAR2,  
    command        IN VARCHAR2,  
    tablespace_name IN VARCHAR2,  
    parallel        IN NUMBER(38) DEFAULT NULL);
```

Description

Alters an entailment (rules index). Currently, the only action supported is to move the entailment to a specified tablespace.

Parameters

entailment_name

Name of the entailment.

command

Must be the string `MOVE`.

tablespace_name

Name of the destination tablespace.

parallel

Degree of parallelism to be associated with the operation. For more information about parallel execution, see *Oracle Database VLDB and Partitioning Guide*.

Usage Notes

For an explanation of entailments, see [Section 1.3.7](#).

Examples

The following example moves the entailment named `rdfs_rix_family` to the tablespace named `my_tbs`.

```
EXECUTE SEM_APIS.ALTER_ENTAILMENT('rdfs_rix_family', 'MOVE', 'my_tbs');
```

SEM_APIS.ALTER_MODEL

Format

```
SEM_APIS.ALTER_MODEL(  
    model_name      IN VARCHAR2,  
    command         IN VARCHAR2,  
    tablespace_name IN VARCHAR2,  
    parallel        IN NUMBER(38) DEFAULT NULL);
```

Description

Alters a model. Currently, the only action supported is to move the model to a specified tablespace.

Parameters

model_name

Name of the model.

command

Must be the string `MOVE`.

tablespace_name

Name of the destination tablespace.

parallel

Degree of parallelism to be associated with the operation. For more information about parallel execution, see *Oracle Database VLDB and Partitioning Guide*.

Usage Notes

For an explanation of models, see [Section 1.2, "Semantic Data Modeling"](#) and [Section 1.3, "Semantic Data in the Database"](#).

Examples

The following example moves the model named `family` to the tablespace named `my_tbs`.

```
EXECUTE SEM_APIS.ALTER_MODEL('family', 'MOVE', 'my_tbs');
```

SEM_APIS.ALTER_SEM_INDEX_ON_ENTAILMENT

Format

```
SEM_APIS.ALTER_SEM_INDEX_ON_ENTAILMENT(  
    entailment_name IN VARCHAR2,  
    index_code      IN VARCHAR2,  
    command         IN VARCHAR2,  
    tablespace_name IN VARCHAR2 DEFAULT NULL,  
    use_compression IN BOOLEAN DEFAULT NULL,  
    parallel        IN NUMBER(38) DEFAULT NULL,  
    online          IN BOOLEAN DEFAULT FALSE);
```

Description

Alters a semantic network index on an entailment.

Parameters

entailment_name

Name of the entailment.

index_code

Index code string.

command

String value containing one of the following commands: `REBUILD` rebuilds the semantic network index on the entailment, or `UNUSABLE` marks as unusable the semantic network index on the entailment. The value for this parameter is not case-sensitive.

tablespace_name

Name of the destination tablespace for the rebuild operation.

use_compression

Specifies whether compression should be used when rebuilding the index.

parallel

Degree of parallelism to be associated with the operation. For more information about parallel execution, see *Oracle Database VLDB and Partitioning Guide*.

online

`TRUE` allows DML operations affecting the index during the rebuilding of the index; `FALSE` (the default) does not allow DML operations affecting the index during the rebuilding of the index.

Usage Notes

For an explanation of semantic network indexes, see [Section 1.8](#).

Examples

The following example rebuilds (and makes usable if it is unusable) the semantic network index on the entailment named `rdfs_rix_family`.

```
EXECUTE SEM_APIS.ALTER_SEM_INDEX_ON_ENTAILMENT('rdfs_rix_family', 'pscm',  
'rebuild');
```

SEM_APIS.ALTER_SEM_INDEX_ON_MODEL

Format

```
SEM_APIS.ALTER_SEM_INDEX_ON_MODEL(  
    model_name    IN VARCHAR2,  
    index_code    IN VARCHAR2,  
    command       IN VARCHAR2,  
    tablespace_name IN VARCHAR2 DEFAULT NULL,  
    use_compression IN BOOLEAN DEFAULT NULL,  
    parallel       IN NUMBER(38) DEFAULT NULL,  
    online        IN BOOLEAN DEFAULT FALSE);
```

Description

Alters a semantic network index on a model.

Parameters

model_name

Name of the model.

index_code

Index code string.

command

String value containing one of the following commands: `REBUILD` rebuilds the semantic network index on the model, or `UNUSABLE` marks as unusable the semantic network index on the model. The value for this parameter is not case-sensitive.

tablespace_name

Name of the destination tablespace for the rebuild operation.

use_compression

Specifies whether compression should be used when rebuilding the index.

parallel

Degree of parallelism to be associated with the operation. For more information about parallel execution, see *Oracle Database VLDB and Partitioning Guide*.

online

`TRUE` allows DML operations affecting the index during the rebuilding of the index; `FALSE` (the default) does not allow DML operations affecting the index during the rebuilding of the index.

Usage Notes

For an explanation of semantic network indexes, see [Section 1.8](#).

Examples

The following example rebuilds (and makes usable if it is unusable) the semantic network index on the model named `family`.

```
EXECUTE SEM_APIS.ALTER_SEM_INDEX_ON_MODEL('family', 'pscm', 'rebuild');
```

SEM_APIS.ANALYZE_ENTAILMENT

Format

```
SEM_APIS.ANALYZE_ENTAILMENT(
    entailment_name IN VARCHAR2,
    estimate_percent IN NUMBER DEFAULT to_estimate_percent_type (get_param('ESTIMATE_
PERCENT')),
    method_opt      IN VARCHAR2 DEFAULT get_param('METHOD_OPT'),
    degree          IN NUMBER DEFAULT to_degree_type(get_param('DEGREE')),
    cascade         IN BOOLEAN DEFAULT to_cascade_type(get_param('CASCADE')),
    no_invalidate   IN BOOLEAN DEFAULT to_no_invalidate_type (get_param('NO_INVALIDATE')),
    force          IN BOOLEAN DEFAULT FALSE);
```

Description

Collects statistics for a specified entailment (rules index).

Parameters

entailment_name

Name of the entailment.

estimate_percent

Percentage of rows to estimate in the internal table partition containing information about the entailment (NULL means compute). The valid range is [0.000001,100]. Use the constant DBMS_STATS.AUTO_SAMPLE_SIZE to have Oracle determine the appropriate sample size for good statistics. This is the usual default.

method_opt

Accepts either of the following options, or both in combination, for the internal table partition containing information about the entailment:

- FOR ALL [INDEXED | HIDDEN] COLUMNS [size_clause]
- FOR COLUMNS [size clause] column | attribute [size_clause] [,column | attribute [size_clause]...]

size_clause is defined as size_clause := SIZE {integer | REPEAT | AUTO | SKEWONLY}

column is defined as column := column_name | (extension)

- integer : Number of histogram buckets. Must be in the range [1,254].
- REPEAT : Collects histograms only on the columns that already have histograms.
- AUTO : Oracle determines the columns to collect histograms based on data distribution and the workload of the columns.
- SKEWONLY : Oracle determines the columns to collect histograms based on the data distribution of the columns.

- column_name : name of a column

- extension: Can be either a column group in the format of (column_name, column_name [, ...]) or an expression.

The usual default is FOR ALL COLUMNS SIZE AUTO.

degree

Degree of parallelism for the internal table partition containing information about the entailment. The usual default for `degree` is `NULL`, which means use the table default value specified by the `DEGREE` clause in the `CREATE TABLE` or `ALTER TABLE` statement. Use the constant `DBMS_STATS.DEFAULT_DEGREE` to specify the default value based on the initialization parameters. The `AUTO_DEGREE` value determines the degree of parallelism automatically. This is either 1 (serial execution) or `DEFAULT_DEGREE` (the system default value based on number of CPUs and initialization parameters) according to size of the object.

cascade

Gathers statistics on the indexes for the internal table partition containing information about the entailment. Use the constant `DBMS_STATS.AUTO_CASCADE` to have Oracle determine whether index statistics are to be collected or not. This is the usual default.

no_invalidate

Does not invalidate the dependent cursors if set to `TRUE`. The procedure invalidates the dependent cursors immediately if set to `FALSE`. Use `DBMS_STATS.AUTO_INVALIDATE` to have Oracle decide when to invalidate dependent cursors. This is the usual default.

force

`TRUE` gathers statistics even if the entailment is locked; `FALSE` (the default) does not gather statistics if the entailment is locked.

Usage Notes

Index statistics collection can be parallelized except for cluster, domain, and join indexes.

This procedure internally calls the `DBMS_STATS.GATHER_TABLE_STATS` procedure, which collects statistics for the internal table partition that contains information about the entailment. The `DBMS_STATS.GATHER_TABLE_STATS` procedure is documented in *Oracle Database PL/SQL Packages and Types Reference*.

For information about entailments, see [Section 1.3.7](#).

Examples

The following example collects statistics for the entailment named `rdfs_rix_family`.

```
EXECUTE SEM_APIS.ANALYZE_ENTAILMENT('rdfs_rix_family');
```

SEM_APIS.ANALYZE_MODEL

Format

```
SEM_APIS.ANALYZE_MODEL(
    model_name      IN VARCHAR2,
    estimate_percent IN NUMBER DEFAULT to_estimate_percent_type (get_param('ESTIMATE_
PERCENT')),
    method_opt      IN VARCHAR2 DEFAULT get_param('METHOD_OPT'),
    degree          IN NUMBER DEFAULT to_degree_type(get_param('DEGREE')),
    cascade         IN BOOLEAN DEFAULT to_cascade_type(get_param('CASCADE')),
    no_invalidate   IN BOOLEAN DEFAULT to_no_invalidate_type (get_param('NO_INVALIDATE')),
    force          IN BOOLEAN DEFAULT FALSE);
```

Description

Collects optimizer statistics for a specified model.

Parameters

model_name

Name of the model.

estimate_percent

Percentage of rows to estimate in the internal table partition containing information about the model (NULL means compute). The valid range is [0.000001,100]. Use the constant DBMS_STATS.AUTO_SAMPLE_SIZE to have Oracle determine the appropriate sample size for good statistics. This is the usual default.

method_opt

Accepts either of the following options, or both in combination, for the internal table partition containing information about the model:

- FOR ALL [INDEXED | HIDDEN] COLUMNS [size_clause]
- FOR COLUMNS [size clause] column | attribute [size_clause] [,column | attribute [size_clause]...]

size_clause is defined as size_clause := SIZE {integer | REPEAT | AUTO | SKEWONLY}

column is defined as column := column_name | (extension)

- integer : Number of histogram buckets. Must be in the range [1,254].
- REPEAT : Collects histograms only on the columns that already have histograms.
- AUTO : Oracle determines the columns to collect histograms based on data distribution and the workload of the columns.
- SKEWONLY : Oracle determines the columns to collect histograms based on the data distribution of the columns.

- column_name : name of a column

- extension: Can be either a column group in the format of (column_name, column_name [, ...]) or an expression.

The usual default is FOR ALL COLUMNS SIZE AUTO.

degree

Degree of parallelism for the internal table partition containing information about the model. The usual default for `degree` is `NULL`, which means use the table default value specified by the `DEGREE` clause in the `CREATE TABLE` or `ALTER TABLE` statement. Use the constant `DBMS_STATS.DEFAULT_DEGREE` to specify the default value based on the initialization parameters. The `AUTO_DEGREE` value determines the degree of parallelism automatically. This is either 1 (serial execution) or `DEFAULT_DEGREE` (the system default value based on number of CPUs and initialization parameters) according to size of the object.

cascade

Gathers statistics on the indexes for the internal table partition containing information about the model. Use the constant `DBMS_STATS.AUTO_CASCADE` to have Oracle determine whether index statistics are to be collected or not. This is the usual default.

no_invalidate

Does not invalidate the dependent cursors if set to `TRUE`. The procedure invalidates the dependent cursors immediately if set to `FALSE`. Use `DBMS_STATS.AUTO_INVALIDATE` to have Oracle decide when to invalidate dependent cursors. This is the usual default.

force

`TRUE` gathers statistics even if the model is locked; `FALSE` (the default) does not gather statistics if the model is locked.

Usage Notes

Index statistics collection can be parallelized except for cluster, domain, and join indexes.

This procedure internally calls the `DBMS_STATS.GATHER_TABLE_STATS` procedure, which collects optimizer statistics for the internal table partition that contains information about the model. The `DBMS_STATS.GATHER_TABLE_STATS` procedure is documented in *Oracle Database PL/SQL Packages and Types Reference*.

Examples

The following example collects statistics for the semantic model named `family`.

```
EXECUTE SEM_APIS.ANALYZE_MODEL('family');
```

SEM_APIS.BULK_LOAD_FROM_STAGING_TABLE

Format

```
SEM_APIS.BULK_LOAD_FROM_STAGING_TABLE(  
    model_name  IN VARCHAR2,  
    table_owner IN VARCHAR2,  
    table_name  IN VARCHAR2,  
    flags       IN VARCHAR2 DEFAULT NULL,  
    debug       IN BINARY_INTEGER DEFAULT NULL,  
    start_comment IN VARCHAR2 DEFAULT NULL,  
    end_comment  IN VARCHAR2 DEFAULT NULL);
```

Description

Loads semantic data from a staging table.

Parameters

model_name

Name of the model.

table_owner

Name of the schema that owns the staging table that holds semantic data to be loaded.

table_name

Name of the staging table that holds semantic data to be loaded.

flags

An optional quoted string with one or more of the following keyword specifications:

- `PARALLEL_CREATE_INDEX` allows internal indexes to be created in parallel, which may improve the performance of the bulk load processing.
- `PARALLEL=<integer>` allows much of the processing used during bulk load to be done in parallel using the specified degree of parallelism to be associated with the operation.
- `<task>_JOIN_HINT=<join_type>`, where `<task>` can be any of the following internal tasks performed during bulk load: `IZC` (is zero collisions), `MBV` (merge batch values), or `MBT` (merge batch triples, used when adding triples to a non-empty model), and where `<join_type>` can be `USE_NL` and `USE_HASH`.

debug

(Reserved for future use)

start_comment

Optional comment about the start of the load operation.

end_comment

Optional comment about the end of the load operation.

Usage Notes

You must first load semantic data into a staging table before calling this procedure. See [Section 1.7.1](#) for more information.

Using BULK_LOAD_FROM_STAGING_TABLE with Fine Grained Access Control (VPD and OLS)

When fine-grained access control (explained in [Chapter 5](#)) is enabled for a specific model using VPD or for the entire network using OLS, only a user with FULL access privileges to the associated policy may perform the bulk load operation. Full access privileges to a VPD policy are granted by setting the context attribute defined by the package constant `sem_rdfsa.VPD_FULL_ACCESS` to 1 for the namespace associated with the VPD policy (see [Section 5.1.1](#)). When OLS is enabled, full access privileges to the OLS policy are granted using the `SA_USER_ADMIN.SET_USER_PRIVS` procedure.

The data loaded into a model with VPD enabled is immediately available for access and does not need any maintenance operations. However, when the OLS is used, the label column in the tables storing the RDF triples must be maintained. By default, with OLS enabled, the label column in the tables storing the RDF triples is set to null. If you have FULL access, you can reset the labels for the newly inserted triples as well as any resources introduced by the new batch of triples by using appropriate subprograms ([SEM_RDFSA.SET_RESOURCE_LABEL](#) and [SEM_RDFSA.SET_PREDICATE_LABEL](#)).

Optionally, you can define a numeric column named `RDF$STC_CTXT1` in the staging table and the application table, to assign the sensitivity label of the triple before the data is loaded into the desired model. Such labels are automatically applied to the corresponding triples stored in the `MDSYS.RDF_LINK$` table. The labels for the newly introduced resources may still have to be applied separately before or after the load, and the system does not validate the labels assigned during bulk load operation.

The `RDF$STC_CTXT1` column in the application table has no significance, and it may be dropped after the bulk load operation.

Examples

The following example loads semantic data stored in the staging table named `STAGE_TABLE` in schema `SCOTT` into the semantic model named `family`. The example includes some join hints.

```
EXECUTE SEM_APIS.BULK_LOAD_FROM_STAGING_TABLE('family', 'scott', 'stage_table',
flags => 'IZC_JOIN_HINT=USE_HASH MBV_JOIN_HINT=USE_HASH');
```

SEM_APIS.CLEANUP_FAILED

Format

```
SEM_APIS.CLEANUP_FAILED(  
    rdf_object_type IN VARCHAR2,  
    rdf_object_name IN VARCHAR2);
```

Description

Drops (deletes) a specified rulebase or entailment if it is in a failed state.

Parameters

rdf_object_type

Type of the RDF object: RULEBASE for a rulebase or RULES_INDEX for an entailment (rules index).

rdf_object_name

Name of the RDF object of type `rdf_object_type`.

Usage Notes

This procedure checks to see if the specified RDF object is in a failed state; and if the object is in a failed state, the procedure deletes the object.

A rulebase or entailment is in a failed state if a system failure occurred during the creation of that object. You can check if a rulebase or entailment is in a failed state by checking to see if the value of the STATUS column is FAILED in the SDO_RULEBASE_INFO view (described in [Section 1.3.6](#)) or the SDO_RULES_INDEX_INFO view (described in [Section 1.3.7](#)), respectively.

If the rulebase or entailment is not in a failed state, this procedure performs no action and returns a successful status.

An exception is generated if the RDF object is currently being used.

Examples

The following example deletes the rulebase named `family_rb` if (and only if) that rulebase is in a failed state.

```
EXECUTE SEM_APIS.CLEANUP_FAILED('RULEBASE', 'family_rb');
```

SEM_APIS.COMPOSE_RDF_TERM

Format

```
SEM_APIS.COMPOSE_RDF_TERM(  
    value_name  IN VARCHAR2,  
    value_type  IN VARCHAR2,  
    literal_type IN VARCHAR2,  
    language_type IN VARCHAR2  
    ) RETURN VARCHAR2;
```

or

```
SEM_APIS.COMPOSE_RDF_TERM(  
    value_name  IN VARCHAR2,  
    value_type  IN VARCHAR2,  
    literal_type IN VARCHAR2,  
    language_type IN VARCHAR2,  
    long_value  IN CLOB,  
    options     IN VARCHAR2 DEFAULT NULL,  
    ) RETURN CLOB;
```

Description

Creates and returns an RDF term using the specified parameters.

Parameters

value_name

Value name. Must match a value in the VALUE_NAME column in the MDSYS.RDF_VALUE\$ table (described in [Section 1.3.2](#)) or in the *var* attribute returned from SEM_MATCH table function.

value_type

The type of text information. Must match a value in the VALUE_TYPE column in the MDSYS.RDF_VALUE\$ table (described in [Section 1.3.2](#)) or in the *var*\$RDFVTYP attribute returned from SEM_MATCH table function.

literal_type

For typed literals, the type information; otherwise, null. Must either be a null value or match a value in the LITERAL_TYPE column in the MDSYS.RDF_VALUE\$ table (described in [Section 1.3.2](#)) or in the *var*\$RDFLTYP attribute returned from SEM_MATCH table function.

language_type

Language tag. Must match a value in the LANGUAGE_TYPE column in the MDSYS.RDF_VALUE\$ table (described in [Section 1.3.2](#)) or in the *var*\$RDFLANG attribute returned from SEM_MATCH table function.

long_value

The character string if the length of the lexical value is greater than 4000 bytes. Must match a value in the LONG_VALUE column in the MDSYS.RDF_VALUE\$ table (described in [Section 1.3.2](#)) or in the *var*\$RDFCLOB attribute returned from SEM_MATCH table function.

options

(Reserved for future use.)

Usage Notes

If you specify an inconsistent combination of values for the parameters, this function returns a null value. If a null value is returned but you believe that the values for the parameters are appropriate (reflecting columns from the same row in the MDSYS.RDF_VALUE\$ table or from a SEM_MATCH query for the same variable), contact Oracle Support.

Examples

The following example returns, for each member of the family whose height is known, the RDF term for the height and also just the value portion of the height.

```
SELECT x, SEM_APIS.COMPOSE_RDF_TERM(h, h$RDFVTYP, h$RDFLTYP, h$RDFLANG)
       h_rdf_term, h
FROM TABLE(SEM_MATCH(
  '{?x :height ?h}',
  SEM_Models('family'),
  null,
  SEM_ALIASES(SEM_ALIAS('', 'http://www.example.org/family/')),
  null))
ORDER BY x;
X
-----
H_RDF_TERM
-----
H
-----
http://www.example.org/family/Cathy
"5.8"^^<http://www.w3.org/2001/XMLSchema#decimal>
5.8

http://www.example.org/family/Cindy
"6"^^<http://www.w3.org/2001/XMLSchema#decimal>
6

http://www.example.org/family/Jack
"6"^^<http://www.w3.org/2001/XMLSchema#decimal>
6

http://www.example.org/family/Tom
"5.75"^^<http://www.w3.org/2001/XMLSchema#decimal>
5.75

4 rows selected.
```

The following example returns the RDF terms for a few of the values stored in the MDSYS.RDF_VALUE\$ table.

```
SELECT SEM_APIS.COMPOSE_RDF_TERM(value_name, value_type, literal_type,
                                language_type)
```

```
FROM MDSYS.RDF_VALUE$ WHERE ROWNUM < 5;
```

```
SEM_APIS.COMPOSE_RDF_TERM(VALUE_NAME, VALUE_TYPE, LITERAL_TYPE, LANGUAGE_TYPE)
```

```
-----  
<http://www.w3.org/1999/02/22-rdf-syntax-ns#object>  
<http://www.w3.org/1999/02/22-rdf-syntax-ns#type>  
<http://www.w3.org/1999/02/22-rdf-syntax-ns#subject>  
<http://www.w3.org/1999/02/22-rdf-syntax-ns#Property>
```

SEM_APIS.CREATE_ENTAILMENT

Format

```
SEM_APIS.CREATE_ENTAILMENT(
    entailment_name_in IN VARCHAR2,
    models_in          IN SEM_MODELS,
    rulebases_in       IN SEM_RULEBASES,
    passes              IN NUMBER DEFAULT SEM_APIS.REACH_CLOSURE,
    inf_components_in  IN VARCHAR2 DEFAULT NULL,
    options             IN VARCHAR2 DEFAULT NULL,
    delta_in           IN SEM_MODELS DEFAULT NULL,
    label_gen          IN RDFSA_LABELGEN DEFAULT NULL);
```

Description

Creates an entailment (rules index) that can be used to perform OWL or RDFS inferencing, and optionally use user-defined rules.

Parameters

entailment_name_in

Name of the entailment to be created.

models_in

One or more model names. Its data type is SEM_MODELS, which has the following definition: TABLE OF VARCHAR2 (25)

rulebases_in

One or more rulebase names. Its data type is SEM_RULEBASES, which has the following definition: TABLE OF VARCHAR2 (25) . Rules and rulebases are explained in [Section 1.3.6](#).

passes

The number of rounds that the inference engine should run. The default value is SEM_APIS.REACH_CLOSURE, which means the inference engine will run till a closure is reached. If the number of rounds specified is less than the number of actual rounds needed to reach a closure, the status of the entailment will then be set to INCOMPLETE.

inf_components_in

A comma-delimited string of keywords representing inference components, for performing selective or component-based inferencing. If this parameter is null, the default set of inference components is used. See the Usage Notes for more information about inference components.

options

A comma-delimited string of options to control the inference process by overriding the default inference behavior. To enable an option, specify *option-name=T*; to disable an option, you can specify *option-name=F* (the default). The available option-name values are COL_COMPRESS, DISTANCE, DOP, ENTAIL_ANYWAY, HASH_PART, INC,

OPT_SAMEAS, RAW8, PROOF, and USER_RULES. See the Usage Notes for explanations of each value.

delta_in

If incremental inference is in effect, specifies one or more models on which to perform incremental inference. Its data type is SEM_MODELS, which has the following definition: TABLE OF VARCHAR2 (25)

The triples in the first model in `delta_in` are copied to the first model in `models_in`, and the entailment (rules index) in `rules_index_in` is updated; then the triples in the second model (if any) in `delta_in` are copied to the second model (if any) in `models_in`, and the entailment in `rules_index_in` is updated; and so on until all triples are copied and the entailment is updated. (The `delta_in` parameter has no effect if incremental inference is not enabled for the entailment.)

label_gen

An instance of MDSYS.RDFSA_LABELGEN or a subtype of it, defining the logic for generating Oracle Label Security (OLS) labels for inferred triples. What you specify for this parameter depends on whether you use the default label generator or a custom label generator:

- If you use the default label generator, specify one of the following constants: `SEM_RDFSA.LABELGEN_RULE` for Use Rule Label, `SEM_RDFSA.LABELGEN_SUBJECT` for Use Subject Label, `SEM_RDFSA.LABELGEN_PREDICATE` for Use Predicate Label, `SEM_RDFSA.LABELGEN_OBJECT` for Use Object Label, `SEM_RDFSA.LABELGEN_DOMINATING` for Use Dominating Label, `SEM_RDFSA.LABELGEN_ANTECED` for Use Antecedent Labels. For a detailed explanation of each constant, see [Section 5.2.2.4](#).
- If you use a custom label generator, specify the custom label generator type. For information about creating and implementing a custom label generator, see [Section 5.2.2.5](#).

Usage Notes

For the `inf_components_in` parameter, you can specify any combination of the following keywords: SCOH, COMPH, DISJH, SYMMH, INVH, SPIH, MBRH, SPOH, DOMH, RANH, EQCH, EQPH, FPH, IFPH, DOM, RAN, SCO, DISJ, COMP, INV, SPO, FP, IFP, SYMM, TRANS, DIF, SAM, CHAIN, HASKEY, ONEOF, INTERSECT, INTERSECTSCOH, MBRLST, PROPDISJH, SKOSAXIOMS, SNOMED, SVFH, THINGH, THINGSAM, UNION, RDFP1, RDFP2, RDFP3, RDFP4, RDFP6, RDFP7, RDFP8AX, RDFP8BX, RDFP9, RDFP10, RDFP11, RDFP12A, RDFP12B, RDFP12C, RDFP13A, RDFP13B, RDFP13C, RDFP14A, RDFP14BX, RDFP15, RDFP16, RDFS2, RDFS3, RDFS4a, RDFS4b, RDFS5, RDFS6, RDFS7, RDFS8, RDFS9, RDFS10, RDFS11, RDFS12, RDFS13. For an explanation of the meaning of these keywords, see [Table 9–1](#), where the keywords are listed in alphabetical order.

The default set of inference components for the OWLPrime vocabulary includes the following: SCOH, COMPH, DISJH, SYMMH, INVH, SPIH, SPOH, DOMH, RANH, EQCH, EQPH, FPH, IFPH, SAMH, DOM, RAN, SCO, DISJ, COMP, INV, SPO, FP, IFP, SYMM, TRANS, DIF, RDFP14A, RDFP14BX, RDFP15, RDFP16. However, note the following:

- Component SAM is not in this default OWLPrime list, because it tends to generate many new triples for some ontologies.
- Effective with Release 11.2, the native OWL inference engine supports the following new inference components: CHAIN, HASKEY, INTERSECT, INTERSECTSCOH, MBRLST, ONEOF, PROPDISJH, SKOSAXIOMS, SNOMED, SVFH, THINGH, THINGSAM, UNION. However, for backward compatibility, the OWLPrime rulebase and any existing rulebases do not include these new

components by default; instead, to use these new inference components, you must specify them explicitly, and they are included in [Table 9–1](#). The following example creates an OWLPrime entailment for two OWL ontologies named LUBM and UNIV. Because of the additional inference components specified, this entailment will include the new semantics introduced in those inference components.

```
EXECUTE sem_apis.create_entailment('lubm1000_idx', sem_models('lubm', 'univ'),
  sem_rulebases('owlprime'), SEM_APIS.REACH_CLOSURE,
  'INTERSECT, INTERSECTSCOH, SVFH, THINGH, THINGSAM, UNION');
```

Table 9–1 *Inferencing Keywords for `inf_components_in` Parameter*

Keyword	Explanation
CHAIN	Captures the property chain semantics defined in OWL 2. Only chains of length 2 are supported. By default, this is included in the SKOSCORE rulebase. Subproperty chaining is an OWL 2 feature, and for backward compatibility this component is not by default included in the OWLPrime rulebase. (For information about property chain handling, see Section 3.2.2 .) (New as of Release 11.2.)
COMPH	Performs inference based on owl:complementOf assertions and the interaction of owl:complementOf with other language constructs.
DIF	Generates owl:differentFrom assertions based on the symmetricity of owl:differentFrom.
DISJ	Infers owl:differentFrom relationships at instance level using owl:disjointWith assertions.
DISJH	Performs inference based on owl:disjointWith assertions and their interactions with other language constructs.
DOM	Performs inference based on RDFS2.
DOMH	Performs inference based on rdfs:domain assertions and their interactions with other language constructs.
EQCH	Performs inference that are relevant to owl:equivalentClass.
EQPH	Performs inference that are relevant to owl:equivalentProperty.
FP	Performs instance-level inference using instances of owl:FunctionalProperty.
FPH	Performs inference using instances of owl:FunctionalProperty.
HASKEY	Covers the semantics behind "keys" defined in OWL 2. In OWL 2, a collection of properties can be treated as a key to a class expression. For efficiency, the size of the collection must not exceed 3. (New as of Release 11.2.)
IFP	Performs instance-level inference using instances of owl:InverseFunctionalProperty.
IFPH	Performs inference using instances of owl:InverseFunctionalProperty.
INTERSECT	Handles the core semantics of owl:intersectionOf. For example, if class C is the intersection of classes C1, C2 and C3, then C is a subclass of C1, C2, and C3. In addition, common instances of all C1, C2, and C3 are also instances of C. (New as of Release 11.2.)
INTERSECTSCOH	Handles the fact that an intersection is the maximal common subset. For example, if class C is the intersection of classes C1, C2, and C3, then any common subclass of all C1, C2, and C3 is a subclass of C. (New as of Release 11.2.)
INV	Performs instance-level inference using owl:inverseOf assertions.
INVH	Performs inference based on owl:inverseOf assertions and their interactions with other language constructs.

Table 9–1 (Cont.) Inferencing Keywords for *inf_components_in Parameter*

Keyword	Explanation
MBRLST	Captures the semantics that for any resource, every item in the list given as the value of the <code>skos:memberList</code> property is also a value of the <code>skos:member</code> property. (See S36 in the SKOS detailed specification.) By default, this is included in the SKOSCORE rulebase. (New as of Release 11.2.)
ONEOF	Generates classification assertions based on the definition of the enumeration classes. In OWL, class extensions can be enumerated explicitly with the <code>owl:oneOf</code> constructor. (New as of Release 11.2.)
PROPDISJH	Captures the interaction between <code>owl:propertyDisjointWith</code> and <code>rdfs:subPropertyOf</code> . By default, this is included in SKOSCORE rulebase. <code>propertyDisjointWith</code> is an OWL 2 feature, and for backward compatibility this component is not by default included in the OWLPrime rulebase. (New as of Release 11.2.)
RANH	Performs inference based on <code>rdfs:range</code> assertions and their interactions with other language constructs.
RDFP*	(The rules corresponding to components with a prefix of <i>RDFP</i> can be found in <i>Completeness, decidability and complexity of entailment for RDF Schema and a semantic extension involving the OWL vocabulary</i> , by H.J. Horst.)
RDFS2, ... RDFS13	RDFS2, RDFS3, RDFS4a, RDFS4b, RDFS5, RDFS6, RDFS7, RDFS8, RDFS9, RDFS10, RDFS11, RDFS12, and RDFS13 are described in Section 7.3 of <i>RDF Semantics</i> (http://www.w3.org/TR/rdf-mt/). Note that many of the RDFS components are not relevant for OWL inference.
SAM	Performs inference about individuals based on existing assertions for those individuals and <code>owl:sameAs</code> .
SAMH	Infers <code>owl:sameAs</code> assertions using transitivity and symmetricity of <code>owl:sameAs</code> .
SCO	Performs inference based on RDFS9.
SCOH	Generates the <code>subClassOf</code> hierarchy based on existing <code>rdfs:subClassOf</code> assertions. Basically, <code>C1 rdfs:subClassOf C2</code> and <code>C2 rdfs:subClassOf C3</code> will infer <code>C1 rdfs:subClassOf C3</code> based on transitivity. SCOH is also an alias of RDFS11.
SKOSAXIOMS	Captures most of the axioms defined in the SKOS detailed specification. By default, this is included in the SKOSCORE rulebase. (New as of Release 11.2.)
SNOMED	Performs inference based on the semantics of the OWL 2 EL profile, which captures the expressiveness of SNOMED CT (Systematized Nomenclature of Medicine - Clinical Terms), which is one of the most expressive and complex medical terminologies. (New as of Release 11.2.)
SPIH	Performs inference based on interactions between <code>rdfs:subPropertyOf</code> and <code>owl:inverseOf</code> assertions.
SPO	Performs inference based on RDFS7.
SPOH	Generates <code>rdfs:subPropertyOf</code> hierarchy based on transitivity of <code>rdfs:subPropertyOf</code> . It is an alias of RDFS5.
SVFH	Handles the following semantics that involves the interaction between <code>owl:someValuesFrom</code> and <code>rdfs:subClassOf</code> . Consider two existential restriction classes <code>C1</code> and <code>C2</code> that both use the same restriction property. Assume further that the <code>owl:someValuesFrom</code> constraint class for <code>C1</code> is a subclass of that for <code>C2</code> . Then <code>C1</code> can be inferred as a subclass of <code>C2</code> . (New as of Release 11.2.)

Table 9–1 (Cont.) Inferencing Keywords for `inf_components_in Parameter`

Keyword	Explanation
SYMM	Performs instance-level inference using instances of owl:SymmetricProperty.
SYMH	Performs inference for properties of type owl:SymmetricProperty.
THINGH	Handles the semantics that any defined OWL class is a subclass of owl:Thing. The consequence of this rule is that instances of all defined OWL classes will become instances of owl:Thing. The size of the inferred graph will very likely be bigger with this component selected. (New as of Release 11.2.)
THINGSAM	Handles the semantics that instances of owl:Thing are equal to (owl:sameAs) themselves. This component is provided for the convenience of some applications. Note that an application does not have to select this inference component to figure out an individual is equal to itself; this kind of information can easily be built in the application logic. (New as of Release 11.2.)
TRANS	Calculates transitive closure for instances of owl:TransitiveProperty.
UNION	Captures the core semantics of the owl:unionOf construct. Basically, the union class is a superclass of all member classes. For backward compatibility, this component is not by default included in the OWLPrime rulebase. (New as of Release 11.2.)

To deselect a component, use the component name followed by a minus (-) sign. For example, `SCOH-` deselects inference of the `subClassOf` hierarchy.

For the `options` parameter, you can enable the following options to override the default inferencing behavior:

- `COL_COMPRESS=T` uses hybrid columnar compression to create temporary, intermediate working tables. This option can reduce the space required for such tables, and can improve the performance of the `CREATE_ENTAILMENT` operation with large data sets.

Note: You can specify `COL_COMPRESS=T` only if the storage is on Exadata Storage Server.

- `DISTANCE=T` generates ancillary distance information that is useful for semantic operators.
- `DOP=n` specifies the degree of parallelism for parallel inference, which can improve inference performance. For information about parallel inference, see [Section 2.2.10](#).
- `ENTAIL_ANYWAY=T` forces OWL inferencing to proceed and reuse existing inferred data (entailment) when the entailment has a valid status. By default, `SEM_APIS.CREATE_ENTAILMENT` quits immediately if there is already a valid entailment for the combination of models and rulebases.
- `HASH_PART=n` creates the specified number of hash partitions for internal working tables. (The number must be a power of 2: 2, 4, 8, 16, 32, and so on.) You may want to specify a value if there are many distinct predicates in the semantic data model. In Oracle internal testing on benchmark ontologies, `HASH_PART=32` worked well.
- `INC=T` enables incremental inference for the entailment. For information about incremental inference, see [Section 2.2.9](#).

- `OPT_SAMEAS=T` uses consolidated `owl:sameAs` entailment for the entailment. If you specify this option, you cannot specify `PROOF=T`. For information about optimizing `owl:sameAs` inference, see [Section 2.2.8](#).
- `RAW8=T` uses RAW8 datatypes for the auxiliary inference tables. This option can improve entailment performance by up to 30% in some cases.
- `PROOF=T` generates proof for inferred triples. Do not specify this option unless you need to; it slows inference performance because it causes more data to be generated. If you specify this option, you cannot specify `OPT_SAMEAS=T`.
- `USER_RULES=T` causes any user-defined rules to be applied. If you specify this option, you cannot specify `PROOF=T` or `DISTANCE=T`, and you must accept the default value for the `passes` parameter.

For the `delta_in` parameter, inference performance is best if the value is small compared to the overall size of those models. In a typical scenario, the best results might be achieved when the delta contains fewer than 10,000 triples; however, some tests have shown significant inference performance improvements with deltas as large as 100,000 triples.

For the `label_gen` parameter, if you want to use the default OLS label generator, specify the appropriate `SEM_RDFSA` package constant value from [Table 9–2](#).

Table 9–2 SEM_RDFSA Package Constants for label_gen Parameter

Constant	Description
<code>SEM_RDFSA.LABELGEN_SUBJECT</code>	Label generator that applies the label associated with the inferred triple's subject as the triple's label.
<code>SEM_RDFSA.LABELGEN_PREDICATE</code>	Label generator that applies the label associated with the inferred triple's subject as the triple's label.
<code>SEM_RDFSA.LABELGEN_OBJECT</code>	Label generator that applies the label associated with the inferred triple's subject as the triple's label.
<code>SEM_RDFSA.LABELGEN_RULE</code>	Label generator that applies the label associated with the rule that directly produced the inferred triple as the triple's label. If you specify this option, you must also specify <code>PROOF=T</code> in the <code>options</code> parameter.
<code>SEM_RDFSA.LABELGEN_DOMINATING</code>	Label generator that computes a dominating label of all the available labels for the triple's components (subject, predicate, object, and rule), and applies it as the label for the inferred triple.

Fine-Grained Access Control (VPD and OLS) Considerations

When fine-grained access control is enabled for a specific model using VPD or for the entire network using OLS, only a user with FULL access privileges to the associated policy may create an entailment. Full access privileges to a VPD policy are granted by setting the context attribute defined by the package constant `sem_rdfsa.VPD_FULL_ACCESS` to 1 for the namespace associated with the VPD policy (see [Section 5.1.1, "VPD Policy for RDF Data"](#)). When OLS is enabled, full access privileges to the OLS policy are granted using the `SA_USER_ADMIN.SET_USER_PRIVS` procedure. VPD policy is automatically enforced for any entailment created using at least one VPD enabled RDF model. As discussed in [Section 5.1.1](#), the RDF metadata associated with the VPD policy may need to be maintained using the newly inferred data to ensure that the predefined VPD policies are not circumvented using inferred data.

Inferred triples accessed through generated labels might not be same as conceptual triples inferred directly from the user accessible triples and rules. The labels generated using a subset of triple components may be weaker than intended. For example, one of

the antecedents for the inferred triple may have a higher label than any of the components of the triple. When the label is generated based on just the triple components, end users with no access to one of the antecedents may still have access to the inferred triple. Even when the antecedents are used for custom label generation, the generated label may be stronger than intended. The inference process is not exhaustive, and information pertaining to any alternate ways of inferring the same triple is not available. So, the label generated using a given set of antecedents may be too strong, because the user with access to all the triples in the alternate path could infer the triple with lower access.

Even when generating a label that dominates all its components and antecedents, the label may not be precise. This is the case when labels considered for dominating relationship have non-overlapping group information. For example, consider two labels `L:C:NY` and `L:C:NH` where `L` is a level, `C` is a component and `NY` and `NH` are two groups. A simple label that dominates these two labels is `L:C:NY, NH`, and a true supremum for the two labels is `L:C:US`, where `US` is parent group for both `NY` and `NH`. Unfortunately, neither of these two dominating labels is precise for the triple inferred from the triples with first two labels. If `L:C:NY, NH` is used for the inferred triple, a user with membership in either of these groups has access to the inferred triple, whereas the same user does not have access to one of its antecedents. On the other hand, if `L:C:US` is used for the inferred triple, a user with membership in both the groups and not in the `US` group will not be able to access the inferred triple, whereas that user could infer the triple by directly accessing its components and antecedents.

Because of these unique challenges with inferred triples, extra caution must be taken when choosing or implementing the label generator.

See also the OLS example in the Examples section.

Examples

The following example creates an entailment named `OWLTST_IDX` using the `OWLPrime` rulebase, and it causes proof to be generated for inferred triples.

```
EXECUTE sem_apis.create_entailment('owlstst_idx', sem_models('owlstst'), sem_
rulebases('OWLPRIME'), SEM_APIS.REACH_CLOSURE, null, 'PROOF=T');
```

The following example assumes an OLS environment. It creates a rulebase with a rule, and it creates an entailment.

```
-- Create an entailment with a rule. --
exec sdo_rdf_inference.create_entailment('contracts_rb');

insert into mdsys.rdf_r_contracts_rb values (
  'projectLedBy', '(?x :drivenBy ?y) (?y :hasVP ?z)', NULL,
  '(?x :isLedBy ?z)',
  SDO_RDF_Aliases(SDO_RDF_Alias('', 'http://www.myorg.com/pred/')));

-- Assign sensitivity label for the predicate to be inferred. --
-- The predicate label may be set globally or it can be assign to --
-- the one or the models used to infer the data - e.g: CONTRACTS.
begin
  sem_rdfsa.set_predicate_label(
    model_name   => 'rdf$global',
    predicate    => 'http://www.myorg.com/pred/isLedBy',
    label_string => 'TS:US_SPCL');
end;
/
```

```
-- Create index with a specific label generator. --
begin
  sem_apis.create_entailment(
    entailment_name_in => 'contracts_inf',
    models_in          => SDO_RDF_Models('contracts'),
    rulebases_in       => SDO_RDF_Rulebases('contracts_rb'),
    options             => 'USER_RULES=T',
    label_gen          => sem_rdfsa.LABELGEN_PREDICATE);
end;
/

-- Check for any label exceptions and update them accordingly. --
update mdsys.rdfi_contracts_inf set ctxt1 = 1100 where ctxt1 = -1;

-- The new entailment is now ready for use in SEM_MATCH queries. --
```

SEM_APIS.CREATE_RULEBASE

Format

```
SEM_APIS.CREATE_RULEBASE(  
    rulebase_name IN VARCHAR2);
```

Description

Creates a rulebase.

Parameters

rulebase_name
Name of the rulebase.

Usage Notes

This procedure creates a user-defined rulebase. After creating the rulebase, you can add rules to it. To cause the rules in the rulebase to be applied in a query of RDF data, you can specify the rulebase in the call to the SEM_MATCH table function.

Rules and rulebases are explained in [Section 1.3.6](#). The SEM_MATCH table function is described in [Section 1.6](#),

Examples

The following example creates a rulebase named family_rb. (It is an excerpt from [Example 1–25](#) in [Section 1.10.2](#).)

```
EXECUTE SEM_APIS.CREATE_RULEBASE('family_rb');
```

SEM_APIS.CREATE_SEM_MODEL

Format

```
SEM_APIS.CREATE_SEM_MODEL(  
    model_name      IN VARCHAR2,  
    table_name      IN VARCHAR2,  
    column_name     IN VARCHAR2,  
    model_tablespace IN VARCHAR2 DEFAULT NULL);
```

Description

Creates a semantic technology model.

Parameters

model_name

Name of the model.

table_name

Name of the table to hold references to semantic technology data for this model.

column_name

Name of the column of type SDO_RDF_TRIPLE_S in `table_name`.

model_tablespace

Name of the tablespace for the tables and other database objects used by Oracle to support this model. The default value is the tablespace that was specified in the call to the [SEM_APIS.CREATE_SEM_NETWORK](#) procedure.

Usage Notes

You must create the table to hold references to semantic technology data before calling this procedure to create the semantic technology model. For more information, see [Section 1.9](#).

This procedure adds the model to the MDSYS.SEM_MODEL\$ view, which is described in [Section 1.3.1](#).

This procedure is the only supported way to create a model. Do not use SQL INSERT statements with the MDSYS.SEM_MODEL\$ view.

To delete a model, use the [SEM_APIS.DROP_SEM_MODEL](#) procedure.

Examples

The following example creates a semantic technology model named `articles`. References to the triple data for the model will be stored in the TRIPLE column of the ARTICLES_RDF_DATA table. (This example is an excerpt from [Example 1-24](#) in [Section 1.10.2](#).)

```
EXECUTE SEM_APIS.CREATE_SEM_MODEL('articles', 'articles_rdf_data', 'triple');
```

The definition of the ARTICLES_RDF_DATA table is as follows:

```
CREATE TABLE articles_rdf_data (id NUMBER, triple SDO_RDF_TRIPLE_S);
```

SEM_APIS.CREATE_SEM_NETWORK

Format

```
SEM_APIS.CREATE_SEM_NETWORK(  
    tablespace_name IN VARCHAR2
```

Description

Creates structures for persistent storage of semantic data.

Parameters

tablespace_name

Name of the tablespace to be used for tables created by this procedure. This tablespace will be the default for all models that you create, although you can override the default when you create a model by specifying the `model_tablespace` parameter in the call to the [SEM_APIS.CREATE_SEM_MODEL](#) procedure.

Usage Notes

This procedure creates system tables and other database objects used for semantic technology support.

You should create a tablespace for the semantic technology system tables and specify the tablespace name in the call to this procedure. (You should *not* specify the `SYSTEM` tablespace.) The size needed for the tablespace that you create will depend on the amount of semantic technology data you plan to store.

You must connect to the database as a user with DBA privileges in order to call this procedure, and you should call the procedure only once for the database.

To drop these structures for persistent storage of semantic data, you must connect as a user with DBA privileges and call the [SEM_APIS.DROP_SEM_NETWORK](#) procedure.

Examples

The following example creates a tablespace for semantic technology system tables and creates structures for persistent storage of semantic data in this tablespace.

```
CREATE TABLESPACE rdf_tblspace  
    DATAFILE '/oradata/orcl/rdf_tblspace.dat' SIZE 1024M REUSE  
    AUTOEXTEND ON NEXT 256M MAXSIZE UNLIMITED  
    SEGMENT SPACE MANAGEMENT AUTO;  
.  
.  
EXECUTE SEM_APIS.CREATE_SEM_NETWORK('rdf_tblspace');
```

SEM_APIS.CREATE_VIRTUAL_MODEL

Format

```
SEM_APIS.CREATE_VIRTUAL_MODEL(  
    vm_name IN VARCHAR2,  
    models   IN SEM_MODELS,  
    rulebases IN SEM_RULEBASES DEFAULT NULL,  
    options  IN VARCHAR2 DEFAULT NULL);
```

Description

Creates a virtual model containing the specified semantic models and rulebases.

Parameters

vm_name

Name of the virtual model to be created.

models

One or more semantic model names. Its data type is SEM_MODELS, which has the following definition: TABLE OF VARCHAR2 (25) . At least one semantic model must be specified.

rulebases

One or more rulebase names. Its data type is SEM_RULEBASES, which has the following definition: TABLE OF VARCHAR2 (25) . If this parameter is null, no rulebases are included in the virtual model definition. Rules and rulebases are explained in [Section 1.3.6](#).

options

(Reserved for future use.)

Usage Notes

For an explanation of virtual models, including usage information, see [Section 1.3.8](#).

An entailment must exist for each specified combination of semantic model and rulebase.

To create a virtual model, you must either be (A) the owner of each specified model and any corresponding entailments, or (B) a user with DBA privileges.

This procedure creates views with names in the following format:

- SEMV_ *vm_name*, which corresponds to a UNION ALL of the triples in each model and entailment. This view may contain duplicates.
- SEMU_ *vm_name*, which corresponds to a UNION of the triples in each model and entailment. This view will not contain duplicates (thus, the *U* in SEMU indicates *unique*).

However, the SEMU_ *vm_name* view is not created if the virtual model contains only one semantic model and no entailment.

To use the example in [Section 1.3.8](#) of a virtual model vm1 created from models m1, m2, m3, and with an entailment created for m1, m2 ,and m3 using the OWLPrime

rulebase, this procedure will create the following two views (assuming that m1, m2, and m3, and the OWLPRIME entailment have internal model_id values 1, 2, 3, 4):

```
CREATE VIEW MDSYS.SEMV_VM1 AS
  SELECT start_node_id, p_value_id, canon_end_node_id, end_node_id
  FROM MDSYS.rdf_link$
  WHERE model_id IN (1, 2, 3, 4);

CREATE VIEW MDSYS.SEMU_VM1 AS
  SELECT start_node_id, p_value_id, canon_end_node_id, MAX(end_node_id)
  FROM MDSYS.rdf_link$
  WHERE model_id IN (1, 2, 3, 4)
  GROUP BY start_node_id, p_value_id, canon_end_node_id;
```

The user that invokes this procedure will be the owner of the virtual model and will have SELECT WITH GRANT privileges on the SEMU_ *vm_name* and SEMV_ *vm_name* views. To query the corresponding virtual model, a user must have select privileges on these views.

Examples

The following example creates a virtual model named VM1.

```
EXECUTE sem_apis.create_virtual_model('VM1', sem_models('model_1', 'model_2'),
sem_rulebases('OWLPRIME'));
```

SEM_APIS.DISABLE_CHANGE_TRACKING

Format

```
SEM_APIS.DISABLE_CHANGE_TRACKING(  
    models_in IN SEM_MODELS);
```

Description

Disables change tracking for a specified set of models.

Parameters

models_in

One or more model names. Its data type is SEM_MODELS, which has the following definition: TABLE OF VARCHAR2 (25)

Usage Notes

Disabling change tracking on a model automatically disables incremental inference on all entailment that use the model.

To use this procedure, you must be the owner of the specified model, and incremental inference must have been previously enabled.

For an explanation of incremental inference, including usage information, see [Section 2.2.9](#).

Examples

The following example disables change tracking for the family model.

```
EXECUTE sem_apis.disable_change_tracking(sem_models('family'));
```

SEM_APIS.DISABLE_INC_INFERENCE

Format

```
SEM_APIS.DISABLE_INC_INFERENCE(  
    entailment_name IN VARCHAR2);
```

Description

Disables incremental inference for a specified entailment (rules index).

Parameters

entailment_name

Name of the entailment for which to disable incremental inference.

Usage Notes

To use this procedure, you must be the owner of the specified entailment, and incremental inference must have been previously enabled by the [SEM_APIS.ENABLE_INC_INFERENCE](#) procedure.

Calling this procedure automatically disables change tracking for all models owned by the invoking user that were having changes tracked only because of this particular inference.

For an explanation of incremental inference, including usage information, see [Section 2.2.9](#).

Examples

The following example enables incremental inference for the entailment named RDFS_RIX_FAMILY.

```
EXECUTE sem_apis.disable_inc_inference('rdfs_rix_family');
```

SEM_APIS.DROP_ENTAILMENT

Format

```
SEM_APIS.DROP_ENTAILMENT(  
    entailment_name_in IN VARCHAR2);
```

Description

Drops (deletes) an entailment (rules index).

Parameters

entailment_name_in

Name of the entailment to be deleted.

Usage Notes

You can use this procedure to delete an entailment that you created using the [SEM_APIS.CREATE_ENTAILMENT](#) procedure.

Examples

The following example deletes a entailment named OWLTST_IDX.

```
EXECUTE sem_apis.drop_entailment('owlstst_idx');
```

SEM_APIS.DROP_RULEBASE

Format

```
SEM_APIS.DROP_RULEBASE(  
    rulebase_name IN VARCHAR2);
```

Description

Deletes a rulebase.

Parameters

rulebase_name
Name of the rulebase.

Usage Notes

This procedure deletes the specified rulebase, making it no longer available for use in calls to the SEM_MATCH table function. For information about rulebases, see [Section 1.3.6](#).

Only the creator of a rulebase can delete the rulebase.

Examples

The following example drops the rulebase named `family_rb`.

```
EXECUTE SEM_APIS.DROP_RULEBASE('family_rb');
```

SEM_APIS.DROP_SEM_INDEX

Format

```
SEM_APIS.DROP_SEM_INDEX(  
    index_code IN VARCHAR2);
```

Description

Drops a semantic network index on the models and entailments of the semantic network.

Parameters

index_code

Index code string. Must match the `index_code` value that was specified in an earlier call to the [SEM_APIS.ADD_SEM_INDEX](#) procedure.

Usage Notes

For an explanation of semantic network indexes, see [Section 1.8](#).

Examples

The following example drops a semantic network index with the index code string `pCSM` on the models and entailments of the semantic network.

```
EXECUTE SEM_APIS.DROP_SEM_INDEX('pCSM');
```

SEM_APIS.DROP_SEM_MODEL

Format

```
SEM_APIS.DROP_SEM_MODEL(  
    model_name IN VARCHAR2);
```

Description

Drops (deletes) a semantic technology model.

Parameters

model_name
Name of the model.

Usage Notes

This procedure deletes the model from the MDSYS.SEM_MODEL\$ view, which is described in [Section 1.3.1](#).

This procedure is the only supported way to delete a model. Do not use SQL DELETE statements with the MDSYS.SEM_MODEL\$ view.

Only the creator of a model can delete the model.

Examples

The following example drops the semantic technology model named `articles`.

```
EXECUTE SEM_APIS.DROP_SEM_MODEL('articles');
```

SEM_APIS.DROP_SEM_NETWORK

Format

```
SEM_APIS.DROP_SEM_NETWORK(  
    cascade IN BOOLEAN DEFAULT FALSE);
```

Description

Removes structures used for persistent storage of semantic data.

Parameters

cascade

TRUE drops any existing semantic technology models and rulebases, and removes structures used for persistent storage of semantic data; FALSE (the default) causes the operation to fail if any semantic technology models or rulebases exist.

Usage Notes

To remove structures used for persistent storage of semantic data, you must connect as a user with DBA privileges and call this procedure.

If any version-enabled models exist, this procedure will fail regardless of the value of the *cascade* parameter.

Examples

The following example removes structures used for persistent storage of semantic data.

```
EXECUTE SEM_APIS.DROP_SEM_NETWORK;
```

SEM_APIS.DROP_USER_INFERENCE_OBJS

Format

```
SEM_APIS.DROP_USER_INFERENCE_OBJS(  
    uname IN VARCHAR2);
```

Description

Drops (deletes) all rulebases and entailments owned by a specified database user.

Parameters

uname

Name of a database user. (This value is case-sensitive; for example, HERMAN and herman are considered different users.)

Usage Notes

You must have sufficient privileges to delete rules and rulebases for the specified user.

This procedure does not delete the database user. It deletes only RDF rulebases and entailments owned by that user.

Examples

The following example deletes all rulebases and entailments owned by user SCOTT.

```
EXECUTE SEM_APIS.DROP_USER_INFERENCE_OBJS('SCOTT');
```

PL/SQL procedure successfully completed.

SEM_APIS.DROP_VIRTUAL_MODEL

Format

```
SEM_APIS.DROP_VIRTUAL_MODEL(  
    vm_name IN VARCHAR2);
```

Description

Drops (deletes) a virtual model.

Parameters

vm_name
Name of the virtual model to be deleted.

Usage Notes

You can use this procedure to delete a virtual model that you created using the [SEM_APIS.CREATE_VIRTUAL_MODEL](#) procedure. A virtual model is deleted automatically if any of its component models, rulebases, or entailment are deleted.

To use this procedure, you must be the owner of the specified virtual model.

For an explanation of virtual models, including usage information, see [Section 1.3.8](#).

Examples

The following example deletes a virtual model named VM1.

```
EXECUTE sem_apis.drop_virtual_model('VM1');
```

SEM_APIS.ENABLE_CHANGE_TRACKING

Format

```
SEM_APIS.ENABLE_CHANGE_TRACKING(  
    models_in IN SEM_MODELS);
```

Description

Enables change tracking for a specified set of models.

Parameters

models_in

One or more model names. Its data type is SEM_MODELS, which has the following definition: TABLE OF VARCHAR2 (25)

Usage Notes

Change tracking must be enabled on a model before incremental inference can be enabled on any entailments that use the model.

To use this procedure, you must be the owner of the specified model or models.

If the owner of an entailment is also an owner of any underlying models, then enabling incremental inference on the entailment (by calling the [SEM_APIS.ENABLE_INC_INFERENCE](#) procedure) automatically enables change tracking on those models owned by that user.

To disable change tracking for a set of models, use the [SEM_APIS.DISABLE_CHANGE_TRACKING](#) procedure.

For an explanation of incremental inference, including usage information, see [Section 2.2.9](#).

Examples

The following example enables change tracking for the family model.

```
EXECUTE sem_apis.enable_change_tracking(sem_models('family'));
```

SEM_APIS.ENABLE_INC_INFERENCE

Format

```
SEM_APIS.ENABLE_INC_INFERENCE(  
    entailment_name IN VARCHAR2);
```

Description

Enables incremental inference for a specified entailment (rules index).

Parameters

entailment_name

Name of the entailment for which to enable incremental inference.

Usage Notes

To use this procedure, you must be the owner of the specified entailment.

Before this procedure is executed, all underlying models involved in the entailment must have change tracking enabled. If the owner of the entailment is also an owner of any underlying models, calling this procedure automatically enables change tracking on those models. However, if some underlying model are not owned by the owner of the entailment, the appropriate model owners must first call the [SEM_APIS.ENABLE_CHANGE_TRACKING](#) procedure to enable change tracking on those models.

To disable incremental inference for an entailment, use the [SEM_APIS.DISABLE_INC_INFERENCE](#) procedure.

For an explanation of incremental inference, including usage information, see [Section 2.2.9](#).

Examples

The following example enables incremental inference for the entailment named RDFS_RIX_FAMILY.

```
EXECUTE sem_apis.enable_inc_inference('rdfs_rix_family');
```

SEM_APIS.GET_CHANGE_TRACKING_INFO

Format

```
SEM_APIS.GET_CHANGE_TRACKING_INFO(
    model_name      IN VARCHAR2,
    enabled         OUT BOOLEAN,
    tracking_start_time OUT TIMESTAMP);
```

Description

Returns change tracking information for a model.

Parameters

model_name

Name of the semantic technology model.

enabled

Boolean value returned by the procedure: `TRUE` if change tracking is enabled for the model, or `FALSE` if change tracking is not enabled for the model.

timestamp

Timestamp indicating when change tracking was enabled for the model (if it is enabled).

Usage Notes

The `model_name` value must match a value in the `MODEL_NAME` column in the `MDSYS.SEM_MODEL$` view, which is described in [Section 1.3.1](#).

To enable change tracking for a set of models, use the [SEM_APIS.ENABLE_CHANGE_TRACKING](#) procedure.

For an explanation of incremental inference, including usage information, see [Section 2.2.9](#).

Examples

The following example displays change tracking information for a model.

```
DECLARE
    bEnabled boolean;
    tsEnabled timestamp;

BEGIN
    EXECUTE IMMEDIATE 'create table m1 (t SDO_RDF_TRIPLE_S)';
    sem_apis.create_sem_model('m1', 'm1', 't');

    sem_apis.enable_change_tracking(sem_models('m1'));

    sem_apis.get_change_tracking_info('m1', bEnabled, tsEnabled);
    dbms_output.put_line('is enabled:' || case when bEnabled then 'true' else
'false' end);
    dbms_output.put_line('enabled at:' || tsEnabled);
END;
/
```

SEM_APIS.GET_INC_INF_INFO

Format

```
SEM_APIS.GET_INC_INF_INFO(  
    entailment_name IN VARCHAR2,  
    enabled          OUT BOOLEAN,  
    prev_inf_start_time OUT TIMESTAMP);
```

Description

Returns incremental inference information for an entailment.

Parameters

entailment_name

Name of the entailment.

enabled

Boolean value returned by the procedure: `TRUE` if incremental inference is enabled for the entailment, or `FALSE` if incremental inference is not enabled for the entailment.

timestamp

Timestamp indicating when the entailment was most recently updated (if incremental inference is enabled).

Usage Notes

To enable incremental inference for an entailment, use the [SEM_APIS.ENABLE_INC_INFERENCE](#) procedure.

For an explanation of incremental inference, including usage information, see [Section 2.2.9](#).

Examples

The following example displays incremental inference information for an entailment.

```
DECLARE  
    bEnabled boolean;  
    tsEnabled timestamp;  
  
DECLARE  
    EXECUTE IMMEDIATE 'create table m1 (t SDO_RDF_TRIPLE_S)';  
    sem_apis.create_sem_model('m1', 'm1', 't');  
  
    sem_apis.create_entailment('m1_inf', sem_models('m1'),  
sem_rulebases('owlprime'), null, null, 'INC=T');  
  
    sem_apis.get_inc_inf_info('m1_inf', bEnabled, tsEnabled);  
    dbms_output.put_line('is enabled: ' || case when bEnabled then 'true' else  
'false'  
end);  
    dbms_output.put_line('enabled at: ' || tsEnabled);  
END  
/
```

SEM_APIS.GET_MODEL_ID

Format

```
SEM_APIS.GET_MODEL_ID(  
    model_name IN VARCHAR2  
    ) RETURN NUMBER;
```

Description

Returns the model ID number of a semantic technology model.

Parameters

model_name
Name of the semantic technology model.

Usage Notes

The `model_name` value must match a value in the `MODEL_NAME` column in the `MDSYS.SEM_MODEL$` view, which is described in [Section 1.3.1](#).

Examples

The following example returns the model ID number for the model named `articles`. (This example is an excerpt from [Example 1–24](#) in [Section 1.10.2](#).)

```
SELECT SEM_APIS.GET_MODEL_ID('articles') AS model_id FROM DUAL;
```

```
MODEL_ID  
-----  
1
```

SEM_APIS.GET_MODEL_NAME

Format

```
SEM_APIS.GET_MODEL_NAME(  
    model_id IN NUMBER  
    ) RETURN VARCHAR2;
```

Description

Returns the model name of a semantic technology model.

Parameters

model_id
ID number of the semantic technology model.

Usage Notes

The `model_id` value must match a value in the `MODEL_ID` column in the `MDSYS.SEM_MODEL$` view, which is described in [Section 1.3.1](#).

Examples

The following example returns the model ID number for the model with the ID value of 1. This example is an excerpt from [Example 1–24](#) in [Section 1.10.2](#).)

```
SQL> SELECT SEM_APIS.GET_MODEL_NAME(1) AS model_name FROM DUAL;
```

```
MODEL_NAME
```

```
-----  
ARTICLES
```

SEM_APIS.GET_TRIPLE_ID

Format

```
SEM_APIS.GET_TRIPLE_ID(  
    model_id IN NUMBER,  
    subject  IN VARCHAR2,  
    property IN VARCHAR2,  
    object   IN VARCHAR2  
    ) RETURN VARCHAR2;
```

or

```
SEM_APIS.GET_TRIPLE_ID(  
    model_name IN VARCHAR2,  
    subject    IN VARCHAR2,  
    property   IN VARCHAR2,  
    object     IN VARCHAR2  
    ) RETURN VARCHAR2;
```

Description

Returns the ID of a triple in the specified semantic technology model, or a null value if the triple does not exist.

Parameters

model_id

ID number of the semantic technology model. Must match a value in the MODEL_ID column of the MDSYS.SEM_MODEL\$ view, which is described in [Section 1.3.1](#).

model_name

Name of the semantic technology model. Must match a value in the MODEL_NAME column of the MDSYS.SEM_MODEL\$ view, which is described in [Section 1.3.1](#).

subject

Subject. Must match a value in the VALUE_NAME column of the MDSYS.RDF_VALUE\$ table, which is described in [Section 1.3.2](#).

property

Property. Must match a value in the VALUE_NAME column of the MDSYS.RDF_VALUE\$ table, which is described in [Section 1.3.2](#).

object

Object. Must match a value in the VALUE_NAME column of the MDSYS.RDF_VALUE\$ table, which is described in [Section 1.3.2](#).

Usage Notes

This function has two formats, enabling you to specify the semantic technology model by its model number or its name.

Examples

The following example returns the ID number of a triple. (This example is an excerpt from [Example 1-24](#) in [Section 1.10.2](#).)

```
SELECT SEM_APIS.GET_TRIPLE_ID(  
  'articles',  
  'http://nature.example.com/Article2',  
  'http://purl.org/dc/terms/references',  
  'http://nature.example.com/Article3') AS RDF_triple_id FROM DUAL;
```

```
RDF_TRIPLE_ID
```

```
-----  
2_9F2BFF05DA0672E_90D25A8B08C653A_46854582F25E8AC5
```

SEM_APIS.GETV\$DATETIMETZVAL

Format

```
SEM_APIS.GETV$DATETIMETZVAL(  
    value_type    IN VARCHAR2,  
    vname_prefix  IN VARCHAR2,  
    vname_suffix  IN VARCHAR2,  
    literal_type   IN VARCHAR2,  
    language_type IN VARCHAR2,  
    ) RETURN NUMBER;
```

Description

Returns a `TIMESTAMP WITH TIME ZONE` value for `xsd:dateTime` typed literals, and returns a null value for all other RDF terms. Greenwich Mean Time is used as the default time zone for `xsd:dateTime` values without time zones.

Parameters

value_type

Type of the RDF term.

vname_prefix

Prefix value of the RDF term.

vname_suffix

Suffix value of the RDF term.

literal_type

Literal type of the RDF term.

language_type

Language type of the RDF term.

Usage Notes

For better performance, consider creating a function-based index on this function. For more information, see [Section 1.6.5.2](#).

Examples

The following example returns `TIMESTAMP WITH TIME ZONE` values for all `xsd:dateTime` literals in the `MDSYS.RDF_VALUE$` table:

```
SELECT SEM_APIS.GETV$DATETIMETZVAL(value_type, vname_prefix, vname_suffix,  
    literal_type, language_type)  
FROM MDSYS.RDF_VALUE$;
```

SEM_APIS.GETV\$DATETZVAL

Format

```
SEM_APIS.GETV$DATETZVAL(  
    value_type    IN VARCHAR2,  
    vname_prefix  IN VARCHAR2,  
    vname_suffix  IN VARCHAR2,  
    literal_type   IN VARCHAR2,  
    language_type IN VARCHAR2,  
) RETURN TIMESTAMP WITH TIME ZONE;
```

Description

Returns a `TIMESTAMP WITH TIME ZONE` value for `xsd:date` typed literals, and returns a null value for all other RDF terms. Greenwich Mean Time is used as the default time zone for `xsd:date` values without time zones.

Parameters

value_type

Type of the RDF term.

vname_prefix

Prefix value of the RDF term.

vname_suffix

Suffix value of the RDF term.

literal_type

Literal type of the RDF term.

language_type

Language type of the RDF term.

Usage Notes

For better performance, consider creating a function-based index on this function. For more information, see [Section 1.6.5.2](#).

Examples

The following example returns `TIMESTAMP WITH TIME ZONE` values for all `xsd:date` literals in the `MDSYS.RDF_VALUE$` table:

```
SELECT SEM_APIS.GETV$DATETZVAL(value_type, vname_prefix, vname_suffix,  
    literal_type, language_type)  
FROM MDSYS.RDF_VALUE$;
```

SEM_APIS.GETV\$NUMERICVAL

Format

```
SEM_APIS.GETV$NUMERICVAL(  
    value_type    IN VARCHAR2,  
    vname_prefix  IN VARCHAR2,  
    vname_suffix  IN VARCHAR2,  
    literal_type   IN VARCHAR2,  
    language_type IN VARCHAR2,  
) RETURN NUMBER;
```

Description

Returns a numeric value for XML Schema numeric typed literals, and returns a null value for all other RDF terms.

Parameters

value_type

Type of the RDF term.

vname_prefix

Prefix value of the RDF term.

vname_suffix

Suffix value of the RDF term.

literal_type

Literal type of the RDF term.

language_type

Language type of the RDF term.

Usage Notes

For better performance, consider creating a function-based index on this function. For more information, see [Section 1.6.5.2](#).

Examples

The following example returns numeric values for all numeric literals in the MDSYS.RDF_VALUE\$ table:

```
SELECT SEM_APIS.GETV$NUMERICVAL(value_type, vname_prefix, vname_suffix,  
    literal_type, language_type)  
FROM MDSYS.RDF_VALUE$;
```

SEM_APIS.GETV\$STRINGVAL

Format

```
SEM_APIS.GETV$STRINGVAL(  
    value_type    IN VARCHAR2,  
    vname_prefix  IN VARCHAR2,  
    vname_suffix  IN VARCHAR2,  
    literal_type   IN VARCHAR2,  
    language_type IN VARCHAR2,  
) RETURN TIMESTAMP WITH TIME ZONE;
```

Description

Returns a VARCHAR2 string of the lexical form of plain literals and xsd:string typed literals, and returns a null value for all other RDF terms. CHR(0) is returned for empty literals.

Parameters

value_type

Type of the RDF term.

vname_prefix

Prefix value of the RDF term.

vname_suffix

Suffix value of the RDF term.

literal_type

Literal type of the RDF term.

language_type

Language type of the RDF term.

Usage Notes

For better performance, consider creating a function-based index on this function. For more information, see [Section 1.6.5.2](#).

Examples

The following example returns lexical values for all plain literals and xsd:string literals in the MDSYS.RDF_VALUE\$ table:

```
SELECT SEM_APIS.GETV$STRINGVAL(value_type, vname_prefix, vname_suffix,  
    literal_type, language_type)  
FROM MDSYS.RDF_VALUE$;
```

SEM_APIS.GETV\$TIMETZVAL

Format

```
SEM_APIS.GETV$TIMETZVAL(  
    value_type    IN VARCHAR2,  
    vname_prefix  IN VARCHAR2,  
    vname_suffix  IN VARCHAR2,  
    literal_type   IN VARCHAR2,  
    language_type IN VARCHAR2,  
    ) RETURN TIMESTAMP WITH TIME ZONE;
```

Description

Returns a `TIMESTAMP WITH TIME ZONE` value for `xsd:time` typed literals, and returns a null value for all other RDF terms. Greenwich Mean Time is used as the default time zone for `xsd:time` values without time zones. 2009-06-26 is used as the default date in all the generated `TIMESTAMP WITH TIME ZONE` values.

Parameters

value_type

Type of the RDF term.

vname_prefix

Prefix value of the RDF term.

vname_suffix

Suffix value of the RDF term.

literal_type

Literal type of the RDF term.

language_type

Language type of the RDF term.

Usage Notes

For better performance, consider creating a function-based index on this function. For more information, see [Section 1.6.5.2](#).

Because `xsd:time` values include only a time but not a date, the returned `TIMESTAMP WITH TIME ZONE` values (which include a date component) have 2009-06-26 added as the date. This is done so that the returned values can be indexed internally, and so that the date is the same for all of them.

Examples

The following example returns `TIMESTAMP WITH TIME ZONE` values (using the default 2009-06-26 for the date) for all `xsd:time` literals in the `MDSYS.RDF_VALUE$` table. (

```
SELECT SEM_APIS.GETV$DATETIMETZVAL(value_type, vname_prefix, vname_suffix,  
    literal_type, language_type)
```

```
FROM MDSYS.RDF_VALUE$;
```

SEM_APIS.IS_TRIPLE

Format

```
SEM_APIS.IS_TRIPLE(  
    model_id IN NUMBER,  
    subject  IN VARCHAR2,  
    property IN VARCHAR2,  
    object   IN VARCHAR2) RETURN VARCHAR2;
```

or

```
SEM_APIS.IS_TRIPLE(  
    model_name IN VARCHAR2,  
    subject    IN VARCHAR2,  
    property   IN VARCHAR2,  
    object     IN VARCHAR2) RETURN VARCHAR2;
```

Description

Checks if a statement is an existing triple in the specified model in the database.

Parameters

model_id

ID number of the semantic technology model. Must match a value in the MODEL_ID column of the MDSYS.SEM_MODEL\$ view, which is described in [Section 1.3.1](#).

model_name

Name of the semantic technology model. Must match a value in the MODEL_NAME column of the MDSYS.SEM_MODEL\$ view, which is described in [Section 1.3.1](#).

subject

Subject. Must match a value in the VALUE_NAME column of the MDSYS.RDF_VALUE\$ table, which is described in [Section 1.3.2](#).

property

Property. Must match a value in the VALUE_NAME column of the MDSYS.RDF_VALUE\$ table, which is described in [Section 1.3.2](#).

object

Object. Must match a value in the VALUE_NAME column of the MDSYS.RDF_VALUE\$ table, which is described in [Section 1.3.2](#).

Usage Notes

This function returns the string value FALSE, TRUE, or TRUE (EXACT):

- FALSE means that the statement is not a triple in the specified model the database.
- TRUE means that the statement matches the value of a triple or is the canonical representation of the value of a triple in the specified model the database.

- TRUE (EXACT) means that the specified subject, property, and object values have exact matches in a triple in the specified model in the database.

Examples

The following checks if a statement is a triple in the database. In this case, there is an exact match. (This example is an excerpt from [Example 1–24](#) in [Section 1.10.2](#).)

```
SELECT SEM_APIS.IS_TRIPLE(  
  'articles',  
  'http://nature.example.com/Article2',  
  'http://purl.org/dc/terms/references',  
  'http://nature.example.com/Article3') AS is_triple FROM DUAL;
```

```
IS_TRIPLE
```

```
-----  
TRUE (EXACT)
```

SEM_APIS.LOOKUP_ENTAILMENT

Format

```
SEM_APIS.LOOKUP_ENTAILMENT (
    models    IN SEM_MODELS,
    rulebases IN SEM_RULEBASES
) RETURN VARCHAR2;
```

Description

Returns the name of the entailment (rules index) based on the specified models and rulebases.

Parameters

models

One or more model names. Its data type is SEM_MODELS, which has the following definition: TABLE OF VARCHAR2 (25)

rulebases

One or more rulebase names. Its data type is SEM_RULEBASES, which has the following definition: TABLE OF VARCHAR2 (25) Rules and rulebases are explained in [Section 1.3.6](#).

Usage Notes

For a rulebase index to be returned, it must be based on all specified models and rulebases.

Examples

The following example finds the entailment that is based on the `family` model and the `RDFS` and `family_rb` rulebases. (It is an excerpt from [Example 1–25](#) in [Section 1.10.2](#).)

```
SELECT SEM_APIS.LOOKUP_ENTAILMENT(SEM_MODELS('family'),
    SEM_RULEBASES('RDFS','family_rb')) AS lookup_entailment FROM DUAL;
```

```
LOOKUP_ENTAILMENT
```

```
-----
RDFS_RIX_FAMILY
```

SEM_APIS.MERGE_MODELS

Format

```
SEM_APIS.MERGE_MODELS(  
    source_model      IN VARCHAR2,  
    destination_model IN VARCHAR2,  
    rebuild_apptab_index IN BOOLEAN DEFAULT TRUE,  
    drop_source_model IN BOOLEAN DEFAULT FALSE,  
    options           IN VARCHAR2 DEFAULT NULL);
```

Description

Inserts the content from a source model into a destination model, and updates the destination application table.

Parameters

source_model

Name of the source model.

destination_model

Name of the destination model.

rebuild_apptab_index

TRUE causes indexes on the destination application table to be rebuilt after the models are merged; FALSE does not rebuild any indexes.

drop_source_model

TRUE causes the source model (`source_model`) to be deleted after the models are merged; FALSE (the default) does not delete the source model.

options

A comma-delimited string of options that overrides the default behavior of the procedure. Currently, only the `DOP` (degree of parallelism) option is supported, to enable parallel execution of this procedure and to specify the degree of parallelism to be associated with the operation.

Usage Notes

Before you merge any models, if you are using positional parameters, check to be sure that you are specifying the correct models for the first and second parameters (source model for the first, destination model for the second). This is especially important if you plan to specify `drop_source_model=TRUE`.

If appropriate, make copies of the destination model or both models before performing the merge. To make a copy of a model, use [SEM_APIS.CREATE_SEM_MODEL](#) to create an empty model with the desired name for the copy, and use `SEM_APIS.MERGE_MODELS` to populate the newly created copy as the destination model.

Some common uses for this procedure include the following:

- If you have read-only access to a model that you want to modify, you can clone that model into an empty model on which you have full access, and then modify this latter model.
- If you want to consolidate multiple models, you can use this procedure as often as necessary to merge the necessary models. Merging all models beforehand and using only the merged model simplifies entailment and can improve entailment performance.

On a multi-core or multi-cpu machine, the `DOP` (degree of parallelism) option can be beneficial. See Examples for an example that uses the `DOP` option.

If the source model is large, you may want to update the optimizer statistics on the destination after the merge operation by calling the [SEM_APIS.ANALYZE_MODEL](#) procedure.

The following considerations apply to the use of this procedure:

- You must be the owner of the destination model and have `SELECT` privilege on the source model. If `drop_second_model=TRUE`, you must also be owner of the source model.
- This procedure cannot be used on `VPD`-enabled or `versioning`-enabled semantic models.
- This procedure is not supported on virtual models (explained in [Section 1.3.8](#)).
- No table constraints are allowed on the destination application table.

Examples

The following example inserts the contents of model `M1` into `M2`.

```
EXECUTE SEM_APIS.MERGE_MODELS('M1', 'M2');
```

The following example inserts the contents of model `M1` into `M2`, and it specifies a degree of parallelism of 4 (up to four parallel threads for execution of the merge operation).

```
EXECUTE SEM_APIS.MERGE_MODELS('M1', 'M2', null, null, 'DOP=4');
```

SEM_APIS.REMOVE_DUPLICATES

Format

```
SEM_APIS.REMOVE_DUPLICATES(  
    model_name      IN VARCHAR2,  
    threshold       IN FLOAT DEFAULT 0.3,  
    rebuild_apptab_index IN BOOLEAN DEFAULT TRUE);
```

Description

Removes duplicate triples from a model.

Parameters

model_name

Name of the model.

threshold

A value to determine how numerous triples must be in order for the removal operation to be performed. This procedure removes triples only if the number of triples in the model exceeds the following formula: $(\text{total-triples} - \text{total-unique-triples} + 0.01) / (\text{total-unique-triples} + 0.01)$. For the default value of 0.3 and a model containing 1000 total triples (including duplicates), duplicate triples would be removed only if the number of duplicates exceeds approximately 230.

The lower the threshold value, the fewer duplicates are needed for the procedure to remove duplicates; the higher the threshold value, the more duplicates are needed for the procedure to remove duplicates.

rebuild_apptab_index

TRUE (the default) causes all usable indexes on tables that were affected by this operation to be rebuilt after the duplicate triples are removed; FALSE does not rebuild any indexes.

Usage Notes

When duplicate triples are removed, all information in the removed rows is lost, including information in columns other than the triple column.

This procedure is not supported on virtual models (explained in [Section 1.3.8](#)).

If the model is empty, or if it contains no duplicate triples or not enough duplicate triples (as computed using the `threshold` value), this procedure does not perform any removal operations.

If there are not enough duplicates (as computed using the `threshold` value) to perform the operation, an informational message is displayed.

Examples

The following example removes duplicate triples in the model named `family`. It accepts the default threshold value of 0.3 and (by default) rebuilds indexes after the duplicates are removed.

```
EXECUTE SEM_APIS.REMOVE_DUPLICATES('family');
```

SEM_APIS.RENAME_ENTAILMENT

Format

```
SEM_APIS.RENAME_ENTAILMENT(  
    old_name IN VARCHAR2,  
    new_name IN VARCHAR2);
```

Description

Renames an entailment (rules index).

Parameters

old_name

Name of the existing entailment to be renamed.

new_name

New name for the entailment.

Usage Notes

(None.)

Examples

The following example renames a entailment named OWLTST_IDX to MY_OWLTST_IDX.

```
EXECUTE sem_apis.rename_entailment('owlstst_idx', 'my_owlstst_idx');
```

SEM_APIS.RENAME_MODEL

Format

```
SEM_APIS.RENAME_MODEL(  
    old_name IN VARCHAR2,  
    new_name IN VARCHAR2);
```

Description

Renames a model.

Parameters

old_name
Name of the existing model to be renamed.

new_name
New name for the model.

Usage Notes

The following considerations apply to the use of this procedure:

- You must be the owner of the existing model.
- This procedure cannot be used on VPD-enabled or versioning-enabled semantic models.
- This procedure is not supported on virtual models (explained in [Section 1.3.8](#)).

Contrast this procedure with [SEM_APIS.SWAP_NAMES](#), which swaps (exchanges) the names of two existing models.

Examples

The following example renames a model named MODEL1 to MODEL2.

```
EXECUTE sem_apis.rename_model('model1', 'model2');
```

SEM_APIS.SWAP_NAMES

Format

```
SEM_APIS.SWAP_NAMES(  
    model1 IN VARCHAR2,  
    model2 IN VARCHAR2);
```

Description

Swaps (exchanges) the names of two existing models.

Parameters

model1

Name of a model.

model2

Name of another model.

Usage Notes

As a result of this procedure, the name of model `model1` is changed to the (old) name of `model2`, and the name of model `model2` is changed to the (old) name of `model1`.

The order of the names does not affect the result. For example, you could specify `TEST` for `model1` and `PRODUCTION` for `model2`, or `PRODUCTION` for `model1` and `TEST` for `model2`, and the result will be the same.

Contrast this procedure with [SEM_APIS.RENAME_MODEL](#), which renames an existing model.

Examples

The following example changes the name of the (old) `TEST` model to `PRODUCTION`, and the name of the (old) `PRODUCTION` model to `TEST`.

```
EXECUTE sem_apis.swap_names('test', 'production');
```

SEM_APIS.VALIDATE_ENTAILMENT

Format

```
SEM_APIS.VALIDATE_ENTAILMENT(  
    models_in      IN SEM_MODELS,  
    rulebases_in   IN SEM_RULEBASES,  
    criteria_in     IN VARCHAR2 DEFAULT NULL,  
    max_conflict   IN NUMBER DEFAULT 100,  
    options        IN VARCHAR2 DEFAULT NULL  
) RETURN RDF_LONGVARCHARARRAY;
```

Description

Validates entailments (rules indexes) that can be used to perform OWL or RDFS inferencing for one or more models.

Parameters

models_in

One or more model names. Its data type is SEM_MODELS, which has the following definition: TABLE OF VARCHAR2 (25)

rulebases_in

One or more rulebase names. Its data type is SEM_RULEBASES, which has the following definition: TABLE OF VARCHAR2 (25) . Rules and rulebases are explained in [Section 1.3.6](#).

criteria_in

A comma-delimited string of validation checks to run. If you do not specify this parameter, by default all of the following checks are run:

- UNSAT: Find unsatisfiable classes.
- EMPTY: Find instances that belong to unsatisfiable classes.
- SYNTAX_S: Find triples whose subject is neither URI nor blank node.
- SYNTAX_P: Find triples whose predicate is not URI.
- SELF_DIF: Find individuals that are different from themselves.
- INST: Find individuals that simultaneously belong to two disjoint classes.
- SAM_DIF: Find pairs of individuals that are same (owl:sameAs) and different (owl:differentFrom) at the same time.

To specify fewer checks, specify a string with only the checks to be performed. For example, `criteria_in => 'UNSAT'` causes the validation process to search only for unsatisfiable classes.

max_conflict

The maximum number of conflicts to find before the validation process stops. The default value is 100.

options

(Not currently used. Reserved for Oracle use.).

Usage Notes

This procedure can be used to detect inconsistencies in the original entailment. For more information, see [Section 2.2.5](#).

This procedure returns a null value if no errors are detected or (if errors are detected) an object of type RDF_LONGVARCHARARRAY, which has the following definition:
VARRAY(32767) OF VARCHAR2(4000)

To create an entailment, use the [SEM_APIS.CREATE_ENTAILMENT](#) procedure.

Examples

For an example of this procedure, see [Example 2-5](#) in [Section 2.2.5](#).

SEM_APIS.VALIDATE_MODEL

Format

```
SEM_APIS.VALIDATE_MODEL(  
    models_in      IN SEM_MODELS,  
    criteria_in    IN VARCHAR2 DEFAULT NULL,  
    max_conflict   IN NUMBER DEFAULT 100,  
    options        IN VARCHAR2 DEFAULT NULL  
    ) RETURN RDF_LONGVARCHARARRAY;
```

Description

Validates one or more models.

Parameters

models_in

One or more model names. Its data type is SEM_MODELS, which has the following definition: TABLE OF VARCHAR2 (25)

criteria_in

A comma-delimited string of validation checks to run. If you do not specify this parameter, by default all of the following checks are run:

- UNSAT: Find unsatisfiable classes.
- EMPTY: Find instances that belong to unsatisfiable classes.
- SYNTAX_S: Find triples whose subject is neither URI nor blank node.
- SYNTAX_P: Find triples whose predicate is not URI.
- SELF_DIF: Find individuals that are different from themselves.
- INST: Find individuals that simultaneously belong to two disjoint classes.
- SAM_DIF: Find pairs of individuals that are same (owl:sameAs) and different (owl:differentFrom) at the same time.

To specify fewer checks, specify a string with only the checks to be performed. For example, `criteria_in => 'UNSAT'` causes the validation process to search only for unsatisfiable classes.

max_conflict

The maximum number of conflicts to find before the validation process stops. The default value is 100.

options

(Not currently used. Reserved for Oracle use.).

Usage Notes

This procedure can be used to detect inconsistencies in the original data model. For more information, see [Section 2.2.5](#).

This procedure returns a null value if no errors are detected or (if errors are detected) an object of type `RDF_LONGVARCHARARRAY`, which has the following definition:
`VARRAY(32767) OF VARCHAR2(4000)`

Examples

The following example validates the model named `family`.

```
SELECT SEM_APIS.VALIDATE_MODEL(SEM_MODELS('family')) FROM DUAL;
```

SEM_APIS.VALUE_NAME_PREFIX

Format

```
SEM_APIS.VALUE_NAME_PREFIX (  
    value_name IN VARCHAR2,  
    value_type IN VARCHAR2  
) RETURN VARCHAR2;
```

Description

Returns the value in the VNAME_PREFIX column for the specified value name and value type pair in the MDSYS.RDF_VALUE\$ table.

Parameters

value_name

Value name. Must match a value in the VALUE_NAME column in the MDSYS.RDF_VALUE\$ table, which is described in [Section 1.3.2](#).

value_type

Value type. Must match a value in the VALUE_TYPE column in the MDSYS.RDF_VALUE\$ table, which is described in [Section 1.3.2](#).

Usage Notes

This function usually causes an index on the MDSYS.RDF_VALUE\$ table to be used for processing a lookup for values, and thus can make a query run faster.

Examples

The following query returns value name portions of all the lexical values in MDSYS.RDF_VALUE\$ table with a prefix value same as that returned by the VALUE_NAME_PREFIX function. This query uses an index on the MDSYS.RDF_VALUE\$ table, thereby providing efficient lookup.

```
SELECT value_name FROM MDSYS.RDF_VALUE$  
    WHERE vname_prefix = SEM_APIS.VALUE_NAME_PREFIX(  
        'http://www.w3.org/1999/02/22-rdf-syntax-ns#type', 'UR');
```

VALUE_NAME

```
-----  
http://www.w3.org/1999/02/22-rdf-syntax-ns#Alt  
http://www.w3.org/1999/02/22-rdf-syntax-ns#Bag  
http://www.w3.org/1999/02/22-rdf-syntax-ns#List  
http://www.w3.org/1999/02/22-rdf-syntax-ns#Property  
http://www.w3.org/1999/02/22-rdf-syntax-ns#Seq  
http://www.w3.org/1999/02/22-rdf-syntax-ns#Statement  
http://www.w3.org/1999/02/22-rdf-syntax-ns#XMLLiteral  
http://www.w3.org/1999/02/22-rdf-syntax-ns#first  
http://www.w3.org/1999/02/22-rdf-syntax-ns#nil  
http://www.w3.org/1999/02/22-rdf-syntax-ns#object  
http://www.w3.org/1999/02/22-rdf-syntax-ns#predicate  
http://www.w3.org/1999/02/22-rdf-syntax-ns#rest  
http://www.w3.org/1999/02/22-rdf-syntax-ns#subject  
http://www.w3.org/1999/02/22-rdf-syntax-ns#type
```

`http://www.w3.org/1999/02/22-rdf-syntax-ns#value`

15 rows selected.

SEM_APIS.VALUE_NAME_SUFFIX

Format

```
SEM_APIS.VALUE_NAME_SUFFIX (  
    value_name IN VARCHAR2,  
    value_type  IN VARCHAR2  
) RETURN VARCHAR2;
```

Description

Returns the value in the VNAME_SUFFIX column for the specified value name and value type pair in the MDSYS.RDF_VALUE\$ table.

Parameters

value_name

Value name. Must match a value in the VALUE_NAME column in the MDSYS.RDF_VALUE\$ table, which is described in [Section 1.3.2](#).

value_type

Value type. Must match a value in the VALUE_TYPE column in the MDSYS.RDF_VALUE\$ table, which is described in [Section 1.3.2](#).

Usage Notes

This function usually causes an index on the MDSYS.RDF_VALUE\$ table to be used for processing a lookup for values, and thus can make a query run faster.

Examples

The following query returns value name portions of all the lexical values in MDSYS.RDF_VALUE\$ table with a suffix value same as that returned by the VALUE_NAME_SUFFIX function. This query uses an index on the MDSYS.RDF_VALUE\$ table, thereby providing efficient lookup.

```
SELECT value_name FROM MDSYS.RDF_VALUE$  
    WHERE vname_suffix = SEM_APIS.VALUE_NAME_SUFFIX(  
        'http://www.w3.org/1999/02/22-rdf-syntax-ns#type', 'UR');
```

```
VALUE_NAME
```

```
-----  
http://www.w3.org/1999/02/22-rdf-syntax-ns#type
```

SEM_PERF Package Subprograms

The SEM_PERF package contains subprograms for examining and enhancing the performance of the Resource Description Framework (RDF) and Web Ontology Language (OWL) support in an Oracle database. To use the subprograms in this chapter, you must understand the conceptual and usage information in [Chapter 1, "Oracle Database Semantic Technologies Overview"](#) and [Chapter 2, "OWL Concepts"](#).

This chapter provides reference information about the subprograms, listed in alphabetical order.

SEM_PERF.GATHER_STATS

Format

```
SEM_PERF.GATHER_STATS();  
    just_on_values_table IN BOOLEAN DEFAULT FALSE,  
    degree                IN NUMBER(38) DEFAULT NULL);
```

Description

Gathers statistics about RDF and OWL tables and their indexes.

Parameters

just_on_values_table

TRUE collects statistics only on the table containing the lexical values of triples; FALSE (the default) collects statistics on all major tables related to the storage of RDF and OWL data.

A value of TRUE reduces the execution time for the procedure; and it may be sufficient if you need only to collect statistics on the values table (for example, if you use other interfaces to collect any other statistics that you might need).

degree

Degree of parallelism. For more information about parallel execution, see *Oracle Database VLDB and Partitioning Guide*.

Usage Notes

To use this procedure, you must connect as a user with permission to execute it. By default, when Spatial is installed as part of Oracle Database, only the MDSYS user can execute this procedure; however execution permission on this procedure can be granted to users as needed.

This procedure collects statistical information that can help you to improve inferencing performance, as explained in [Section 2.2.7](#). This procedure internally calls the DBMS_STATS.GATHER_TABLE_STATS procedure to collect statistics on RDF- and OWL-related tables and their indexes, and stores the statistics in the Oracle Database data dictionary. For information about using the DBMS_STATS package, see *Oracle Database PL/SQL Packages and Types Reference*.

Gathering statistics uses significant system resources, so execute this procedure when it cannot adversely affect essential applications and operations.

Examples

The following example gathers statistics about RDF and OWL related tables and their indexes.

```
EXECUTE SEM_PERF.GATHER_STATS;
```

SEM_RDFCTX Package Subprograms

The SEM_RDFCTX package contains subprograms (functions and procedures) to manage extractor policies and semantic indexes created for documents. To use the subprograms in this chapter, you should understand the conceptual and usage information in [Chapter 4, "Semantic Indexing for Documents"](#).

This chapter provides reference information about the subprograms, listed in alphabetical order.

SEM_RDFCTX.CREATE_POLICY

Format

```
SEM_RDFCTX.CREATE_POLICY(  
    policy_name IN VARCHAR2,  
    extractor    mdsys.rdfctx_extractor,  
    preferences  sys.XMLType DEFAULT NULL);
```

or

```
SEM_RDFCTX.CREATE_POLICY(  
    policy_name IN VARCHAR2,  
    base_policy IN VARCHAR2,  
    user_models mdsys.rdf_models default null);
```

Description

Creates an extractor policy. (The first format is for a base policy; the second format is for a policy that is dependent on a base policy.)

Parameters

policy_name

Name of the extractor policy.

extractor

An instance of a subtype of the `RDFCTX_EXTRACTOR` type that encapsulates the extraction logic for the information extractor.

preferences

Any preferences associated with the policy.

base_policy

Base extractor policy for a dependent policy.

user_models

List of user models for a dependent policy.

Usage Notes

An extractor policy created using this procedure determines the characteristics of a semantic index that is created using the policy. Each extractor policy refers to an instance of an extractor type, either directly or indirectly. An extractor policy with a direct reference to an extractor type instance can be used to compose other extractor policies that include additional RDF models for ontologies.

An instance of the extractor type assigned to the extractor parameter must be an instance of a direct or indirect subtype of type `mdsys.rdfctx_extractor`.

The RDF models specified in the `user_models` parameter must be accessible to the user that is creating the policy.

The preferences specified for extractor policy determine the type of repository used for the documents to be indexed and other relevant information. For more information, see [Section 4.8, "Indexing External Documents"](#).

Examples

The following example creates an extractor policy using the `gatenlp_extractor` extractor type, which is included with the Oracle Database support for semantic indexing.

```
begin
  sem_rdfctx.create_policy (policy_name => 'SEM_EXTR',
                           extractor   => mdsys.gatenlp_extractor());
end;
/
```

The following example creates a dependent policy for the previously created extractor policy, and it adds the user-defined RDF model `geo_ontology` to the dependent policy.

```
begin
  sem_rdfctx.create_policy (policy_name => 'SEM_EXTR_PLUS_GEOONT',
                           base_policy  => 'SEM_EXTR',
                           user_models => SEM_MODELS ('geo_ontology'));
end;
/
```

SEM_RDFCTX.DROP_POLICY

Format

```
SEM_RDFCTX.DROP_POLICY(  
    policy_name IN VARCHAR2);
```

Description

Deletes (drops) an unused extractor policy.

Parameters

policy_name
Name of the extractor policy.

Usage Notes

An exception is generated if the specified policy being is used for a semantic index for documents or if a dependent extractor policy exists for the specified policy.

Examples

The following example drops the SEM_EXTR_PLUS_GEOONT extractor policy.

```
begin  
    sem_rdfctx.drop_policy (policy_name => 'SSEM_EXTR_PLUS_GEOONT');  
end;  
/
```

SEM_RDFCTX.MAINTAIN_TRIPLES

Format

```
SEM_RDFCTX.MAINTAIN_TRIPLES(  
    index_name    IN VARCHAR2,  
    where_clause  IN VARCHAR2,  
    rdfxml_content sys.XMLType,  
    policy_name   IN VARCHAR2 DEFAULT NULL,  
    action        IN VARCHAR2 DEFAULT 'ADD');
```

Description

Adds one or more triples to graphs that contain information extracted from specific documents.

Parameters

index_name

Name of the semantic index for documents.

where_clause

A SQL predicate (WHERE clause text without the WHERE keyword) on the table in which the documents are stored, to identify the rows for which to maintain the index.

rdxml_content

Triples, in the form of an RDF/XML document, to be added to the individual graphs corresponding to the documents.

policy_name

Name of the extractor policy. If `policy_name` is null (the default), the triples are added to the information extracted by the default (or the only) extractor policy for the index; if you specify a policy name, the triples are added to the information extracted by that policy.

action

Type of maintenance operation to perform on the triples. The only value currently supported is `ADD` (the default), which adds the triples that are specified in the `rdxml_content` parameter.

Usage Notes

The information extracted from the semantically indexed documents may be incomplete and lacking in proper context. This procedure enables a domain expert to add triples to individual graphs pertaining to specific semantically indexed documents, so that all subsequent `SEM_CONTAINS` queries can consider these triples in their document search criteria.

This procedure accepts the index name and WHERE clause text to identify the specific documents to be annotated with the additional triples. For example, the `where_clause` might be specified as a simple predicate involving numeric data, such as `'docId IN (1, 2, 3)'`.

Examples

The following example annotates a specific document with the semantic index `ArticleIndex` by adding triples to the corresponding individual graph.

```
begin
  sem_rdfctx.maintain_triples(
    index_name      => 'ArticleIndex',
    where_clause    => 'docid = 15',
    rdfxml_content => sys.xmltype(
      '<rdf:RDF xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
        xmlns:rdfs="http://www.w3.org/2000/01/rdf-schema#"
        xmlns:pred="http://myorg.com/pred/">
        <rdf:Description rdf:about=" http://newscorp.com/Org/ExampleCorp">
          <pred:hasShortName
            rdf:datatype="http://www.w3.org/2001/XMLSchema#string">
            Example
          </pred:hasShortName>
        </rdf:Description>
      </rdf:RDF>');
end;
/
```

SEM_RDFCTX.SET_DEFAULT_POLICY

Format

```
SEM_RDFCTX.SET_DEFAULT_POLICY(  
    index_name  IN VARCHAR2,  
    policy_name IN VARCHAR2);
```

Description

Sets the default extractor policy for a semantic index that is configured with multiple extractor policies.

Parameters

index_name

Name of the semantic index for documents.

policy_name

Name of the extractor policy to be used as the default extractor policy for the specified semantic index. Must be one of the extractor policies listed in the PARAMETERS clause of the CREATE INDEX statement that created `index_name`.

Usage Notes

When you create a semantic index for documents, you can specify multiple extractor policies as a space-separated list of names in the PARAMETERS clause of the CREATE INDEX statement. As explained in [Section 4.3, "Semantically Indexing Documents"](#), the first policy from this list is used as the default extractor policy for all SEM_CONTAINS queries that do not identify an extractor policy by name. You can use the SEM_RDFCTX.SET_DEFAULT_POLICY procedure to set a different default policy for the index.

Examples

The following example sets CITY_EXTR as the default extractor policy for the ArticleIndex index.

```
begin  
    sem_rdfctx.set_default_policy (index_name => 'ArticleIndex',  
                                  policy_name => 'CITY_EXTR');  
end;  
/
```

SEM_RDFCTX.SET_EXTRACTOR_PARAM

Format

```
SEM_RDFCTX.SET_EXTRACTOR_PARAM(  
    param_key  IN VARCHAR2,  
    param_value IN VARCHAR2,  
    param_desc IN VARCHAR2);
```

Description

Configures the Oracle Database semantic indexing support to work with external information extractors, such as Calais and GATE.

Parameters

param_key

Key for the parameter to be set.

param_value

Value for the parameter to be set.

param_desc

Short description for the parameter to be set.

Usage Notes

You must have the SYSDBA role to use this procedure.

To work with the Calais extractor type (see [Section 4.9](#)), you must specify values for the following parameters:

- CALAIS_WS_ENDPOINT: Web service end point for Calais.
- CALAIS_KEY: License key for Calais.
- CALAIS_WS_SOAPACTION: SOAP action for the Calais Web service.

To work with the General Architecture for Text Engineering (GATE) extractor type (see [Section 4.10](#)), you must specify values for the following parameters:

- GATE_NLP_HOST: Host for the GATE NLP Listener.
- GATE_NLP_PORT: Port for the GATE NLP Listener.

In addition to these parameters, you may need to specify a value for the HTTP_PROXY parameter to work with information extractors or index documents that are outside the firewall.

A database instance only has one set of values for these parameters, and they are used for all instances of semantic indexes using the corresponding information extractor. You can use this procedure if you need to change the existing values of any of the parameters.

Examples

For examples, see the following sections:

- [Section 4.9, "Configuring the Calais Extractor type"](#)

- [Section 4.10, "Working with General Architecture for Text Engineering \(GATE\)"](#)

SEM_RDFSA Package Subprograms

The SEM_RDFSA package contains subprograms (functions and procedures) for providing fine-grained access control to RDF data, using either a virtual private database (VPD) or Oracle Label Security (OLS). To use the subprograms in this chapter, you should understand the conceptual and usage information in [Chapter 1, "Oracle Database Semantic Technologies Overview"](#) and [Chapter 5, "Fine-Grained Access Control for RDF Data"](#).

This chapter provides reference information about the subprograms, listed in alphabetical order.

SEM_RDFS.ADD_VPD_CONSTRAINT

Format

```
SEM_RDFS.ADD_VPD_CONSTRAINT(  
    policy_name  IN VARCHAR2,  
    constr_name  IN VARCHAR2,  
    match_pattern IN VARCHAR2,  
    apply_pattern IN VARCHAR2,  
    constr_group IN VARCHAR2 DEFAULT NULL);
```

Description

Adds a data access constraint to a VPD policy.

Parameters

policy_name

Name of an existing VPD policy.

constr_name

Unique case-insensitive name for the constraint to be defined in the VPD policy.

match_pattern

Match pattern that determines the target of the constraint.

apply_pattern

The constraint's apply pattern that enforces the access restriction.

constr_group

Case-insensitive name for the group to which the constraint belongs.

Usage Notes

This procedure adds a data access constraint to a VPD policy. Only the owner of a VPD policy can add a new constraint to the policy. The newly added constraint comes into effect immediately and it is enforced for queries on all RDF models associated with the VPD policy.

A constraint group may be specified for each policy such that they can be selectively activated and deactivated at runtime based on the application context (as explained in [Section 5.1.1](#)). A constraint with no constraint group is always active. See [Section 5.1.3](#) for details about the match and apply patterns passed to this procedure.

See also the MDSYS.RDFVPD_POLICY_CONSTRAINTS view, which is described in [Section 5.1.6](#).

For information about support for VPD, see [Section 5.1](#).

Examples

The following example adds data access constraint for the RDF Class Contracts to the VPD policy and assigns it a constraint group named user:

```
begin
```

```

sem_rdfsa.add_vpd_constraint(
    policy_name => 'contracts_policy',
    constr_name => 'andy_constraint_1',
    match_pattern => '{?contract rdf:type
        <http://www.myorg.com/classes/Contract>}',
    apply_pattern => '{?contract pred:hasMember
        `sys_context(`sa$appctx`,`app_user_uri`)`^^orardf:instruction }',
    constr_group => 'user');
end;
/

```

The preceding example makes use of secure application context to identify the user issuing the query and binds its value in the apply pattern to ensure that the user has access to a specific contract. The secure application context with the namespace sa\$appctx is expected to initialize the value for the attribute app_user_uri to the URI identifying the user logged in.

The following example adds a data access constraint for the RDF property hasContractValue to the same VPD policy and assigns it to a constraint group named vp.

```

begin
    sem_rdfsa.add_vpd_constraint(
        policy_name => 'contracts_policy',
        constr_name => `vp_access_to_contr_value`,
        match_pattern => '{?contract pred:hasContractValue ?cvalue }',
        apply_pattern => '{?contract pred:drivenBy      ?dept .
            ?dept      pred:hasVP
            `sys_context(`sa$appctx`,`app_user_uri`)`^^orardf:instruction }',
        constr_group => 'vp');
end;
/

```

SEM_RDFSA.APPLY_OLS_POLICY

Format

```
SEM_APIS.APPLY_OLS_POLICY(  
    policy_name IN VARCHAR2,  
    rdfsa_options IN NUMBER DEFAULT SEM_RDFSA.SECURE_SUBJECT,  
    table_options IN VARCHAR2 DEFAULT 'ALL_CONTROL',  
    label_function IN VARCHAR2 DEFAULT NULL,  
    predicate IN VARCHAR2 DEFAULT NULL);
```

Description

Applies an OLS policy to the semantic data store.

Parameters

policy_name

Name of an existing OLS policy.

rdfsa_options

Options specifying the mode of fine-grained access control to be enabled for RDF data. The default option for securing RDF data involves assigning sensitivity labels for the resources appearing the triples' subject position. You can override the defaults by using the `rdfsa_options` parameter and specifying one of the constants defined in [Table 12-1](#) in the Usage Notes.

table_options

Policy enforcement options. The default value (`ALL_CONTROL`) is the only supported value for this procedure

label_function

A string invoking a function to return a label value to use as the default.

predicate

An additional predicate to combine with the label-based predicate.

Usage Notes

The OLS policy specified with this procedure must be created with CTXT1 as the column name, and it should use default policy options. For information about policy options, see *Oracle Label Security Administrator's Guide*.

This procedure invokes the `sa_policy_admin.apply_table_policy` procedure on multiple tables defined in the MDSYS schema. The parameters `table_options`, `label_function`, and `predicate` for the `SEM_APIS.APPLY_OLS_POLICY` procedure have same semantics as the parameters with same names in the `sa_policy_admin.apply_table_policy` procedure.

For the `rdfsa_options` parameter, you can specify the package constant for the desired option. [Table 12-1](#) lists these constants and their descriptions.

Table 12-1 SEM_RDFSA Package Constants for rdfsa_options Parameter

Constant	Description
SEM_RDFSA.SECURE_SUBJECT	Assigns sensitivity labels for the resources appearing the triples' subject position.
SEM_RDFSA.SECURE_PREDICATE	Assigns sensitivity labels for the resources appearing the triples' predicate position.
SEM_RDFSA.SECURE_OBJECT	Assigns sensitivity labels for the resources appearing the triples' object position.
SEM_RDFSA.TRIPLE_LEVEL_ONLY	Applies triple-level security. Provides good performance, and eliminates the need to assign labels to individual resources. (Requires that Patch 9819833, available from My Oracle Support, be installed.)
SEM_RDFSA.OPT_DEFINE_BEFORE_USE	Restricts the use of an RDF resource in a triple before the sensitivity label is defined for the resource. If this option is not specified, the user's initial row label is used as the default label for the resource upon first use.
SEM_RDFSA.OPT_RELAX_TRIPLE_LABEL	Relaxes the dominating relationship that exists between the triple label and the labels associated with all its components. With this option, a triple can be defined if the user has READ access to all the triple components and the triple label may not bear any relationship with the component labels. Without this option, the triple label should at least cover the label for all its components.

You can specify a function in the `label_function` parameter to generate custom labels for newly inserted triples. The label function is associated with the `MDSYS.RDF_LINK$` table, and the columns in this table may be configured as parameters to the label function as shown in the following example:

```
fgac_admin.new_triple_label(:new.model_id,
                           :new.start_node_id,
                           :new.p_value_id,
                           :new.canon_end_node_id) '
```

Because the OLS policy is applied to more than one table with different structures, the only valid column reference in any predicates assigned to the `predicate` parameter is that of the label column: `CTXT1`. If OLS is enabled for a semantic data store with existing data, you can specify a predicate of the form `'OR CTXT1 is null'` to be able to continue using this data with no access restrictions.

An OLS-enabled semantic data store uses sensitivity labels for all the RDF triples organized in multiple models. User access to such triples, through model views and `SEM_MATCH` queries, is restricted by the OLS policy. Additionally, independent of a user owning the application table, access to the triple column (of type `SDO_RDF_TRIPLE_S`) in the table is restricted to users with `FULL` access privileges with the OLS policy.

The triples are inserted into a specific RDF model using the `INSERT` privileges on the corresponding application table. A sensitivity label for the new triple is generated using the user's session context (initial row label) or the label function. The triple is validated for any RDF policy violations using labels associated with the triple components. Although the triple information may not be accessed through the application table, the model view may be queried to access the triples, while enforcing the OLS policy restrictions. If you have the necessary policy privileges (such as `writeup`, `writeacross`), you can update the `CTXT1` column in the model view to reset the label assigned to the triple. The new label is automatically validated for any RDF policy violations involving the triple components. Update privilege on the `CTXT1`

column of the model view is granted to the owner of the model, and this user may selectively grant this privilege to other users.

If the RDF models are created in schemas other than the user with FULL access, necessary privileges on the model objects -- specifically, read/write access on the application table, read access to the model view, and write access to the CTEXT1 column in the model view -- can be granted to such users for maintenance operations. These operations include bulk loading into the model, resetting any sensitivity labels assigned to the triples, and creating entailments using the model.

To disable the OLS policy, use the [SEM_RDFSA.DISABLE_OLS_POLICY](#) procedure.

For information about support for OLS, see [Section 5.2](#).

Examples

The following example enable secure access to RDF data with secure subject and secure predicate options.

```
begin
  sem_rdfsa.apply_ols_policy(
    policy_name => 'defense',
    rdfsa_options => sem_rdfsa.SECURE_SUBJECT+
                    sem_rdfsa.SECURE_PREDICATE);
end;
/
```

The following example extends the preceding example by specifying a Define Before Use option, which allows a user to define a triple only if the triple components secured (Subject, Predicate or Object) are predefined with an associated sensitivity label. This configuration is effective if the user inserting the triple does not have execute privileges on the SEM_RDFSA package.

```
begin
  sem_rdfsa.apply_ols_policy(
    policy_name => 'defense',
    rdfsa_options => sem_rdfsa.SECURE_SUBJECT+
                    sem_rdfsa.SECURE_PREDICATE+
                    sem_rdfsa.OPT_DEFINE_BEFORE_USE);
end;
/
```

SEM_RDFSA.APPLY_VPD_POLICY

Format

```
SEM_APIS.APPLY_VPD_POLICY(  
    policy_name IN VARCHAR2,  
    model_name IN VARCHAR2);
```

Description

Applies a VPD policy to an RDF model.

Parameters

policy_name

Name of an existing VPD policy.

model_name

Name of the model to which to apply the VPD policy.

Usage Notes

This procedure applies a VPD policy to an RDF model. The owner of a VPD policy can apply it to any model in the database instance. The owner must also have EXECUTE privileges on the SYS.DBMS_RLS package.

After a policy is applied to an RDF model, the data stored in the model and the data inferred from this model can be accessed only using SPARQL query patterns within a SEM_MATCH operation. All other forms of data access (such as through model views or using classic graph pattern syntax in a SEM_MATCH query) are not permitted.

A VPD policy may not be applied to a model participating in a virtual model. Similarly, a virtual model may not be defined to include any VPD-enabled models.

See also the MDSYS.RDFVPD_POLICIES view, which is described in [Section 5.1.4](#).

For information about support for VPD, see [Section 5.1](#).

Examples

The following example applies a VPD policy to an RDF model.

```
begin  
    sem_rdfsa.apply_vpd_policy(  
        policy_name => 'contracts_policy',  
        model_name  => 'contracts');  
end;  
/
```

SEM_RDFSA.CREATE_VPD_POLICY

Format

```
SEM_APIS.CREATE_VPD_POLICY(  
    policy_name      IN VARCHAR2,  
    namespace_map   IN RDF_ALIASES DEFAULT NULL,  
    policy_context   IN VARCHAR2 DEFAULT NULL);
```

Description

Creates a new VPD policy in a user schema.

Parameters

policy_name

Name for the VPD policy.

namespace_map

A mapping of namespaces and their prefixes to be used in the VPD constraints.

policy_context

Name of the context created specifically to manage constraint groups defined in the VPD policy.

Usage Notes

You must have EXECUTE privileges on the SYS.DBMS_RLS package.

The namespace map associated with the policy may be used to define namespace prefixes that are subsequently used in the policy's metadata statements added using the [SEM_RDFSA.MAINT_VPD_METADATA](#) procedure and the policy's data access constraints defined using the [SEM_RDFSA.ADD_VPD_CONSTRAINT](#) procedure.

The name of the application context assigned to the `policy_context` parameter is used to manage the constraint groups dynamically at run time. Such context must be created using the CREATE CONTEXT command before associating it with the VPD policy. Each data access constraint defined in the VPD policy may specify the name of a constraint group to which it belongs. At run time, the name of the constraint group is matched with the name of the `policy_context` value to selectively activate the group. (For more information, see [Section 5.1.1](#)).

See also the MDSYS.RDFVPD_POLICIES view, which is described in [Section 5.1.4](#).

For information about support for VPD, see [Section 5.1](#).

Examples

The following example creates a VPD policy with a namespace map and also associates a policy context to manage constraint groups.

```
create context contracts_appctx using sec_admin.contracts_appctx;  
begin  
    sem_rdfsa.create_vpd_policy(  
        policy_name => 'contracts_policy',  
        namespace_map =>  
            mdsys.rdf_aliases(  

```

```
mdsys.rdf_alias('', 'http://www.myorg.com/classes/'),
mdsys.rdf_alias('pred', 'http://www.myorg.com/pred/'),
mdsys.rdf_alias('emp', 'http://www.myorg.com/employee/'),
policy_context => 'contracts_appctx');
end;
/
```

SEM_RDFS.DELETE_VPD_CONSTRAINT

Format

```
SEM_RDFS.DELETE_VPD_CONSTRAINT(  
    policy_name  IN VARCHAR2,  
    constr_name  IN VARCHAR2);
```

Description

Deletes a data access constraint from a VPD policy.

Parameters

policy_name

Name of an existing VPD policy.

constr_name

Unique case-insensitive name for the constraint to be deleted from the VPD policy.

Usage Notes

This procedure deletes a data access constraint from a VPD policy. Only the owner of a VPD policy can delete a constraint from the policy.

See also the MDSYS.RDFVPD_POLICY_CONSTRAINTS view, which is described in [Section 5.1.6](#).

For information about support for VPD, see [Section 5.1](#).

Examples

The following example adds data access constraint named `vp_access_to_contr_value` from the VPD policy named `contracts_policy`:

```
begin  
    sem_rdfs.delete_vpd_policy(  
        policy_name => 'contracts_policy',  
        constr_name => 'vp_access_to_contr_value');  
end;  
/
```

SEM_RDFSA.DISABLE_OLS_POLICY

Format

SEM_APIS.DISABLE_OLS_POLICY;

Description

Disables the OLS policy that has been previously applied to or enabled on the semantic data store.

Parameters

(None.)

Usage Notes

You can use this procedure to disable temporarily the OLS policy that had been applied to or enabled for the semantic data store. The user disabling the policy should have the necessary privileges to administer OLS policies and should also have access to the OLS policy applied to RDF data.

The sensitivity labels assigned to various RDF resources and triples are preserved and the OLS policy may be re-enabled to enforce them. New resources with specific labels can be added, or labels for existing triples and resources can be updated when the OLS policy is disabled.

To apply an OLS policy, use the [SEM_RDFSA.APPLY_OLS_POLICY](#) procedure; to enable an OLS policy that had been disabled, use the [SEM_RDFSA.ENABLE_OLS_POLICY](#) procedure.

For information about support for OLS, see [Section 5.2](#).

Examples

The following example disables the OLS policy for the semantic data store.

```
begin
  sem_rdfsa.disable_ols_policy;
end;
/
```

SEM_RDFSA.DROP_VPD_POLICY

Format

```
SEM_RDFSA.DROP_VPD_POLICY(  
    policy_name IN VARCHAR2);
```

Description

Drops an unused VPD policy.

Parameters

policy_name
Name of an existing VPD policy.

Usage Notes

This procedure permanently drops an unused VPD policy along with its metadata and constraints. You must be the owner of a VPD policy or a user with a DBA role to perform this operation.

For information about support for VPD, see [Section 5.1](#).

Examples

The following example adds data access constraint named `vp_access_to_contr_value` from the VPD policy named `contracts_policy`:

```
begin  
    sem_rdfsa.delete_vpd_policy(  
        policy_name => 'contracts_policy',  
        constr_name  => 'vp_access_to_contr_value');  
end;  
/
```

SEM_RDFSA.ENABLE_OLS_POLICY

Format

```
SEM_APIS.ENABLE_OLS_POLICY;
```

Description

Enables the OLS policy that has been previously disabled.

Parameters

(None.)

Usage Notes

You can use this procedure to enable the OLS policy that had been disabled for the semantic data store. The user enabling the policy should have the necessary privileges to administer OLS policies and should also have access to the OLS policy applied to RDF data.

To disable an OLS policy, use the [SEM_RDFSA.DISABLE_OLS_POLICY](#) procedure.

For information about support for OLS, see [Section 5.2](#).

Examples

The following example enables the OLS policy for the semantic data store.

```
begin
  sem_rdfsa.enable_ols_policy;
end;
/
```

SEM_RDFS.MAINT_VPD_METADATA

Format

```
SEM_RDFS.MAINT_VPD_METADATA(  
    policy_name IN VARCHAR2,  
    t_subject   IN VARCHAR2,  
    t_predicate IN VARCHAR2,  
    t_object    IN VARCHAR2,  
    action      IN VARCHAR2 DEFAULT 'ADD');
```

Description

Maintains the VPD metadata by accepting RDF schema statements with their subject, predicate, and object terms.

Parameters

policy_name

Name of an existing VPD policy.

t_subject

Subject of the metadata triple.

t_predicate

Predicate of the metadata triple.

t_object

Object of the metadata triple.

action

Maintenance operation to be performed: ADD (add the specified triple to the metadata) or DELETE (delete the specified triple from the metadata).

Usage Notes

This procedure maintains the metadata associated with the VPD policy by accepting RDF Schema statements and performing appropriate actions on its dictionary. Only the owner of the VPD policy or a user with FULL access to the VPD policy can maintain its metadata.

The types metadata statements that you can add using this procedure are determined by the terms assigned to the `t_predicate` parameter. The accepted values for this parameter are:

```
http://www.w3.org/2000/01/rdf-schema#domain  
http://www.w3.org/2000/01/rdf-schema#range  
http://www.w3.org/2000/01/rdf-schema#subClassOf  
http://www.w3.org/2000/01/rdf-schema#subPropertyOf  
http://www.w3.org/2002/07/owl#equivalentProperty
```

MDSYS.RDFVPD_PREDICATE_MDATA and MDSYS.RDFVPD_RESOURCE_REL views, which are described in [Section 5.1.7](#) and [Section 5.1.8](#), respectively.

For information about support for VPD, see [Section 5.1](#).

Examples

The following example specifies `Contract` as a subclass of `Project` and adds domain information for the `hasContractValue` property:

```
begin
  sem_rdfsa.maint_vpd_metadata(
    policy_name => 'contracts_policy',
    t_subject   => '<http://www.myorg.com/classes/Project>',
    t_predicate => '<http://www.w3.org/2000/01/rdf-schema#subClassOf>',
    t_object    => '<http://www.myorg.com/classes/Contract>',
    action      => 'add');
end;

begin
  sem_rdfsa.maint_vpd_metadata(
    policy_name => 'contracts_policy',
    t_subject   => '<http://www.myorg.com/property/hasConfValue>',
    t_predicate => 'rdfs:domain',
    t_object    => '<http://www.myorg.com/classes/Contract>');
end;
```

SEM_RDFSA.REMOVE_OLS_POLICY

Format

```
SEM_APIS.REMOVE_OLS_POLICY;
```

Description

Permanently removes or detaches the OLS policy from the semantic data store.

Parameters

(None.)

Usage Notes

You should have the necessary privileges to administer OLS policies, and you should also have access to the OLS policy applied to RDF data. Once the OLS policy is detached from the semantic data store, all the sensitivity labels previously assigned to the triples and resources are lost.

This operation drops objects that are specifically created to maintain the RDF security policies.

To apply an OLS policy, use the [SEM_RDFSA.APPLY_OLS_POLICY](#) procedure.

For information about support for OLS, see [Section 5.2](#).

Examples

The following example removes the OLS policy that had been previously applied to the semantic data store.

```
begin
  sem_rdfsa.remove_ols_policy;
end;
/
```

SEM_RDFSA.REMOVE_VPD_POLICY

Format

```
SEM_APIS.REMOVE_VPD_POLICY(  
    policy_name IN VARCHAR2,  
    model_name IN VARCHAR2);
```

Description

Removes (detaches) a VPD policy from an RDF model.

Parameters

policy_name

Name of an existing VPD policy.

model_name

Name of the model to which to apply the VPD policy.

Usage Notes

This procedure permanently removes or detaches a VPD policy from an RDF Model. You must be the owner of the VPD policy or a user with a DBA role to perform this operation.

After a VPD policy is removed, fine-grained access control for the specific model is turned off and the users with SELECT privileges on the model view can access all the data in the model.

For information about support for VPD, see [Section 5.1](#).

Examples

The following example removes a VPD policy from an RDF model.

```
begin  
    sem_rdfsa.remove_vpd_policy(  
        policy_name => 'contracts_policy',  
        model_name  => 'contracts');  
end;  
/
```

SEM_RDFSA.RESET_MODEL_LABELS

Format

```
SEM_APIS.RESET_MODEL_LABELS(  
    model_name IN VARCHAR2);
```

Description

Resets the labels associated with a model or with global resources; requires that the associated model or models be empty.

Parameters

model_name

Name of the model for which the labels should be reset, or the string `RDF$GLOBAL` to reset the labels associated with all global resources.

Usage Notes

If you specify a model name, the model must be empty. If you specify `RDF$GLOBAL`, all the models must be empty (that is, no triples in the RDF repository).

You must have `FULL` access privilege with the OLS policy applied to the semantic data store.

For information about support for OLS, see [Section 5.2](#).

Examples

The following example removes all resources and their labels associated with the `Contracts` model.

```
begin  
    sem_rdfsa.reset_model_labels(model_name => 'Contracts');  
end;  
/
```

SEM_RDFSA.SET_PREDICATE_LABEL

Format

```
SEM_APIS.SET_PREDICATE_LABEL(  
    model_name IN VARCHAR2,  
    predicate   IN VARCHAR2,  
    label_string IN VARCHAR2);
```

Description

Sets a sensitivity label for a predicate at the model level or for the whole repository.

Parameters

model_name

Name of the model to which the predicate belongs, or the string `RDF$GLOBAL` if the same label should be applied for the use of the predicate in all models.

predicate

Predicate for which the label should be assigned.

label_string

OLS row label in string representation.

Usage Notes

If you specify a model name, you must have read access to the model and execute privileges on the `SEM_RDFSA` package to perform this operation. If you specify `RDF$GLOBAL`, you must have `FULL` access privilege with the OLS policy applied to RDF data.

You must have access to the specified label and OLS policy privilege to overwrite an existing label if a label already exists for the predicate. The `SECURE_PREDICATE` option must be enabled for RDF data.

If an existing predicate label is updated with this operation, the labels for the triples using this predicate must all dominate the new predicate label. The only exception is when the `OPT_RELAX_TRIPLE_LABEL` option is chosen for the OLS-enabled RDF data.

If you specify `RDF$GLOBAL`, a global predicate with a unique sensitivity label across models is created. If the same predicate is previously defined in one or more models, the global label dominates all such labels and the model-specific labels are replaced for the given predicate.

After a label for a predicate is set, new triples with the predicate can be added only if the triple label (which may be initialized from user's initial row label or using a label function) dominates the predicate's sensitivity label. This dominance relationship can be relaxed with the `OPT_RELAX_TRIPLE_LABEL` option, in which case the user should at least have read access to the predicate to be able to define a new triple using the predicate.

For information about support for OLS, see [Section 5.2](#).

Examples

The following example sets a predicate label for `Contracts` model and another predicate label for all models in the database instance.

```
begin
  sem_rdfsa.set_predicate_label(
    model_name => 'contracts',
    predicate   => '<http://www.myorg.com/pred/hasContractValue>',
    label_string => 'TS:US_SPCL');
end;
/

begin
  sem_rdfsa.set_predicate_label(
    model_name => 'rdf$global',
    predicate   => '<http://www.myorg.com/pred/hasStatus>',
    label_string => 'SE:US_SPCL:US');
end;
/
```

SEM_RDFSA.SET_RDFS_LABEL

Format

```
SEM_APIS.SET_RDFS_LABEL(  
    label_string IN VARCHAR2,  
    inf_override IN VARCHAR2);
```

Description

Sets a sensitivity label for RDFS schema elements.

Parameters

label_string

OLS row label in string representation, to be used as the sensitivity label for all RDF schema constructs.

inf_override

OLS row label to be used as the override for generating labels for inferred triples.

Usage Notes

This procedure sets or resets the sensitivity label associated with the RDF schema resources, often recognized by `http://www.w3.org/1999/02/22-rdf-syntax-ns#` and `http://www.w3.org/2000/01/rdf-schema#` prefixes for their URIs. You can assign a sensitivity label with restricted access to these resources, so that operations such as creating new RDF classes and adding new properties can be restricted to users with higher privileges.

You must have FULL access privilege with policy applied to RDF data.

RDF schema elements implicitly use the relaxed triple label option, so that the triples using RDFS and OWL constructs for subject, predicate, or object are not forced to have a sensitivity label that dominates the labels associated with the schema constructs. Therefore, a user capable of defining new RDF classes and properties must at least have read access to the schema elements.

When RDF schema elements are referred to in the inferred triples, the system-defined and custom label generators consider the inference override label in determining the appropriate label for the inferred triples. If a custom label generator is used, this override label is passed instead of the actual label when an RDF schema element is involved.

For information about support for OLS, see [Section 5.2](#).

Examples

The following example sets a label with a unique compartment for all RDF schema elements. A user capable of defining new RDF classes and properties is expected to have an exclusive membership to the compartment.

```
begin  
    sem_rdfsa.set_rdfs_label(  
        label_string => 'SE:RDFS:',  
        inf_override => 'SE:US_SPCL:US');
```

```
end;  
/
```

SEM_RDFSASET_RESOURCE_LABEL

Format

```
SEM_APIS.SET_RESOURCE_LABEL(  
    model_name IN VARCHAR2,  
    resource_uri IN VARCHAR2,  
    label_string IN VARCHAR2,  
    resource_pos IN VARCHAR2 DEFAULT 'S');
```

Description

Sets a sensitivity label for a resource that may be used in the subject and/or object position of a triple.

Parameters

model_name

Name of the model to which the resource belongs, or the string `RDF$GLOBAL` if the same label should be applied for using the resource in all models.

resource_uri

URI for the resource that may be used as subject or object in one or more triples.

label_string

OLS row label in string representation.

resource_pos

Position of the resource within a triple: `S`, `O`, or `S, O`. You can specify up to two separate labels for the same resource, one to be considered when the resource is used in the subject position of a triple and the other to be considered when it appears in the object position. The values `'S'`, `'O'` or `'S, O'` set a label for the resource in subject, object or both subject and object positions, respectively.

Usage Notes

If you specify a model name, you must have read access to the model and execute privileges on the `SEM_RDFSASET` package to perform this operation. If you specify `RDF$GLOBAL`, you must have `FULL` access privilege with the OLS policy applied to RDF data.

You must have access to the specified label and OLS policy privilege to overwrite an existing label if a label already exists for the predicate. The `SECURE_PREDICATE` option must be enabled for RDF data.

If an existing resource label is updated with this operation, the labels for the triples using this resource in the specified position must all dominate the new resource label. The only exception is when the `OPT_RELAX_TRIPLE_LABEL` option is chosen for the OLS-enabled RDF data.

If you specify `RDF$GLOBAL`, a global resource with a unique sensitivity label across models is created. If the same resource is previously defined in one or more models with the same triple position, the global label dominates all such labels and the model-specific labels are replaced for the given resource in that position.

After a label for a predicate is set, new triples using the resource in the specified position can be added only if the triple label dominates the resource's sensitivity label. This dominance relationship can be relaxed with `OPT_RELAX_TRIPLE_LABEL` option, in which case, the user should at least have read access to the resource.

For information about support for OLS, see [Section 5.2](#).

Examples

The following example sets sensitivity labels for multiple resources based on their position.

```
begin
  sem_rdfsa.set_resource_label(
    model_name   => 'contracts',
    resource_uri => '<http://www.myorg.com/contract/projectHLS>',
    label_string => 'SE:US_SPCL:US',
    resource_pos => 'S,O');
end;
/

begin
  sem_rdfsa.set_resource_label(
    model_name   => 'rdf$global',
    resource_uri => '<http://www.myorg.com/contract/status/Complete>',
    label_string => 'SE:US_SPCL:US',
    resource_pos => 'O');
end;
/
```

SEM_RDFSA.SET_RULE_LABEL

Format

```
SEM_APIS.SET_RULE_LABEL(  
    rule_base IN VARCHAR2,  
    rule_name IN VARCHAR2,  
    label_string IN VARCHAR2);
```

Description

Sets sensitivity label for a rule belonging to a rulebase.

Parameters

rule_base

Name of an existing RDF rulebase.

rule_name

Name of the rule belonging to the rulebase.

label_string

OLS row label in string representation.

Usage Notes

The sensitivity label assigned to the rule is used to generate the label for the inferred triples when an appropriate label generator option is chosen.

You must have access have access to the rulebase, and you must have FULL access privilege with the OLS policy can assign labels for system-defined rules in the RDFS rulebase.

There is no support for labels assigned to user-defined rules.

For information about support for OLS, see [Section 5.2](#).

Examples

The following example assigns a sensitivity label for an RDFS rule.

```
begin  
sem_rdfsa.set_rule_label (rule_base    => 'RDFS',  
                          rule_name    => 'RDF-AXIOMS',  
                          label_string => 'SE:US_SPCL:');  
end;  
/
```

Enabling, Downgrading, or Removing Semantic Technologies Support

This appendix describes the required steps that you must perform before you can use any types, synonyms, or PL/SQL packages related to Oracle semantic technologies support in the current Oracle Database release. You must run one or more scripts, and you must ensure that Spatial is installed and the Partitioning option is enabled. These requirements are explained in [Section A.1](#).

This appendix also describes the steps if, after enabling semantic technologies support, you need to do any of the following:

- Downgrade the semantic technologies support to that provided with a previous Oracle Database release, as explained in [Section A.2](#).
- Remove all support for semantic technologies from the database, as explained in [Section A.3](#).

A.1 Enabling Semantic Technologies Support

Before you can use any types, synonyms, or PL/SQL packages related to Oracle semantic technologies support in the current Oracle Database release, you must either install the capabilities in a new Oracle Database installation or upgrade the capabilities from a previous release, following the steps in whichever of the following sections applies to your situation:

- [Section A.1.1, "Enabling Semantic Technologies Support in a New Database Installation"](#)
- [Section A.1.2, "Upgrading Semantic Technologies Support from Release 11.1"](#)
- [Section A.1.3, "Upgrading Semantic Technologies Support from Release 10.2"](#)

If you upgraded to Release 11.2.0.2.0 and your Semantic Technologies installation is invalid, see [Section A.1.4, "Release 11.2.0.2: Required Actions if Semantic Technologies Installation is Invalid"](#)

In addition, you must ensure that Spatial is installed and the Partitioning option is enabled, as explained in [Section A.1.5](#).

A.1.1 Enabling Semantic Technologies Support in a New Database Installation

To enable semantic technologies support in a new installation of Oracle Database Release 11.2 (or for an upgrade from Release 10.2 if no RDF network exists, as explained in [Section A.1.3](#)), follow these steps:

1. Connect to the database as the SYS user with SYSDBA privileges (SYS AS SYSDBA, and enter the SYS account password when prompted).
2. Start SQL*Plus, and enter the following statement:
 - Linux: @\$ORACLE_HOME/md/admin/catsem.sql
 - Windows: @%ORACLE_HOME%\md\admin\catsem.sql

If a semantic network already exists, or if any semantic technologies types, tables, or PL/SQL packages already exist, the `catsem.sql` script exits with an error.

If the script completes successfully, a row with the following column values is inserted into the `MDSYS.RDF_PARAMETER` table:

- NAMESPACE: MDSYS
- ATTRIBUTE: SEM_VERSION
- VALUE: 112
- DESCRIPTION: VALID

If you use Workspace Manager with RDF data, you must also run the appropriate script *after* you run `catsem.sql`, as explained in [Section 6.1, "Enabling Workspace Manager Support for RDF Data"](#).

A.1.2 Upgrading Semantic Technologies Support from Release 11.1

If you are upgrading from Oracle Database Release 11.1 that includes the semantic technologies support for Release 11.1, the semantic technologies support is automatically upgraded to Release 11.2 when the database is upgraded. If you use Workspace Manager with RDF data, you must also run the appropriate script *after* the upgrade of semantic technologies support, as explained in [Section 6.1, "Enabling Workspace Manager Support for RDF Data"](#).

However, you will also need to migrate RDF data if you have an existing Release 11.1 RDF network containing triples that include typed literal values of type `xsd:float`, `xsd:double`, `xsd:boolean`, or `xsd:time`.

To check if you need to migrate RDF data, connect to the database as a user with DBA privileges and query the `MDSYS.RDF_PARAMETER` table, as follows:

```
SELECT namespace, attribute, value FROM mdsys.rdf_parameter
WHERE namespace='MDSYS'
AND attribute IN ('FLOAT_DOUBLE_DECIMAL',
                 'XSD_TIME', 'XSD_BOOLEAN',
                 'DATA_CONVERSION_CHECK');
```

If the `FLOAT_DOUBLE_DECIMAL`, `XSD_TIME`, or `XSD_BOOLEAN` attributes have the string value `INVALID` or if the `DATA_CONVERSION_CHECK` attribute has the string value `FAILED_UNABLE_TO_LOCK_APPLICATION_TABLES`, `FAILED_INSUFFICIENT_WORKSPACE_PRIVILEGES`, or `FAILED_OLS_POLICIES_ARE_ENABLED`, you need to migrate RDF data.

However, if the `FLOAT_DOUBLE_DECIMAL`, `XSD_TIME`, and `XSD_BOOLEAN` attributes do not exist or have the string value `VALID` and if the `DATA_CONVERSION_CHECK` attribute does not exist, you do *not* need to migrate RDF data. However, if your semantic network may have any empty RDF literals, see [Section A.1.2.1, "Handling of Empty RDF Literals"](#); and if you choose to migrate existing empty literals to the new format, follow the steps in this section.

To migrate RDF data, follow these steps:

1. Connect to the database as the SYS user with SYSDBA privileges (SYS AS SYSDBA, and enter the SYS account password when prompted), and enter: `SET CURRENT_SCHEMA=MDSYS`
2. Ensure that the user MDSYS has the following privileges:
 - INSERT privilege on all application tables in the semantic network
 - ALTER ANY INDEX privilege (optional: only necessary if Semantic Indexing for Documents is being used)
 - ACCESS privilege for any workspace in which version-enabled application tables have been modified (optional: only necessary if Workspace Manager is being used for RDF data)
3. Ensure that any OLS policies for RDF data are temporarily disabled (optional: only necessary if OLS for RDF Data is being used). OLS policies can be re-enabled after running `convert_old_rdf_data`.
4. Start SQL*Plus. If you want to migrate the RDF data without converting existing empty literals to the new format (see [Section A.1.2.1](#)), enter the following statement:

```
EXECUTE sdo_rdf_internal.convert_old_rdf_data;
```

If you want to migrate the RDF data and also convert existing empty literals to the new format, call `convert_old_rdf_data` with the `flags` parameter set to `'CONVERT_ORARDF_NULL'`. In addition, you can use an optional `tablespace_name` parameter to specify the tablespace to use when creating intermediate tables during data migration. For example, the following statement migrates old semantic data, converts existing `"orardf:null "` values to `""`, and uses the `MY_TBS` tablespace for any intermediate tables:

```
EXECUTE sdo_rdf_internal.convert_old_rdf_data(
  flags=>'CONVERT_ORARDF_NULL',
  tablespace_name=>'MY_TBS');
```

The `sdo_rdf_internal.convert_old_rdf_data` procedure may take a significant amount of time to run if the semantic network contains many triples that are using (or affected by use of) `xsd:float`, `xsd:double`, `xsd:time`, or `xsd:boolean` typed literals.

5. Enter the following statement:
 - Linux: `@$ORACLE_HOME/md/admin/semrelod.sql`
 - Windows: `@%ORACLE_HOME%\md\admin\semrelod.sql`

Note: You may encounter the ORA-00904 (invalid identifier) error when executing a `SEM_MATCH` query if the `sdo_rdf_internal.convert_old_rdf_data` procedure and the `semrelod.sql` script were not run after the upgrade to Release 11.2.

A.1.2.1 Handling of Empty RDF Literals

The way empty-valued RDF literals are handled has changed in Release 11.2. Before this release, the values of empty-valued literals were converted to `"orardf:null "`. In Release 11.2, such values are stored without modification (that is, as `""`). However, whether you migrate existing `"orardf:null "` values to `""` is optional.

To check if "orardf:null " values exist in your semantic network, connect to the database as a user with DBA privileges and query the MDSYS.RDF_PARAMETER table, as follows:

```
SELECT namespace, attribute, value FROM mdsys.rdf_parameter
WHERE namespace='MDSYS'
AND attribute = 'NULL_LITERAL';
```

If the NULL_LITERAL attribute has the value EXISTS, then "orardf:null " values are present in your semantic network.

A.1.3 Upgrading Semantic Technologies Support from Release 10.2

If you are upgrading from Oracle Database Release 10.2 that includes the semantic technologies support for Release 10.2, the actions required depend on whether there is an existing RDF network.

If there is not an existing RDF network, skip the rest of this section and follow the instructions in [Section A.1.1, "Enabling Semantic Technologies Support in a New Database Installation"](#).

If there is an existing RDF network, perform the following steps after the Oracle Database upgrade:

1. Connect to the database (Release 11.2) as the SYS user with SYSDBA privileges (SYS AS SYSDBA, and enter the SYS account password when prompted).
2. Start SQL*Plus, and enter the following statement:
 - Linux: @\$ORACLE_HOME/md/admin/catsem10i.sql
 - Windows: @%ORACLE_HOME%\md\admin\catsem10i.sql

The catsem10i.sql script enables Release 11.2 semantic technologies support and migrates RDF data from Release 10.2 to Release 11.2 format. The script may take a long time to run if the existing Release 10.2 RDF network contains a large amount of RDF data.

A.1.4 Release 11.2.0.2: Required Actions if Semantic Technologies Installation is Invalid

Further action may be required if your Semantic Technologies installation is invalid after upgrading to Release 11.2.0.2.0. Action is required if either or both of the following are true:

- A row exists with the following values in the MDSYS.RDF_PARAMETER table:

```
MDSYS SEM_VERSION 11202 INVALID
```

- The STATUS column value is INVALID in any row returned by the following query:

```
SELECT object_name, status FROM all_objects WHERE object_name =
'SEMCONTEXTINDEXMETHODS' or object_name = 'PRLIIDX_CREATE';
```

In such a case, enter the following sequence of commands as SYSDBA to complete the upgrade of your installation:

```
SQL> @ $ORACLE_HOME/md/admin/sdordfctx.sql
SQL> @ $ORACLE_HOME/md/admin/semrelod.sql
SQL> EXECUTE sys.validate_sdo;
```

For the preceding commands:

- When running `sdordfctx.sql`, you can ignore any ORA-01921, ORA-02303, ORA-00955, and ORA-29809 errors.
- Executing `sys.validate_sdo` is needed only if SDO is invalid, which it could be if Semantic Technologies is invalid; however, there is no harm in executing `sys.validate_sdo` in any case.

After running the preceding commands, check whether your Semantic Technologies installation is valid by checking if a row exists with the following values in the `MDSYS.RDF_PARAMETER` table:

```
MDSYS SEM_VERSION 11202 VALID
```

A.1.5 Spatial and Partitioning Requirements

Oracle Spatial must be installed before you can use any of the RDF and OWL capabilities. Oracle Locator is not sufficient. For information about Spatial and Locator, see *Oracle Spatial Developer's Guide*.

The Partitioning option must be enabled before you can use any of the RDF and OWL capabilities. For licensing information about the Partitioning option, see *Oracle Database Licensing Information*. For usage information about partitioning, see *Oracle Database VLDB and Partitioning Guide*.

A.2 Downgrading Semantic Technologies Support to a Previous Release

This section explains how to downgrade the semantic technologies support, in conjunction with an Oracle Database downgrade to Release 11.1 or 10.2.

Downgrading is *strongly discouraged*, except for rare cases where it is necessary. If you downgrade to a previous release, you will not benefit from bug fixes and enhancements that have been made in intervening releases.

If you have enabled Workspace Manager support for RDF data, you must remove that support *before* you downgrade semantic technologies support in the database, as explained in [Section 6.1.1](#).

A.2.1 Downgrading to Release 11.1 Semantic Technologies Support

If you need to downgrade to Oracle Database Release 11.1, the semantic technologies component will be downgraded automatically when you downgrade the database. However, any RDF or OWL data that is specific to Release 11.2 (that is, Release 11.2 RDF/OWL persistent structures that are not supported in previous versions) must be dropped *before* you perform the downgrade, so that the database is compatible with Release 11.1.

Any virtual models will not be preserved during a downgrade, because they are only available through a Release 11.1.0.7.0 patch (number 7600122) that was made available on My Oracle Support (MetaLink) in November, 2008. To use virtual models, you must reapply this patch after the downgrade, and then re-create the virtual models. For convenience, you can use the `semvmrecreate.sql` script to generate a script that you can later use (after the downgrade) to automatically re-create any virtual models that were present in the Release 11.2 semantic network. To do so, follow these steps before you downgrade the database :

1. Connect to the database (Release 11.2) as the SYS user with SYSDBA privileges (SYS AS SYSDBA, and enter the SYS account password when prompted).

2. Start SQL*Plus, and enter a statement in the following format:

- Linux: @\$ORACLE_HOME/md/admin/semvmrecreate.sql /my_dir_path/my_vm_recreate.sql
- Windows: @%ORACLE_HOME%\md\admin\semvmrecreate.sql \my_dir_path\my_vm_recreate.sql

where *my_dir_path* is the path to the location in which to create the *my_vm_recreate.sql* script file. (You can use another file name for the script, if you want.)

To check if any Release 11.2 RDF data is incompatible with Release 11.1, perform the following steps:

1. Connect to the database (Release 11.2) as the SYS user with SYSDBA privileges (SYS AS SYSDBA, and enter the SYS account password when prompted).
2. Start SQL*Plus, and enter the following statements:

```
SET SERVEROUT ON  
EXECUTE SDO_SEM_DOWNGRADE.CHECK_111_COMPATIBLE;
```

If any RDF data is incompatible with Release 11.1, the procedure generates an error and displays a list of the incompatible data. In this case, you must run the *semrelod111.sql* script after the database downgrade, as follows:

1. In the Release 11.2 database, save a copy of the *semrelod111.sql* file, which is in the following location:
 - Linux: \$ORACLE_HOME/md/admin/semrelod111.sql
 - Windows: %ORACLE_HOME%\md\admin\semrelod111.sql
2. If you have any virtual models that you want to be able to re-create after the download, run the *semvmrecreate.sql* script (if you have not already done so), as explained earlier in this section.
3. Remove any Release 11.2 release-specific RDF or OWL data (including virtual models) if you have not already done so, as explained earlier in this section.
4. Perform the database downgrade.
5. In the Release 11.1 database, copy the saved copy of the *semrelod111.sql* file to the following location:
 - Linux: \$ORACLE_HOME/md/admin/
 - Windows: %ORACLE_HOME%\md\admin\
6. Connect to the Release 11.1 database as the SYS user with SYSDBA privileges (SYS AS SYSDBA, and enter the SYS account password when prompted).
7. Start SQL*Plus, and enter the following statement:
 - Linux: @\$ORACLE_HOME/md/admin/semrelod111.sql
 - Windows: @%ORACLE_HOME%\md\admin\semrelod111.sql

After the *semrelod111.sql* script completes successfully, Oracle semantic technologies support for Release 11.1 is enabled and ready to use, and all Release 11.1-compatible data is preserved.

8. If you want to enable support for virtual models, apply the Release 11.1.0.7 interim patch number 7600122.

9. If you previously generated a `my_vm_recreate.sql` script to re-create your virtual models after the downgrade, go to the `my_dir_path` location, connect to the database as the SYS user with SYSDBA privileges, start SQL*Plus, and run the `my_vm_recreate.sql` script.

A.2.2 Downgrading to Release 10.2 Semantic Technologies Support

If you need to downgrade to Oracle Database Release 10.2, follow the instructions in [Section A.2.1](#) to downgrade to Release 11.1, and then follow the instructions in the rest of this section (taken from the Release 11.1 manual) to downgrade from Release 11.1 to Release 10.2.

If you need to downgrade to Oracle Database Release 10.2, and if you used Oracle Database Release 11 RDF or OWL features and want to preserve existing semantic data and rulebases, you must execute a statement to prepare for the downgrade, perform the downgrade, and execute another statement to restore the semantic data.

However, the following considerations apply:

- Entailed graph data will not be preserved, because the same information can be regenerated using the Oracle Database Release 10.2 RDF inference API.
- No rulebases or rules indexes related to OWL are preserved, because Oracle Database Release 10.2 did not support the OWL vocabulary.

Perform the following steps:

1. Before the database downgrade, connect to the Release 11 database as the SYS user with SYSDBA privileges (`SYS AS SYSDBA`, and enter the SYS account password when prompted).
2. Start SQL*Plus and enter the following statement:

```
EXECUTE SDO_SEM_DOWNGRADE.PREPARE_DOWNGRADE_FROM_11;
```

When this statement executes successfully, all existing semantic data and rulebases are saved. You will restore the semantic data after the database downgrade.

3. Perform the database downgrade.
4. Download the following file from the Semantic Technologies page of the Oracle Technology Network site: `sdosemdgu.plb`
5. If (and only if) your Oracle Database Release 10.2 release number is 10.2.0.1, click the Software link, and download and install the RDF-specific patch. (This patch is needed because Release 10.2.0.1 did not have the batch loading feature, which is used to restore the semantic data.)
6. Connect to the Release 10.2 database as the SYS user with SYSDBA privileges.
7. Start SQL*Plus and enter a statement in the following statement:

```
EXECUTE SDO_SEM_DOWNGRADE_UTL.PREPARE_DOWNGRADE_TO_102('<tablespace-name>');
```

Where `<tablespace-name>` is the name of the tablespace in which the RDF network will be created.

When this statement executes successfully, all semantic data that had been saved before the downgrade is restored and ready to use.

A.3 Removing Semantic Technologies Support

This section explains how to remove the semantic technologies support from the database. Removing this support is *strongly discouraged*, unless you have a strong reason for doing it. After you remove this support, no applications or database users will be able to use any types, synonyms, or PL/SQL packages related to Oracle semantic technologies support.

If you have enabled Workspace Manager support for RDF data, you must remove that support *before* you remove semantic technologies support from the database, as explained in [Section 6.1.1](#).

To remove the semantic technologies support from the database, perform the following steps:

1. Connect to the database (Release 11.2) as the SYS user with SYSDBA privileges (SYS AS SYSDBA, and enter the SYS account password when prompted).
2. Start SQL*Plus, and enter the following statement:
 - Linux: @\$ORACLE_HOME/md/admin/semremov.sql
 - Windows: @%ORACLE_HOME%\md\admin\semremov.sql

The `semremov.sql` script drops the semantic network and removes any semantic technologies types, tables, and PL/SQL packages:

Glossary

The following are selected terms relevant to the Oracle Database implementation of semantic technologies support. This is not a comprehensive RDF and OWL glossary.

apply pattern

Part of a data access constraint defines additional graph patterns to be applied on the resources that match the match pattern before they can be used to construct the query results. *See also:* [match pattern](#)

clique

A graph in which every node of it is connected to, bidirectionally, every other node in the same graph.

Cytoscape

An open source bioinformatics software platform for visualizing molecular interaction networks and integrating these interactions with gene expression profiles and other state data. (See <http://www.cytoscape.org/>.) An RDF viewer (available for download) is provided as a Cytoscape plug-in.

entailment

An object containing precomputed triples that can be inferred from applying a specified set of rulebases to a specified set of models. *See also:* [rulebase](#)

extractor policy

A named dictionary entity that determines the characteristics of a semantic index that is created using the policy. Each extractor policy refers, directly or indirectly, to an instance of an extractor type.

graph pattern

A combination of triples constructed by combining triple patterns in various ways, including conjunction of triple patterns into groups, optionally using filter conditions, and then combining such groups via connectors similar to disjunctions, outer-joins, and so on. SPARQL querying is based around graph pattern matching.

inferencing

The ability to make logical deductions based on rules. Inferencing enables you to construct queries that perform semantic matching based on meaningful relationships among pieces of data, as opposed to just syntactic matching based on string or other values. Inferencing involves the use of rules, either supplied by Oracle or user-defined, placed in rulebases.

information extractor

An application that processes unstructured documents and extract meaningful information from them, often using natural-language processing engines with the aid of ontologies.

Jena Adapter for Oracle Database

An Oracle-supplied adapter (available for download) for Jena, which is a Java framework for building Semantic Web applications.

match pattern

Part of a constraint that determines the type of access restriction it enforces and binds one or more variables to the corresponding data instances accessed in the user query.

See also: [apply pattern](#)

model

A user-created semantic structure that has a model name, and refers to triples stored in a specified table column. Examples in this manual are the Articles and Family models.

ontology

A shared conceptualization of knowledge in a particular domain. It consists of a collection of classes, properties, and optionally instances. Classes are typically related by class hierarchy (subclass/ superclass relationship). Similarly, the properties can be related by property hierarchy (subproperty/ superproperty relationship). Properties can be symmetric or transitive, or both. Properties can also have domain, ranges, and cardinality constraints specified for them.

OWLPrime

An Oracle-defined subset of OWL capabilities; refers to the elements of the OWL standard supported by the Oracle Database semantic technologies native inferencing engine.

reasoning

See [inferencing](#)

rule

An object that can be applied to draw inferences from semantic data.

rulebase

An object that can contain rules. *See also:* [rule](#)

rules index

See: [entailment](#)

semantic index

An index of type MDSYS.SEMCONTEXT, created on textual documents stored in a column of a table, and used with information extractors to locate and extract meaningful information from unstructured documents. *See also:* [information extractor](#)

Sesame Adapter for Oracle Database

An Oracle-supplied adapter (available for download) that integrates the popular Sesame Java APIs with Oracle Semantic Technologies support.

Simple Knowledge Organization System (SKOS)

A data model that is especially useful for representing thesauri, classification schemes, taxonomies, and other types of controlled vocabulary. SKOS is based on standard semantic web technologies including RDF and OWL, which makes it easy to define the formal semantics for those knowledge organization systems and to share the semantics across applications.

triple pattern

Similar to an RDF triple, but allows use of a variable in place of any of the three components (subject, predicate, or object). Triple patterns are basic elements in graph patterns used in SPARQL queries. A triple pattern used in a query against an RDF graph is said to match if, substitution of RDF terms for the variables present in the triple pattern, creates a triple that is present in the RDF graph. *See also:* [graph pattern](#)

A

ADD_SEM_INDEX procedure, 9-2
ADD_VPD_CONSTRAINT procedure, 12-2
Advanced Compression Option
 required for columnar compression with SEM_ APIS.CREATE_ENTAILMENT, 9-23
aliases
 SEM_ALIASES and SEM_ALIAS data types, 1-18, 4-5
ALL_BGP_HASH
 query option for SEM_MATCH, 1-19
ALL_BGP_NL
 query option for SEM_MATCH, 1-19
ALL_ORDERED
 query option for SEM_MATCH, 1-19
ALLOW_DUP=Y
 query option for SEM_MATCH, 1-19
ALTER_ENTAILMENT procedure, 9-3
ALTER_MODEL procedure, 9-4
ALTER_SEM_INDEX_ON_ENTAILMENT procedure, 9-5
ALTER_SEM_INDEX_ON_MODEL procedure, 9-7
ANALYZE_ENTAILMENT procedure, 9-9
ANALYZE_MODEL procedure, 9-11
apply pattern, 5-7
APPLY_OLS_POLICY procedure, 12-4
APPLY_VPD_POLICY procedure, 12-7

B

batch (bulk) loading, 9-13
batch loading semantic data, 1-31
blank nodes, 1-7
 constructor for reusing, 1-17
bulk loading, 9-13
bulk loading semantic data, 1-30
BULK_LOAD_FROM_STAGING_TABLE procedure, 9-13

C

Calais
 configuring the Calais extractor type, 4-10
canonical forms, 1-6
catsem10i.sql script, A-4, A-6

catsem.sql script, A-1
change tracking
 disabling, 9-32
 enabling, 9-41
 getting information, 9-43
CLEANUP_FAILED procedure, 9-15
client identifiers, 7-8
cliques (sameAs), 2-9
columnar compression
 requires Advanced Compression Option, 9-23
COMPOSE_RDF_TERM function, 9-16
connection pooling
 support in Jena Adapter, 7-25
 support in Sesame Adapter, 8-20
constructors for semantic data, 1-15
convert_old_rdf_data procedure, A-3
CREATE_ENTAILMENT procedure, 9-19
CREATE_POLICY procedure, 11-2
CREATE_RULEBASE procedure, 9-27
CREATE_SEM_MODEL procedure, 9-28
CREATE_SEM_NETWORK procedure, 9-29
CREATE_VIRTUAL_MODEL procedure, 9-30
CREATE_VPD_POLICY procedure, 12-8

D

data types
 for literals, 1-6
data types for semantic data, 1-15
DELETE_VPD_CONSTRAINT procedure, 12-10
demo files
 semantic data, 1-36
DISABLE_CHANGE_TRACKING procedure, 9-32
DISABLE_INC_INFERENCE procedure, 9-33
DISABLE_OLS_POLICY procedure, 12-11
discussion forum
 semantic technologies, 1-45
documents
 semantic indexing for, 4-1
downgrading
 semantic technologies support to Release 10.2, A-7
 semantic technologies support to Release 11.1, A-5
downloads
 semantic technologies, 1-45

- DROP_ENTAILMENT procedure, 9-34
- DROP_POLICY procedure, 11-4
- DROP_RULEBASE procedure, 9-35
- DROP_SEM_INDEX procedure, 9-36
- DROP_SEM_MODEL procedure, 9-37
- DROP_SEM_NETWORK procedure, 9-38
- DROP_USER_INFERENCE_OBJS procedure, 9-39
- DROP_VIRTUAL_MODEL procedure, 9-40
- DROP_VPD_POLICY procedure, 12-12
- duplicate triples
 - checking for, 1-6
 - removing from model, 9-60

E

- ENABLE_CHANGE_TRACKING procedure, 9-41
- ENABLE_INC_INFERENCE procedure, 9-42
- ENABLE_OLS_POLICY procedure, 12-13
- entailment
 - invalid status, 1-19
- entailment rules, 1-8
- entailments, 1-10
 - altering, 9-3
 - deleting if in failed state, 9-15
 - incomplete status, 1-19, 2-14
 - invalid status, 2-14
 - SEM_RULES_INDEX_DATASETS view, 1-11
 - SEM_RULES_INDEX_INFO view, 1-10
- rules indexes
 - See* entailments
- examples
 - Java (on Oracle Technology Network), 1-36
 - PL/SQL, 1-36
- exporting semantic data, 1-30
- external documents
 - indexing, 4-8
- extractor policies, 4-3
 - RDFCTX_POLICIES view, 4-13
- extractors
 - information, 4-2
 - policies, 4-3

F

- failed state
 - rulebase or entailment, 9-15
- federated queries, 7-16
- filter
 - attribute of SEM_MATCH, 1-19, 4-5

G

- GATE (General Architecture for Text Engineering)
 - sample Java implementation, 4-11
 - using, 4-11
- GATHER_STATS procedure, 10-2
- General Architecture for Text Engineering (GATE)
 - sample Java implementation, 4-11
 - using, 4-11
- GET_CHANGE_TRACKING_INFO procedure, 9-43
- GET_INC_INF_INFO procedure, 9-44

- GET_MODEL_ID function, 9-45
- GET_MODEL_NAME function, 9-46
- GET_TRIPLE_ID function, 9-47
- GETV\$DATETIMETZVAL function, 9-49
- GETV\$DATETZVAL function, 9-50
- GETV\$NUMERICVAL function, 9-51
- GETV\$STRINGVAL function, 9-52
- GETV\$TIMETZVAL function, 9-53

H

- HINTO
 - query option for SEM_MATCH, 1-19

I

- incremental inference, 2-11
 - disabling, 9-33
 - enabling, 9-42
- incremental inferencing
 - getting information, 9-44
- index_status
 - attribute of SEM_MATCH, 1-19, 2-14
- INF_ONLY
 - query option for SEM_MATCH, 1-20
- inferencing, 1-7
- information extractors, 4-2
- inverseOf keyword
 - using to force use of semantic index, 2-17
- IS_TRIPLE function, 9-55

J

- Java examples
 - GATE listener, 4-11
 - OTN semantic technologies page, 1-36
- Jena Adapter, 7-1
 - functions supported in SPARQL queries, 7-18
 - optimized handling of SPARQL queries, 7-10
 - optimized handling or property paths, 7-11
 - query examples, 7-28
 - RDFa support with prepareBulk, 7-28
 - SEM_MATCH and Jena Adapter queries compared, 7-9
 - setting up software environment, 7-1
 - setting up SPARQL service, 7-3
 - support for connection pooling, 7-25
 - support for semantic model PL/SQL interfaces, 7-26
 - support for virtual models, 7-24
- Joseki
 - using with Jena Adapter, 7-3

L

- literals
 - data types for, 1-6
- loading semantic data, 1-30
 - bulk, 9-13
- LOOKUP_ENTAILMENT procedure, 9-57

M

MAINT_VPD_METADATA procedure, 12-14
MAINTAIN_TRIPLES procedure, 11-5
match pattern, 5-7
mdsys.SemContent index type, 4-4
MERGE_MODELS procedure, 9-58
metadata
 semantic, 1-3
metadata tables and views for semantic data, 1-14
methods for semantic data, 1-15
model ID
 getting, 9-45
model name
 getting, 9-46
models, 1-3
 altering, 9-4
 creating, 9-28
 deleting (dropping), 9-37
 disabling support in the database, 9-38
 enabling support in the database, 9-29
 merging, 9-58
 renaming, 9-62
 SEM_MODELS data type, 1-18
 SEMI_entailment-name view, 1-10
 SEMM_model-name view, 1-4
 swapping names, 9-63
 virtual, 1-11

O

objects, 1-7
options
 attribute of SEM_MATCH, 1-19
Oracle Label Security (OLS), 5-20
 applying policy, 12-4
 disabling policy, 12-11
 enabling policy, 12-13
 removing policy, 12-16
 resetting labels associated with a model, 12-18
 resource-level security, 5-14
 setting sensitivity label for a resource that may be used in the subject and/or object position of a triple, 12-23
 setting sensitivity level for a predicate, 12-19
 setting sensitivity level for a rule belonging to a rulebase, 12-25
 setting sensitivity level for RDFS schema elements, 12-21
 triple-level security, 5-12
 using with RDF data, 5-12
Oracle Spatial
 prerequisite software for RDF and OWL capabilities, A-5
OTN page
 semantic technologies, 1-45
OWL
 queries using the SEM_DISTANCE ancillary operator, 2-15
 queries using the SEM_RELATED operator, 2-13
owl

SameAs
 optimizing inference, 2-9
sameAs
 SEMCL_entailment-name view, 2-10

P

parallel inference, 2-12
Partitioning
 must be enabled for RDF and OWL, A-5
PelletInfGraph class
 support deprecated in Jena Adapter, 7-26
properties, 1-7
property chain handling, 3-4
property paths
 optimized handling by Jena Adapter, 7-11

Q

quality of search, 4-8
queries
 using the SEM_DISTANCE ancillary operator, 2-15
 using the SEM_MATCH table function, 1-18
 using the SEM_RELATED operator, 2-13

R

RDF rulebase
 subset of RDFS rulebase, 1-8
RDF\$SET_TAB table, 1-31
RDF_VALUE\$ table, 1-5
RDFa
 support with prepareBulk (Jena Adapter), 7-28
RDFCTX_INDEX_EXCEPTIONS view, 4-14
RDFCTX_POLICIES view, 4-13
RDFOLS_SECURE_RESOURCE view, 5-20
RDFS entailment rules, 1-8
RDFS rulebase
 implements RDFS entailment rules, 1-8
RDFVPD_MODELS view, 5-10
RDFVPD_POLICIES view, 5-10
RDFVPD_POLICY_CONSTRAINTS view, 5-11
RDFVPD_PREDICATE_MDATA view, 5-11
RDFVPD_RESOURCE_REL view, 5-12
REMOVE_DUPLICATES procedure, 9-60
REMOVE_OLS_POLICY procedure, 12-16
REMOVE_VPD_POLICY procedure, 12-17
removing semantic technologies support, A-8
RENAME_ENTAILMENT procedure, 9-61
RENAME_MODEL procedure, 9-62
RESET_MODEL_LABELS procedure, 12-18
resource-level security, 5-14
rulebases, 1-7
 attribute of SEM_MATCH, 2-14
 deleting if in failed state, 9-15
 SEM_RULEBASE_INFO view, 1-9
 SEM_RULEBASES data type, 1-18
 SEMR_rulebase-name view, 1-9
rules, 1-7

S

sameAs

optimizing inference (OWL), 2-9

sameTerm built-in function, 1-29

sdo_rdf_internal.convert_old_rdf_data

procedure, A-3

sdordfwm_rm.sql script, 6-2

sdordfwm.sql script, 6-1

search

quality of, 4-8

security considerations, 1-14

SEM_ALIAS data type, 1-18, 4-5

SEM_ALIASES data type, 1-18, 4-5

SEM_APIS package

ADD_SEM_INDEX, 9-2

ALTER_ENTAILMENT, 9-3

ALTER_MODEL, 9-4

ALTER_SEM_INDEX_ON_ENTAILMENT

semantic network indexes

altering on entailment, 9-5

ALTER_SEM_INDEX_ON_MODEL, 9-7

ANALYZE_ENTAILMENT, 9-9

ANALYZE_MODEL, 9-11

BULK_LOAD_FROM_STAGING_TABLE, 9-13

CLEANUP_FAILED, 9-15

COMPOSE_RDF_TERM, 9-16

CREATE_ENTAILMENT, 9-19

CREATE_RULEBASE, 9-27

CREATE_SEM_MODEL, 9-28

CREATE_SEM_NETWORK, 9-29

CREATE_VIRTUAL_MODEL, 9-30

DISABLE_CHANGE_TRACKING, 9-32

DISABLE_INC_INFERENCE, 9-33

DROP_ENTAILMENT, 9-34

DROP_RULEBASE, 9-35

DROP_SEM_INDEX, 9-36

DROP_SEM_MODEL, 9-37

DROP_SEM_NETWORK, 9-38

DROP_USER_INFERENCE_OBJS, 9-39

DROP_VIRTUAL_MODEL, 9-40

ENABLE_CHANGE_TRACKING, 9-41

ENABLE_INC_INFERENCE, 9-42

GET_CHANGE_TRACKING_INFO, 9-43

GET_INC_INF_INFO, 9-44

GET_MODEL_ID, 9-45

GET_MODEL_NAME, 9-46

GET_TRIPLE_ID, 9-47

GETV\$DATETIMETZVAL, 9-49

GETV\$DATETZVAL, 9-50

GETV\$NUMERICVAL, 9-51

GETV\$STRINGVAL, 9-52

GETV\$TIMETZVAL, 9-53

LOOKUP_ENTAILMENT, 9-57

MERGE_MODELS, 9-58

reference information, 9-1, 10-1

REMOVE_DUPLICATES, 9-60

RENAME_ENTAILMENT, 9-61

RENAME_MODEL, 9-62

SWAP_NAMES, 9-63

TRIPLE, 9-55

VALIDATE_ENTAILMENT, 9-64

VALIDATE_MODEL, 9-66

VALUE_NAME_PREFIX, 9-68, 9-70

SEM_CONTAINS operator

syntax, 4-5

SEM_CONTAINS_SELECT ancillary operator

syntax, 4-5

using in queries, 4-7

SEM_DISTANCE ancillary operator, 2-15

SEM_INDEXTYPE index type, 2-16

SEM_MATCH table function, 1-18

SEM_MODEL\$ view, 1-3

virtual model entries, 1-13

SEM_MODELS data type, 1-18

SEM_PERF package

GATHER_STATS, 10-2

SEM_RDFCTX package

CREATE_POLICY, 11-2

DROP_POLICY, 11-4

MAINTAIN_TRIPLES, 11-5

reference information, 11-1

SET_DEFAULT_POLICY, 11-7

SET_EXTRACTOR_PARAM, 11-8

SEM_RDFSA package

ADD_VPD_CONSTRAINT, 12-2

APPLY_OLS_POLICY, 12-4

APPLY_VPD_POLICY, 12-7

CREATE_VPD_POLICY, 12-8

DELETE_VPD_CONSTRAINT, 12-10

DISABLE_OLS_POLICY, 12-11

DROP_VPD_POLICY, 12-12

ENABLE_OLS_POLICY, 12-13

MAINT_VPD_METADATA, 12-14

reference information, 12-1

REMOVE_OLS_POLICY, 12-16

REMOVE_VPD_POLICY, 12-17

RESET_MODEL_LABELS, 12-18

SET_PREDICATE_LABEL, 12-19

SET_RDFS_LABEL, 12-21

SET_RESOURCE_LABEL, 12-23

SET_RULE_LABEL, 12-25

SEM_RELATED operator, 2-13

SEM_RULEBASE_INFO view, 1-9

SEM_RULEBASES data type, 1-18

SEM_RULES_INDEX_DATASETS view, 1-11

SEM_RULES_INDEX_INFO view, 1-10

SEM_VMODEL_DATASETS view, 1-13

SEM_VMODEL_INFO view, 1-13

semantic data

blank nodes, 1-7

constructors, 1-15

data types, 1-15

demo files, 1-36

examples (Java), 1-36

examples (PL/SQL), 1-36

in the database, 1-3

metadata, 1-3

metadata tables and views, 1-14

methods, 1-15

modeling, 1-3

- objects, 1-7
- properties, 1-7
- queries using the SEM_MATCH table
 - function, 1-18
- security considerations, 1-14
- statements, 1-5
- steps for using, 1-35
- subjects, 1-7
- semantic index
 - creating (MDSYS.SEM_INDEXTYPE), 2-16
 - indexing documents, 4-4
 - using for documents, 4-1
- semantic indexes
 - RDFCTX_INDEX_EXCEPTIONS view, 4-14
- semantic network indexes
 - adding, 9-2
 - altering on model, 9-7
 - dropping, 9-36
 - using, 1-34
- Resource Description Framework
 - See* semantic technologies
- semantic technologies
 - overview, 1-1
- semantic technologies support
 - downgrading to Release 10.2, A-7
 - downgrading to Release 11.1, A-5
 - enabling, A-1
 - removing, A-8
 - upgrading from Release 10.2, A-4
 - upgrading from Release 11.1, A-2
- SEMCL_entailment-name view, 2-10
- SemContent
 - mdsys.SemContent index type, 4-4
- SEMI_entailment-name view, 1-10
- SEMM_model-name view, 1-4
- SEMR_rulebase-name view, 1-9
- semreod111.sql script, A-6
- semreod.sql script, A-3
- semremov.sql script, A-8
- Sesame Adapter, 8-1
 - optimized handling of SPARQL queries, 8-16
 - performance recommendations, 8-16
 - query examples, 8-26
 - SEM_MATCH and Sesame Adapter queries
 - compared, 8-15
 - setting up software environment, 8-3
 - setting up SPARQL endpoint, 8-4
 - support for connection pooling, 8-20
 - support for semantic model PL/SQL
 - interfaces, 8-21
 - support for virtual models, 8-19
- SET_DEFAULT_POLICY procedure, 11-7
- SET_EXTRACTOR_PARAM procedure, 11-8
- SET_PREDICATE_LABEL procedure, 12-19
- SET_RDFS_LABEL procedure, 12-21
- SET_RESOURCE_LABEL procedure, 12-23
- SET_RULE_LABEL procedure, 12-25
- Simple Knowledge Organization System (SKOS)
 - property chain handling, 3-4
 - support for, 3-1

- SKOS (Simple Knowledge Organization System)
 - property chain handling, 3-4
 - support for, 3-1
- SNOMED CT (Systematized Nomenclature of Medicine - Clinical Terms)
 - support for, 9-22
- SPARQL
 - configuring the service, 7-6, 8-14
 - optimized handling of queries, 7-10, 8-16
 - searching for documents using SPARQL query
 - pattern, 4-6
 - setting up service for Jena Adapter, 7-3
 - setting up service for Sesame Adapter, 8-4
- Spatial
 - prerequisite software for RDF and OWL
 - capabilities, A-5
- staging table
 - loading data from, 9-13
- staging table for bulk loading semantic data, 1-30
- statements
 - RDF_VALUE\$ table, 1-5
- statistics
 - gathering for RDF and OWL, 10-2
- subjects, 1-7
- subproperty chaining, 3-4
- SWAP_NAMES procedure, 9-63
- Systematized Nomenclature of Medicine - Clinical Terms (SNOMED CT)
 - support for, 9-22

T

- triple-level security, 5-12
- triples
 - constructor for inserting, 1-17
 - duplication checking, 1-6
 - IS_TRIPLE function, 9-55

U

- uninstalling semantic technologies support, A-8
- upgrading
 - semantic technologies support from Release 10.2, A-4
 - semantic technologies support from Release 11.1, A-2
- URI prefix
 - using when values are not stored as URIs, 2-18
- URIPREFIX keyword, 2-18

V

- VALIDATE_ENTAILMENT procedure, 9-64
- VALIDATE_MODEL procedure, 9-66
- VALUE_NAME_PREFIX function, 9-68, 9-70
- version-enabling an RDF model, 6-2, 6-3
- virtual models, 1-11
 - SEM_MODEL\$ view entries, 1-13
 - SEM_VMODEL_DATASETS view, 1-13
 - SEM_VMODEL_INFO view, 1-13
 - support in Jena Adapter, 7-24

- support in Sesame Adapter, 8-19
- Virtual Private Database (VPD), 5-10, 5-11, 5-12
- virtual private database (VPD)
 - adding constraint, 12-2
 - applying policy, 12-7
 - creating policy, 12-8
 - deleting constraint, 12-10
 - dropping policy, 12-12
 - maintaining metadata, 12-14
 - removing policy, 12-17
 - using with RDF data, 5-2

W

- Workspace Manager
 - enabling support for RDF data, 6-1
 - inferring from version-enabled RDF models, 6-3
 - merging and refreshing workspaces, 6-3
 - removing support for RDF data, 6-2
 - version-enabling an RDF model, 6-2
- workspaces
 - merging and refreshing, 6-3