

# 2

## Restricting and Sorting Data

# Objectives

**After completing this lesson, you should be able to do the following:**

- **Limit the rows that are retrieved by a query**
- **Sort the rows that are retrieved by a query**

# Limiting Rows Using a Selection

## EMPLOYEES

EMPLOYEE_ID	LAST_NAME	JOB_ID	DEPARTMENT_ID
100	King	AD_PRES	90
101	Kochhar	AD_VP	90
102	De Haan	AD_VP	90
103	Hunold	IT_PROG	60
104	Ernst	IT_PROG	60
107	Lorentz	IT_PROG	60
124	Mourgos	ST_MAN	50

...

20 rows selected.

**“retrieve all  
employees in  
department 90”**



EMPLOYEE_ID	LAST_NAME	JOB_ID	DEPARTMENT_ID
100	King	AD_PRES	90
101	Kochhar	AD_VP	90
102	De Haan	AD_VP	90

# Limiting the Rows That Are Selected

- **Restrict the rows that are returned by using the WHERE clause:**

```
SELECT * | { [DISTINCT] column | expression [alias] , ... }  
FROM table  
[WHERE condition(s) ] ;
```

- **The WHERE clause follows the FROM clause.**

# Using the WHERE Clause

```
SELECT employee_id, last_name, job_id, department_id
FROM employees
WHERE department_id = 90 ;
```

EMPLOYEE_ID	LAST_NAME	JOB_ID	DEPARTMENT_ID
100	King	AD_PRES	90
101	Kochhar	AD_VP	90
102	De Haan	AD_VP	90

# Character Strings and Dates

- Character strings and date values are enclosed by single quotation marks.
- Character values are case-sensitive, and date values are format-sensitive.
- The default date format is DD-MON-RR.

```
SELECT last_name, job_id, department_id
FROM employees
WHERE last_name = 'Whalen' ;
```

# Comparison Conditions

Operator	Meaning
=	Equal to
>	Greater than
>=	Greater than or equal to
<	Less than
<=	Less than or equal to
<>	Not equal to
BETWEEN ...AND...	Between two values (inclusive)
IN (set)	Match any of a list of values
LIKE	Match a character pattern
IS NULL	Is a null value

# Using Comparison Conditions

```
SELECT last_name, salary
FROM employees
WHERE salary <= 3000 ;
```

LAST_NAME	SALARY
Matos	2600
Vargas	2500



# Using the BETWEEN Condition

Use the BETWEEN condition to display rows based on a range of values:

```
SELECT last_name, salary
FROM employees
WHERE salary BETWEEN 2500 AND 3500 ;
```

Lower limit

Upper limit

LAST_NAME	SALARY
Rajs	3500
Davies	3100
Matos	2600
Vargas	2500

# Using the IN Condition

Use the IN membership condition to test for values in a list:

```
SELECT employee_id, last_name, salary, manager_id
FROM employees
WHERE manager_id IN (100, 101, 201) ;
```

EMPLOYEE_ID	LAST_NAME	SALARY	MANAGER_ID
202	Fay	6000	201
200	Whalen	4400	101
205	Higgins	12000	101
101	Kochhar	17000	100
102	De Haan	17000	100
124	Mourgos	5800	100
149	Zlotkey	10500	100
201	Hartstein	13000	100

8 rows selected.

# Using the LIKE Condition

- Use the **LIKE** condition to perform wildcard searches of valid search string values.
- Search conditions can contain either literal characters or numbers:
  - % denotes zero or many characters.
  - \_ denotes one character.

```
SELECT  first_name
FROM    employees
WHERE   first_name LIKE 'S%';
```

# Using the LIKE Condition

- You can combine pattern-matching characters:

```
SELECT last_name  
FROM employees  
WHERE last_name LIKE '_o%' ;
```

LAST_NAME
Kochhar
Lorentz
Mourgos

- You can use the `ESCAPE` identifier to search for the actual `%` and `_` symbols.

# Using the NULL Conditions

Test for nulls with the IS NULL operator.

```
SELECT last_name, manager_id  
FROM employees  
WHERE manager_id IS NULL ;
```

LAST_NAME	MANAGER_ID
King	

# Logical Conditions

Operator	Meaning
AND	Returns <b>TRUE</b> if <i>both</i> component conditions are true
OR	Returns <b>TRUE</b> if <i>either</i> component condition is true
NOT	Returns <b>TRUE</b> if the following condition is false

# Using the AND Operator

AND requires both conditions to be true:

```
SELECT employee_id, last_name, job_id, salary
FROM employees
WHERE salary >=10000
AND job_id LIKE '%MAN%' ;
```

EMPLOYEE_ID	LAST_NAME	JOB_ID	SALARY
149	Zlotkey	SA_MAN	10500
201	Hartstein	MK_MAN	13000

# Using the OR Operator

OR requires either condition to be true:

```
SELECT employee_id, last_name, job_id, salary
FROM employees
WHERE salary >= 10000
OR job_id LIKE '%MAN%' ;
```

EMPLOYEE_ID	LAST_NAME	JOB_ID	SALARY
100	King	AD_PRES	24000
101	Kochhar	AD_VP	17000
102	De Haan	AD_VP	17000
124	Mourgos	ST_MAN	5800
149	Zlotkey	SA_MAN	10500
174	Abel	SA_REP	11000
201	Hartstein	MK_MAN	13000
205	Higgins	AC_MGR	12000

8 rows selected.



# Using the NOT Operator

```
SELECT last_name, job_id
FROM employees
WHERE job_id
      NOT IN ('IT_PROG', 'ST_CLERK', 'SA_REP') ;
```

LAST_NAME	JOB_ID
King	AD_PRES
Kochhar	AD_VP
De Haan	AD_VP
Mourgos	ST_MAN
Zlotkey	SA_MAN
Whalen	AD_ASST
Hartstein	MK_MAN
Fay	MK_REP
Higgins	AC_MGR
Gietz	AC_ACCOUNT

10 rows selected.

# Rules of Precedence

Operator	Meaning
1	Arithmetic operators
2	Concatenation operator
3	Comparison conditions
4	IS [NOT] NULL, LIKE, [NOT] IN
5	[NOT] BETWEEN
6	Not equal to
7	NOT logical condition
8	AND logical condition
9	OR logical condition

You can use parentheses to override rules of precedence.

# Rules of Precedence

```
SELECT last_name, job_id, salary
FROM employees
WHERE job_id = 'SA_REP'
OR job_id = 'AD_PRES'
AND salary > 15000;
```

1

LAST_NAME	JOB_ID	SALARY
King	AD_PRES	24000
Abel	SA_REP	11000
Taylor	SA_REP	8600
Grant	SA_REP	7000

```
SELECT last_name, job_id, salary
FROM employees
WHERE (job_id = 'SA_REP'
OR job_id = 'AD_PRES')
AND salary > 15000;
```

2

LAST_NAME	JOB_ID	SALARY
King	AD_PRES	24000

# Using the ORDER BY Clause

- Sort retrieved rows with the ORDER BY clause:
  - ASC: ascending order, default
  - DESC: descending order
- The ORDER BY clause comes last in the SELECT statement:

```
SELECT last_name, job_id, department_id, hire_date
FROM employees
ORDER BY hire_date ;
```

LAST_NAME	JOB_ID	DEPARTMENT_ID	HIRE_DATE
King	AD_PRES	90	17-JUN-87
Whalen	AD_ASST	10	17-SEP-87
Kochhar	AD_VP	90	21-SEP-89
Hunold	IT_PROG	60	03-JAN-90
Ernst	IT_PROG	60	21-MAY-91

...

20 rows selected.

# Sorting

- **Sorting in descending order:**

```
SELECT last_name, job_id, department_id, hire_date
FROM employees
ORDER BY hire_date DESC ;
```

1

- **Sorting by column alias:**

```
SELECT employee_id, last_name, salary*12 annsal
FROM employees
ORDER BY annsal ;
```


2

- **Sorting by multiple columns:**

```
SELECT last_name, department_id, salary
FROM employees
ORDER BY department_id, salary DESC ;
```

3

# Substitution Variables



# Substitution Variables

- **Use substitution variables to:**
  - Temporarily store values with single-ampersand (&) and double-ampersand (&&) substitution
- **Use substitution variables to supplement the following:**
  - **WHERE** conditions
  - **ORDER BY** clauses
  - **Column** expressions
  - **Table** names
  - **Entire SELECT** statements

# Using the & Substitution Variable

Use a variable prefixed with an ampersand (&) to prompt the user for a value:

```
SELECT employee_id, last_name, salary, department_id
FROM   employees
WHERE  employee_id = &employee_num ;
```

Connected as ORA1@T6

 Input Required

Cancel Continue

Enter value for employee\_num:



# Character and Date Values with Substitution Variables

Use single quotation marks for date and character values:

```
SELECT last_name, department_id, salary*12
FROM employees
WHERE job_id = '&job_title' ;
```

 Input Required

Enter value for job\_title:

LAST_NAME	DEPARTMENT_ID	SALARY*12
Hunold	60	108000
Ernst	60	72000
Lorentz	60	50400

# Specifying Column Names, Expressions, and Text

```
SELECT employee_id, last_name, job_id, &column_name  
FROM employees  
WHERE &condition  
ORDER BY &order_column ;
```

 Input Required

Cancel Continue

Enter value for column\_name:

Cancel Continue

Enter value for condition:


Cancel Continue

Enter value for order\_column:

# Using the && Substitution Variable

Use the double ampersand (&&) if you want to reuse the variable value without prompting the user each time:

```
SELECT  employee_id, last_name, job_id, &&column_name
FROM    employees
ORDER BY &column name ;
```

 An "Input Required" dialog box with a blue header and a white background. It contains a text input field with the value "department\_id" and two buttons: "Cancel" and "Continue".

EMPLOYEE_ID	LAST_NAME	JOB_ID	DEPARTMENT_ID
200	Whalen	AD_ASST	10
201	Hartstein	MK_MAN	20

...  
20 rows selected.


# Using the DEFINE Command

- Use the DEFINE command to create and assign a value to a variable.
- Use the UNDEFINE command to remove a variable.

```
DEFINE employee_num = 200

SELECT employee_id, last_name, salary, department_id
FROM employees
WHERE employee_id = &employee_num ;

UNDEFINE employee_num
```



# Using the VERIFY Command

Use the VERIFY command to toggle the display of the substitution variable, both before and after replaces substitution variables with values:

```
SET VERIFY ON
SELECT employee_id, last_name, salary, department_id
FROM employees
WHERE employee_id = &employee_num;
```

"employee\_num"

```
old 3: WHERE employee_id = &employee_num
new 3: WHERE employee_id = 200
```

# Summary

In this lesson, you should have learned how to:

- Use the **WHERE** clause to restrict rows of output:
  - Use the comparison conditions
  - Use the **BETWEEN**, **IN**, **LIKE**, and **NULL** conditions
  - Apply the logical **AND**, **OR**, and **NOT** operators
- Use the **ORDER BY** clause to sort rows of output:

```
SELECT  * | { [DISTINCT] column | expression [alias], ... }  
FROM    table  
[WHERE  condition(s)]  
[ORDER BY {column, expr, alias} [ASC|DESC]] ;
```